

# L<sup>A</sup>T<sub>E</sub>X Author Guidelines for CVPR Proceedings

Anonymous CVPR submission

Paper ID \*\*\*\*

## Abstract

pass

## 1. Introduction

The importance of our research area

Some progress in sketch based image retrieval

Difficulty in Zero-shot setup and some possible solutions

Our proposed methods and their advantages

itemize our contributions in this paper

## 2. Related Work

### 2.1. Sketch-based image retrieval

### 2.2. Zero-Shot Learning

### 2.3. Disentangled Representation

## 3. Methodology

There will be five parts in this section. Sec. 3.1 defines the our targeted problem and briefly introduce our framework. Sec. 3.2 introduce the encoders in our model. Sec. 3.3 introduce the decoder in our model. Sec. 3.4 introduce the discriminator in our model. Sec. 3.5 introduce the design of loss functions during training procedure.

### 3.1. Problem Definition

In this paper, we focus on solving the problem of hand-free sketch-based image retrieval under zero-shot setup, where only the sketches and images from seen class are used during training stage. Our proposed framework is expected to use the sketches to retrieve the images, the categories of which have never appeared during training.

We first provide a definition of the SBIR in zero-shot setting. Given a dataset  $S = \{(x_i^{img}, x_i^{ske}, x_i^{sem}, y_i) | y_i \in \mathcal{Y}\}$ , where  $x_i^{img}$ ,  $x_i^{ske}$ ,  $x_i^{sem}$  and  $y_i$  are corresponding to the image, sketch, semantic representation and class label. Following the zero-shot setting in [?], we split all classes  $\mathcal{Y}$  into  $\mathcal{Y}_{train}$  and  $\mathcal{Y}_{test}$  according to whether the label exists in ImageNet[?], where no overlap exists between two label set, i.e.  $\mathcal{Y}_{train} \cap \mathcal{Y}_{test} = \emptyset$ . Based on the partition of label set  $\mathcal{Y}$ , we split dataset into  $S_{train}$  and  $S_{test}$ . Our model need to disentangle structure representations of image using data in  $S_{train}$ . During test, given  $x^{ske}$  from  $S_{test}$ , our model need to retrieve several images from test images candidate.

Our goal is to learn a two-way map between image feature domain to sketch feature domain. To this end, we propose a new deep network (shown in Figure ??), which contains two structure encoders  $\{E_s^{img}, E_s^{ske}\}$ , one appearance encoder  $E_a^{img}$ , two feature decoder  $\{G^{img}, G^{ske}\}$ , a semantic decoder and two domain discriminators  $\{D^{img}, D^{ske}\}$ . Note that, the overall model can be regrad as two cVAE-GANs working parallelly, which target to reconstruct sketch features from image and reconstruct image features from both sketches and images. To better capture the semantics information inside the sketches and images, we also add a semantic decoder to preserve semantics information while reconstructing the image features.

108	<b>3.2. Encoder</b>	162
109		163
110	<b>3.3. Generator</b>	164
111		165
112	<b>3.4. Discriminator</b>	166
113	<b>3.5. Loss Function</b>	167
114		168
115	<b>4. Experiment</b>	169
116	<b>4.1. Experiment Setup</b>	170
117		171
118	<b>4.1.1 Dataset</b>	172
119	<b>4.1.2 Implementation Details</b>	173
120		174
121	<b>4.2. Comparison</b>	175
122	<b>4.3. Ablation Study</b>	176
123		177
124	<b>4.4. Case study</b>	178
125		179
126	<b>5. Conclusion</b>	180
127		181
128	<b>6. To Discuss</b>	182
129	• Whether to generator the whole image/sketch.	183
130		184
131	• If the poses between the image and the sketch are dif-	185
132	ferent, can the model learn the sketch information be-	186
133	tween image and sketch.	187
134		188
135	• Where to add the semantics information to further su-	189
136	pervise the model's training.	190
137		191
138		192
139		193
140		194
141		195
142		196
143		197
144		198
145		199
146		200
147		201
148		202
149		203
150		204
151		205
152		206
153		207
154		208
155		209
156		210
157		211
158		212
159		213
160		214
161		215