COVTL Lab Console — User Manual

A laboratory bench for articulatory speech synthesis

Frédéric Berthommier

October 2026 — console v3, engine covtl-pipeline v1.1.0

Contents

1 Welcome — what articulatory synthesis is **1**

2 Installing **2**

3 First sounds in five minutes **2**

4 The three-step pipeline **3**

5 Typing text vs writing SAMPA **3**

6 The red-reject guard **4**

7 Reading the continuous polar display **5**

8 The transport **6**

9 The syllable block compiler **6**

10 Timings and expressive prosody **7**

11 Audio, spectrogram, downloads and exports **7**

12 Troubleshooting, shortcuts, FAQ **8**

12.1 Troubleshooting 8

12.2 Keyboard reference 8

12.3 FAQ 9

1 Welcome — what articulatory synthesis is

Most speech synthesizers you have met are *statistical*: they cut recorded audio into pieces and glue them back together. An *articulatory* synthesizer works the other way around. It models the vocal tract itself — the position of the tongue, the lips, the jaw — and computes the sound

that such a geometry would produce. You do not record speech; you *build* it, gesture by gesture. The engine behind this console, **covtl-pipeline**, couples the Berthommier COVTL model with the VocalTractLab 2.4 synthesizer.

The COVTL model describes each vocalic gesture as a point in a *polar plane*: a radius ρ (how open or close the gesture is) and an angle θ (where in the vowel space it sits). Consonants live in a second, *consonantal* branch of the same plane. An utterance is a sequence of *targets* — one per phoneme — and the engine interpolates between them. Two properties make this model special:

- **Coarticulation.** A gesture is never finished in isolation; the trajectory toward the next target begins before the current one is fully reached. The curved paths you will see on the polar display are the real engine trajectories, not decorations.
- **Anchors.** The engine plans an utterance as a walk between *anchors* — vowel targets, pauses, the utterance start and end. Everything the console shows you (block boundaries, scrub ticks, spectrogram lines) is derived from that anchor list.

You do not need any programming background to use the console. If you can use a web browser and a media player, you can drive it.

2 Installing

The console is a local web page served by a small Python bridge. Full per-system instructions (Windows, macOS, Linux, and the no-Python demo mode) live in the repository's `README.md`; in short:

1. Install the engine: clone `https://github.com/FBerthommier/covtl-pipeline` and run `pip install .` inside it (Python 3.9+, 3.12 recommended).
2. In the console folder, run `pip install fastapi uvicorn`.
3. Run `python server.py` and open `http://127.0.0.1:8421` in Chrome, Edge or Firefox.

The header's *backend chip* must read **live**. If it reads *demo*, the engine was not importable and the console is simulating — fine for exploring the interface, not for research.

No Python at all? Double-click `covtl-console-standalone.html`: the whole console runs from that single file in demo mode, and it goes live automatically whenever a bridge is reachable on port 8421.

3 First sounds in five minutes

1. **Pick a language** in the top-left *Language & Speaker* group (say, English). The example chips below the input box reload for that language.
2. **Click the chip** *EN · this is easy for us.* The console previews it immediately: the *Preview stack* on the right fills with three rows — G2P, Enriched, Final SAMPA (Figure 1).
3. **Press S** (or click *Synthesize from preview*). A progress strip runs G2P → trajectory → VTL → WAV; a few seconds later the result summary appears (*2.37 s audio, 11 anchors,* ...).




Figure 1: The preview stack on the worked example: G2P output, the enriched string, and the final SAMPA the engine will receive — guard checked, nothing synthesized yet.

4. **Press Space** to play. Watch the round *polar display* (Figure 3): a white head travels the trajectory, anchor dots light up, phonetic labels appear at their target positions, and the spectrogram below draws the sound with amber anchor lines.

That is the whole loop: *pick, preview, synthesize, listen, look.*

4 The three-step pipeline

The console is deliberately organized around three questions, printed in the flow guide above the action bar:

1. **Preview** — ***what will the engine receive?*** Press **P**. The engine converts your text to phonetics (G2P), adds prosodic markers, and runs the SAMPA guard. You see the exact string — including any rejected symbol in red — *before* any synthesis. This step never makes sound.
2. **Compile** — ***what is the articulation plan?*** The syllable compiler panel runs the engine's own anchor walk over the SAMPA (Section 9). Metric tiles, a chip per segment, clickable block cards. No sound either.
3. **Synthesize** — ***what does it sound like?*** Press **S**. The engine computes the full trajectory and renders the WAV through VocalTractLab. What you hear is exactly the string you inspected.

The wait indicators. Every step that contacts the engine shows you that it is working: the Preview button relabels to *"Previewing…"* (with its hourglass spinner) and a pill in the header counts *"n in flight…"*. During synthesis, the progress strip lights the current stage (G2P, trajectory, VTL, WAV, MP4) and fills a progress bar. The polar display typically starts moving *while the WAV is still rendering* — that is the start-early feature (Section 7), not a bug.

5 Typing text vs writing SAMPA

The *Input* group has two modes. **Orthographic** is ordinary spelling; the engine's grapheme-to-phoneme module converts it. **Phonetic** is SAMPA, the machine-readable phonetic alphabet the engine speaks; what you type is what the engine receives (after the guard).

Three separators matter, and the engine treats them differently:

- **Dot `.`** — a syllable *link*: no pause, the consonants around the dot form one coarticulated cluster (`ba.da` is one word of two syllables).
- **Space** — a short pause (default 200 ms), written ␣.
- **Vertical bar `|`** — a long pause (default 320 ms), the phrase separator.
- **Percent `%`** — a *breath* pause (130 ms); it also appears as a breath anchor on the display.
- **Tilde `~`** after a vowel — nasality (`a~` is nasalized *a*, as in French *banque*).

The per-language chips (EN, FR, ES, DE, IT, PT, plus two phonetic presets and a guard demo) fill the input and trigger a preview immediately — the fastest way to hear each language's calibration.

6 The red-reject guard

The engine knows a fixed inventory of symbols (vowels `a e i o u y E O @ 2 6 9` plus nasals, consonants `p b t d k g ...`, and the markers above). Anything else — a stray `c`, an IPA *esh* (`S` in SAMPA), an apostrophe — would be *silently dropped* by the engine's tokenizer. The console refuses to let that happen quietly: such symbols are shown struck through in red, with a count badge and a banner (Figure 2).




Figure 2: The guard in `error` policy on `cleanpan`: the `c` is rejected with suggestions `k` / `s`, and synthesis is blocked until you fix, strip, or downgrade the policy.

Three policies, in the *Engine & Guard* group:

- **warn** (default) — proceed knowingly: the label changes to *"Synthesize anyway (N dropped)"* and the engine drops the red symbols.
- **error** — blocked: no synthesis until every red symbol is fixed or stripped.
- **off** — pass-through (engine CLI semantics; know what you are doing).

The banner offers one-click *suggestions* (`c` → `k / s`, IPA *esh* → `S`, ...) and a *strip* action that removes all red symbols at once. You can also hand-edit the final string: *Edit SAMPA* opens an editor on the final row; the *edited* badge reminds you the string is yours, and **E** synthesizes exactly that edited string.




Figure 3: The continuous polar display mid-utterance (Block 5/10, synced on the audio clock). Red trail: vocalic branch; blue dot and ring: consonantal branch; small dots: anchors reached; dashed ring: next anchor; labels appear at phoneme targets as their blocks activate.

7 Reading the continuous polar display

The round display is the heart of the console. Angle θ runs from the top (0°), clockwise; radius ρ is normalized so the engine's own radius range fills the disc (1.0 = the outer dashed ring). Two branches share the disc:

- The **vocalic branch** (red trail) carries the vowel trajectory. The trail fades over roughly 300 ms, so you see where the gesture *came from* — coarticulation made visible.
- The **consonantal branch** (blue marker) carries the consonant closure gesture. It is only active inside consonant clusters; elsewhere its channels are null.

Labels. Phonetic labels pop in at their target positions as the syllabic blocks that own them activate. A count like **"i·4"** means *four phonemes share this same target position* — the engine's target-sharing, printed as `key·n`.

Stretches. On the compiler cards, a segment label like **"i⁓k"** reads: vowel `i` fused with the following consonant `k`. The tie `⁓` marks consonants that follow a vowel *inside the same anchor-to-anchor stretch* — the coda of one syllable coarticulated with the next onset. That is exactly how the engine groups gestures; it is not a dictionary syllable.

Start-early. The trajectory (anchors, blocks, polar points) is computed *before* the audio renders. The display therefore starts on its own clock while the WAV is still being computed — honest, because it is the same engine data — and re-anchors seamlessly on the audio clock when the sound is ready. The badge next to the block counter tells you which clock is master: *polar-only* then *synced · audio clock*.

8 The transport

The bar under the polar display is a media player whose *ruler* is the anchor list:

- **Play / Pause** — **Space** or **K**. **Stop** (back to start) — **Shift+S**.
- **[and]** — previous / next *anchor*. The head lands exactly on the anchor, never between.
- **The scrub bar** — its ticks *are* the anchors; click a tick to snap to it. The amber band marks the current block. **Loop** (**L**) repeats the current block.
- **Speeds** — **0**–**3** for 0.25×, 0.5×, 1×, 2×; applies to playback, the polar head and the spectrogram cursor.
- **Downloads** (**D**) — the artifacts of the current job (Section 11).

Clicking a syllable-compiler card after synthesis *seeks* the polar display to exactly that segment — the fastest way to audit one block.

9 The syllable block compiler




Figure 4: The compiler on the worked example: metric tiles, one chip per anchor-to-anchor segment, and clickable block cards (S3 expanded, showing onset cluster targets in (ρ, θ) and the nucleus plateau).

Press **C** to focus the compiler (Enter compiles). "Compile" means exactly what the engine does before synthesizing — tokenize the SAMPA, walk the anchors, emit the block schedule — but *without* any synthesis: it is the cheap structural half, so you can iterate freely.

The panel (Figure 4) shows:

- **Metric tiles** — syllables, anchors, blocks, consonant and vowel counts, planned duration.
- **Block sequence** — one chip per anchor-to-anchor segment, in time order; the stretch labels (with the ~ marker) appear here.
- **Block cards** — click to expand: onset cluster consonants with their (ρ, θ) targets, the nucleus vowel plateau, block kinds, and time span. *"Use in phonetic input →"* pushes the compiled string to the stage (phonetic mode, previewed); after synthesis, clicking a card seeks the polar display to that segment.

The compiler auto-follows the preview: every preview's final SAMPA is compiled automatically. Type your own blocks to explore — the presets (`ba da ga | iowa a g`, `pta.kli.pra`, ...) are one click away. An *inventory palette* of vowel, consonant and marker chips lets you compose without typing.

10 Timings and expressive prosody

The *Timings* group carries the four engine durations, as steppers (±10 ms):

- **Tcons** — consonantal gesture time (default 100 ms in English).
- **Tvoy** — vocalic plateau time (default 80 ms).
- **tpause / tpause-long** — short and long pause durations (200 / 320 ms).

One engine gesture step is 10 ms at the 100 Hz planning rate — durations are rounded to steps. Each language has its own profile; a slider that has drifted from the profile gets an amber edge, and *Reset to language profile* restores it.

The *Prosody* group toggles **expressive prosody**: breathing groups (the `%` breath pause, 130 ms) and an F0 contour — declination over each breathing group, re-attacks, pitch accents on content words. It touches only the glottis F0 column and pause durations, so it composes with any speaker. The *Base f0* field (60–350 Hz, clamped) is pre-filled from the speaker registry; *reset to speaker* restores it.

11 Audio, spectrogram, downloads and exports

When a job finishes, the audio plays through the transport and the **spectrogram** (Figure 5) is computed locally from the WAV. The *amber vertical lines are the anchors* — the same ticks as the scrub bar; click anywhere on the spectrogram to seek, the polar display follows. Buttons: *f0 overlay* (draws the F0 contour on top), *Download PNG*.

Downloads (D). The WAV and the SAMPA text are *always* offered. The **Optional exports** checkbox (Display & Exports group) adds the TRACT file (the raw articulatory timeline) and the polar data file. Everything lands in the console's `out/` folder; the Display group prints the resolved absolute path so "`out`" is never a mystery.

Video. The *Output* selector can request a **sagittal MP4** (animated mid-sagittal views) or a **dual-panel polar MP4**. Rendering takes markedly longer than audio and the file appears in the Downloads menu when ready; it is not shown inline.




Figure 5: Spectrogram of the worked example with the anchor overlay — click to seek; the polar display follows.

12 Troubleshooting, shortcuts, FAQ

12.1 Troubleshooting

Symptom	Fix
Backend chip reads *demo*	The bridge could not import the engine. Start `python server.py` in the same Python environment you installed covtl-pipeline into; check `/api/status` → `reason`.
Header shows *degraded*	A registry probe failed (speaker or lexicon). Click the backend chip for the full `/api/health` payload; reinstall the language pack or speaker on the engine side.
First preview is slow	The first G2P call loads lexicons (seconds). Later previews are cached and fast.
"Unverified combination" banner	Language-pack vowels are calibrated on the `jd3` speaker only; audio on other speakers may differ. This is a warning, not an error.
No sound	Check the browser's autoplay: click *Play* once (a user gesture unlocks audio). The polar display itself runs regardless.
Synthesis blocked by red symbols	Fix them, use the banner's strip action, or set the guard policy to *warn* (Section 6).
422 on Synthesize	The guard policy is `error` and the input still contains rejected symbols — same fix as above.
Job seems stuck	Long inputs and MP4 modes take minutes. **Esc** cancels.
Polar display freezes in a background tab	Expected: browsers throttle background tabs; the clock catches up (watchdog), rendering resumes on focus.

12.2 Keyboard reference

Space/**K**	play / pause	[/]	prev / next anchor
Shift+S	stop (to start)	**L**	loop current block
P	preview (no sound)	**0**–**3**	speed 0.25/0.5/1/2×
S	synthesize current	**E**	synthesize edited SAMPA
C	focus compiler	**D**	downloads menu
Esc	cancel / stop	**?**	shortcut help

Shortcuts are plain keys, active when you are *not* typing in an editor.

12.3 FAQ

Is anything sent to the internet? No. The bridge binds 127.0.0.1 only; there is no telemetry and no cloud service.

Why 11 anchors for "this is easy for us" and not 6? The engine's anchor list includes the utterance start, word-end anchors and the terminal anchor — the display follows the engine's own list, by design.

What exactly does Synthesize use? The string shown in the final SAMPA row — the previewed one (**S**), your edited one (**E**), or the compiler's output when you pushed it to the stage. What you see is what you hear.

Where are my files? In `out/` under the console folder; the Display & Exports group prints the absolute path.

Can I trust the demo mode? For the interface and guard semantics, yes — they are the real code paths. The G2P, compiler and audio are *approximate simulations*, labeled as demo everywhere.