

SIEMENS MAGNETOM TrioTim syngo MR B15

\\USER\head\daniel\resting\BOLD resting state

TA: 7:45 PAT: Off Voxel size: 3.0x3.0x4.0 mm Rel. SNR: 1.00 SIEMENS: ep2d_bold

Properties

Prio Recon	Off
Before measurement	
After measurement	
Load to viewer	On
Inline movie	Off
Auto store images	On
Load to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	Off
AutoAlign Spine	Off
Start measurement without further preparation	On
Wait for user to start	Off
Start measurements	single

Routine

Slice group 1	
Slices	34
Dist. factor	0 %
Position	R6.1 A6.8 H8.8
Orientation	T > C-8.6
Phase enc. dir.	A >> P
Rotation	0.00 deg
Phase oversampling	0 %
FoV read	192 mm
FoV phase	100.0 %
Slice thickness	4.0 mm
TR	2300 ms
TE	30 ms
Averages	1
Concatenations	1
Filter	None
Coil elements	BC

Contrast

MTC	Off
Flip angle	90 deg
Fat suppr.	Fat sat.
Averaging mode	Long term
Reconstruction	Magnitude
Measurements	200
Delay in TR	0 ms
Multiple series	Off

Resolution

Base resolution	64
Phase resolution	100 %
Phase partial Fourier	Off
Interpolation	Off
PAT mode	None
Matrix Coil Mode	Auto (CP)
Distortion Corr.	Off
Prescan Normalize	Off
Raw filter	On
Elliptical filter	Off
Hamming	Off

Geometry

Multi-slice mode	Interleaved
Series	Interleaved
Special sat.	None

System

Body	On
HEP	Off
HEA	Off
Positioning mode	REF
Table position	H
Table position	0 mm
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combine Mode	Sum of Squares
Auto Coil Select	Default
Shim mode	Standard
Adjust with body coil	Off
Confirm freq. adjustment	Off
Assume Silicone	Off
Ref. amplitude 1H	290.333 V
Adjustment Tolerance	Auto
Adjust volume	
Position	R6.1 A6.8 H8.8
Orientation	T > C-8.6
Rotation	0.00 deg
R >> L	192 mm
A >> P	192 mm
F >> H	136 mm

Physio

1st Signal/Mode	None
-----------------	------

BOLD

GLM Statistics	Off
Dynamic t-maps	Off
Starting ignore meas	0
Ignore after transition	0
Model transition states	On
Temp. highpass filter	On
Threshold	4.00
Paradigm size	10
Meas[1]	Baseline
Meas[2]	Baseline
Meas[3]	Baseline
Meas[4]	Baseline
Meas[5]	Baseline
Meas[6]	Baseline
Meas[7]	Baseline
Meas[8]	Baseline
Meas[9]	Baseline
Meas[10]	Baseline
Motion correction	Off
Spatial filter	Off

Sequence

Introduction	Off
Bandwidth	2232 Hz/Px
Free echo spacing	Off
Echo spacing	0.51 ms
EPI factor	64
RF pulse type	Normal
Gradient mode	Fast*

Table of contents

\\USER	head	daniel	resting	BOLD resting state
--------	------	--------	---------	--------------------