
```
import numpy as np
import matplotlib.pyplot as plt
# Section I
# Question 2
def FrotLin(a,v0,alpha,dt=0.001):
    X = [0]
    Y = [0]
    t=0
    g = 10
    while Y[-1] \ge 0:
        t=t+dt
        X.append(v0*np.cos(a)/alpha*(1-np.exp(-alpha*t)))
        Y.append((v0*np.sin(a)*alpha+g)/alpha**2*(1-np.exp(-alpha*t))-g*t/alpha)
    return X, Y
# Question 3
v0 = 10
alpha=1
plt.plot(*FrotLin(np.pi/4,v0,alpha))
plt.plot(*FrotLin(np.pi/3,v0,alpha))
plt.plot(*FrotLin(np.pi/6,v0,alpha))
plt.axis("scaled")
# Question 4
def AngleOptimal(v0,alpha,da=np.pi/180):
    maxdist=0
    aopt=0
    a=da
    while a < np. pi/2:
        X,Y=FrotLin(a,v0,alpha)
        if X[-1] > maxdist:
            aopt=a
            \max dist=X[-1]
        a+=da
    return aopt, maxdist
# Question 5
a,d=AngleOptimal(v0,alpha)
print("v0=",v0,"alpha=",alpha)
print("Angle optimal : ",a,"Distance parcourue : ",d)
plt.plot(*FrotLin(a,v0,alpha))
plt.axis("scaled")
plt.figure()
v0=5
alpha=1
plt.plot(*FrotLin(np.pi/4,v0,alpha))
plt.plot(*FrotLin(np.pi/3,v0,alpha))
plt.plot(*FrotLin(np.pi/6,v0,alpha))
a,d=AngleOptimal(v0,alpha)
print("v0=",v0,"alpha=",alpha)
print("Angle optimal : ",a,"Distance parcourue :",d)
plt.plot(*FrotLin(a,v0,alpha))
```

```
plt.axis("scaled")
plt.figure()
v0=50
alpha=1
plt.plot(*FrotLin(np.pi/4,v0,alpha))
plt.plot(*FrotLin(np.pi/3,v0,alpha))
plt.plot(*FrotLin(np.pi/6,v0,alpha))
a,d=AngleOptimal(v0,alpha)
print("v0=",v0,"alpha=",alpha)
print("Angle optimal : ",a,"Distance parcourue : ",d)
plt.plot(*FrotLin(a,v0,alpha))
plt.axis("scaled")
plt.figure()
v0=10
alpha=0.2
plt.plot(*FrotLin(np.pi/4,v0,alpha))
plt.plot(*FrotLin(np.pi/3,v0,alpha))
plt.plot(*FrotLin(np.pi/6,v0,alpha))
a,d=AngleOptimal(v0,alpha)
print("v0=",v0,"alpha=",alpha)
print("Angle optimal : ",a,"Distance parcourue :",d)
plt.plot(*FrotLin(a,v0,alpha))
plt.axis("scaled")
```



```
# Section II
def FrotLin2(a,v0,alpha,dt=0.001):
    X=[0]
    Y=[0]
    vx=[v0*np.cos(a)]
    vy=[v0*np.sin(a)]
    g=10
    while Y[-1]>=0:
        X.append(X[-1]+vx[-1]*dt)
        Y.append(Y[-1]+vy[-1]*dt)
```

```
vx.append(vx[-1]-alpha*vx[-1]*dt)
        vy.append(vy[-1]-alpha*vy[-1]*dt-g*dt)
    return X,Y
plt.figure()
v0=10
alpha=1
plt.plot(*FrotLin(np.pi/4,v0,alpha))
plt.plot(*FrotLin2(np.pi/4,v0,alpha,dt=0.001))
plt.title('Trajectoires theoriques et numeriques\nFrottements lineaires')
plt.legend(['Theorique', 'Methode d\'Euler'])
plt.axis('scaled')
def AngleOptimal2(v0,alpha,da=np.pi/180,dt=0.001):
    maxdist=0
    aopt=0
    a=da
    while a < np. pi/2:
        X,Y=FrotLin2(a,v0,alpha,dt=dt)
        if X[-1] > maxdist:
            aopt=a
            \max dist = X[-1]
        a+=da
    return aopt, maxdist
a,d=AngleOptimal(v0,alpha)
print("Angle optimal, calculé avec la primitivation theorique:",a,d)
a,d=AngleOptimal2(v0,alpha)
print("Angle optimal, calculé avec la methode d'Euler :",a,d)
# Section III
def FrotNonLin(a,v0,alpha,beta,dt=0.001):
    X = [0]
    Y = [0]
    vx = [v0*np.cos(a)]
    vy=[v0*np.sin(a)]
    g = 10
    while Y[-1] >= 0:
        X.append(X[-1]+vx[-1]*dt)
        Y.append(Y[-1]+vy[-1]*dt)
        v = (vx[-1] **2 + vy[-1] **2) **0.5
        vx.append(vx[-1]-alpha*vx[-1]*dt-beta*vx[-1]*v*dt)
        vy.append(vy[-1]-alpha*vy[-1]*dt-beta*vy[-1]*v*dt-g*dt)
    return X,Y
plt.figure()
v0=10
alpha=0.2
beta=0.05
plt.plot(*FrotLin2(np.pi/4,v0,alpha,dt=0.001))
plt.plot(*FrotNonLin(np.pi/4,v0,alpha,beta,dt=0.001))
def AngleOptimal3(v0,alpha,beta,da=np.pi/180,dt=0.001):
```

```
maxdist=0
aopt=0
a=da
while a<np.pi/2:
    X,Y=FrotNonLin(a,v0,alpha,beta,dt=dt)
    if X[-1]>maxdist:
        aopt=a
        maxdist=X[-1]
    a+=da
    return aopt,maxdist

a,d=AngleOptimal3(v0,alpha,beta)
plt.plot(*FrotNonLin(a,v0,alpha,beta,dt=0.001))
plt.axis('scaled')
plt.title('Trajectoire numerique\nFrottements non lineaires et lineaires\nAngles : 45° et op
plt.legend(['Frottements lineaires 45°','Frottements non lineaires 45°','Non lineaires, distant
```

