

Encoding

Living Standard — Last Updated 29 June 2020



Participate:

[GitHub whatwg/encoding](#) ([new issue](#), [open issues](#))

[IRC: #whatwg on Freenode](#)

Commits:

[GitHub whatwg/encoding/commits](#)

[Snapshot as of this commit](#)

[@encodings](#)

Tests:

[web-platform-tests encoding/](#) ([ongoing work](#))

Translations (non-normative):

[日本語](#)

Abstract

The Encoding Standard defines encodings and their JavaScript API.

Table of Contents

- [1 Preface](#)
- [2 Security background](#)
- [3 Terminology](#)
- [4 Encodings](#)
 - [4.1 Encoders and decoders](#)
 - [4.2 Names and labels](#)
 - [4.3 Output encodings](#)
- [5 Indexes](#)
- [6 Hooks for standards](#)
- [7 API](#)
 - [7.1 Interface mixin `TextDecoderCommon`](#)
 - [7.2 Interface `TextDecoder`](#)
 - [7.3 Interface mixin `TextEncoderCommon`](#)
 - [7.4 Interface `TextEncoder`](#)
 - [7.5 Interface mixin `GenericTransformStream`](#)
 - [7.6 Interface `TextDecoderStream`](#)
 - [7.7 Interface `TextEncoderStream`](#)
- [8 The encoding](#)
 - [8.1 UTF-8](#)
 - [8.1.1 UTF-8 decoder](#)
 - [8.1.2 UTF-8 encoder](#)
- [9 Legacy single-byte encodings](#)
 - [9.1 single-byte decoder](#)
 - [9.2 single-byte encoder](#)
- [10 Legacy multi-byte Chinese \(simplified\) encodings](#)
 - [10.1 GBK](#)
 - [10.1.1 GBK decoder](#)
 - [10.1.2 GBK encoder](#)
 - [10.2 gb18030](#)
 - [10.2.1 gb18030 decoder](#)
 - [10.2.2 gb18030 encoder](#)
- [11 Legacy multi-byte Chinese \(traditional\) encodings](#)
 - [11.1 Big5](#)
 - [11.1.1 Big5 decoder](#)
 - [11.1.2 Big5 encoder](#)
- [12 Legacy multi-byte Japanese encodings](#)
 - [12.1 EUC-JP](#)
 - [12.1.1 EUC-JP decoder](#)
 - [12.1.2 EUC-JP encoder](#)
 - [12.2 ISO-2022-JP](#)
 - [12.2.1 ISO-2022-JP decoder](#)
 - [12.2.2 ISO-2022-JP encoder](#)
 - [12.3 Shift JIS](#)
 - [12.3.1 Shift JIS decoder](#)
 - [12.3.2 Shift JIS encoder](#)
- [13 Legacy multi-byte Korean encodings](#)
 - [13.1 EUC-KR](#)
 - [13.1.1 EUC-KR decoder](#)
 - [13.1.2 EUC-KR encoder](#)

[14 Legacy miscellaneous encodings](#)

[14.1 replacement](#)

[14.1.1 replacement decoder](#)

[14.2 Common infrastructure for UTF-16BE and UTF-16LE](#)

[14.2.1 shared UTF-16 decoder](#)

[14.3 UTF-16BE](#)

[14.3.1 UTF-16BE decoder](#)

[14.4 UTF-16LE](#)

[14.4.1 UTF-16LE decoder](#)

[14.5 x-user-defined](#)

[14.5.1 x-user-defined decoder](#)

[14.5.2 x-user-defined encoder](#)

[15 Browser UI](#)

[Implementation considerations](#)

[Acknowledgments](#)

[Index](#)

[Terms defined by this specification](#)

[Terms defined by reference](#)

[References](#)

[Normative References](#)

[Informative References](#)

[IDL Index](#)

1. Preface §

The UTF-8 encoding is the most appropriate encoding for interchange of Unicode, the universal coded character set. Therefore for new protocols and formats, as well as existing formats deployed in new contexts, this specification requires (and defines) the UTF-8 encoding.

The other (legacy) encodings have been defined to some extent in the past. However, user agents have not always implemented them in the same way, have not always used the same labels, and often differ in dealing with undefined and former proprietary areas of encodings. This specification addresses those gaps so that new user agents do not have to reverse engineer encoding implementations and existing user agents can converge.


In particular, this specification defines all those encodings, their algorithms to go from bytes to scalar values and back, and their canonical names and identifying labels. This specification also defines an API to expose part of the encoding algorithms to JavaScript.

User agents have also significantly deviated from the labels listed in the [IANA Character Sets registry](#). To stop spreading legacy encodings further, this specification is exhaustive about the aforementioned details and therefore has no need for the registry. In particular, this specification does not provide a mechanism for extending any aspect of encodings.

2. Security background §

There is a set of encoding security issues when the producer and consumer do not agree on the encoding in use, or on the way a given encoding is to be implemented. For instance, an attack was reported in 2011 where a [Shift_JIS](#) lead byte 0x82 was used to “mask” a 0x22 trail byte in a JSON resource of which an attacker could control some field. The producer did not see the problem even though this is an illegal byte combination. The consumer decoded it as a single U+FFFD and therefore changed the overall interpretation as U+0022 is an important delimiter. Decoders of encodings that use multiple bytes for scalar values now require that in case of an illegal byte combination, a scalar value in the range U+0000 to U+007F, inclusive, cannot be “masked”. For the aforementioned sequence the output would be U+FFFD U+0022.

This is a larger issue for encodings that map anything that is an [ASCII byte](#) to something that is not an [ASCII code point](#), when there is no lead byte present. These are “ASCII-incompatible” encodings and other than [ISO-2022-JP](#), [UTF-16BE](#), and [UTF-16LE](#), which are unfortunately required due to deployed content, they are not supported. (Investigation is [ongoing](#) whether more labels of other such encodings can be mapped to the [replacement](#) encoding, rather than the unknown encoding fallback.) An example attack is injecting carefully crafted content into a resource and then encouraging the user to override the encoding, resulting in e.g. script execution.

Encoders used by URLs found in HTML and HTML’s form feature can also result in slight information loss when an encoding is used that cannot represent all scalar values. E.g. when a resource uses the [windows-1252](#) encoding a server will not be able to distinguish between an end user entering “” and “💩” into a form.

The problems outlined here go away when exclusively using UTF-8, which is one of the many reasons that is now the mandatory encoding for all things.

Note

See also the [Browser UI](#) chapter.

3. Terminology §

This specification depends on the Infra Standard. [\[INFRA\]](#)

Hexadecimal numbers are prefixed with "0x".

In equations, all numbers are integers, addition is represented by "+", subtraction by "-", multiplication by "x", integer division by "/" (returns the quotient), modulo by "%" (returns the remainder of an integer division), logical left shifts by "<<", logical right shifts by ">>", bitwise AND by "&", and bitwise OR by "|".

For logical right shifts operands must have at least twenty-one bits precision.

A **token** is a piece of data, such as a [byte](#) or [scalar value](#).

A **stream** represents an ordered sequence of [tokens](#). **End-of-stream** is a special [token](#) that signifies no more [tokens](#) are in the [stream](#).

When a [token](#) is **read** from a [stream](#), the first token in the stream must be returned and subsequently removed, and [end-of-stream](#) must be returned otherwise.

When one or more [tokens](#) are **prepended** to a [stream](#), those tokens must be inserted, in given order, before the first token in the stream.

Example

Inserting the sequence of tokens `💩` in a stream `" hello world"`, results in a stream `"💩 hello world"`. The next token to be read would be `&`.

When one or more [tokens](#) are **pushed** to a [stream](#), those tokens must be inserted, in given order, after the last token in the stream.

4. Encodings §

An **encoding** defines a mapping from a [scalar value](#) sequence to a [byte](#) sequence (and vice versa). Each [encoding](#) has a **name**, and one or more **labels**.

Note

This specification defines three [encodings](#) with the same names as encoding schemes defined in the Unicode standard: [UTF-8](#), [UTF-16LE](#), and [UTF-16BE](#). The [encodings](#) differ from the encoding schemes by byte order mark (also known as BOM) handling not being part of the [encodings](#) themselves and instead being part of wrapper algorithms in this specification, whereas byte order mark handling is part of the definition of the encoding schemes in the Unicode Standard. [UTF-8](#) used together with the [UTF-8 decode](#) algorithm matches the encoding scheme of the same name. This specification does not provide wrapper algorithms that would combine with [UTF-16LE](#) and [UTF-16BE](#) to match the similarly-named encoding schemes. [\[UNICODE\]](#)

4.1. Encoders and decoders §

Each [encoding](#) has an associated **decoder** and most of them have an associated **encoder**. Each [decoder](#) and [encoder](#) have a **handler** algorithm. A [handler](#) algorithm takes an input [stream](#) and a [token](#), and returns **finished**, one or more [tokens](#), **error** optionally with a [code point](#), or **continue**.

Note

The [replacement](#), [UTF-16BE](#), and [UTF-16LE](#) encodings have no [encoder](#).

An **error mode** as used below is "replacement" (default) or "fatal" for a [decoder](#) and "fatal" (default) or "html" for an [encoder](#).

Note

An XML processor would set [error mode](#) to "fatal". [\[XML\]](#)

Note

html exists as [error mode](#) due to URLs and HTML forms requiring a non-terminating legacy [encoder](#). The "html" [error mode](#) causes a sequence to be emitted that cannot be distinguished from legitimate input and can therefore lead to silent data loss. Developers are strongly encouraged to use the [UTF-8 encoding](#) to prevent this from happening. [\[URL\]](#) [\[HTML\]](#)

To run an [encoding](#)'s [decoder](#) or [encoder](#) `encoderDecoder` with input [stream](#) input, output [stream](#) output, and optional [error mode](#) mode, run these steps:

1. If *mode* is not given, then set it to "replacement" if *encoderDecoder* is a [decoder](#), otherwise "fatal".
2. Let *encoderDecoderInstance* be a new *encoderDecoder*.
3. While true:
 1. Let *result* be the result of [processing](#) the result of [reading](#) from *input* for *encoderDecoderInstance*, *input*, *output*, and *mode*.
 2. If *result* is not [continue](#), return *result*.
 3. Otherwise, do nothing.

To process a [token](#) token for an [encoding](#)'s [encoder](#) or [decoder](#) instance *encoderDecoderInstance*, [stream](#) input, output [stream](#) output, and optional [error mode](#) mode, run these steps:

1. If *mode* is not given, then set it to "replacement" if *encoderDecoderInstance* is a [decoder](#) instance, otherwise "fatal".
2. Assert: if *encoderDecoderInstance* is an [encoder](#) instance, *token* is not a [surrogate](#).
3. Let *result* be the result of running *encoderDecoderInstance*'s [handler](#) on *input* and *token*.

4. If *result* is [continue](#) or [finished](#), return *result*.
5. Otherwise, if *result* is one or more [tokens](#):
1. Assert: if *encoderDecoderInstance* is a [decoder](#) instance, *result* does not contain any [surrogates](#).
 2. [Push](#) *result* to *output*.
6. Otherwise, if *result* is [error](#), switch on *mode* and run the associated steps:
- ☐ "replacement"

[Push](#) U+FFFD to *output*.
- ☐ "html"

[Prepend](#) U+0026, U+0023, followed by the shortest sequence of [ASCII digits](#) representing *result*'s [code point](#) in base ten, followed by U+003B to *input*.
- ☐ "fatal"

Return [error](#).
7. Return [continue](#).

4.2. Names and labels §

The table below lists all [encodings](#) and their [labels](#) user agents must support. User agents must not support any other [encodings](#) or [labels](#).

Note

For each encoding, [ASCII-lowercasing its name](#) yields one of its [labels](#).

Authors must use the [UTF-8 encoding](#) and must use the [ASCII case-insensitive](#) "utf-8" [label](#) to identify it.

New protocols and formats, as well as existing formats deployed in new contexts, must use the [UTF-8 encoding](#) exclusively. If these protocols and formats need to expose the [encoding's name](#) or [label](#), they must expose it as "utf-8".

To **get an encoding** from a string *label*, run these steps:

1. Remove any leading and trailing [ASCII whitespace](#) from *label*.
2. If *label* is an [ASCII case-insensitive](#) match for any of the [labels](#) listed in the table below, then return the corresponding [encoding](#); otherwise return failure.

Note

This is a more basic and restrictive algorithm of mapping [labels](#) to [encodings](#) than [section 1.4 of Unicode Technical Standard #22](#) prescribes, as that is necessary to be compatible with deployed content.

Name	Labels
The Encoding	
UTF-8	"unicode-1-1-utf-8"
	"unicode11utf8"
	"unicode20utf8"
	"utf-8"
	"utf8"
	"x-unicode20utf8"
Legacy single-byte encodings	

<u>Name</u>	<u>Labels</u>
IBM866	"866"
	"cp866"
	"csibm866"
	"ibm866"
ISO-8859-2	"csisolatin2"
	"iso-8859-2"
	"iso-ir-101"
	"iso8859-2"
	"iso88592"
	"iso_8859-2"
	"iso_8859-2:1987"
	"l2"
	"latin2"
ISO-8859-3	"csisolatin3"
	"iso-8859-3"
	"iso-ir-109"
	"iso8859-3"
	"iso88593"
	"iso_8859-3"
	"iso_8859-3:1988"
	"l3"
	"latin3"
ISO-8859-4	"csisolatin4"
	"iso-8859-4"
	"iso-ir-110"
	"iso8859-4"
	"iso88594"
	"iso_8859-4"
	"iso_8859-4:1988"
	"l4"
	"latin4"
ISO-8859-5	"csisolatincyrillic"
	"cyrillic"
	"iso-8859-5"
	"iso-ir-144"
	"iso8859-5"
	"iso88595"
	"iso_8859-5"
	"iso_8859-5:1988"
ISO-8859-6	"arabic"
	"asmo-708"
	"csiso88596e"
	"csiso88596i"
	"csisolatinarabic"
	"ecma-114"

Name	Labels
	"iso-8859-6"
	"iso-8859-6-e"
	"iso-8859-6-i"
	"iso-ir-127"
	"iso8859-6"
	"iso88596"
	"iso_8859-6"
	"iso_8859-6:1987"
ISO-8859-7	"csisolatingreek"
	"ecma-118"
	"elot_928"
	"greek"
	"greek8"
	"iso-8859-7"
	"iso-ir-126"
	"iso8859-7"
	"iso88597"
	"iso_8859-7"
	"iso_8859-7:1987"
	"sun_eu_greek"
ISO-8859-8	"csiso88598e"
	"csisolatinhebrew"
	"hebrew"
	"iso-8859-8"
	"iso-8859-8-e"
	"iso-ir-138"
	"iso8859-8"
	"iso88598"
	"iso_8859-8"
	"iso_8859-8:1988"
	"visual"
ISO-8859-8-I	"csiso88598i"
	"iso-8859-8-i"
	"logical"
ISO-8859-10	"csisolatin6"
	"iso-8859-10"
	"iso-ir-157"
	"iso8859-10"
	"iso885910"
	"l6"
	"latin6"
ISO-8859-13	"iso-8859-13"
	"iso8859-13"
	"iso885913"
ISO-8859-14	"iso-8859-14"

Name	Labels
	"iso8859-14"
	"iso885914"
ISO-8859-15	"csisolatin9"
	"iso-8859-15"
	"iso8859-15"
	"iso885915"
	"iso_8859-15"
	"l9"
ISO-8859-16	"iso-8859-16"
KOI8-R	"cskoi8r"
	"koi"
	"koi8"
	"koi8-r"
	"koi8_r"
KOI8-U	"koi8-ru"
	"koi8-u"
macintosh	"csmacintosh"
	"mac"
	"macintosh"
	"x-mac-roman"
windows-874	"dos-874"
	"iso-8859-11"
	"iso8859-11"
	"iso885911"
	"tis-620"
	"windows-874"
windows-1250	"cp1250"
	"windows-1250"
	"x-cp1250"
windows-1251	"cp1251"
	"windows-1251"
	"x-cp1251"
windows-1252	"ansi_x3.4-1968"
	"ascii"
	"cp1252"
	"cp819"
	"csisolatin1"
	"ibm819"
	"iso-8859-1"
	"iso-ir-100"
	"iso8859-1"
	"iso88591"
	"iso_8859-1"
	"iso_8859-1:1987"
	"l1"

Name	Labels
	"latin1"
	"us-ascii"
	"windows-1252"
	"x-cp1252"
windows-1253	"cp1253"
	"windows-1253"
	"x-cp1253"
windows-1254	"cp1254"
	"csisolatin5"
	"iso-8859-9"
	"iso-ir-148"
	"iso8859-9"
	"iso88599"
	"iso_8859-9"
	"iso_8859-9:1989"
	"l5"
	"latin5"
	"windows-1254"
	"x-cp1254"
windows-1255	"cp1255"
	"windows-1255"
	"x-cp1255"
windows-1256	"cp1256"
	"windows-1256"
	"x-cp1256"
windows-1257	"cp1257"
	"windows-1257"
	"x-cp1257"
windows-1258	"cp1258"
	"windows-1258"
	"x-cp1258"
x-mac-cyrillic	"x-mac-cyrillic"
	"x-mac-ukrainian"

[Legacy multi-byte Chinese \(simplified\) encodings](#)

GBK	"chinese"
	"csgb2312"
	"csiso58gb231280"
	"gb2312"
	"gb_2312"
	"gb_2312-80"
	"gbk"
	"iso-ir-58"
	"x-gbk"
gb18030	"gb18030"

[Legacy multi-byte Chinese \(traditional\) encodings](#)

Name	Labels
Big5	"big5"
	"big5-hkscs"
	"cn-big5"
	"csbig5"
	"x-x-big5"

[Legacy multi-byte Japanese encodings](#)

EUC-JP	"cseucpkdfmtjapanese"
	"euc-jp"
	"x-euc-jp"
ISO-2022-JP	"csiso2022jp"
	"iso-2022-jp"
Shift JIS	"csshiftjis"
	"ms932"
	"ms_kanji"
	"shift-jis"
	"shift_jis"
	"sjis"
	"windows-31j"
	"x-sjis"

[Legacy multi-byte Korean encodings](#)

EUC-KR	"cseuckr"
	"csksc56011987"
	"euc-kr"
	"iso-ir-149"
	"korean"
	"ks_c_5601-1987"
	"ks_c_5601-1989"
	"ksc5601"
	"ksc_5601"
	"windows-949"

[Legacy miscellaneous encodings](#)

replacement	"csiso2022kr"
	"hz-gb-2312"
	"iso-2022-cn"
	"iso-2022-cn-ext"
	"iso-2022-kr"
	"replacement"
UTF-16BE	"unicodeffff"
	"utf-16be"
UTF-16LE	"csunicode"
	"iso-10646-ucs-2"
	"ucs-2"
	"unicode"
	"unicodefeff"
	"utf-16"

Name	Labels
	"utf-16le"
x-user-defined	"x-user-defined"

Note

All [encodings](#) and their [labels](#) are also available as non-normative [encodings.json](#) resource.

Note

The set of supported [encodings](#) is primarily based on the intersection of the sets supported by major browser engines when the development of this standard started, while removing encodings that were rarely used legitimately but that could be used in attacks. The inclusion of some encodings is questionable in the light of anecdotal evidence of the level of use by existing Web content. That is, while they have been broadly supported by browsers, it is unclear if they are broadly used by Web content. However, an effort has not been made to eagerly remove [single-byte encodings](#) that were broadly supported by browsers or are part of the ISO 8859 series. In particular, the necessity of the inclusion of [IBM866](#), [macintosh](#), [x-mac-cyrillic](#), [ISO-8859-3](#), [ISO-8859-10](#), [ISO-8859-14](#), and [ISO-8859-16](#) is doubtful for the purpose of supporting existing content, but there are no plans to remove these.

4.3. Output encodings §

To **get an output encoding** from an [encoding](#) encoding, run these steps:

1. If *encoding* is [replacement](#), [UTF-16BE](#), or [UTF-16LE](#), return [UTF-8](#).
2. Return *encoding*.

Note

The [get an output encoding](#) algorithm is useful for URL parsing and HTML form submission, which both need exactly this.

5. Indexes §

Most legacy [encodings](#) make use of an **index**. An [index](#) is an ordered list of entries, each entry consisting of a pointer and a corresponding code point. Within an [index](#) pointers are unique and code points can be duplicated.

Note

An efficient implementation likely has two [indexes](#) per [encoding](#). One optimized for its [decoder](#) and one for its [encoder](#).

To find the pointers and their corresponding code points in an [index](#), let *lines* be the result of splitting the resource's contents on U+000A. Then remove each item in *lines* that is the empty string or starts with U+0023. Then the pointers and their corresponding code points are found by splitting each item in *lines* on U+0009. The first subitem is the pointer (as a decimal number) and the second is the corresponding code point (as a hexadecimal number). Other subitems are not relevant.

Note

To signify changes an [index](#) includes an Identifier and a Date. If an Identifier has changed, so has the [index](#).

The **index code point** for *pointer* in *index* is the code point corresponding to *pointer* in *index*, or null if *pointer* is not in *index*.

The **index pointer** for *code point* in *index* is the *first* pointer corresponding to *code point* in *index*, or null if *code point* is not in *index*.

Note

There is a non-normative visualization for each [index](#) other than [index gb18030 ranges](#) and [index ISO-2022-JP katakana](#). [index jis0208](#) also has an alternative [Shift_JIS](#) visualization. Additionally, there is visualization of the Basic Multilingual Plane coverage of each [index](#) other than [index gb18030 ranges](#) and [index ISO-2022-JP katakana](#).

The legend for the visualizations is:

- *Unmapped*
- *Two bytes in UTF-8*
- *Two bytes in UTF-8, code point follows immediately the code point of previous pointer*
- *Three bytes in UTF-8 (non-PUA)*
- *Three bytes in UTF-8 (non-PUA), code point follows immediately the code point of previous pointer*
- *Private Use*
- *Private Use, code point follows immediately the code point of previous pointer*
- *Four bytes in UTF-8*
- *Four bytes in UTF-8, code point follows immediately the code point of previous pointer*
- *Duplicate code point already mapped at an earlier index*
- *CJK Compatibility Ideograph*
- *CJK Unified Ideographs Extension A*

These are the [indexes](#) defined by this specification, excluding [index single-byte](#), which have their own table:

Index				Notes
index Big5	index-big5.txt	index Big5 visualization	index Big5 BMP coverage	This matches the Big5 standard in combination with the Hong Kong Supplementary Character Set and other common extensions.
index EUC-KR	index-euc-kr.txt	index EUC-KR visualization	index EUC-KR BMP coverage	This matches the KS X 1001 standard and the Unified Hangul Code, more commonly known together as Windows Codepage 949. It covers the Hangul Syllables block of Unicode in its entirety. The Hangul block whose top left corner in the visualization is at pointer 9026 is in the Unicode order. Taken separately, the rest of the Hangul syllables in this index are in the Unicode order, too.
index gb18030	index-gb18030.txt	index gb18030 visualization	index gb18030 BMP coverage	This matches the GB18030-2005 standard for code points encoded as two bytes, except for 0xA3 0xA0 which maps to U+3000 to be compatible with deployed content. This index covers the CJK Unified Ideographs block of Unicode in its entirety. Entries from that block that are above or to the left of (the first) U+3000 in the visualization are in the Unicode order.
index gb18030 ranges	index-gb18030-ranges.txt			This index works different from all others. Listing all code points would result in over a million items whereas they can be represented neatly in 207 ranges combined with trivial limit checks. It therefore only superficially matches the GB18030-2005 standard for code points encoded as four bytes. See also index gb18030 ranges code point and index gb18030 ranges pointer below.
index jis0208	index-jis0208.txt	index jis0208 visualization, Shift JIS visualization	index jis0208 BMP coverage	This is the JIS X 0208 standard including formerly proprietary extensions from IBM and NEC.
index jis0212	index-jis0212.txt	index jis0212 visualization	index jis0212 BMP coverage	This is the JIS X 0212 standard. It is only used by the EUC-JP decoder due to lack of widespread support elsewhere.
index ISO-2022-JP katakana	index-iso-2022-jp-katakana.txt			This maps halfwidth to fullwidth katakana as per Unicode Normalization Form KC, except that U+FF9E and U+FF9F map to U+309B and U+309C rather than U+3099 and U+309A. It is only used by the ISO-2022-JP encoder . [UNICODE]

The **index gb18030 ranges code point** for *pointer* is the return value of these steps:

1. If *pointer* is greater than 39419 and less than 189000, or *pointer* is greater than 1237575, return null.
2. If *pointer* is 7457, return code point U+E7C7.
3. Let *offset* be the last pointer in [index gb18030 ranges](#) that is less than or equal to *pointer* and let *code point offset* be its corresponding code point.
4. Return a code point whose value is *code point offset* + *pointer* – *offset*.

The **index gb18030 ranges pointer** for *code point* is the return value of these steps:

1. If *code point* is U+E7C7, return pointer 7457.
2. Let *offset* be the last code point in [index gb18030 ranges](#) that is less than or equal to *code point* and let *pointer offset* be its corresponding pointer.
3. Return a pointer whose value is *pointer offset* + *code point* – *offset*.

The **index Shift_JIS pointer** for *code point* is the return value of these steps:

1. Let *index* be [index jis0208](#) excluding all entries whose pointer is in the range 8272 to 8835, inclusive.

Note

The [index jis0208](#) contains duplicate code points so the exclusion of these entries causes later code points to be used.

2. Return the [index pointer](#) for *code point* in *index*.

The **index Big5 pointer** for *code point* is the return value of these steps:

1. Let *index* be [index Big5](#) excluding all entries whose pointer is less than $(0xA1 - 0x81) \times 157$.

Note

Avoid returning Hong Kong Supplementary Character Set extensions literally.

2. If *code point* is U+2550, U+255E, U+2561, U+256A, U+5341, or U+5345, return the *last* pointer corresponding to *code point* in *index*.

Note

There are other duplicate code points, but for those the first pointer is to be used.

3. Return the [index pointer](#) for *code point* in *index*.

Note

All [indexes](#) are also available as a non-normative [indexes.json](#) resource. ([Index gb18030 ranges](#) has a slightly different format here, to be able to represent ranges.)

6. Hooks for standards §

Note

The algorithms defined below ([decode](#), [UTF-8 decode](#), [UTF-8 decode without BOM](#), [UTF-8 decode without BOM or fail](#), [encode](#), [UTF-8 encode](#), and [BOM sniff](#)) are intended for usage by other standards.

For decoding, [UTF-8 decode](#) is to be used by new formats. For identifiers or byte sequences within a format or protocol, use [UTF-8 decode without BOM](#) or [UTF-8 decode without BOM or fail](#).

For encoding, [UTF-8 encode](#) is to be used.

Standards are strongly discouraged from using [decode](#), [encode](#), and [BOM sniff](#), except as needed for compatibility.

The [get an encoding](#) algorithm is to be used to turn a [label](#) into an [encoding](#).

Standards are to ensure that the streams they pass to the [encode](#) and [UTF-8 encode](#) algorithms are effectively scalar value streams, i.e., they contain no [surrogates](#).

To **decode** a byte stream *stream* using fallback encoding *encoding*, run these steps:

1. Let *BOMEncoding* be the result of [BOM sniffing](#) *stream*.
2. If *BOMEncoding* is non-null:
 1. Set *encoding* to *BOMEncoding*.
 2. [Read](#) three bytes from *stream*, if *BOMEncoding* is [UTF-8](#); otherwise [read](#) two bytes. (Do nothing with those bytes.)

Note

For compatibility with deployed content, the byte order mark is more authoritative than anything else. In a context where HTTP is used this is in violation of the semantics of the `Content-Type` header.

3. Let *output* be a scalar value [stream](#).
4. [Run](#) *encoding*'s [decoder](#) with *stream* and *output*.
5. Return *output*.

To **UTF-8 decode** a byte stream *stream*, run these steps:

1. Let *buffer* be an empty byte sequence.
2. [Read](#) three bytes from *stream* into *buffer*.
3. If *buffer* does not match 0xEF 0xBB 0xBF, [prepend](#) *buffer* to *stream*.
4. Let *output* be a scalar value [stream](#).
5. [Run](#) [UTF-8](#)'s [decoder](#) with *stream* and *output*.
6. Return *output*.

To **UTF-8 decode without BOM** a byte stream *stream*, run these steps:

1. Let *output* be a scalar value [stream](#).
2. [Run](#) [UTF-8](#)'s [decoder](#) with *stream* and *output*.
3. Return *output*.

To **UTF-8 decode without BOM or fail** a byte stream *stream*, run these steps:

1. Let *output* be a scalar value *stream*.

2. Let *potentialError* be the result of [running UTF-8's decoder](#) with *stream*, *output*, and "fatal".
3. If *potentialError* is [error](#), return failure.
4. Return *output*.

To **encode** a scalar value stream *stream* using encoding *encoding*, run these steps:

1. Assert: *encoding* is not [replacement](#), [UTF-16BE](#) or [UTF-16LE](#).
2. Let *output* be a byte [stream](#).
3. [Run](#) *encoding*'s [encoder](#) with *stream*, *output*, and "html".
4. Return *output*.

Note

This is mostly a legacy hook for URLs and HTML forms. Layering [UTF-8 encode](#) on top is safe as it never triggers [errors](#). [\[URL\]](#) [\[HTML\]](#)

To **UTF-8 encode** a scalar value stream *stream*, return the result of [encoding](#) *stream* using encoding [UTF-8](#).

To **BOM sniff** a byte stream *stream*, run these steps:

1. Wait until *stream* has three bytes available or the [end-of-stream](#) has been reached, whichever comes first.
2. For each of the rows in the table below, starting with the first one and going down, if *stream* [starts with](#) the bytes given in the first column, return the [encoding](#) given in the cell in the second column of that row. (Do not consume those bytes.)

Byte order mark	Encoding
0xEF 0xBB 0xBF	UTF-8
0xFE 0xFF	UTF-16BE
0xFF 0xFE	UTF-16LE

3. Return null.

Note

This hook is a workaround for the fact that [decode](#) has no way to communicate back to the caller that it has found a byte order mark and is therefore not using the provided encoding. The hook is to be invoked before [decode](#), and it will return an encoding corresponding to the byte order mark found, or null otherwise.

7. API §

This section uses terminology from Web IDL. Browser user agents must support this API. JavaScript implementations should support this API. Other user agents or programming languages are encouraged to use an API suitable to their needs, which might not be this one. [\[WEBIDL\]](#)

Example

The following example uses the [TextEncoder](#) object to encode an array of strings into an [ArrayBuffer](#). The result is a [Uint8Array](#) containing the number of strings (as a [Uint32Array](#)), followed by the length of the first string (as a [Uint32Array](#)), the [UTF-8](#) encoded string data, the length of the second string (as a [Uint32Array](#)), the string data, and so on.

```
function encodeArrayOfStrings(strings) {
    var encoder, encoded, len, bytes, view, offset;

    encoder = new TextEncoder();
    encoded = [];

    len = Uint32Array.BYTES_PER_ELEMENT;
    for (var i = 0; i < strings.length; i++) {
        len += Uint32Array.BYTES_PER_ELEMENT;
        encoded[i] = encoder.encode(strings[i]);
        len += encoded[i].byteLength;
    }

    bytes = new Uint8Array(len);
    view = new DataView(bytes.buffer);
    offset = 0;

    view.setUint32(offset, strings.length);
    offset += Uint32Array.BYTES_PER_ELEMENT;
    for (var i = 0; i < encoded.length; i += 1) {
        len = encoded[i].byteLength;
        view.setUint32(offset, len);
        offset += Uint32Array.BYTES_PER_ELEMENT;
        bytes.set(encoded[i], offset);
        offset += len;
    }
    return bytes.buffer;
}
```

The following example decodes an [ArrayBuffer](#) containing data encoded in the format produced by the previous example, or an equivalent algorithm for encodings other than [UTF-8](#), back into an array of strings.

```
function decodeArrayOfStrings(buffer, encoding) {
    var decoder, view, offset, num_strings, strings, len;

    decoder = new TextDecoder(encoding);
    view = new DataView(buffer);
    offset = 0;
    strings = [];

    num_strings = view.getUint32(offset);
    offset += Uint32Array.BYTES_PER_ELEMENT;
    for (var i = 0; i < num_strings; i++) {
        len = view.getUint32(offset);
        offset += Uint32Array.BYTES_PER_ELEMENT;
        strings[i] = decoder.decode(
```

```

        new DataView(view.buffer, offset, len));
    offset += len;
}
return strings;
}

```

7.1. Interface mixin [TextDecoderCommon](#) §

IDL

```

interface mixin TextDecoderCommon {
    readonly attribute DOMString encoding;
    readonly attribute boolean fatal;
    readonly attribute boolean ignoreBOM;
};

```

The [TextDecoderCommon](#) interface mixin defines common getters that are shared between [TextDecoder](#) and [TextDecoderStream](#) objects. These objects have an associated:

encoding

An [encoding](#).

decoder

A [decoder](#).

stream

A [stream](#).

ignore BOM

A boolean, initially false.

BOM seen

A boolean, initially false.

error mode

An [error mode](#), initially "replacement".

The **serialize stream** algorithm, given a [TextDecoderCommon](#) *decoder* and a [stream](#) *stream*, runs these steps:

1. Let *output* be the empty string.
2. While true:
 1. Let *token* be the result of [reading](#) from *stream*.
 2. If *token* is [end-of-stream](#), then return *output*.
 3. If *decoder*'s [encoding](#) is [UTF-8](#), [UTF-16BE](#), or [UTF-16LE](#), and *decoder*'s [ignore BOM](#) and [BOM seen](#) are false, then:
 1. Set *decoder*'s [BOM seen](#) to true.
 2. If *token* is U+FEFF, then [continue](#).
 4. Append *token* to *output*.

Note

This algorithm is intentionally different with respect to BOM handling from the [decode](#) algorithm used by the rest of the platform to give API users more control.

The **encoding** getter steps are to return [this's encoding's name](#), [ASCII lowercased](#).

The **fatal** getter steps are to return true if [this's error mode](#) is "fatal", otherwise false.

The **ignoreBOM** getter steps are to return [this's ignore BOM](#).

7.2. Interface **TextDecoder** §

IDL	<pre>dictionary TextDecoderOptions { boolean fatal = false; boolean ignoreBOM = false; }; dictionary TextDecodeOptions { boolean stream = false; }; [Exposed=(Window,Worker)] interface TextDecoder { constructor(optional DOMString label = "utf-8", optional TextDecoderOptions options = {}); USVString decode(optional [AllowShared] BufferSource input, optional TextDecodeOptions options = {}); }; TextDecoder includes TextDecoderCommon;</pre>
-----	---

A **TextDecoder** object has an associated **do not flush**, which is a boolean, initially false.

For web developers (non-normative)

`decoder = new TextDecoder([label = "utf-8" [, options]])`

Returns a new **TextDecoder** object.

If *label* is either not a [label](#) or is a [label](#) for [replacement](#), [throws a RangeError](#).

`decoder . encoding`

Returns [encoding's name](#), lowercased.

`decoder . fatal`

Returns true if [error mode](#) is "fatal", otherwise false.

`decoder . ignoreBOM`

Returns the value of [ignore BOM](#).

`decoder . decode([input [, options]])`

Returns the result of running [encoding's decoder](#). The method can be invoked zero or more times with *options's* [stream](#) set to true, and then once without *options's* [stream](#) (or set to false), to process a fragmented stream. If the invocation without *options's* [stream](#) (or set to false) has no *input*, it's clearest to omit both arguments.

¶ Example

```
var string = "", decoder = new TextDecoder(encoding), buffer;  
while(buffer = next_chunk()) {  
  string += decoder.decode(buffer, {stream:true});  
}  
string += decoder.decode(); // end-of-stream
```

If the [error mode](#) is "fatal" and [encoding's decoder](#) returns [error](#), [throws a TypeError](#).

The **`new TextDecoder(label, options)`** constructor steps are:

1. Let *encoding* be the result of [getting an encoding](#) from *label*.
2. If *encoding* is failure or [replacement](#), then [throw](#) a [RangeError](#).
3. Set *this*'s [encoding](#) to *encoding*.
4. If *options*["[fatal](#)"] is true, then set *this*'s [error mode](#) to "fatal".
5. Set *this*'s [ignore BOM](#) to *options*["[ignoreBOM](#)"].

The **`decode(input, options)`** method steps are:

1. If *this*'s [do not flush](#) is false, then set *this*'s [decoder](#) to a new [decoder](#) for *this*'s [encoding](#), *this*'s [stream](#) to a new [stream](#), and *this*'s [BOM seen](#) to false.
2. Set *this*'s [do not flush](#) to *options*["[stream](#)"].
3. If *input* is given, then [push](#) a [copy of input](#) to *this*'s [stream](#).

Note

Implementations are strongly encouraged to use an implementation strategy that avoids this copy. When doing so they will have to make sure that changes to input do not affect future calls to [decode\(\)](#).

⚠ Warning!

The memory exposed by SharedArrayBuffer objects does not adhere to data race freedom properties required by the memory model of programming languages typically used for implementations. When implementing, take care to use the appropriate facilities when accessing memory exposed by SharedArrayBuffer objects.

4. Let *output* be a new [stream](#).
5. While true:
 1. Let *token* be the result of [reading](#) from *this*'s [stream](#).
 2. If *token* is [end-of-stream](#) and *this*'s [do not flush](#) is true, then return the result of running [serialize stream](#) with *this* and *output*.

Note

*The way streaming works is to not handle [end-of-stream](#) here when *this*'s [do not flush](#) is true and to not set it to false. That way in a subsequent invocation *this*'s [decoder](#) is not set anew in the first step of the algorithm and its state is preserved.*

3. Otherwise:
 1. Let *result* be the result of [processing](#) *token* for *this*'s [decoder](#), *this*'s [stream](#), *output*, and *this*'s [error mode](#).
 2. If *result* is [finished](#), then return the result of running [serialize stream](#) with *this* and *output*.
 3. Otherwise, if *result* is [error](#), then [throw](#) a [TypeError](#).

7.3. Interface mixin [TextEncoderCommon](#) §

```
IDL
interface mixin TextEncoderCommon {
    readonly attribute DOMString encoding;
};
```

The [TextEncoderCommon](#) interface mixin defines common getters that are shared between [TextEncoder](#) and [TextEncoderStream](#) objects.

The [encoding](#) getter steps are to return "utf-8".

7.4. Interface [TextEncoder](#) §

```
IDL
dictionary TextEncoderEncodeIntoResult {
    unsigned long long read;
    unsigned long long written;
};

[Exposed=(Window,Worker)]
interface TextEncoder {
    constructor();

    [NewObject] Uint8Array encode(optional USVString input = "");
    TextEncoderEncodeIntoResult encodeInto(USVString source, [AllowShared] Uint8Array destination);
};
TextEncoder includes TextEncoderCommon;
```

Note

A [TextEncoder](#) object offers no label argument as it only supports [UTF-8](#). It also offers no stream option as no [encoder](#) requires buffering of scalar values.

For web developers (non-normative)

`encoder = new TextEncoder()`

Returns a new [TextEncoder](#) object.

`encoder . encoding`

Returns "utf-8".

`encoder . encode([input = ""])`

Returns the result of running [UTF-8](#)'s [encoder](#).

`encoder . encodeInto(source, destination)`

Runs the [UTF-8 encoder](#) on *source*, stores the result of that operation into *destination*, and returns the progress made as an object wherein [read](#) is the number of converted [code units](#) of *source* and [written](#) is the number of bytes modified in *destination*.

The new [TextEncoder](#)() constructor steps are to do nothing.

The [encode](#)(*input*) method steps are:

1. Convert *input* to a [stream](#).
2. Let *output* be a new [stream](#).

3. While true:

1. Let *token* be the result of [reading](#) from *input*.
2. Let *result* be the result of [processing](#) *token* for the [UTF-8 encoder](#), *input*, *output*.
3. Assert: *result* is not [error](#).

Note

The [UTF-8 encoder](#) cannot return [error](#).

4. If *result* is [finished](#), convert *output* into a byte sequence, and then return a [Uint8Array](#) object wrapping an [ArrayBuffer](#) containing *output*.

The [encodeInto\(source, destination\)](#) method steps are:

1. Let *read* be 0.
2. Let *written* be 0.
3. Let *destinationBytes* be the result of [getting a reference to the bytes held by](#) *destination*.
4. Let *unused* be a new [stream](#).

Note

The [handler](#) algorithm invoked below requires this argument, but it is not used by the [UTF-8 encoder](#).

5. Convert *source* to a [stream](#).

6. While true:

1. Let *token* be the result of [reading](#) from *source*.
2. Let *result* be the result of running the [UTF-8 encoder](#)'s [handler](#) on *unused* and *token*.
3. If *result* is [finished](#), then [break](#).
4. Otherwise:

1. If *destinationBytes*'s [length](#) – *written* is greater than or equal to the number of bytes in *result*, then:

1. If *token* is greater than U+FFFF, then increment *read* by 2.
2. Otherwise, increment *read* by 1.
3. Write the bytes in *result* into *destinationBytes*, from byte offset *written*.

 **Warning!**

See the [warning for SharedArrayBuffer objects](#) above.

4. Increment *written* by the number of bytes in *result*.

2. Otherwise, [break](#).

7. Return «["[read](#)" → *read*, "[written](#)" → *written*]».

Example

The [encodeInto\(\)](#) method can be used to encode a string into an existing [ArrayBuffer](#) object. Various details below are left as an exercise for the reader, but this demonstrates an approach one could take to use this method:

```
function convertString(buffer, input, callback) {  
  let bufferSize = 256,  
      bufferStart = malloc(buffer, bufferSize),
```

```

        writeOffset = 0,
        readOffset = 0;
    while (true) {
        const view = new Uint8Array(buffer, bufferStart + writeOffset, bufferSize - writeOffset),
            {read, written} = cachedEncoder.encodeInto(input.substring(readOffset), view);
        readOffset += read;
        writeOffset += written;
        if (readOffset === input.length) {
            callback(bufferStart, writeOffset);
            free(buffer, bufferStart);
            return;
        }
        bufferSize *= 2;
        bufferStart = realloc(buffer, bufferStart, bufferSize);
    }
}

```

7.5. Interface mixin [GenericTransformStream](#) §

The [GenericTransformStream](#) interface mixin represents the concept of a [transform stream](#) in IDL. It is not a [TransformStream](#), though it has the same interface and it delegates to one.

IDL

```

interface mixin GenericTransformStream {
    readonly attribute ReadableStream readable;
    readonly attribute WritableStream writable;
};

```

An object that includes [GenericTransformStream](#) has an associated **transform** of type [TransformStream](#).

The **readable** getter steps are to return [this](#)'s [transform](#).[[readable]].

The **writable** getter steps are to return [this](#)'s [transform](#).[[writable]].

7.6. Interface [TextDecoderStream](#) §

IDL

```

[Exposed=(Window,Worker)]
interface TextDecoderStream {
    constructor(optional DOMString label = "utf-8", optional TextDecoderOptions options = {});
};
TextDecoderStream includes TextDecoderCommon;
TextDecoderStream includes GenericTransformStream;

```

For web developers (non-normative)

`decoder = new TextDecoderStream([label = "utf-8" [, options]])`

Returns a new [TextDecoderStream](#) object.

If *label* is either not a [label](#) or is a [label](#) for replacement, throws a [RangeError](#).

`decoder . encoding`

Returns [encoding](#)'s [name](#), lowercased.

`decoder . fatal`

Returns true if [error mode](#) is "fatal", and false otherwise.

`decoder . ignoreBOM`

Returns the value of [ignore BOM](#).

`decoder . readable`

Returns a [readable stream](#) whose [chunks](#) are strings resulting from running [encoding's decoder](#) on the chunks written to [writable](#).

`decoder . writable`

Returns a [writable stream](#) which accepts [[AllowShared](#)] [BufferSource](#) chunks and runs them through [encoding's decoder](#) before making them available to [readable](#).

Typically this will be used via the [pipeThrough\(\)](#) method on a [ReadableStream](#) source.

¶ Example

```
var decoder = new TextDecoderStream(encoding);
byteReadable
  .pipeThrough(decoder)
  .pipeTo(textWritable);
```

If the [error mode](#) is "fatal" and [encoding's decoder](#) returns [error](#), both [readable](#) and [writable](#) will be errored with a [TypeError](#).

The `new TextDecoderStream(Label, options)` constructor steps are:

1. Let *encoding* be the result of [getting an encoding](#) from *label*.
2. If *encoding* is failure or [replacement](#), then [throw](#) a [RangeError](#).
3. Set *this*'s [encoding](#) to *encoding*.
4. If *options*["[fatal](#)"] is true, then set *this*'s [error mode](#) to "fatal".
5. set *this*'s [ignore BOM](#) to *options*["[ignoreBOM](#)"].
6. Set *this*'s [decoder](#) to a new [decoder](#) for *this*'s [encoding](#), and set *this*'s [stream](#) to a new [stream](#).
7. Let *startAlgorithm* be an algorithm that takes no arguments and returns nothing.
8. Let *transformAlgorithm* be an algorithm which takes a *chunk* argument and runs the [decode and enqueue a chunk](#) algorithm with [this](#) and *chunk*.
9. Let *flushAlgorithm* be an algorithm which takes no arguments and runs the [flush and enqueue](#) algorithm with [this](#).
10. Let *transform* be the result of calling [CreateTransformStream](#)(*startAlgorithm*, *transformAlgorithm*, *flushAlgorithm*).
11. Set *this*'s [transform](#) to *transform*.

The **decode and enqueue a chunk** algorithm, given a [TextDecoderStream](#) object *decoder* and a *chunk*, runs these steps:

1. Let *bufferSource* be the result of [converting](#) *chunk* to an [[AllowShared](#)] [BufferSource](#). If this throws an exception, then return a promise rejected with that exception.
2. [Push](#) a [copy of](#) *bufferSource* to *decoder*'s [stream](#). If this throws an exception, then return a promise rejected with that exception.

⚠ Warning!

See the [warning for SharedArrayBuffer objects](#) above.

3. Let *controller* be *decoder*'s [transform](#).[\[\[transformStreamController\]\]](#).
4. Let *output* be a new [stream](#).

5. While true, run these steps:

1. Let *token* be the result of [reading](#) from *decoder*'s [stream](#).
2. If *token* is [end-of-stream](#), run these steps:
 1. Let *outputChunk* be the result of running [serialize stream](#) with *decoder* and *output*.
 2. if *outputChunk* is non-empty, call [TransformStreamDefaultControllerEnqueue](#)(*controller*, *outputChunk*).
 3. Return a new promise resolved with undefined.
3. Let *result* be the result of [processing](#) *token* for *decoder*'s [decoder](#), *decoder*'s [stream](#), *output*, and *decoder*'s [error mode](#).
4. If *result* is [error](#), then return a new promise rejected with a [TypeError](#) exception.

The **flush and enqueue** algorithm, which handles the end of data from the input [ReadableStream](#) object, given a [TextDecoderStream](#) object *decoder*, runs these steps:

1. Let *output* be a new [stream](#).
2. Let *result* be the result of [processing end-of-stream](#) for *decoder*'s [decoder](#) and *decoder*'s [stream](#), *output*, and *decoder*'s [error mode](#).
3. If *result* is [finished](#), run these steps:
 1. Let *outputChunk* be the result of running [serialize stream](#) with *decoder* and *output*.
 2. Let *controller* be *decoder*'s [transform](#).[[*transformStreamController*]].
 3. If *outputChunk* is non-empty, call [TransformStreamDefaultControllerEnqueue](#)(*controller*, *outputChunk*).
 4. Return a new promise resolved with undefined.
4. Otherwise, return a new promise rejected with a [TypeError](#) exception.

7.7. Interface [TextEncoderStream](#) §

IDL	<pre>[Exposed=(Window,Worker)] interface TextEncoderStream { constructor(); }; TextEncoderStream includes TextEncoderCommon; TextEncoderStream includes GenericTransformStream;</pre>
-----	---

A [TextEncoderStream](#) object has an associated:

encoder

An [encoder](#).

pending high surrogate

Null or a [surrogate](#), initially null.

Note

A [TextEncoderStream](#) object offers no label argument as it only supports [UTF-8](#).

For web developers (non-normative)

encoder = new [TextEncoderStream](#)()

Returns a new [TextEncoderStream](#) object.

`encoder . encoding`

Returns "utf-8".

`encoder . readable`

Returns a [readable stream](#) whose [chunks](#) are [Uint8Arrays](#) resulting from running [UTF-8's encoder](#) on the chunks written to [writable](#).

`encoder . writable`

Returns a [writable stream](#) which accepts string chunks and runs them through [UTF-8's encoder](#) before making them available to [readable](#).

Typically this will be used via the [pipeThrough\(\)](#) method on a [ReadableStream](#) source.

¶ Example

```
textReadable
  .pipeThrough(new TextEncoderStream())
  .pipeTo(byteWritable);
```

The [new TextEncoderStream\(\)](#) constructor steps are:

1. Set [this's encoder](#) to [UTF-8's encoder](#).
2. Let *startAlgorithm* be an algorithm that takes no arguments and returns nothing.
3. Let *transformAlgorithm* be an algorithm which takes a *chunk* argument and runs the [encode and enqueue a chunk](#) algorithm with [this](#) and *chunk*.
4. Let *flushAlgorithm* be an algorithm which runs the [encode and flush](#) algorithm with [this](#).
5. Let *transform* be the result of calling [CreateTransformStream](#)(*startAlgorithm*, *transformAlgorithm*, *flushAlgorithm*).
6. Set [this's transform](#) to *transform*.

The **encode and enqueue a chunk** algorithm, given a [TextEncoderStream](#) object *encoder* and *chunk*, runs these steps:

1. Let *input* be the result of [converting](#) *chunk* to a [DOMString](#). If this throws an exception, then return a promise rejected with that exception.

Note

[DOMString](#) is used here so that a surrogate pair that is split between chunks can be reassembled into the appropriate scalar value. The behavior is otherwise identical to [USVString](#). In particular, lone surrogates will be replaced with U+FFFD.

2. Convert *input* to a [stream](#).
3. Let *output* be a new [stream](#).
4. Let *controller* be *encoder's transform*.[\[\[transformStreamController\]\]](#).
5. While true, run these steps:
 1. Let *token* be the result of [reading](#) from *input*.
 2. If *token* is [end-of-stream](#), run these steps:
 1. Convert *output* into a byte sequence.
 2. If *output* is non-empty, run these steps:

1. Let *chunk* be a [Uint8Array](#) object wrapping an [ArrayBuffer](#) containing *output*.
2. Call [TransformStreamDefaultControllerEnqueue\(controller, chunk\)](#).
3. Return a new promise resolved with undefined.
3. Let *result* be the result of executing the [convert code unit to scalar value](#) algorithm with *encoder*, *token* and *input*.
4. If *result* is not [continue](#), then [process](#) *result* for [encoder](#), *input*, *output*.

The **convert code unit to scalar value** algorithm, given a [TextEncoderStream](#) object *encoder*, *token*, and stream *input*, runs these steps:

1. If *encoder*'s [pending high surrogate](#) is non-null, run these steps:
 1. Let *high surrogate* be *encoder*'s [pending high surrogate](#).
 2. Set *encoder*'s [pending high surrogate](#) to null.
 3. If *token* is in the range U+DC00 to U+DFFF, inclusive, then return a code point whose value is $0x10000 + ((\text{high surrogate} - 0xD800) \ll 10) + (\text{token} - 0xDC00)$.
 4. [Prepend](#) *token* to *input*.
 5. Return U+FFFD.
2. If *token* is in the range U+D800 to U+DBFF, inclusive, then set [pending high surrogate](#) to *token* and return [continue](#).
3. If *token* is in the range U+DC00 to U+DFFF, inclusive, then return U+FFFD.
4. Return *token*.

Note

This is equivalent to the "[convert a string into a scalar value string](#)" algorithm from the [Infra Standard](#), but allows for surrogate pairs that are split between strings. [\[INFRA\]](#)

The **encode and flush** algorithm, given a [TextEncoderStream](#) object *encoder*, runs these steps:

1. If *encoder*'s [pending high surrogate](#) is non-null, run these steps:
 1. Let *controller* be *encoder*'s [transform](#).[\[\[transformStreamController\]\]](#).
 2. Let *output* be the byte sequence 0xEF 0xBF 0xBD.

Note

This is the replacement character U+FFFD encoded as UTF-8.

3. Let *chunk* be a [Uint8Array](#) object wrapping an [ArrayBuffer](#) containing *output*.
4. Call [TransformStreamDefaultControllerEnqueue\(controller, chunk\)](#).
2. Return a new promise resolved with undefined.

8. The encoding §

8.1. UTF-8

8.1.1. UTF-8 decoder

Note

A byte order mark has priority over a [label](#) as it has been found to be more accurate in deployed content. Therefore it is not part of the [UTF-8 decoder](#) algorithm but rather the [decode](#) and [UTF-8 decode](#) algorithms.

[UTF-8](#)'s [decoder](#)'s has an associated **UTF-8 code point**, **UTF-8 bytes seen**, and **UTF-8 bytes needed** (all initially 0), a **UTF-8 lower boundary** (initially 0x80), and a **UTF-8 upper boundary** (initially 0xBF).

[UTF-8](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [UTF-8 bytes needed](#) is not 0, set [UTF-8 bytes needed](#) to 0 and return [error](#).
2. If *byte* is [end-of-stream](#), return [finished](#).
3. If [UTF-8 bytes needed](#) is 0, based on *byte*:

0x00 to 0x7F

Return a code point whose value is *byte*.

0xC2 to 0xDF

1. Set [UTF-8 bytes needed](#) to 1.
2. Set [UTF-8 code point](#) to *byte* & 0x1F.

Note

The five least significant bits of byte.

0xE0 to 0xEF

1. If *byte* is 0xE0, set [UTF-8 lower boundary](#) to 0xA0.
2. If *byte* is 0xED, set [UTF-8 upper boundary](#) to 0x9F.
3. Set [UTF-8 bytes needed](#) to 2.
4. Set [UTF-8 code point](#) to *byte* & 0xF.

Note

The four least significant bits of byte.

0xF0 to 0xF4

1. If *byte* is 0xF0, set [UTF-8 lower boundary](#) to 0x90.
2. If *byte* is 0xF4, set [UTF-8 upper boundary](#) to 0x8F.
3. Set [UTF-8 bytes needed](#) to 3.
4. Set [UTF-8 code point](#) to *byte* & 0x7.

Note

The three least significant bits of byte.

Otherwise

Return [error](#).

Return [continue](#).

4. If *byte* is not in the range [UTF-8 lower boundary](#) to [UTF-8 upper boundary](#), inclusive, then:

1. Set [UTF-8 code point](#), [UTF-8 bytes needed](#), and [UTF-8 bytes seen](#) to 0, set [UTF-8 lower boundary](#) to 0x80, and set [UTF-8 upper boundary](#) to 0xBF.
2. [Prepend](#) *byte* to *stream*.
3. Return [error](#).

5. Set [UTF-8 lower boundary](#) to 0x80 and [UTF-8 upper boundary](#) to 0xBF.

6. Set [UTF-8 code point](#) to $(\text{UTF-8 code point} \ll 6) | (\text{byte} \& 0x3F)$

Note

*Shift the existing bits of [UTF-8 code point](#) left by six places and set the newly-vacated six least significant bits to the six least significant bits of *byte*.*




7. Increase [UTF-8 bytes seen](#) by one.
8. If [UTF-8 bytes seen](#) is not equal to [UTF-8 bytes needed](#), return [continue](#).
9. Let *code point* be [UTF-8 code point](#).
10. Set [UTF-8 code point](#), [UTF-8 bytes needed](#), and [UTF-8 bytes seen](#) to 0.
11. Return a code point whose value is *code point*.

Note

The constraints in the [UTF-8 decoder](#) above match “Best Practices for Using U+FFFD” from the Unicode standard. No other behavior is permitted per the Encoding Standard (other algorithms that achieve the same result are fine, even encouraged). [\[UNICODE\]](#)

8.1.2. UTF-8 encoder

[UTF-8](#)’s [encoder](#)’s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. Set *count* and *offset* based on the range *code point* is in:
 -  **U+0080 to U+07FF, inclusive**
1 and 0xC0
 -  **U+0800 to U+FFFF, inclusive**
2 and 0xE0
 -  **U+10000 to U+10FFFF, inclusive**
3 and 0xF0
4. Let *bytes* be a byte sequence whose first byte is $(\text{code point} \gg (6 \times \text{count})) + \text{offset}$.
5. While *count* is greater than 0:
 1. Set *temp* to $\text{code point} \gg (6 \times (\text{count} - 1))$.
 2. Append to *bytes* $0x80 | (\text{temp} \& 0x3F)$.
 3. Decrease *count* by one.

6. Return bytes *bytes*, in order.

Note

This algorithm has identical results to the one described in the Unicode standard. It is included here for completeness. [\[UNICODE\]](#)

9. Legacy single-byte encodings §

An [encoding](#) where each byte is either a single code point or nothing, is a **single-byte encoding**. [Single-byte encodings](#) share the [decoder](#) and [encoder](#). **Index single-byte**, as referenced by the [single-byte decoder](#) and [single-byte encoder](#), is defined by the following table, and depends on the [single-byte encoding](#) in use. All but two [single-byte encodings](#) have a unique [index](#).

IBM866	index-ibm866.txt	index IBM866 visualization	index IBM866 BMP coverage
ISO-8859-2	index-iso-8859-2.txt	index ISO-8859-2 visualization	index ISO-8859-2 BMP coverage
ISO-8859-3	index-iso-8859-3.txt	index ISO-8859-3 visualization	index ISO-8859-3 BMP coverage
ISO-8859-4	index-iso-8859-4.txt	index ISO-8859-4 visualization	index ISO-8859-4 BMP coverage
ISO-8859-5	index-iso-8859-5.txt	index ISO-8859-5 visualization	index ISO-8859-5 BMP coverage
ISO-8859-6	index-iso-8859-6.txt	index ISO-8859-6 visualization	index ISO-8859-6 BMP coverage
ISO-8859-7	index-iso-8859-7.txt	index ISO-8859-7 visualization	index ISO-8859-7 BMP coverage
ISO-8859-8	index-iso-8859-8.txt	index ISO-8859-8 visualization	index ISO-8859-8 BMP coverage
ISO-8859-8-I			
ISO-8859-10	index-iso-8859-10.txt	index ISO-8859-10 visualization	index ISO-8859-10 BMP coverage
ISO-8859-13	index-iso-8859-13.txt	index ISO-8859-13 visualization	index ISO-8859-13 BMP coverage
ISO-8859-14	index-iso-8859-14.txt	index ISO-8859-14 visualization	index ISO-8859-14 BMP coverage
ISO-8859-15	index-iso-8859-15.txt	index ISO-8859-15 visualization	index ISO-8859-15 BMP coverage
ISO-8859-16	index-iso-8859-16.txt	index ISO-8859-16 visualization	index ISO-8859-16 BMP coverage
KOI8-R	index-koi8-r.txt	index KOI8-R visualization	index KOI8-R BMP coverage
KOI8-U	index-koi8-u.txt	index KOI8-U visualization	index KOI8-U BMP coverage
macintosh	index-macintosh.txt	index macintosh visualization	index macintosh BMP coverage
windows-874	index-windows-874.txt	index windows-874 visualization	index windows-874 BMP coverage
windows-1250	index-windows-1250.txt	index windows-1250 visualization	index windows-1250 BMP coverage
windows-1251	index-windows-1251.txt	index windows-1251 visualization	index windows-1251 BMP coverage
windows-1252	index-windows-1252.txt	index windows-1252 visualization	index windows-1252 BMP coverage
windows-1253	index-windows-1253.txt	index windows-1253 visualization	index windows-1253 BMP coverage
windows-1254	index-windows-1254.txt	index windows-1254 visualization	index windows-1254 BMP coverage
windows-1255	index-windows-1255.txt	index windows-1255 visualization	index windows-1255 BMP coverage
windows-1256	index-windows-1256.txt	index windows-1256 visualization	index windows-1256 BMP coverage
windows-1257	index-windows-1257.txt	index windows-1257 visualization	index windows-1257 BMP coverage
windows-1258	index-windows-1258.txt	index windows-1258 visualization	index windows-1258 BMP coverage
x-mac-cyrillic	index-x-mac-cyrillic.txt	index x-mac-cyrillic visualization	index x-mac-cyrillic BMP coverage

Note

ISO-8859-8 and ISO-8859-8-I are distinct [encoding names](#), because ISO-8859-8 has influence on the layout direction. And although historically this might have been the case for ISO-8859-6 and "ISO-8859-6-I" as well, that is no longer true.

9.1. single-byte decoder

[Single-byte encodings](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#), return [finished](#).
2. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
3. Let *code point* be the [index code point](#) for *byte* – 0x80 in [index single-byte](#).

4. If *code point* is null, return [error](#).
5. Return a code point whose value is *code point*.

9.2. single-byte encoder

[Single-byte encodings](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. Let *pointer* be the [index pointer](#) for *code point* in [index single-byte](#).
4. If *pointer* is null, return [error](#) with *code point*.
5. Return a byte whose value is *pointer* + 0x80.

10. Legacy multi-byte Chinese (simplified) encodings §

10.1. GBK

10.1.1. GBK decoder §

[GBK's decoder](#) is [gb18030's decoder](#).

10.1.2. GBK encoder §

[GBK's encoder](#) is [gb18030's encoder](#) with its [is GBK](#) set to true.

Note

Not fully aliasing [GBK](#) with [gb18030](#) is a conservative move to decrease the chances of breaking legacy servers and other consumers of content generated with [GBK's encoder](#).

10.2. gb18030

10.2.1. gb18030 decoder §

[gb18030's decoder](#) has an associated **gb18030 first**, **gb18030 second**, and **gb18030 third** (all initially 0x00).

[gb18030's decoder's handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [gb18030 first](#), [gb18030 second](#), and [gb18030 third](#) are 0x00, return [finished](#).
2. If *byte* is [end-of-stream](#), and [gb18030 first](#), [gb18030 second](#), or [gb18030 third](#) is not 0x00, set [gb18030 first](#), [gb18030 second](#), and [gb18030 third](#) to 0x00, and return [error](#).
3. If [gb18030 third](#) is not 0x00, then:
 1. If *byte* is not in the range 0x30 to 0x39, inclusive, then:
 1. [Prepend gb18030 second](#), [gb18030 third](#), and *byte* to *stream*.
 2. Set [gb18030 first](#), [gb18030 second](#), and [gb18030 third](#) to 0x00.
 3. Return [error](#).
 2. Let *code point* be the [index gb18030 ranges code point](#) for $((\text{gb18030 first} - 0x81) \times (10 \times 126 \times 10)) + ((\text{gb18030 second} - 0x30) \times (10 \times 126)) + ((\text{gb18030 third} - 0x81) \times 10) + \text{byte} - 0x30$.
 3. Set [gb18030 first](#), [gb18030 second](#), and [gb18030 third](#) to 0x00.
 4. If *code point* is null, return [error](#).
 5. Return a code point whose value is *code point*.
4. If [gb18030 second](#) is not 0x00, then:
 1. If *byte* is in the range 0x81 to 0xFE, inclusive, set [gb18030 third](#) to *byte* and return [continue](#).
 2. [Prepend gb18030 second](#) followed by *byte* to *stream*, set [gb18030 first](#) and [gb18030 second](#) to 0x00, and return [error](#).
5. If [gb18030 first](#) is not 0x00, then:
 1. If *byte* is in the range 0x30 to 0x39, inclusive, set [gb18030 second](#) to *byte* and return [continue](#).

2. Let *lead* be [gb18030 first](#), let *pointer* be null, and set [gb18030 first](#) to 0x00.
 3. Let *offset* be 0x40 if *byte* is less than 0x7F, otherwise 0x41.
 4. If *byte* is in the range 0x40 to 0x7E, inclusive, or 0x80 to 0xFE, inclusive, set *pointer* to $(lead - 0x81) \times 190 + (byte - offset)$.
 5. Let *code point* be null if *pointer* is null, otherwise the [index code point](#) for *pointer* in [index gb18030](#).
 6. If *code point* is non-null, return a code point whose value is *code point*.
 7. If *byte* is an [ASCII byte](#), [prepend](#) *byte* to *stream*.
 8. Return [error](#).
6. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
 7. If *byte* is 0x80, return code point U+20AC.
 8. If *byte* is in the range 0x81 to 0xFE, inclusive, set [gb18030 first](#) to *byte* and return [continue](#).
 9. Return [error](#).

10.2.2. gb18030 encoder §

[gb18030](#)'s [encoder](#) has an associated **is GBK** (initially false).

[gb18030](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. If *code point* is U+E5E5, return [error](#) with *code point*.

Note

[Index gb18030](#) maps 0xA3 0xA0 to U+3000 rather than U+E5E5 for compatibility with deployed content. Therefore it cannot roundtrip.

4. If [is GBK](#) is true and *code point* is U+20AC, return byte 0x80.
5. Let *pointer* be the [index pointer](#) for *code point* in [index gb18030](#).
6. If *pointer* is non-null, then:
 1. Let *lead* be $pointer / 190 + 0x81$.
 2. Let *trail* be $pointer \% 190$.
 3. Let *offset* be 0x40 if *trail* is less than 0x3F, otherwise 0x41.
 4. Return two bytes whose values are *lead* and $trail + offset$.
7. If [is GBK](#) is true, return [error](#) with *code point*.
8. Set *pointer* to the [index gb18030 ranges pointer](#) for *code point*.
9. Let *byte1* be $pointer / (10 \times 126 \times 10)$.
10. Set *pointer* to $pointer \% (10 \times 126 \times 10)$.
11. Let *byte2* be $pointer / (10 \times 126)$.
12. Set *pointer* to $pointer \% (10 \times 126)$.

13. Let *byte3* be *pointer* / 10.
14. Let *byte4* be *pointer* % 10.
15. Return four bytes whose values are *byte1* + 0x81, *byte2* + 0x30, *byte3* + 0x81, *byte4* + 0x30.

11. Legacy multi-byte Chinese (traditional) encodings §

11.1. Big5

11.1.1. Big5 decoder §

[Big5](#)'s [decoder](#) has an associated **Big5 lead** (initially 0x00).

[Big5](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [Big5 lead](#) is not 0x00, set [Big5 lead](#) to 0x00 and return [error](#).
2. If *byte* is [end-of-stream](#) and [Big5 lead](#) is 0x00, return [finished](#).
3. If [Big5 lead](#) is not 0x00, let *lead* be [Big5 lead](#), let *pointer* be null, set [Big5 lead](#) to 0x00, and then:
 1. Let *offset* be 0x40 if *byte* is less than 0x7F, otherwise 0x62.
 2. If *byte* is in the range 0x40 to 0x7E, inclusive, or 0xA1 to 0xFE, inclusive, set *pointer* to $(\text{lead} - 0x81) \times 157 + (\text{byte} - \text{offset})$.
 3. If there is a row in the table below whose first column is *pointer*, return the *two* code points listed in its second column (the third column is irrelevant):

Pointer	Code points	Notes
1133	U+00CA U+0304	Ě (LATIN CAPITAL LETTER E WITH CIRCUMFLEX AND MACRON)
1135	U+00CA U+030C	Ě (LATIN CAPITAL LETTER E WITH CIRCUMFLEX AND CARON)
1164	U+00EA U+0304	ẽ (LATIN SMALL LETTER E WITH CIRCUMFLEX AND MACRON)
1166	U+00EA U+030C	ẽ (LATIN SMALL LETTER E WITH CIRCUMFLEX AND CARON)

Note

Since [indexes](#) are limited to single code points this table is used for these pointers.

4. Let *code point* be null if *pointer* is null, otherwise the [index code point](#) for *pointer* in [index Big5](#).
5. If *code point* is non-null, return a code point whose value is *code point*.
6. If *byte* is an [ASCII byte](#), [prepend](#) *byte* to *stream*.
7. Return [error](#).
4. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
5. If *byte* is in the range 0x81 to 0xFE, inclusive, set [Big5 lead](#) to *byte* and return [continue](#).
6. Return [error](#).

11.1.2. Big5 encoder §

[Big5](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. Let *pointer* be the [index Big5 pointer](#) for *code point*.
4. If *pointer* is null, return [error](#) with *code point*.
5. Let *lead* be $\text{pointer} / 157 + 0x81$.

6. Let *trail* be *pointer* % 157.
7. Let *offset* be 0x40 if *trail* is less than 0x3F, otherwise 0x62.
8. Return two bytes whose values are *lead* and *trail* + *offset*.

12. Legacy multi-byte Japanese encodings §

12.1. EUC-JP

12.1.1. EUC-JP decoder

[EUC-JP](#)'s [decoder](#) has an associated **EUC-JP jis0212** (initially false) and **EUC-JP lead** (initially 0x00).

[EUC-JP](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [EUC-JP lead](#) is not 0x00, set [EUC-JP lead](#) to 0x00, and return [error](#).
2. If *byte* is [end-of-stream](#) and [EUC-JP lead](#) is 0x00, return [finished](#).
3. If [EUC-JP lead](#) is 0x8E and *byte* is in the range 0xA1 to 0xDF, inclusive, set [EUC-JP lead](#) to 0x00 and return a code point whose value is $0xFF61 - 0xA1 + \textit{byte}$.
4. If [EUC-JP lead](#) is 0x8F and *byte* is in the range 0xA1 to 0xFE, inclusive, set [EUC-JP jis0212](#) to true, set [EUC-JP lead](#) to *byte*, and return [continue](#).
5. If [EUC-JP lead](#) is not 0x00, let *lead* be [EUC-JP lead](#), set [EUC-JP lead](#) to 0x00, and then:
 1. Let *code point* be null.
 2. If *lead* and *byte* are both in the range 0xA1 to 0xFE, inclusive, then set *code point* to the [index code point](#) for $(\textit{lead} - 0xA1) \times 94 + \textit{byte} - 0xA1$ in [index jis0208](#) if [EUC-JP jis0212](#) is false and in [index jis0212](#) otherwise.
 3. Set [EUC-JP jis0212](#) to false.
 4. If *code point* is non-null, return a code point whose value is *code point*.
 5. If *byte* is an [ASCII byte](#), [prepend](#) *byte* to *stream*.
 6. Return [error](#).
6. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
7. If *byte* is 0x8E, 0x8F, or in the range 0xA1 to 0xFE, inclusive, set [EUC-JP lead](#) to *byte* and return [continue](#).
8. Return [error](#).

12.1.2. EUC-JP encoder §

[EUC-JP](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. If *code point* is U+00A5, return byte 0x5C.
4. If *code point* is U+203E, return byte 0x7E.
5. If *code point* is in the range U+FF61 to U+FF9F, inclusive, return two bytes whose values are 0x8E and $\textit{code point} - 0xFF61 + 0xA1$.
6. If *code point* is U+2212, set it to U+FF0D.
7. Let *pointer* be the [index pointer](#) for *code point* in [index jis0208](#).

Note

If pointer is non-null, it is less than 8836 due to the nature of [index jis0208](#) and the [index pointer](#) operation.

8. If *pointer* is null, return [error](#) with *code point*.
9. Let *lead* be *pointer* / 94 + 0xA1.
10. Let *trail* be *pointer* % 94 + 0xA1.
11. Return two bytes whose values are *lead* and *trail*.

12.2. ISO-2022-JP

12.2.1. ISO-2022-JP decoder §

[ISO-2022-JP](#)'s [decoder](#) has an associated **ISO-2022-JP decoder state** (initially [ASCII](#)), **ISO-2022-JP decoder output state** (initially [ASCII](#)), **ISO-2022-JP lead** (initially 0x00), and **ISO-2022-JP output** (initially false).

[ISO-2022-JP](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps, switching on [ISO-2022-JP decoder state](#):

☐ **ASCII**

Based on *byte*:

☐ **0x1B**

Set [ISO-2022-JP decoder state](#) to [escape start](#) and return [continue](#).

☐ **0x00 to 0x7F, excluding 0x0E, 0x0F, and 0x1B**

Set [ISO-2022-JP output](#) to false and return a code point whose value is *byte*.

☐ **end-of-stream**

Return [finished](#).

☐ **Otherwise**

Set [ISO-2022-JP output](#) to false and return [error](#).

☐ **Roman**

Based on *byte*:

☐ **0x1B**

Set [ISO-2022-JP decoder state](#) to [escape start](#) and return [continue](#).

☐ **0x5C**

Set [ISO-2022-JP output](#) to false and return code point U+00A5.

☐ **0x7E**

Set [ISO-2022-JP output](#) to false and return code point U+203E.

☐ **0x00 to 0x7F, excluding 0x0E, 0x0F, 0x1B, 0x5C, and 0x7E**

Set [ISO-2022-JP output](#) to false and return a code point whose value is *byte*.

☐ **end-of-stream**

Return [finished](#).

☐ **Otherwise**

Set [ISO-2022-JP output](#) to false and return [error](#).

☐ **katakana**

Based on *byte*:

☐ **0x1B**

Set [ISO-2022-JP decoder state](#) to [escape start](#) and return [continue](#).

☐ **0x21 to 0x5F**

Set [ISO-2022-JP output](#) to false and return a code point whose value is $0xFF61 - 0x21 + \text{byte}$.

☐ **end-of-stream**

Return [finished](#).

☐ **Otherwise**

Set [ISO-2022-JP output](#) to false and return [error](#).

☐ **Lead byte**

Based on *byte*:

☐ **0x1B**

Set [ISO-2022-JP decoder state](#) to [escape start](#) and return [continue](#).

☐ **0x21 to 0x7E**

Set [ISO-2022-JP output](#) to false, [ISO-2022-JP lead](#) to *byte*, [ISO-2022-JP decoder state](#) to [trail byte](#), and return [continue](#).

☐ **end-of-stream**

Return [finished](#).

☐ **Otherwise**

Set [ISO-2022-JP output](#) to false and return [error](#).

☐ **Trail byte**

Based on *byte*:

☐ **0x1B**

Set [ISO-2022-JP decoder state](#) to [escape start](#) and return [error](#).

☐ **0x21 to 0x7E**

1. Set the [ISO-2022-JP decoder state](#) to [lead byte](#).
2. Let *pointer* be $(\text{ISO-2022-JP lead} - 0x21) \times 94 + \text{byte} - 0x21$.
3. Let *code point* be the [index code point](#) for *pointer* in [index jis0208](#).
4. If *code point* is null, return [error](#).
5. Return a code point whose value is *code point*.

☐ **end-of-stream**

Set the [ISO-2022-JP decoder state](#) to [lead byte](#), [prepend byte](#) to *stream*, and return [error](#).

☐ **Otherwise**

Set [ISO-2022-JP decoder state](#) to [lead byte](#) and return [error](#).

☐ **Escape start**

1. If *byte* is either 0x24 or 0x28, set [ISO-2022-JP lead](#) to *byte*, [ISO-2022-JP decoder state](#) to [escape](#), and return [continue](#).
2. [Prepend byte](#) to *stream*.
3. Set [ISO-2022-JP output](#) to false, [ISO-2022-JP decoder state](#) to [ISO-2022-JP decoder output state](#), and return [error](#).

☐ **Escape**

1. Let *lead* be [ISO-2022-JP lead](#) and set [ISO-2022-JP lead](#) to 0x00.
2. Let *state* be null.
3. If *lead* is 0x28 and *byte* is 0x42, set *state* to [ASCII](#).

4. If *lead* is 0x28 and *byte* is 0x4A, set *state* to [Roman](#).
5. If *lead* is 0x28 and *byte* is 0x49, set *state* to [katakana](#).
6. If *lead* is 0x24 and *byte* is either 0x40 or 0x42, set *state* to [lead byte](#).
7. If *state* is non-null, then:
 1. Set [ISO-2022-JP decoder state](#) and [ISO-2022-JP decoder output state](#) to *state*.
 2. Let *output* be the value of [ISO-2022-JP output](#).
 3. Set [ISO-2022-JP output](#) to true.
 4. Return [continue](#), if *output* is false, and [error](#) otherwise.
8. [Prepend](#) *lead* and *byte* to *stream*.
9. Set [ISO-2022-JP output](#) to false, [ISO-2022-JP decoder state](#) to [ISO-2022-JP decoder output state](#) and return [error](#).

12.2.2. ISO-2022-JP encoder

Note

The [ISO-2022-JP encoder](#) is the only [encoder](#) for which the concatenation of multiple outputs can result in an [error](#) when run through the corresponding [decoder](#).

¶ Example

Encoding U+00A5 gives 0x1B 0x28 0x4A 0x5C 0x1B 0x28 0x42. Doing that twice, concatenating the results, and then decoding yields U+00A5 U+FFFD U+00A5.

[ISO-2022-JP](#)'s [encoder](#) has an associated **ISO-2022-JP encoder state** which is **ASCII**, **Roman**, or **jis0208** (initially [ASCII](#)).

[ISO-2022-JP](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#) and [ISO-2022-JP encoder state](#) is not [ASCII](#), [prepend](#) *code point* to *stream*, set [ISO-2022-JP encoder state](#) to [ASCII](#), and return three bytes 0x1B 0x28 0x42.
2. If *code point* is [end-of-stream](#) and [ISO-2022-JP encoder state](#) is [ASCII](#), return [finished](#).
3. If [ISO-2022-JP encoder state](#) is [ASCII](#) or [Roman](#), and *code point* is U+000E, U+000F, or U+001B, return [error](#) with U+FFFD.

Note

This returns U+FFFD rather than code point to prevent attacks.

4. If [ISO-2022-JP encoder state](#) is [ASCII](#) and *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
5. If [ISO-2022-JP encoder state](#) is [Roman](#) and *code point* is an [ASCII code point](#), excluding U+005C and U+007E, or is U+00A5 or U+203E, then:
 1. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
 2. If *code point* is U+00A5, return byte 0x5C.
 3. If *code point* is U+203E, return byte 0x7E.
6. If *code point* is an [ASCII code point](#), and [ISO-2022-JP encoder state](#) is not [ASCII](#), [prepend](#) *code point* to *stream*, set [ISO-2022-JP encoder state](#) to [ASCII](#), and return three bytes 0x1B 0x28 0x42.
7. If *code point* is either U+00A5 or U+203E, and [ISO-2022-JP encoder state](#) is not [Roman](#), [prepend](#) *code point* to *stream*, set [ISO-2022-JP encoder state](#) to [Roman](#), and return three bytes 0x1B 0x28 0x4A.

8. If *code point* is U+2212, set it to U+FF0D.
9. If *code point* is in the range U+FF61 to U+FF9F, inclusive, set it to the [index code point](#) for *code point* – 0xFF61 in [index ISO-2022-JP katakana](#).
10. Let *pointer* be the [index pointer](#) for *code point* in [index jis0208](#).

Note

If pointer is non-null, it is less than 8836 due to the nature of [index jis0208](#) and the [index pointer](#) operation.

11. If *pointer* is null, return [error](#) with *code point*.
12. If [ISO-2022-JP encoder state](#) is not [jis0208](#), [prepend](#) *code point* to *stream*, set [ISO-2022-JP encoder state](#) to [jis0208](#), and return three bytes 0x1B 0x24 0x42.
13. Let *lead* be *pointer* / 94 + 0x21.
14. Let *trail* be *pointer* % 94 + 0x21.
15. Return two bytes whose values are *lead* and *trail*.

12.3. Shift_JIS

12.3.1. Shift_JIS decoder §

[Shift_JIS](#)'s [decoder](#) has an associated **Shift_JIS lead** (initially 0x00).

[Shift_JIS](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [Shift_JIS lead](#) is not 0x00, set [Shift_JIS lead](#) to 0x00 and return [error](#).
2. If *byte* is [end-of-stream](#) and [Shift_JIS lead](#) is 0x00, return [finished](#).
3. If [Shift_JIS lead](#) is not 0x00, let *lead* be [Shift_JIS lead](#), let *pointer* be null, set [Shift_JIS lead](#) to 0x00, and then:
 1. Let *offset* be 0x40 if *byte* is less than 0x7F, otherwise 0x41.
 2. Let *lead offset* be 0x81 if *lead* is less than 0xA0, otherwise 0xC1.
 3. If *byte* is in the range 0x40 to 0x7E, inclusive, or 0x80 to 0xFC, inclusive, set *pointer* to $(\text{lead} - \text{lead offset}) \times 188 + \text{byte} - \text{offset}$.
 4. If *pointer* is in the range 8836 to 10715, inclusive, return a code point whose value is $0xE000 - 8836 + \text{pointer}$.

Note

This is interoperable legacy from Windows known as EUDC.

5. Let *code point* be null if *pointer* is null, otherwise the [index code point](#) for *pointer* in [index jis0208](#).
6. If *code point* is non-null, return a code point whose value is *code point*.
7. If *byte* is an [ASCII byte](#), [prepend](#) *byte* to *stream*.
8. Return [error](#).
4. If *byte* is an [ASCII byte](#) or 0x80, return a code point whose value is *byte*.
5. If *byte* is in the range 0xA1 to 0xDF, inclusive, return a code point whose value is $0xFF61 - 0xA1 + \text{byte}$.
6. If *byte* is in the range 0x81 to 0x9F, inclusive, or 0xE0 to 0xFC, inclusive, set [Shift_JIS lead](#) to *byte* and return [continue](#).
7. Return [error](#).

12.3.2. Shift_JIS encoder §

[Shift_JIS](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#) or U+0080, return a byte whose value is *code point*.
3. If *code point* is U+00A5, return byte 0x5C.
4. If *code point* is U+203E, return byte 0x7E.
5. If *code point* is in the range U+FF61 to U+FF9F, inclusive, return a byte whose value is *code point* – 0xFF61 + 0xA1.
6. If *code point* is U+2212, set it to U+FF0D.
7. Let *pointer* be the [index Shift_JIS pointer](#) for *code point*.
8. If *pointer* is null, return [error](#) with *code point*.
9. Let *lead* be *pointer* / 188.
10. Let *lead offset* be 0x81 if *lead* is less than 0x1F, otherwise 0xC1.
11. Let *trail* be *pointer* % 188.
12. Let *offset* be 0x40 if *trail* is less than 0x3F, otherwise 0x41.
13. Return two bytes whose values are *lead* + *lead offset* and *trail* + *offset*.

13. Legacy multi-byte Korean encodings §

13.1. EUC-KR

13.1.1. EUC-KR decoder §

[EUC-KR](#)'s [decoder](#) has an associated **EUC-KR lead** (initially 0x00).

[EUC-KR](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and [EUC-KR lead](#) is not 0x00, set [EUC-KR lead](#) to 0x00 and return [error](#).
2. If *byte* is [end-of-stream](#) and [EUC-KR lead](#) is 0x00, return [finished](#).
3. If [EUC-KR lead](#) is not 0x00, let *lead* be [EUC-KR lead](#), let *pointer* be null, set [EUC-KR lead](#) to 0x00, and then:
 1. If *byte* is in the range 0x41 to 0xFE, inclusive, set *pointer* to $(lead - 0x81) \times 190 + (byte - 0x41)$.
 2. Let *code point* be null if *pointer* is null, otherwise the [index code point](#) for *pointer* in [index EUC-KR](#).
 3. If *code point* is non-null, return a code point whose value is *code point*.
 4. If *byte* is an [ASCII byte](#), [prepend](#) *byte* to *stream*.
 5. Return [error](#).
4. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
5. If *byte* is in the range 0x81 to 0xFE, inclusive, set [EUC-KR lead](#) to *byte* and return [continue](#).
6. Return [error](#).

13.1.2. EUC-KR encoder §

[EUC-KR](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. Let *pointer* be the [index pointer](#) for *code point* in [index EUC-KR](#).
4. If *pointer* is null, return [error](#) with *code point*.
5. Let *lead* be $pointer / 190 + 0x81$.
6. Let *trail* be $pointer \% 190 + 0x41$.
7. Return two bytes whose values are *lead* and *trail*.

14. Legacy miscellaneous encodings §

14.1. replacement

Note

The [replacement encoding](#) exists to prevent certain attacks that abuse a mismatch between [encodings](#) supported on the server and the client.

14.1.1. replacement decoder §

[replacement](#)'s [decoder](#) has an associated **replacement error returned** (initially false).

[replacement](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#), return [finished](#).
2. If [replacement error returned](#) is false, set [replacement error returned](#) to true and return [error](#).
3. Return [finished](#).

14.2. Common infrastructure for [UTF-16BE](#) and [UTF-16LE](#) §

14.2.1. shared UTF-16 decoder


Note


A byte order mark has priority over a [label](#) as it has been found to be more accurate in deployed content. Therefore it is not part of the [shared UTF-16 decoder](#) algorithm but rather the [decode](#) algorithm.

[shared UTF-16 decoder](#) has an associated **UTF-16 lead byte** and **UTF-16 lead surrogate** (both initially null), and is **UTF-16BE decoder** (initially false).

[shared UTF-16 decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#) and either [UTF-16 lead byte](#) or [UTF-16 lead surrogate](#) is non-null, set [UTF-16 lead byte](#) and [UTF-16 lead surrogate](#) to null, and return [error](#).
2. If *byte* is [end-of-stream](#) and [UTF-16 lead byte](#) and [UTF-16 lead surrogate](#) are null, return [finished](#).
3. If [UTF-16 lead byte](#) is null, set [UTF-16 lead byte](#) to *byte* and return [continue](#).
4. Let *code unit* be the result of:

 [is UTF-16BE decoder](#) is true
 $(\text{UTF-16 lead byte} \ll 8) + \text{byte}$.

 [is UTF-16BE decoder](#) is false
 $(\text{byte} \ll 8) + \text{UTF-16 lead byte}$.

Then set [UTF-16 lead byte](#) to null.

5. If [UTF-16 lead surrogate](#) is non-null, let *lead surrogate* be [UTF-16 lead surrogate](#), set [UTF-16 lead surrogate](#) to null, and then:
 1. If *code unit* is in the range U+DC00 to U+DFFF, inclusive, return a code point whose value is $0x10000 + ((\text{lead surrogate} - 0xD800) \ll 10) + (\text{code unit} - 0xDC00)$.

2. Let *byte1* be *code unit* >> 8.
3. Let *byte2* be *code unit* & 0x00FF.
4. Let *bytes* be two bytes whose values are *byte1* and *byte2*, if [is UTF-16BE decoder](#) is true, and *byte2* and *byte1* otherwise.
5. [Prepend](#) the *bytes* to *stream* and return [error](#).
6. If *code unit* is in the range U+D800 to U+DBFF, inclusive, set [UTF-16 lead surrogate](#) to *code unit* and return [continue](#).
7. If *code unit* is in the range U+DC00 to U+DFFF, inclusive, return [error](#).
8. Return code point *code unit*.

14.3. UTF-16BE

14.3.1. UTF-16BE decoder §

[UTF-16BE](#)'s [decoder](#) is [shared UTF-16 decoder](#) with its [is UTF-16BE decoder](#) set to true.

14.4. UTF-16LE

Note

"utf-16" is a [label](#) for [UTF-16LE](#) to deal with deployed content.

14.4.1. UTF-16LE decoder §

[UTF-16LE](#)'s [decoder](#) is [shared UTF-16 decoder](#).

14.5. x-user-defined

Note

While technically this is a [single-byte encoding](#), it is defined separately as it can be implemented algorithmically.

14.5.1. x-user-defined decoder §

[x-user-defined](#)'s [decoder](#)'s [handler](#), given a *stream* and *byte*, runs these steps:

1. If *byte* is [end-of-stream](#), return [finished](#).
2. If *byte* is an [ASCII byte](#), return a code point whose value is *byte*.
3. Return a code point whose value is 0xF780 + *byte* – 0x80.

14.5.2. x-user-defined encoder §

[x-user-defined](#)'s [encoder](#)'s [handler](#), given a *stream* and *code point*, runs these steps:

1. If *code point* is [end-of-stream](#), return [finished](#).
2. If *code point* is an [ASCII code point](#), return a byte whose value is *code point*.
3. If *code point* is in the range U+F780 to U+F7FF, inclusive, return a byte whose value is $\text{code point} - 0xF780 + 0x80$.
4. Return [error](#) with *code point*.

15. Browser UI §

Browsers are encouraged to not enable overriding the encoding of a resource. If such a feature is nonetheless present, browsers should not offer either [UTF-16BE](#) or [UTF-16LE](#) as option due to aforementioned security issues. Browsers also should disable this feature if the resource was decoded using either [UTF-16BE](#) or [UTF-16LE](#).

Implementation considerations §

Instead of supporting [streams](#) with arbitrary [prepend](#), the [decoders](#) for [encodings](#) in this standard could be implemented with:

1. The ability to unread the current byte.
2. A single-byte buffer for [gb18030](#) (an [ASCII byte](#)) and [ISO-2022-JP](#) (0x24 or 0x28).

¶ Example

For [gb18030](#) when hitting a bogus byte while [gb18030 third](#) is not 0x00, [gb18030 second](#) could be moved into the single-byte buffer to be returned next, and [gb18030 third](#) would be the new [gb18030 first](#), checked for not being 0x00 after the single-byte buffer was returned and emptied. This is possible as the range for the first and third byte in [gb18030](#) is identical.

The [ISO-2022-JP encoder](#) needs [ISO-2022-JP encoder state](#) as additional state, but other than that, none of the [encoders](#) for [encodings](#) in this standard require additional state or buffers.

Acknowledgments §

There have been a lot of people that have helped make encodings more interoperable over the years and thereby furthered the goals of this standard. Likewise many people have helped making this standard what it is today.

With that, many thanks to Adam Rice, Alan Chaney, Alexander Shtuchkin, Allen Wirfs-Brock, Andreu Botella, Aneesh Agrawal, Arkadiusz Michalski, Asmus Freytag, Ben Noordhuis, Bnaya Peretz, Boris Zbarsky, Bruno Haible, Cameron McCormack, Charles McCathieNeville, Christopher Foo, CodifierNL, David Carlisle, Domenic Denicola, Dominique Hazaël-Massieux, Doug Ewell, Erik van der Poel, 譚永鋒 (Frank Yung-Fong Tang), Glenn Maynard, Gordon P. Hemsley, Henri Sivonen, Ian Hickson, James Graham, Jeffrey Yasskin, John Tamplin, Joshua Bell, 村井純 (Jun Murai), 신정식 (Jungshik Shin), Jxck, 강 성훈 (Kang Seonghoon), 川幡太一 (Kawabata Taichi), Ken Lunde, Ken Whistler, Kenneth Russell, 田村健人 (Kent Tamura), Leif Halvard Silli, Luke Wagner, Maciej Hirszt, Makoto Kato, Mark Callow, Mark Crispin, Mark Davis, Martin Dürst, Masatoshi Kimura, Mattias Buelens, Ms2ger, Nigel Megitt, Nigel Tao, Norbert Lindenberg, Øistein E. Andersen, Peter Krefting, Philip Jägenstedt, Philip Taylor, Richard Ishida, Robbert Broersma, Robert Mustacchi, Ryan Dahl, Sam Sneddon, Shawn Steele, Simon Montagu, Simon Pieters, Simon Sapin, 寺田健 (Takeshi Terada), Vyacheslav Matva, and 成瀬ゆい (Yui Naruse) for being awesome.

This standard is written by [Anne van Kesteren](#) ([Mozilla](#), annevk@annevk.nl). The [API](#) chapter was initially written by Joshua Bell ([Google](#)).

Copyright © WHATWG (Apple, Google, Mozilla, Microsoft). This work is licensed under a [Creative Commons Attribution 4.0 International License](#).

Index §

Terms defined by this specification §

- [Big5](#), in §11
- [Big5 decoder](#), in §11.1
- [Big5 encoder](#), in §11.1.1
- [Big5 lead](#), in §11.1.1
- [BOM seen](#), in §7.1
- [BOM sniff](#), in §6
- constructor()
 - [constructor for TextDecoder](#), in §7.2
 - [constructor for TextDecoderStream](#), in §7.6
 - [constructor for TextEncoder](#), in §7.4
 - [constructor for TextEncoderStream](#), in §7.7
- constructor(label)
 - [constructor for TextDecoder](#), in §7.2
 - [constructor for TextDecoderStream](#), in §7.6
- constructor(label, options)
 - [constructor for TextDecoder](#), in §7.2
 - [constructor for TextDecoderStream](#), in §7.6
- [continue](#), in §4.1
- [convert code unit to scalar value](#), in §7.7
- [decode](#), in §6
- [decode\(\)](#), in §7.2
- [decode and enqueue a chunk](#), in §7.6
- [decode\(input\)](#), in §7.2
- [decode\(input, options\)](#), in §7.2
- decoder
 - [definition of](#), in §4.1
 - [dfn for TextDecoderCommon](#), in §7.1
- [do not flush](#), in §7.2
- [encode](#), in §6
- [encode\(\)](#), in §7.4
- [encode and enqueue a chunk](#), in §7.7
- [encode and flush](#), in §7.7
- [encode\(input\)](#), in §7.4
- [encodeInto\(source, destination\)](#), in §7.4
- encoder
 - [definition of](#), in §4.1
 - [dfn for TextEncoderStream](#), in §7.7
- encoding
 - [attribute for TextDecoderCommon](#), in §7.1
 - [attribute for TextEncoderCommon](#), in §7.3
 - [definition of](#), in §4
 - [dfn for TextDecoderCommon](#), in §7.1
- [End-of-stream](#), in §3
- [error](#), in §4.1
- error mode
 - [definition of](#), in §4.1
 - [dfn for TextDecoderCommon](#), in §7.1
- [EUC-JP](#), in §12
- [EUC-JP decoder](#), in §12.1
- [EUC-JP encoder](#), in §12.1.1
- [EUC-JP jis0212](#), in §12.1.1
- [EUC-JP lead](#), in §12.1.1
- [EUC-KR](#), in §13
- [EUC-KR decoder](#), in §13.1

- [EUC-KR encoder](#), in §13.1.1
- [EUC-KR lead](#), in §13.1.1
- fatal
 - [attribute for TextDecoderCommon](#), in §7.1
 - [dict-member for TextDecoderOptions](#), in §7.2
- [finished](#), in §4.1
- [flush and enqueue](#), in §7.6
- [gb18030](#), in §10.1.2
- [gb18030 decoder](#), in §10.2
- [gb18030 encoder](#), in §10.2.1
- [gb18030 first](#), in §10.2.1
- [gb18030 second](#), in §10.2.1
- [gb18030 third](#), in §10.2.1
- [GBK](#), in §10
- [GBK decoder](#), in §10.1
- [GBK encoder](#), in §10.1.1
- [GenericTransformStream](#), in §7.5
- [get an encoding](#), in §4.2
- [get an output encoding](#), in §4.3
- [getting an encoding](#), in §4.2
- [handler](#), in §4.1
- [IBM866](#), in §9
- [ignore BOM](#), in §7.1
- ignoreBOM
 - [attribute for TextDecoderCommon](#), in §7.1
 - [dict-member for TextDecoderOptions](#), in §7.2
- [index](#), in §5
- [index Big5](#), in §5
- [index Big5 pointer](#), in §5
- [index code point](#), in §5
- [index EUC-KR](#), in §5
- [index gb18030](#), in §5
- [index gb18030 ranges](#), in §5
- [index gb18030 ranges code point](#), in §5
- [index gb18030 ranges pointer](#), in §5
- [index ISO-2022-JP katakana](#), in §5
- [index jis0208](#), in §5
- [index jis0212](#), in §5
- [index pointer](#), in §5
- [index Shift JIS pointer](#), in §5
- [Index single-byte](#), in §9
- [is GBK](#), in §10.2.2
- [ISO-2022-JP](#), in §12.1.2
- [ISO-2022-JP decoder](#), in §12.2
- [ISO-2022-JP decoder ASCII](#), in §12.2.1
- [ISO-2022-JP decoder escape](#), in §12.2.1
- [ISO-2022-JP decoder escape start](#), in §12.2.1
- [ISO-2022-JP decoder katakana](#), in §12.2.1
- [ISO-2022-JP decoder lead byte](#), in §12.2.1
- [ISO-2022-JP decoder output state](#), in §12.2.1
- [ISO-2022-JP decoder Roman](#), in §12.2.1
- [ISO-2022-JP decoder state](#), in §12.2.1
- [ISO-2022-JP decoder trail byte](#), in §12.2.1
- [ISO-2022-JP encoder](#), in §12.2.1
- [ISO-2022-JP encoder ASCII](#), in §12.2.2
- [ISO-2022-JP encoder jis0208](#), in §12.2.2
- [ISO-2022-JP encoder Roman](#), in §12.2.2
- [ISO-2022-JP encoder state](#), in §12.2.2

- [ISO-2022-JP lead](#), in §12.2.1
- [ISO-2022-JP output](#), in §12.2.1
- [ISO-8859-10](#), in §9
- [ISO-8859-13](#), in §9
- [ISO-8859-14](#), in §9
- [ISO-8859-15](#), in §9
- [ISO-8859-16](#), in §9
- [ISO-8859-2](#), in §9
- [ISO-8859-3](#), in §9
- [ISO-8859-4](#), in §9
- [ISO-8859-5](#), in §9
- [ISO-8859-6](#), in §9
- [ISO-8859-7](#), in §9
- [ISO-8859-8](#), in §9
- [ISO-8859-8-I](#), in §9
- [is UTF-16BE decoder](#), in §14.2.1
- [KOI8-R](#), in §9
- [KOI8-U](#), in §9
- [label](#), in §4
- [macintosh](#), in §9
- [name](#), in §4
- [pending high surrogate](#), in §7.7
- [prepended](#), in §3
- [process](#), in §4.1
- [pushed](#), in §3
- read
 - [dfn for stream](#), in §3
 - [dict-member for TextEncoderEncodeIntoResult](#), in §7.4
- [readable](#), in §7.5
- [replacement](#), in §14
- [replacement decoder](#), in §14.1
- [replacement error returned](#), in §14.1.1
- [run](#), in §4.1
- [serialize stream](#), in §7.1
- [shared UTF-16 decoder](#), in §14.2
- [Shift_JIS](#), in §12.2.2
- [Shift_JIS decoder](#), in §12.3
- [Shift_JIS encoder](#), in §12.3.1
- [Shift_JIS lead](#), in §12.3.1
- [single-byte decoder](#), in §9
- [single-byte encoder](#), in §9.1
- [single-byte encoding](#), in §9
- stream
 - [definition of](#), in §3
 - [dfn for TextDecoderCommon](#), in §7.1
 - [dict-member for TextDecodeOptions](#), in §7.2
- [TextDecodeOptions](#), in §7.2
- [TextDecoder](#), in §7.2
- [TextDecoder\(\)](#), in §7.2
- [TextDecoderCommon](#), in §7.1
- [TextDecoder\(label\)](#), in §7.2
- [TextDecoder\(label, options\)](#), in §7.2
- [TextDecoderOptions](#), in §7.2
- [TextDecoderStream](#), in §7.6
- [TextDecoderStream\(\)](#), in §7.6
- [TextDecoderStream\(label\)](#), in §7.6
- [TextDecoderStream\(label, options\)](#), in §7.6
- [TextEncoder](#), in §7.4

- [TextEncoder\(\)](#), in §7.4
- [TextEncoderCommon](#), in §7.3
- [TextEncoderEncodeIntoResult](#), in §7.4
- [TextEncoderStream](#), in §7.7
- [TextEncoderStream\(\)](#), in §7.7
- [token](#), in §3
- [transform](#), in §7.5
- [UTF-16BE](#), in §14.2.1
- [UTF-16BE decoder](#), in §14.3
- [UTF-16LE](#), in §14.3.1
- [UTF-16 lead byte](#), in §14.2.1
- [UTF-16 lead surrogate](#), in §14.2.1
- [UTF-16LE decoder](#), in §14.4
- [UTF-8](#), in §8
- [UTF-8 bytes needed](#), in §8.1.1
- [UTF-8 bytes seen](#), in §8.1.1
- [UTF-8 code point](#), in §8.1.1
- [UTF-8 decode](#), in §6
- [UTF-8 decoder](#), in §8.1
- [UTF-8 decode without BOM](#), in §6
- [UTF-8 decode without BOM or fail](#), in §6
- [UTF-8 encode](#), in §6
- [UTF-8 encoder](#), in §8.1.1
- [UTF-8 lower boundary](#), in §8.1.1
- [UTF-8 upper boundary](#), in §8.1.1
- [windows-1250](#), in §9
- [windows-1251](#), in §9
- [windows-1252](#), in §9
- [windows-1253](#), in §9
- [windows-1254](#), in §9
- [windows-1255](#), in §9
- [windows-1256](#), in §9
- [windows-1257](#), in §9
- [windows-1258](#), in §9
- [windows-874](#), in §9
- [writable](#), in §7.5
- [written](#), in §7.4
- [x-mac-cyrillic](#), in §9
- [x-user-defined](#), in §14.4.1
- [x-user-defined decoder](#), in §14.5
- [x-user-defined encoder](#), in §14.5.1

Terms defined by reference §

- [INFRA] defines the following terms:
 - ascii byte
 - ascii case-insensitive
 - ascii code point
 - ascii digit
 - ascii lowercase
 - ascii whitespace
 - break
 - byte
 - code point
 - code unit

- continue
- convert
- length
- scalar value
- scalar value string
- starts with
- string
- surrogate
- [STREAMS] defines the following terms:
 - CreateTransformStream
 - ReadableStream
 - TransformStream
 - TransformStreamDefaultControllerEnqueue
 - WritableStream
 - chunk
 - pipeThrough(transform)
 - readable stream
 - transform stream
 - writable stream
- [WEBIDL] defines the following terms:
 - AllowShared
 - ArrayBuffer
 - BufferSource
 - DOMString
 - Exposed
 - NewObject
 - RangeError
 - TypeError
 - USVString
 - Uint32Array
 - Uint8Array
 - boolean
 - converted to an idl value
 - get a copy of the buffer source
 - get a reference to the buffer source
 - this
 - throw
 - unsigned long long

References §

Normative References §

[INFRA]

Anne van Kesteren; Domenic Denicola. [Infra Standard](https://infra.spec.whatwg.org/). Living Standard. URL: <https://infra.spec.whatwg.org/>

[STREAMS]

Adam Rice; Domenic Denicola; 吉野剛史 (Takeshi Yoshino). [Streams Standard](https://streams.spec.whatwg.org/). Living Standard. URL: <https://streams.spec.whatwg.org/>

[UNICODE]

[The Unicode Standard](https://www.unicode.org/versions/latest/). URL: <https://www.unicode.org/versions/latest/>

[WEBIDL]

Boris Zbarsky. [Web IDL](https://heycam.github.io/webidl/). URL: <https://heycam.github.io/webidl/>

Informative References §

[HTML]

Anne van Kesteren; et al. [HTML Standard](https://html.spec.whatwg.org/multipage/). Living Standard. URL: <https://html.spec.whatwg.org/multipage/>

[URL]

Anne van Kesteren. [URL Standard](https://url.spec.whatwg.org/). Living Standard. URL: <https://url.spec.whatwg.org/>

[XML]

Tim Bray; et al. [Extensible Markup Language \(XML\) 1.0 \(Fifth Edition\)](https://www.w3.org/TR/xml/). 26 November 2008. REC. URL: <https://www.w3.org/TR/xml/>

IDL Index §

```
IDL
interface mixin TextDecoderCommon {
    readonly attribute DOMString encoding;
    readonly attribute boolean fatal;
    readonly attribute boolean ignoreBOM;
};

dictionary TextDecoderOptions {
    boolean fatal = false;
    boolean ignoreBOM = false;
};

dictionary TextDecodeOptions {
    boolean stream = false;
};

[Exposed=(Window,Worker)]
interface TextDecoder {
    constructor(optional DOMString label = "utf-8", optional TextDecoderOptions options = {});

    USVString decode(optional [AllowShared] BufferSource input, optional TextDecodeOptions options = {});
};
TextDecoder includes TextDecoderCommon;

interface mixin TextEncoderCommon {
    readonly attribute DOMString encoding;
};

dictionary TextEncoderEncodeIntoResult {
    unsigned long long read;
    unsigned long long written;
};

[Exposed=(Window,Worker)]
interface TextEncoder {
    constructor();

    [NewObject] Uint8Array encode(optional USVString input = "");
    TextEncoderEncodeIntoResult encodeInto(USVString source, [AllowShared] Uint8Array destination);
};
TextEncoder includes TextEncoderCommon;

interface mixin GenericTransformStream {
    readonly attribute ReadableStream readable;
    readonly attribute WritableStream writable;
};

[Exposed=(Window,Worker)]
interface TextDecoderStream {
    constructor(optional DOMString label = "utf-8", optional TextDecoderOptions options = {});
};
TextDecoderStream includes TextDecoderCommon;
TextDecoderStream includes GenericTransformStream;

[Exposed=(Window,Worker)]
interface TextEncoderStream {
```

```
constructor();  
};  
TextEncoderStream includes TextEncoderCommon;  
TextEncoderStream includes GenericTransformStream;
```