

Diplomatico – A Graph-based Game Analysis

Filippo Garagnani

199670

October 24, 2025

Tesina del corso Graph Analytics, Prof.ssa Laura Po

Introduction

Theoretical Results


Empirical Results

References

Introduction

The Game

The game is played on a $n \times m$ **Board**:




The Game

The player chooses a square (i, j) in which to start – writing a **1**:

	1			

The Game

Each turn, the player can write the next integer, either moving horizontally/vertically by three squares or moving diagonally by two squares:




The Game

Goal of the game is to fill the whole grid:

	1			


The Game

Goal of the game is to fill the whole grid:




The Game

Goal of the game is to fill the whole grid:




The Game

Goal of the game is to fill the whole grid:



The Game

Goal of the game is to fill the whole grid:



The Game as a Graph

The game can be represented by an undirected graph. Assuming the Board to be of size $n \times m$:

- ◇ **Nodes** – Represent the *cells* of the grid:

$$V = \{v_{(i,j)}, i \in \mathbb{N}_n, j \in \mathbb{N}_m\}$$

The Game as a Graph

The game can be represented by an undirected graph. Assuming the Board to be of size $n \times m$:

- ◇ **Nodes** – Represent the *cells* of the grid:

$$V = \{v_{(i,j)}, i \in \mathbb{N}_n, j \in \mathbb{N}_m\}$$

- ◇ **Edges** – Represent possible moves between cells:

$$E \subseteq \binom{V}{2} \quad \text{s.t.}$$

$$\forall e = \{v_{(i,j)}, v_{(k,\ell)}\} \in E, \quad (|i - k| = 3 \wedge j = \ell) \quad (\text{vertical move})$$

$$\vee (|j - \ell| = 3 \wedge i = k) \quad (\text{horizontal move})$$

$$\vee (|i - k| = |j - \ell| = 2) \quad (\text{diagonal move})$$

The Game as a Graph

A **solution** to the game is an **Hamiltonian Path** of the graph – a sequence of nodes that contains each vertex once and exactly once:

$$\mathfrak{h} = (v^1, v^2, \dots, v^{n \times m})$$

$$\forall \ell \in \mathbb{N}_{n \times m}, \{v^{(\ell)}, v^{(\ell+1)}\} \in E \quad (\text{path})$$

$$\forall v_{(i,j)} \in V, \exists ! \ell \in \mathbb{N}_{n \times m} \text{ s.t. } v^\ell \equiv v_{(i,j)} \quad (\text{hamiltonian})$$

Theoretical Results

Theorem (Solvability)

Each Graph representing a board of size $n \times m$ is solvable (i.e., the graph admits at least one hamiltonian path) iff:

$$m \geq n \geq 4 \wedge (n, m) \neq (4, 4)$$

Theoretical Results

Theorem (Solvability)

Each Graph representing a board of size $n \times m$ is solvable (i.e., the graph admits at least one hamiltonian path) iff:

$$m \geq n \geq 4 \wedge (n, m) \neq (4, 4)$$

Theorem (Number of Solutions)

Given a solvable graph $\mathfrak{G}_{n \times m}$ representing a grid of size $n \times m$, the number of solutions $\mathbf{N}(\mathfrak{G}_{n \times m})$ (i.e., how many distinct hamiltonian paths it has) is:

$$2^{(n-4)(m-4)/25} \leq \mathbf{N}(\mathfrak{G}_{n \times m}) < 7^{nm-1}$$

Empirical Results

Finding a Solution

Four different approaches have been tried to find hamiltonian paths:

- ◇ **Neo4J:**

Finding a Solution

Four different approaches have been tried to find hamiltonian paths:

◇ **Neo4J:**

- **Raw** — Expand all possible paths of length $n \times m$ and check which are hamiltonian;

Finding a Solution

Four different approaches have been tried to find hamiltonian paths:

◇ **Neo4J:**

- **Raw** — Expand all possible paths of length $n \times m$ and check which are hamiltonian;
- **Constructive** — The query is built dynamically, at each step pruning choices that would not yield an hamiltonian path;

Finding a Solution

Four different approaches have been tried to find hamiltonian paths:

◇ **Neo4J:**

- **Raw** — Expand all possible paths of length $n \times m$ and check which are hamiltonian;
- **Constructive** — The query is built dynamically, at each step pruning choices that would not yield an hamiltonian path;
- **APOC** — Calling the apposite APOC function to return an hamiltonian path;

Finding a Solution

Four different approaches have been tried to find hamiltonian paths:

◇ **Neo4J:**

- **Raw** — Expand all possible paths of length $n \times m$ and check which are hamiltonian;
- **Constructive** — The query is built dynamically, at each step pruning choices that would not yield an hamiltonian path;
- **APOC** — Calling the apposite APOC function to return an hamiltonian path;

◇ **Python:** Building the graph and searching a path using a backtracking algorithm.

Finding a Solution — Raw Implementation

```
MATCH p = (start:Node) -[:MOVE*{len}] -> (end:Node)
WHERE ALL(
    n IN nodes(p)
    WHERE single(m IN nodes(p) WHERE m = n)
)
RETURN p
```


Finding a Solution — Constructive Implementation

```
MATCH (n0:Node)-[:MOVE]->(n1:Node)
WHERE id(n1) NOT IN {id(n0)}
MATCH (n1)-[:MOVE]->(n2:Node)
WHERE id(n2) NOT IN {id(n0), id(n1)}
...
```

Finding a Solution — APOC Implementation

```
MATCH (start:Node)
CALL apoc.path.expandConfig(
  startNode, {
    relationshipFilter: "MOVE>",
    minLevel: {parameters["pathLength"]},
    maxLevel: {parameters["pathLength"]},
    uniqueness: "NODE_GLOBAL",
    labelFilter: 'Node'
  }
) YIELD path
```

Time Results

Board Size	Raw	Constructive	APOC	Python
4×5	1.1492s	0.0331s	0.0143s	0.0034s
4×6	>30s	0.6907s	0.0307s	0.0503s
4×7	>30s	16.6208s	0.6338s	0.6547s
5×5	>30s	3.1501s	2.9022s	0.4530s

Table 1: Time results in finding every solution, with constraints on the starting and ending nodes.


Time Results

Board Size	APOC	Python
5×6	0.0578s	0.4754s
4×8	3.9755s	6.3072s
5×7	0.1442s	0.0007s
6×6	0.2700s	0.5473s

Table 2: Time results in finding only one solution for larger boards.

So: as boards get larger, the usage of **GraphDBs seems more effective** than a more traditional approach. The APOC library also provides several critical optimization to reduce computing time.

Centrality in a Board







Centrality and Number of Solutions

Board	Betweenness	Closeness	Degree	Eigenvector
4 × 5	-0.8228***	-0.5899**	-0.7845***	-0.1728
4 × 6	-0.7744***	-0.6316***	-0.7197***	-0.5179**
5 × 5	-0.6820***	-0.2543	-0.4037*	-0.1460
4 × 7	-0.9098***	-0.8204***	-0.8596***	-0.5842**
5 × 6	-0.7353*	-0.4310	-0.7729*	-0.5072

Table 3: Correlation coefficients (r) between Hamiltonian paths and centrality measures across different board sizes.

So: the more central a node is, **the less solutions** can be found starting from that node. It's empirically better to start the game from nodes **with low centrality values**.

References

-  R. C. contributors, “Solve a hopido puzzle,”
https://rosettacode.org/wiki/Solve_a_Hopido_puzzle, 2025,
accessed: 2025-09-17.
-  Neo4j Labs, “Apoc: Awesome procedures on cypher,” 2025,
version 2025.07.1core. [Online]. Available:
<https://neo4j.com/labs/apoc>
-  Neo4j, Inc., *Neo4j Graph Data Science Library Manual*, 2025,
online documentation and software plugin. [Online]. Available:
<https://neo4j.com/docs/graph-data-science/current/>
-  M. Sipser, *Introduction to the Theory of Computation*, 3rd ed.
Cengage Learning, 2013, pp. 292–314.



H. C. von Warnsdorff, “Des rösselsprunges einfachste und allgemeinste lösung.” [Online]. Available:

https://zs.thulb.uni-jena.de/receive/jportal_jparticle_00189099

Thank you!

Questions?