

Autodesk® Scaleform®

Scaleform 4.3 AS3

Scaleform 4.3

ActionScript 3.0

Artem Bolgar, Prasad Silva

1.05

2013 2 26

Autodesk® Scaleform® 4.3

© 2013 Autodesk, Inc. All rights reserved. Except as otherwise permitted by Autodesk, Inc., this publication, or parts thereof, may not be reproduced in any form, by any method, for any purpose.

Certain materials included in this publication are reprinted with the permission of the copyright holder.

The following are registered trademarks or trademarks of Autodesk, Inc., and/or its subsidiaries and/or affiliates in the USA and other countries: 123D, 3ds Max, Algor, Alias, AliasStudio, ATC, AutoCAD, AutoCAD Learning Assistance, AutoCAD LT, AutoCAD Simulator, AutoCAD SQL Extension, AutoCAD SQL Interface, Autodesk, Autodesk 123D, Autodesk Homestyler, Autodesk Intent, Autodesk Inventor, Autodesk MapGuide, Autodesk Streamline, AutoLISP, AutoSketch, AutoSnap, AutoTrack, Backburner, Backdraft, Beast, Beast (design/logo), BIM 360, Built with ObjectARX (design/logo), Burn, Buzzsaw, CADmep, CAiCE, CAMduct, CFdesign, Civil 3D, Cleaner, Cleaner Central, ClearScale, Colour Warper, Combustion, Communication Specification, Constructware, Content Explorer, Creative Bridge, Dancing Baby (image), DesignCenter, Design Doctor, Designer's Toolkit, DesignKids, DesignProf, Design Server, DesignStudio, Design Web Format, Discreet, DWF, DWG, DWG (design/logo), DWG Extreme, DWG TrueConvert, DWG TrueView, DWGX, DXF, Ecotect, ESTmep, Evolver, Exposure, Extending the Design Team, FABmep, Face Robot, FBX, Fempro, Fire, Flame, Flare, Flint, FMDesktop, ForceEffect, Freewheel, GDX Driver, Glue, Green Building Studio, Heads-up Design, Heidi, Homestyler, HumanIK, i-drop, ImageModeler, iMOUT, Incinerator, Inferno, Instructables, Instructables (stylized robot design/logo), Inventor, Inventor LT, Kynapse, Kynogon, LandXplorer, Lustre, Map It, Build It, Use It, MatchMover, Maya, Mechanical Desktop, MIMI, Moldflow, Moldflow Plastics Advisers, Moldflow Plastics Insight, Moondust, MotionBuilder, Movimento, MPA, MPA (design/logo), MPI (design/logo), MPX, MPX (design/logo), Mudbox, Multi-Master Editing, Navisworks, ObjectARX, ObjectDBX, Opticore, Pipeplus, Pixlr, Pixlr-o-matic, PolarSnap, Powered with Autodesk Technology, Productstream, ProMaterials, RasterDWG, RealDWG, Real-time Roto, Recognize, Render Queue, Retimer, Reveal, Revit, Revit LT, RiverCAD, Robot, Scaleform, Scaleform GFx, Showcase, Show Me, ShowMotion, SketchBook, Smoke, Softimage, Socialcam, Sparks, SteeringWheels, Stitcher, Stone, StormNET, TinkerBox, ToolClip, Topobase, Toxik, TrustedDWG, T-Splines, U-Vis, ViewCube, Visual, Visual LISP, Vtour, WaterNetworks, Wire, Wiretap, WiretapCentral, XSI.

All other brand names, product names or trademarks belong to their respective holders.

Disclaimer

THIS PUBLICATION AND THE INFORMATION CONTAINED HEREIN IS MADE AVAILABLE BY AUTODESK, INC. "AS IS." AUTODESK, INC. DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THESE MATERIALS.

Autodesk Scaleform

AS3

Autodesk Scaleform Corporation

6305 Ivy Lane, Suite 310

Greenbelt, MD 20770, USA

www.scaleform.com

info@scaleform.com

(301) 446-3200

(301) 446-3199

1		1
2		2
3	DisplayObjectEx	7
4	FocusEventEx	10
5	FocusManager	11
6	GamePad	17
7	GamePadAnalogEvent	18
8	InteractiveObjectEx	20
9	KeyboardEventEx	22
10	MouseEvent	23
11	MouseEventEx	25
12	TextEventEx	28
13	System	30
14	TextFieldEx	31

1 引言

Autodesk Scaleform® SDK™

PC

Adobe® Flash®

Autodesk Scaleform

Suite®)

Flash Web

(IME

) Autodesk Scaleform

“(Extension) ActionScript Scaleform

scaleform.gfx.Extensions.enabled true()

```
scaleform.gfx.Extensions.enabled = true;
```

```
scaleform.gfx.*;  
Extensions.enabled = true;
```

GFXSDK/Resources/AS3/CLIK Flash “ (Source) ”,

ActionScript 3.0 (Flash Studio :‘Edit’() -> ‘Preferences’() -> ‘ActionScript’ ->

‘ActionScript 3.0 Settings...’(ActionScript 3.0 ...) -> ‘Source path’(Source

)) , FLA

,Scaleform ,

Flash

, Flash , Scaleform

Scaleform , SDK

Scaleform

Autodesk API ,

Scaleform API

2

enabled

enabled:Boolean [read-write]

Scaleform 4.0.12

/

noInvisibleAdvance

noInvisibleAdvance:Boolean [read-write]

Scaleform 4.0.12

```
true,
    ,Flash ( , ActionScript
    , ) , true Scaleform Flash
    , true
```

SWF

getTopMostEntity()

```
public function getTopMostEntity(x :Number, y :Number, testAll:Boolean)
:DisplayObject
```

Scaleform 4.0.13

```
(x, y) (stage ) DisplayObject
( ,CLICK MOUSE_DOWN ROLL_OVER
)
```

```
MovieClip.hitTest , hitTest x y , getTopMostEntity
x y ,Extensions.getTopMostEntity(x, y).hitTest(x, y, true) == true
```

```
testAll :Boolean - (false),
(true) , getTopMostEntity true
```

x :Number, y :Number – Stage

[getMouseTopMostEntity](#)

getMouseTopMostEntity()

```
public function getTopMostEntity([testAll : Boolean],
    [mouseIndex : uint]) : DisplayObject
```

Scaleform 4.0.13

DisplayObject

getTopMostEntity, ,

```
testAll :Boolean – (false),
(true) , getTopMostEntity true
mouseIndex :Number –
```

[getTopMostEntity](#)

getMouseCursorType()

```
public function getMouseCursorType([mouseIndex : uint]) : String
```

Scaleform 4.0.13

flash.ui.Mouse.cursor

,

, MouseEvent.CURSOR_CHANGE

mouseIndex :Number –

, flash.ui.MouseCursor , :

- flash.ui.MouseCursor.ARROW : String = "arrow"

- [setMouseCursorType](#)
[MouseEvent](#)

[getMouseCursorType](#)
[MouseEvent](#)

setEdgeAAMode()

public function setEdgeAAMode(dispObj:DisplayObject, mode:uint):void

Scaleform 4.0.12

EdgeAA :

- scaleform.gfx.Extensions.EDGEAA_INHERIT = 0;Inherit EdgeAA On
- scaleform.gfx.Extensions.EDGEAA_ON = 1;Enable EdgeAA – EDGEAA_DISABLE
- scaleform.gfx.Extensions.EDGEAA_OFF = 2;Do not use EdgeAA
- scaleform.gfx.Extensions.EDGEAA_DISABLE = 3;Disable EdgeAA EDGEAA_ON

dispObj :DisplayObject – , EdgeAA
mode :uint – EdgeAA

[getEdgeAAMode](#)

getEdgeAAMode()

static public function getEdgeAAMode(dispObj:DisplayObject):uint

Scaleform 4.0.12

EdgeAA

dispObj :DisplayObject – , EdgeAA

[setEdgeAAMode](#)

visibleRect

visibleRect:Rectangle [read]

Scaleform版本: 4.0.14

, /

isScaleform

isScaleform:Boolean [read]

Scaleform版本: 4.0.14

SWF Gfx Flash , (true)

3 DisplayObjectEx

setRendererString

```
static public function setRendererString(o:DisplayObject, s:String)
```

Scaleform : 4.0.17

MovieClip ActionScript

:

```
import scaleform.gfx.*;
```

```
// m is a MovieClip on stage.
```

```
DisplayObjectEx.setRendererString(m, "Abc");  
trace(DisplayObjectEx.getRendererString(m));
```

getRendererString()

```
static public function getRendererString(o:DisplayObject) : String
```

Scaleform : 4.0.17

setRendererFloat

```
static public function setRendererFloat(o:DisplayObject, f:Number)
```

Scaleform : 4.0.17

```
import scaleform.gfx.*;

// m is a MovieClip on stage.

DisplayObjectEx.setRendererFloat(m, 17.1717);
trace(DisplayObjectEx.getRendererFloat(m));
```

getRendererFloat()静态方法

```
static public function getRendererFloat(o:DisplayObject) : Number
```

Scaleform : 4.0.17

disableBatching

```
static public function disableBatching(o:DisplayObject, b:Boolean)
```

Scaleform : 4.0.17

```
import scaleform.gfx.*;

// m is a MovieClip on stage.

DisplayObjectEx.disableBatching(batchDisable, true);
trace(DisplayObjectEx.isBatchingDisabled(batchDisable));
```

isBatchingDisabled() 静态方法

```
static public function isBatchingDisabled(o:DisplayObject) : Boolean
```

Scaleform : 4.0.17

4 FocusEventEx

```
package scaleform.gfx
{
    import flash.events.FocusEvent;

    public final class FocusEventEx extends FocusEvent
    {
        public var controllerIdx : uint = 0;

        public function FocusEventEx(type:String) { super(type); }
    }
}
```

```

        flash.events.FocusEvent
                                'controllerIdx'
                                Extensions.enabled
                                true
    ,Scaleform
    FocusEventEx
    ,
    FocusEvent
FocusEventEx
    ,
    ,

```

```
import scaleform.gfx.*;
import flash.events.FocusEvent;

Extensions.enabled = true;

function ev(e: FocusEvent)
{
    if (e is FocusEventEx)
    {
        var ee: FocusEventEx = e as FocusEventEx;
        trace("    controllerIdx = "+ee.controllerIdx);
    }
}
stage.addEventListener(FocusEvent.MOUSE_FOCUS_CHANGE, ev);
```

controllerIdx

```
controllerIdx : uint [read]
```

```
Scaleform 4.0.12
```

```
/ ( )
```

5 FocusManager

alwaysEnableArrowKeys

alwaysEnableArrowKeys:Boolean [read-write]

Scaleform 4.0.12

```
-- _focusrect
false( ) , _focusrect = false ,Flash
, alwaysEnableArrowKeys true
```

disableFocusKeys

disableFocusKeys:Boolean [read-write]

Scaleform 4.0.12

```
(TAB Shift-TAB ), ,
```

moveFocus()

```
static public function moveFocus(keyToSimulate : String,
    startFromMovie:InteractiveObject = null,
    includeFocusEnabledChars : Boolean = false,
    controllerIdx : uint = 0) : InteractiveObject
```

Scaleform 4.0.12

```
TAB disableFocusKeys modalClip ,:TAB Shift-
```

```
keyToSimulate :String - " " " " " " " " " "tab"
"shifftab"
startFromMovie:InteractiveObject - , ;moveFocus
( ) (Null)
, ;
```

```

includeFocusEnabledChars : Boolean =
    tabEnabled / tabIndex
false,
tabEnabled / tabIndex
controllerIdx : uint =
    ( 0)

    null

```

[findFocus](#)
[disableFocusKeys](#)
[setModalClip](#)
[getModalClip](#)

findFocus()

```

static public function findFocus(keyToSimulate : String,
    parentMovie:DisplayObjectContainer = null,
    loop : Boolean = false,
    startFromMovie:InteractiveObject = null,
    includeFocusEnabledChars : Boolean = false,
    controllerIdx : uint = 0) : InteractiveObject

```

Scaleform 4.0.12

```

: TAB Shift-
TAB disableFocusKeys setModalClip/getModalClip

keyToSimulate :String - " " " " " " " " " "tab" "shifftab"
parentMovie:DisplayObjectContainer -
    null
loop :Boolean - Boolean
    " " , findFocus "null"(
"false") ( "true")
startFromMovie:InteractiveObject - , ;moveFocus
    null

```

```

includeFocusEnabledChars :Boolean -      ,      moveFocus      focusEnabled
      tabEnabled / tabIndex      ,
false,      tabEnabled / tabIndex
controllerIdx :uint -
      ,
      null

```

[moveFocus](#)
[disableFocusKeys](#)
[setModalClip](#)
[getModalClip](#)

setFocus()

```

static public function setFocus(obj:InteractiveObject, controllerIdx:uint = 0) :void

```

Scaleform 4.0.12

```

stage.focus

```

```

obj:InteractiveObject -
controllerIdx :uint -      /      (      )

```

getFocus()

```

static public function getFocus(controllerIdx:uint = 0) :InteractiveObject

```

Scaleform 4.0.12

```

stage.focus

```

```

controllerIdx :uint -      /      (      )

```

numFocusGroups

numFocusGroups() :uint [read]

Scaleform 4.0.12

```
, setControllerFocusGroup 0 3  
, numFocusGroups 2
```

setFocusGroupMask()

public function setFocusGroupMask(obj:InteractiveObject, mask:uint) :void

Scaleform 4.0.12

```
, setControllerFocusGroup  
,  
, " 1" 0 , " 2" 0 1  
,
```

```
FocusManager.setControllerFocusGroup(0, 0);  
FocusManager.setControllerFocusGroup(1, 1);
```

```
FocusManager.setFocusGroupMask(button1, 0x1); // 0 - 0  
FocusManager.setFocusGroupMask(movieclip2, 0x1 | 0x2); // 0 1 -  
// 0 1
```

"focusGroupMask"

obj:InteractiveObject -
mask:uint -

[setControllerFocusGroup](#)
[getFocusGroupMask](#)

getFocusGroupMask()

static public function getFocusGroupMask(obj:InteractiveObject) :uint

Scaleform 4.0.12

(, setFocusGroupMask)

obj:InteractiveObject -

[setControllerFocusGroup](#)

[setFocusGroupMask](#)

setControllerFocusGroup()

static public function setControllerFocusGroup(controllerIdx:uint,
focusGroupId:uint) : Boolean

Scaleform 4.0.12

controllerIndex , 0

(), setControllerFocusGroup(1,1) 1
setControllerFocusGroup(1,0) 0 1

controllerIdx:uint -

focusGroupId:uint -

, true

getControllerFocusGroup()

static public function getControllerFocusGroup(controllerIdx:uint) :uint

Scaleform 4.0.12

controllerIndex -

setModalClip()

```
static public function setModalClip(mc:Sprite, controllerIdx:uint = 0) : void
```

Scaleform 4.0.12

“tabable” “(modal) TAB Shift-TAB

controllerIdx:uint -
mc:Sprite -

getModalClip()

```
static public function getModalClip(controllerIdx:uint = 0) : Sprite
```

Scaleform 4.0.12

controllerIdx -

6 GamePad

```
        (
            Scaleform
        ),
        SF_KeyCodes.h
        SWF

    ,Scaleform FxPlayer

    '
    '
    Gfx::Movie::HandleEvent
    AS3

    Scaleform FxPlayer
    GamePadAnalogEvents

    GamePad
    ,
    ,
    ,
```

supportsAnalogEvents()

```
public static function supportsAnalogEvents() :Boolean
```

```
Scaleform 4.0.13
```

```
Scaleform (
    true
    GamePadAnalogEvents
```

[GamePadAnalogEvent](#)

7 GamePadAnalogEvent

```

package scaleform.gfx
{
    import flash.events.Event;

    public final class GamePadAnalogEvent extends Event
    {
        public static const CHANGE:String = "gamePadAnalogChange";

        public var code :uint = 0; // scaleform.gfx.GamePad
//
        public var controllerIdx : uint = 0;
        public var xvalue :Number = 0; // [-1, 1]
        public var yvalue :Number = 0; // [-1, 1]

        public function GamePadAnalogEvent(bubbles:Boolean, cancelable:Boolean,
                                           code:uint, controllerIdx:uint = 0,
                                           xvalue:Number = 0, yvalue:Number = 0)
        {
            super(GamePadAnalogEvent.CHANGE, bubbles, cancelable);
            this.code = code;
            this.controllerIdx = controllerIdx;
            this.xvalue = xvalue;
            this.yvalue = yvalue;
        }
    }
}

Scaleform , Stage
, Stage Scaleform FxPlayer 'code' GamePad
, , , Scaleform ( ) :
```

```

import scaleform.gfx.*;

trace("GamePadAnalogEvents supported? " + GamePad.supportsAnalogEvents());

function ev(e: GamePadAnalogEvent)
{
    trace("code = " + ev.code);
    trace("controllerIdx = " + ev.controllerIdx);
    trace("xvalue = " + ev.xvalue);
    trace("yvalue = " + ev.yvalue);
}

```

```
}
stage.addEventListener(GamePadAnalogEvent.CHANGE, ev);
```

code

code : uint

Scaleform 4.0.13

/

Scaleform FxPlayer

[GamePad](#)

controllerIdx

controllerIdx : uint

Scaleform 4.0.13

/

()

xvalue

xvalue : Number

Scaleform 4.0.13

x

-1 1

,

-1 1

yvalue

yvalue : Number

Scaleform 4.0.13

y

-1 1

,

-1 1

8 InteractiveObjectEx

getHitTestDisable()

```
public function getHitTestDisable(o:InteractiveObject) : Boolean
```

Scaleform 4.0.13

```
'hitTestDisable' true ,MovieClip.hitTest  
,  
false
```

o - An interactive object.

'hitTestDisable' Boolean

[InteractiveObjectEx.setHitTestDisable](#)

setHitTestDisable()

```
public function setHitTestDisable(o:InteractiveObject, f:Boolean) : void
```

Scaleform 4.0.13

```
'hitTestDisable' true ,MovieClip.hitTest  
, false
```

o -

f - 'hitTestDisable' Boolean

[InteractiveObjectEx.getHitTestDisable](#)

getTopmostLevel()

```
public function getTopmostLevel (o:InteractiveObject) : Boolean
```

Scaleform 4.0.13

'topmostLevel' true , ,

o - An interactive object.

'topmostLevel' Boolean

[InteractiveObjectEx.setTopmostLevel](#)

setTopmostLevel ()

public function setTopmostLevel(o:InteractiveObject, f:Boolean) : void

Scaleform 4.0.13

```
'topmostLevel' true
, ,
false
"topmostLevel",
, A B "topmostLevel" true
: "topmostLevel",swapDepth ActionScript
false
```

o -

f - 'topmostLevel' Boolean

[InteractiveObjectEx.getTopmostLevel](#)

9 KeyboardEventEx

```

package scaleform.gfx
{
    import flash.events.KeyboardEvent;

    public final class KeyboardEventEx extends KeyboardEvent
    {
        public var controllerIdx : uint = 0;

        public function KeyboardEventEx(type:String) { super(type); }
    }
}

flash.events.KeyboardEvent                                'controllerIdx'
,                                                            Extensions.enabled                    true
,Scaleform KeyboardEventEx ,
KeyboardEvent KeyboardEventEx

, ,

import scaleform.gfx.*;
import flash.events.KeyboardEvent;

Extensions.enabled = true;

function ev(e: KeyboardEvent)
{
    if (e is KeyboardEventEx)
    {
        var ee: KeyboardEventEx = e as KeyboardEventEx;
        trace("    controllerIdx = "+ee.controllerIdx);
    }
}
stage.addEventListener(KeyboardEvent.KEY_DOWN, ev);
stage.addEventListener(KeyboardEvent.KEY_UP, ev);

controllerIdx
controllerIdx : uint [read]
Scaleform 4.0.12
/ ( )

```

10 MouseCursorEvent

```

package scaleform.gfx
{
    import flash.events.Event;

    public final class MouseCursorEvent extends Event
    {
        public var cursor : String = "auto";
        public var mouseIdx : uint = 0;

        static public const CURSOR_CHANGE : String = "mouseCursorChange";

        public function MouseCursorEvent()
        {
            super("MouseCursorEvent", false, true);
        }
    }
}

/ : bubbles – false, (bubble)
cancellable – true, preventDefault() ( )
Scaleform
( , flash.ui.Mouse.cursor ), stage
( Extensions.enabled true ) :

Extensions.enabled = true;

function e(e:MouseCursorEvent)
{
    trace(e.type + " " + e.mouseIdx + " " + e.cursor);
    e.preventDefault();
}
stage.addEventListener(MouseCursorEvent.CURSOR_CHANGE, e);

: Stage ,

```

cursor

cursor : String [read]

Scaleform 4.0.13

- `flash.ui.MouseCursor.ARROW` : String = "arrow"
- `flash.ui.MouseCursor.BUTTON` : String = "button"
- `flash.ui.MouseCursor.HAND` : String = "hand"
- `flash.ui.MouseCursor.IBEAM` : String = "ibeam"

mouseIdx

`mouseIdx` : uint [read]

Scaleform 4.0.13

/ ()

11 MouseEventEx

```
package scaleform.gfx
{
    import flash.events.MouseEvent;

    public final class MouseEventEx extends MouseEvent
    {
        public var mouseIdx : uint = 0;
        public var nestingIdx : uint = 0;
        public var buttonIdx : uint = 0; // LEFT_BUTTON, RIGHT_BUTTON, ...

        public static const LEFT_BUTTON : uint = 0;
        public static const RIGHT_BUTTON : uint = 1;
        public static const MIDDLE_BUTTON : uint = 2;

        public function MouseEventEx(type:String) { super(type); }
    }
}
```

```
flash.events.MouseEvent /
Extensions.enabled true ,Scaleform MouseEventEx ,
MouseEvent MouseEventEx
:
```

```
import scaleform.gfx.*;
Extensions.enabled = true;
```

```
stage.doubleClickEnabled = true;
```

```
function ev(e:MouseEvent):void
{
    trace("!!!! EVENT. " + cnt++);
    trace("    eventType    = "+e.type);
    trace("    bubbles      = "+e.bubbles);
    trace("    eventPhase    = "+e.eventPhase);
    trace("    target        = "+e.target.name);
    trace("    currentTarget = "+e.currentTarget.name);
    if (e is MouseEventEx)
    {
        var ee:MouseEventEx = e as MouseEventEx;
        trace("    mouseIdx      = "+ee.mouseIdx);
        trace("    nestingIdx    = "+ee.nestingIdx);
        trace("    buttonIdx     = "+ee.buttonIdx);
    }
}
```

```

:
,
,
buttonIdx

```

buttonIdx

```
buttonIdx : uint [read]
```

Scaleform 4.0.13

()

- MouseEventEx.LEFT_BUTTON :uint = 0 -
- MouseEventEx.RIGHT_BUTTON :uint = 1 -
- MouseEventEx.MIDDLE_BUTTON :uint = 2 -
- 3 , 2

mousedx

```
mouseIdx : uint [read]
```

Scaleform 4.0.13

/ ()

nestingIdx

```
nestingIdx : uint [read]
```

Scaleform 4.0.13

rollOver/Out mouseOver/Out dragOver/Out
/ (rollover/dragover)

```

rollOver/rollOut mouseOver/Out dragOver/dragOut
(
),
:
0
;
,
1,
rollOver/rollOut
rollOut/mouseOut/dragOut;
0,
rollOut/mouseOut/dragOut

```

12 TextEventEx

```

package scaleform.gfx
{
    import flash.events.TextEvent;

    public final class TextEventEx extends TextEvent
    {
        public var controllerIdx : uint = 0;

        public function TextEventEx(type:String) { super(type); }
    }
}

flash.events.TextEvent          'controllerIdx'
                                Extensions.enabled      true
,Scaleform      TextEventEx      ,      TextEvent
TextEventEx      ,      ,      :

import scaleform.gfx.*;
import flash.events.TextEvent;

Extensions.enabled = true;

function ev(e: TextEvent)
{
    if (e is TextEventEx)
    {
        var ee: TextEventEx = e as TextEventEx;
        trace("      controllerIdx = "+ee.controllerIdx);
    }
}
txf.addEventListener(TextEvent.TEXT_INPUT, ev);

```

controllerIdx

controllerIdx : uint [read]

Scaleform 4.0.12

/ ()

LINK_MOUSE_OVER/LINK_MOUSE_OUT

```
public static const LINK_MOUSE_OVER:String = "linkMouseOver";
public static const LINK_MOUSE_OUT:String = "linkMouse";
```

Scaleform 4.0.14

```
TextFieldEx.LINK_MOUSE_OVER TextFieldEx.LINK_MOUSE_OUT
TextField ( HTML ) over/out AS3
, addEventListener
```

buttonIdx

buttonIdx : uint [read]

Scaleform版本: 4.0.14

```
MouseEventEx.LEFT_BUTTON MouseEventEx.RIGHT_BUTTON
; MouseEventEx.buttonIdx)
```

13 System

actionVerbose

`actionVerbose:Boolean` [read-write]

Scaleform 4.0.12

/

getStackTrace()

`public function getStackTrace() : String`

Scaleform 4.0.12

getCodeFileName()

`public function getCodeFileName() : String`

Scaleform 4.0.12

14 TextFieldEx

appendHtml()

```
public function appendHtml(textField:TextField, newHtml:String) :void
```

Scaleform 4.0.12

```
newHtml HTML htmlText
(+=)( txt.htmlText += moreHtml) htmlText += HTML , HTML
, HTML HTML , newHtml
HTML( newHtml HTML , +=
)
```

```
textField:TextField - HTML
newHtml:String - HTML
```

setIMEEnabled()

```
static public function setIMEEnabled(textField:TextField, isEnabled:Boolean): void
```

Scaleform 4.0.12

```
/ IME isEnabled false,
IME , IME
```

```
textField :TextField -
isEnabled :Boolean - true - IME;
```

setVerticalAlign()

```
public function setVerticalAlign(textField:TextField, valign:String) :void
```

Scaleform 4.0.12

```
TextFieldEx
public static const VALIGN_TOP:String = "top";
public static const VALIGN_CENTER:String = "center";
public static const VALIGN_BOTTOM:String = "bottom";
```

```
center,
bottom, ( ) ;
```



top

```
textField:TextField -
valign:String - ("top", "center", "bottom")
```

getVerticalAlign()

```
static public function getVerticalAlign(textField:TextField) : String
```

Scaleform : 4.0.14

setImageSubstitutions ()静态方法

```

public setImageSubstitutions(substInfoArr:Array) : void
public setImageSubstitutions(substInfo:Object) : void
public setImageSubstitutions(null) : void

```

Scaleform 2.0.38

SWF

SWF

- 1.
2. Windows Macintosh
3. ActionScript myImage
4. OK

BitmapData

ActionScript

```

import flash.display.BitmapData;
var imageBmp:BitmapData = BitmapData.loadBitmap("myImage");

```

```

( import flash.display.BitmapData;
flash.display.BitmapData) " " -

```

ID

subString:String

15

image : BitmapData

width : Number

height : Number

baseLineY : Number

Y

w/o

id : String

ID “updateImageSubstitution ”

“substInfoArr ”

“substInfo ”

setImageS

ubstitutions(substInfo:Object)

setImageSubstitutions(substInfoArr:

Array)

setImageSubstitutions

setImageSubs

tutions(null)

setImageSubstitutions

ActionScript

ActionScript

substInfoArr:Array –

substInfo:Object –

null –

updateImageSubstitution()

var b1 = BitmapData.loadBitmap("smile1");

var b2 = BitmapData.loadBitmap("smile2");

var b3 = BitmapData.loadBitmap("smile3");

var a = new Array;

a[0] = { subString:"=", image:b1, baseLineY:35, width:20, height:20, id:"sm=" };

a[1] = { subString:":-)", image:b2, baseLineY:20, id:"sm:-)" };

a[2] = { subString:":\\", image:b3, baseLineY:35, height:100 };

a[3] = { subString:":-\\", image:b1 };

t.setImageSubstitutions(a);

“ = ”

“ smile1 ”

updateImageSubstitution ()静态方法

```
public updateImageSubstitution(id:String, image:BitmapData) : void
```

Scaleform 2.0.38

setImageSubstitutions

id:String -

ID

setImageSubstitutions

I

D

image:BitmapData -

null

setImageSubstitutions()

```
t.updateImageSubstitution("sm="), b3);
```

onEnterFrame

setInterval

updateImageSu

bstitution

```
var phase = 0;
var b1a = BitmapData.loadBitmap("smile1a");
var b2a = BitmapData.loadBitmap("smile2a");

onEnterFrame = function()
{
    if (phase % 10 == 0)
    {
        if (phase % 20 == 0)
        {
            _root.t.updateImageSubstitution("sm="), b1);
            _root.t.updateImageSubstitution("sm:-)", b2);
        }
        else
        {
            _root.t.updateImageSubstitution("sm="), b1a);
            _root.t.updateImageSubstitution("sm:-)", b2a);
        }
    }
}
```

```

        ++phase;
    }

```

setTextAutoSize()

```
static public function setTextAutoSize(textField:TextField, autoSz:String) : void
```

Scaleform : 4.0.14

TextFieldEx

```

public static const TEXTAUTOSZ_NONE:String = "none";
public static const TEXTAUTOSZ_SHRINK:String = "shrink";
public static const TEXTAUTOSZ_FIT:String = "fit";

```

shrink

fit

5

号

textAutoSize “fit”

“shrink”



textField:TextField –

autoSz:String -

("none", "shrink", "fit")

getTextAutoSize()

```
static public function getTextAutoSize(textField:TextField) : String
```

Scaleform : 4.0.14

"none" "shrink" "fit"

setNoTranslate()

```
static public function setNoTranslate(textField:TextField, noTranslate:Boolean) :  
                                void
```

Scaleform : 4.1.20

```
                                Gfx::Translator  
(true)                        Scaleform::Gfx::Translator::Translate
```

```
textField:TextField -  
noTranslate:Boolean -        /
```

getNoTranslate()

```
static public function getNoTranslate(textField:TextField) : Boolean
```

Scaleform : 4.1.20