

Autodesk® Scaleform®

ActionScript 2 XML

Scaleform 4.3 ActionScript 2 XML

: Prasad Silva
: 3.0
: July 28, 2010

Copyright Notice

Autodesk® Scaleform® 4.3

© 2013 Autodesk, Inc. All rights reserved. Except as otherwise permitted by Autodesk, Inc., this publication, or parts thereof, may not be reproduced in any form, by any method, for any purpose.

Certain materials included in this publication are reprinted with the permission of the copyright holder.

The following are registered trademarks or trademarks of Autodesk, Inc., and/or its subsidiaries and/or affiliates in the USA and other countries: 123D, 3ds Max, Algor, Alias, AliasStudio, ATC, AutoCAD, AutoCAD Learning Assistance, AutoCAD LT, AutoCAD Simulator, AutoCAD SQL Extension, AutoCAD SQL Interface, Autodesk, Autodesk 123D, Autodesk Homestyler, Autodesk Intent, Autodesk Inventor, Autodesk MapGuide, Autodesk Streamline, AutoLISP, AutoSketch, AutoSnap, AutoTrack, Backburner, Backdraft, Beast, Beast (design/logo), BIM 360, Built with ObjectARX (design/logo), Burn, Buzzsaw, CADmep, CAiCE, CAMduct, CFdesign, Civil 3D, Cleaner, Cleaner Central, ClearScale, Colour Warper, Combustion, Communication Specification, Constructware, Content Explorer, Creative Bridge, Dancing Baby (image), DesignCenter, Design Doctor, Designer's Toolkit, DesignKids, DesignProf, Design Server, DesignStudio, Design Web Format, Discreet, DWF, DWG, DWG (design/logo), DWG Extreme, DWG TrueConvert, DWG TrueView, DWGX, DXF, Ecotect, ESTmep, Evolver, Exposure, Extending the Design Team, FABmep, Face Robot, FBX, Fempro, Fire, Flame, Flare, Flint, FMDesktop, ForceEffect, Freewheel, GDX Driver, Glue, Green Building Studio, Heads-up Design, Heidi, Homestyler, HumanIK, i-drop, ImageModeler, iMOUT, Incinerator, Inferno, Instructables, Instructables (stylized robot design/logo), Inventor, Inventor LT, Kynapse, Kynogon, LandXplorer, Lustre, Map It, Build It, Use It, MatchMover, Maya, Mechanical Desktop, MIMI, Moldflow, Moldflow Plastics Advisers, Moldflow Plastics Insight, Moondust, MotionBuilder, Movimento, MPA, MPA (design/logo), MPI (design/logo), MPX, MPX (design/logo), Mudbox, Multi-Master Editing, Navisworks, ObjectARX, ObjectDBX, Opticore, Pipeplus, Pixlr, Pixlr-o-matic, PolarSnap, Powered with Autodesk Technology, Productstream, ProMaterials, RasterDWG, RealDWG, Real-time Roto, Recognize, Render Queue, Retimer, Reveal, Revit, Revit LT, RiverCAD, Robot, Scaleform, Scaleform GFx, Showcase, Show Me, ShowMotion, SketchBook, Smoke, Softimage, Socialcam, Sparks, SteeringWheels, Stitcher, Stone, StormNET, TinkerBox, ToolClip, Topobase, Toxik, TrustedDWG, T-Splines, U-Vis, ViewCube, Visual, Visual LISP, Vtour, WaterNetworks, Wire, Wiretap, WiretapCentral, XSI.

All other brand names, product names or trademarks belong to their respective holders.

Disclaimer

THIS PUBLICATION AND THE INFORMATION CONTAINED HEREIN IS MADE AVAILABLE BY AUTODESK, INC. "AS IS." AUTODESK, INC. DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THESE MATERIALS.

Autodesk Scaleform

XML

Autodesk Scaleform Corporation
6305 Ivy Lane, Suite 310
Greenbelt, MD 20770, USA

www.scaleform.com

info@scaleform.com

(301) 446-3200

(301) 446-3199

.....	1
1. XML	2
1.1 ActionScript XML	2
1.2 C++	2
1.3 C++ DOM	3
1.4	4
2.	5
3.	7
3.1 ActionScript XML	7
3.2 ActionScript XML.status	8
3.3 ActionScript XML.docTypeDecl	8

Autodesk® Scaleform® SDK
 PC
 Flash® Studio
 Scaleform
 Flash®
 Adobe®

Flash AS2 XML API XML XML XMLNode
 DOM XML Scaleform 4.x Scaleform
 DOM SAX2 XML
 Scaleform Player Expat Scaleform XML
 Windows®, Linux®, MacOS®, Xbox 360®, PSP® (PlayStation® Portable), PlayStation®2 (PS2), PlayStation®3 (PS3™), Nintendo® Wii
 Scaleform XML

1. XML

Scaleform XML

1.1 ActionScript XML

ActionScript XML
FxPlayer.cpp

Scaleform

XML

```
...
#include "XML/XML_Expatri.h"
using namespace Scaleform;
...
Ptr<XML::Parser> pexpatXmlParser = *new XML::ParserExpat;
Ptr<XML::SupportBase> pxmlSupport = *new XML::Support(pexpatXmlParser);
mLoader.SetXMLSupport(pxmlSupport);...
```

1.2 C++

XML

C++
DOM

XML
Scaleform

ActionScript XML

```
...
#include "GFx/XML/XML_DOM.h"
using namespace Scaleform;
...

//          DOM
XML::DOMBuilder domBuilder(Loader.GetXMLSupport());
//          DOM
XML::DOMBuilder domBuilder2(Loader.GetXMLSupport(), true);
...
//  xml      DOM
Ptr<XML::Document> pdoc = domBuilder.ParseFile("inputfile.xml",
                                              mLoader.GetFileOpener());

//  xml      DOM
Ptr<XML::ObjectManager> pObjMgr = *new XML::ObjectManager();
Ptr<XML::Document> pdoc2 = domBuilder.ParseFile("inputfile.xml",
                                              mLoader.GetFileOpener(), pObjMgr);
...
```

ActionScript XML

```
...
#include "GFx/XML/XML_DOM.h"
#include "GFx/XML/XML_Expatri.h"
using namespace Scaleform;
...
Ptr<XML::Parser> pexpatXmlParser = *new XML::ParserExpat;
```

```

Ptr<XML::Support> pxmlSupport = *new XML::Support(pexpatXmlParser);
...

//          DOM
XML::DOMBuilder domBuilder(pxmlSupport);
//          DOM
XML::DOMBuilder domBuilder2(pxmlSupport, true);
...
//
...

```

1.3 C++ DOM

<pre> using namespace Scaleform; ... void PrintDOMTree(XML::Node* proot) { switch (proot->Type) { case XML::ElementNodeType: { XML::ElementNode* pnode = static_cast< XML::ElementNode*>(proot); if (pnode->Prefix.GetSize() > 0) { printf("ELEM - '%s:%s' ns:'%s' prefix:'%s'" " localname: '%s'", pnode->Prefix.ToCStr(), pnode->Value.ToCStr(), pnode->Namespace.ToCStr(), pnode->Prefix.ToCStr(), pnode->Value.ToCStr()); } else { printf("ELEM - '%s' ns:'%s' prefix:''" " localname: '%s'", pnode->Value.ToCStr(), pnode->Namespace.ToCStr(), pnode->Value.ToCStr()); } for (XML::Attribute* attr = pnode->FirstAttribute; attr != NULL; attr = attr->Next) { printf(" {%s,%s}", attr->Name.ToCStr(), attr->Value.ToCStr()); } printf("\n"); for (XML::Node* child = pnode->FirstChild; child != NULL; child = child->NextSibling) PrintDOMTree(child); break; </pre>	<pre> using namespace Scaleform; ... void PrintDOMTree(XML::Node* proot) { switch (proot->Type) { case XML::ElementNodeType: { XML::ElementNode* pnode = static_cast< XML::ElementNode*>(proot); if (pnode->Prefix.GetSize() > 0) { printf("ELEM - '%s:%s' ns:'%s' prefix:'%s'" " localname: '%s'", pnode->Prefix.ToCStr(), pnode->Value.ToCStr(), pnode->Namespace.ToCStr(), pnode->Prefix.ToCStr(), pnode->Value.ToCStr()); } else { printf("ELEM - '%s' ns:'%s' prefix:''" " localname: '%s'", pnode->Value.ToCStr(), pnode->Namespace.ToCStr(), pnode->Value.ToCStr()); } for (XML::Attribute* attr = pnode->FirstAttribute; attr != NULL; attr = attr->Next) { printf(" {%s,%s}", attr->Name.ToCStr(), attr->Value.ToCStr()); } printf("\n"); for (XML::Node* child = pnode->FirstChild; child != NULL; child = child->NextSibling) PrintDOMTree(child); break; </pre>
--	--

```

    }
    case TextNodeType:
    {
        printf("TEXT - '%s'\n", proot->Value.ToCStr());
        break;
    }
    default:
    {
        printf("UNKN\n");
    }
}
}
...
Ptr<XML::Document> pdoc = domBuilder.ParseFile("inputfile.xml",
                                              Loader.GetFileOpener());
PrintDOMTree(root);

```

1.4

Scaleform GfxXMLConfig.h XML

XML DOM

```

//
#ifdef SF_BUILD_DEBUG
//          DOM
// #define SF_XML_DOCBUILDER_TRACE
//
//          DOM
// (
//
// #define SF_XML_DOCBUILDER_DOM_TREE_DUMP
//
#endif // #ifdef SF_BUILD_DEBUG

```

2.

Scaleform			XML
GfX::XML::Parser	GfX XML	XML_Support.h	
XML_Support.h	GfX::XML::ParserHandler	SAX2	

```

namespace Scaleform { namespace GfX { namespace XML {
//
// XML
//
//      /
//
// XML
//
class Parser : public RefCountBaseNTS<Parser, Stat_Default_Mem>
{
public:
    virtual ~Parser() {}

    //
    // Parse methods
    //
    virtual bool    ParseFile(const char* pfilename, FileOpenerBase* pfo,
                             ParserHandler* pphandler) = 0;
    virtual bool    ParseString(const char* pdata, UPInt len,
                               ParserHandler* pphandler) = 0;
};
}}} //SF::GfX::XML

```

XML	DOM	GfX::XML::ParserLocator
ParseFile	ParseString	
GfX::XM::LParserHandler		

```

namespace Scaleform { namespace GfX { namespace XML {
// SAX2
// DOM          SAX2
//
//
//
class ParserHandler : public RefCountBase<ParserHandler, StatMV_XML_Mem>
{
public:
    ParserHandler() {}
    virtual ~ParserHandler() {}

    //
    virtual void    StartDocument() = 0;
    virtual void    EndDocument() = 0;

    //
    virtual void    StartElement(const StringRef& prefix,

```

```

                                const StringRef& localname,
                                const ParserAttributes& atts) = 0;
virtual void      EndElement(const StringRef& prefix,
                                const StringRef& localname) = 0;
//
virtual void      PrefixMapping(const StringRef& prefix,
                                const StringRef& uri) = 0;
//
virtual void      Characters(const StringRef& text) = 0;
//
virtual void      IgnorableWhitespace(const StringRef& ws) = 0;
//
virtual void      SkippedEntity(const StringRef& name) = 0;

// Gfx::XMLParser                                Gfx::XML::ParserHandler
// // //                                xml
virtual void      SetDocumentLocator(const ParserLocator* plocator) = 0;
//
virtual void      Comment(const StringRef& text) = 0;
//
virtual void      Error(const ParserException& exception) = 0;
virtual void      FatalError(const ParserException& exception) = 0;
virtual void      Warning(const ParserException& exception) = 0;
};
}}} //SF::Gfx::XML

```

3.

3.1 ActionScript

XML

ActionScript XMLNode XML
ActionScript DOM
DOM
ActionScript
XML.load XMLNode DOM
ActionScript XMLNode DOM
XML XML XMLNode

```
// DOM
XMLNode temp = root.firstChild;
//
temp.someProperty = someValue;
//
XMLNode temp = temp.nextSibling;
//
temp = temp.prevSibling;
//
trace(temp.someProperty)
```

Flash™ Scaleform Scaleform
XMLNode

XMLNode XMLNode ActionScript
XMLNode

```
// DOM
XMLNode temp = root.firstChild;
//
temp.attributes.someProperty = someValue;
//
XMLNode temp = temp.nextSibling;
//
temp = temp.prevSibling;
//
trace(temp.attributes.someProperty)
```

Scaleform

3.2 *ActionScript XML.status*

ActionScript 2.0 XML

ActionScript

- 0
- -2 A CDATA
- -3 XML
- -4 DOCTYPE
- -5
- -6 XML
- -7
- -8
- -9
- -10

ActionScript

```
//  
// XML_ERROR_NONE = 0  
// XML_ERROR_INVALID_TOKEN = 0 (ie: XML.parse("http://www.google.com"))  
// XML_ERROR_UNCLOSED_CDATA_SECTION = -2  
// XML_ERROR_UNCLOSED_TOKEN = -3  
// XML_ERROR_INVALID_TOKEN = -4  
// XML_ERROR_INVALID_TOKEN = -5  
// XML_ERROR_UNCLOSED_TOKEN = -8  
// XML_ERROR_NO_ELEMENTS = -9  
// XML_ERROR_TAG_MISMATCH = -10  
//
```

GfX::XML::DOMBuilder

XML

GfX::XML::ParserLocator

3.3 *ActionScript XML.docTypeDecl*

Flash®	“ActionScript XML		DOCTYPE
XML.docTypeDecl	DTD	”	Flash Scaleform