Autodesk®
Scaleform®

ActionScript 2 XML User Guide

˧˥ ˥̌ ` ̉ ¡ Scaleform 4.3 ` ٪... ٱ ت - ´ ActionScript 2 XML ˦ ˥ ṇ ˥̉ ˜ ˧´ ˜ ˥ ˘ ٣ ˩`
˘ ˥˜ ˘ ٱ

يجي ˧: Prasad Silva
˦ ṇ ˥˩ ˧ ˦: 3.0
ٱ ك فج ˧ ˩: 2010 ˩ 7 ˩ 28 ˩

Autodesk®
GAMEWARE

Copyright Notice

Autodesk® Scaleform® 4.3

© 2013 Autodesk, Inc. All rights reserved. Except as otherwise permitted by Autodesk, Inc., this publication, or parts thereof, may not be reproduced in any form, by any method, for any purpose.

Certain materials included in this publication are reprinted with the permission of the copyright holder.

The following are registered trademarks or trademarks of Autodesk, Inc., and/or its subsidiaries and/or affiliates in the USA and other countries: 123D, 3ds Max, Algor, Alias, AliasStudio, ATC, AutoCAD, AutoCAD Learning Assistance, AutoCAD LT, AutoCAD Simulator, AutoCAD SQL Extension, AutoCAD SQL Interface, Autodesk, Autodesk 123D, Autodesk Homestyler, Autodesk Intent, Autodesk Inventor, Autodesk MapGuide, Autodesk Streamline, AutoLISP, AutoSketch, AutoSnap, AutoTrack, Backburner, Backdraft, Beast, Beast (design/logo), BIM 360, Built with ObjectARX (design/logo), Burn, Buzzsaw, CADmep, CAiCE, CAMduct, CFdesign, Civil 3D, Cleaner, Cleaner Central, ClearScale, Colour Warper, Combustion, Communication Specification, Constructware, Content Explorer, Creative Bridge, Dancing Baby (image), DesignCenter, Design Doctor, Designer's Toolkit, DesignKids, DesignProf, Design Server, DesignStudio, Design Web Format, Discreet, DWF, DWG, DWG (design/logo), DWG Extreme, DWG TrueConvert, DWG TrueView, DWGX, DXF, Ecotect, ESTmep, Evolver, Exposure, Extending the Design Team, FABmep, Face Robot, FBX, Fempro, Fire, Flame, Flare, Flint, FMDesktop, ForceEffect, Freewheel, GDX Driver, Glue, Green Building Studio, Heads-up Design, Heidi, Homestyler, HumanIK, i-drop, ImageModeler, iMOUT, Incinerator, Inferno, Instructables, Instructables (stylized robot design/logo), Inventor, Inventor LT, Kynapse, Kynogon, LandXplorer, Lustre, Map It, Build It, Use It, MatchMover, Maya, Mechanical Desktop, MIMI, Moldflow, Moldflow Plastics Advisers, Moldflow Plastics Insight, Moondust, MotionBuilder, Movimento, MPA, MPA (design/logo), MPI (design/logo), MPX, MPX (design/logo), Mudbox, Multi-Master Editing, Navisworks, ObjectARX, ObjectDBX, Opticore, Pipeplus, Pixlr, Pixlr-o-matic, PolarSnap, Powered with Autodesk Technology, Productstream, ProMaterials, RasterDWG, RealDWG, Real-time Roto, Recognize, Render Queue, Retimer, Reveal, Revit, Revit LT, RiverCAD, Robot, Scaleform, Scaleform GFx, Showcase, Show Me, ShowMotion, SketchBook, Smoke, Softimage, Socialcam, Sparks, SteeringWheels, Stitcher, Stone, StormNET, TinkerBox, ToolClip, Topobase, Toxik, TrustedDWG, T-Splines, U-Vis, ViewCube, Visual, Visual LISP, Vtour, WaterNetworks, Wire, Wiretap, WiretapCentral, XSI.

All other brand names, product names or trademarks belong to their respective holders.

Disclaimer

THIS PUBLICATION AND THE INFORMATION CONTAINED HEREIN IS MADE AVAILABLE BY AUTODESK, INC. "AS IS." AUTODESK, INC. DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF

MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING THESE MATERIALS.

Autodesk Scaleform̉ ᾰ̋ شي<:

˧ ˥ ˧ ˦ ˨ ˩	XML User Guide (XML ˧ ṇ ˅ ṇ ˥̆ 1)
p̲₇	Autodesk Scaleform Corporation 6305 Ivy Lane, Suite 310 Greenbelt, MD 20770, USA
˩ ṇ ˥ ˩ ṇ ˩	www.scaleform.com
Ն / ˦ ṇ ˧	info@scaleform.com
Ն ێ	(301) 446-3200 ṕ ˩ /̉ ף ح ۿ ḭ 050-3685-7107 ` Ṗ
Fax	(301) 446-3199

ᾄ η

1 ̉ ̑ ̣ ́ 1

2 XML̉ ⁒… ȉ 2

  2.1 ActionScript̉ XML ˧ ˨ ṇ ˥˜ أ گ́ ˘. 2

  2.2 C++ ᘓᗴ ˥ ˦ ˥ ˥ ˧ ˥ ̑ 2

  2.3 C++ ᘓᗴ` DOM ˥ ˧ ṇ˜ ˥ ˧ ˧ ṇ ˧˘. 3

  2.4 ˥ ˧ ˥ ˥ ˧ ˨ ṇ ˥̉ ˜ ⁄˧ 5

3 ˥ ˧ ˨ ˥ ˧ ṇ ˧ ṇ̉ ᾅ 6

4 q̉ Ŋڤ 8

  4.1 ActionScript́ ˥ ˧ ˨ ˥ XML ˧ ṇ ˥ ˧ ˧ ˧ ˥̋ ڝ ۇ ˇ ˋ ́ ˥ 8

  4.2 ActionScript XML.status ˧ ˧ ˧ ˥̋ ڝ ۇ ˇ ˋ ́ ˥ 9

  4.3 ActionScript XML.docTypeDecl ˧ ˧ ˧ ˥̋ ڝ ۇ ˇ ˋ ́ ˥ 10

1

Autodesk Scaleform SDK [illegible] Flash® [illegible] PC [illegible] Scaleform [illegible] Adobe® Flash® Studio [illegible]

Flash [illegible] ActionScript 2 XML [illegible] AS2 XML API [illegible] XML [illegible] XMLNode [illegible] DOM [illegible] XML [illegible] Scaleform 4.1 [illegible] Scaleform [illegible] DOM [illegible] SAX2 [illegible] XML [illegible] Scaleform Player [illegible] Expat [illegible] Scaleform [illegible] XML [illegible] :Windows® [illegible] Linux® [illegible] MacOS® [illegible] Xbox 360® [illegible] PSP® (PlayStation®Portable) [illegible] PlayStation®2 (PS2) [illegible] PlayStation®3 (PS3™) [illegible] Wii®

[illegible] Scaleform XML [illegible]

2 XML

[illegible] Scaleform [illegible] XML [illegible]

2.1 ActionScript の XML サポートを有効にする

ActionScript [illegible] XML [illegible] Scaleform [illegible] XML [illegible] Scaleform [illegible] FxPlayer.cpp [illegible]:

```
…
#include "XML/XML_Expat.h"
using namespace Scaleform;
…
Ptr<XML::Parser> pexpatXmlParser = *new XML::ParserExpat;
Ptr<XML::SupportBase> pxmlSupport = *new XML::Support(pexpatXmlParser);
mLoader.SetXMLSupport(pxmlSupport);…
```

2.2 C++言語のドキュメント解析

[illegible] C++ [illegible] XML [illegible] ActionScript XML [illegible] XML [illegible] DOM [illegible] (Scaleform [illegible] SDK [illegible])

```
…
#include "GFx/XML/XML_DOM.h"
using namespace Scaleform;
…
// [illegible] DOM [illegible]
XML::DOMBuilder domBuilder(Loader.GetXMLSupport());
// [illegible] DOM [illegible]
XML::DOMBuilder domBuilder2(Loader.GetXMLSupport(), true);
…
// [illegible] xml [illegible] DOM [illegible]
// ( [illegible] )
Ptr<XML::Document> pdoc = domBuilder.ParseFile("inputfile.xml",
                                               mLoader.GetFileOpener());
// [illegible] xml [illegible] DOM [illegible] ( [illegible] )
Ptr<XML::ObjectManager> pobjMgr = *new XML::ObjectManager();
```

```
Ptr<XML::Document> pdoc2 = domBuilder.ParseFile("inputfile.xml",
                                                 mLoader.GetFileOpener(), pobjMgr);
…
```

ActionScript XML ˥ ꜜ ṇ ꜛ צ أ گ̀ ̉ ́ ˥ ˧ ˧ i̤ ˥ ṇ ˥ ṇ̉ ꜛ ꜛ ˧ 1̄ ˧ ˧̌ ˧ ꜛ ꜛ ˧ ꜛ̃ ð8 ̀ i̤
ڶ ⅄̉ ̣ ڶ́ ⁒… ȉ̃ ̣ ڪ̀ צ̀ ק̃ ̆ :

```
…
#include "GFx/XML/XML_DOM.h"
#include "GFx/XML/XML_Expat.h"
using namespace Scaleform;
…
Ptr<XML::Parser> pexpatXmlParser = *new XML::ParserExpat;
Ptr<XML::Support> pxmlSupport = *new XML::Support(pexpatXmlParser);
…
// پ ڭ إ گ̃ پ ǎ̃ ̣ DOM ˥ ˦ ꜛ̃ ð8 ̃ ̣
XML::DOMBuilder domBuilder(pxmlSupport);
// پ ڭ إ گ̃ پ ێ̃ ̣ DOM ˥ ˦ ꜛ̃ ð8 ̃ ̣
XML::DOMBuilder domBuilder2(pxmlSupport, true);
…
// ⅄̉ ˥ ˥ ˥ ˦ ˦̉ پ ǎ̀ ⁄⊤
…
```

2.3 C++言語で DOM ツリーをトラバースする

ڶ ⅄̉ ꜛ ṇ 1̀ DOM ˥ ꜛ ṇ̉ ꜛ ṇ צ ꜛ ˩ ℵ̉ ̃ ̆ (Scaleform ˥ ṇ ꜛ SDK ꜛ̌ ꜛ ˧ ꜛ צ̒ í̀ ̃):

```
…
using namespace Scaleform;
…
void PrintDOMTree(XML::Node* proot)
{
    switch (proot->Type)
    {
        case XML::ElementNodeType:
        {
            XML::ElementNode* pnode =
                static_cast< XML::ElementNode*>(proot);
            if (pnode->Prefix.GetSize() > 0)
            {
                printf("ELEM - '%s:%s' ns:'%s' prefix:'%s'"
                       " localname: '%s'",
                       pnode->Prefix.ToCStr(),
                       pnode->Value.ToCStr(),
                       pnode->Namespace.ToCStr(),
                      pnode->Prefix.ToCStr(),
                      pnode->Value.ToCStr());
            }
            else
            {
                printf("ELEM - '%s' ns:'%s' prefix:''"
                       " localname: '%s'",
                      pnode->Value.ToCStr(),
                      pnode->Namespace.ToCStr(),
                      pnode->Value.ToCStr());
            }
            for (XML::Attribute* attr = pnode->FirstAttribute;
                  attr != NULL; attr = attr->Next)
            {
                printf(" {%s,%s}", attr->Name.ToCStr(),
                        attr->Value.ToCStr());
            }
            printf("\n");
            for (XML::Node* child = pnode->FirstChild; child != NULL;
                  child = child->NextSibling)
                PrintDOMTree(child);
            break;
        }
        case TextNodeType:
        {
            printf("TEXT - '%s'\n", proot->Value.ToCStr());
            break;
        }
        default:
        {
            printf("UNKN\n");
        }
    }
}
…
Ptr<XML::Document> pdoc = domBuilder.ParseFile("inputfile.xml",
                                               Loader.GetFileOpener());
PrintDOMTree(root);
```

2.4 デバッグレポートの設定

Scaleform ۱ ṇ ۷ ۷ ا ̈ ۱´ ̄ ۷ ۷ ۷˘. ۱ ṇ ۷ ṇ̉ i̯ ợ Ộ ỗ ̑ ﷺ ḱ ỏ Ớ Ộ ݣ ﮕ ۱ ۷ ṇ ۷̉ ۷ ۷ ۷˘ L ۸˘. ̀. XML_DOM.cpp´ ۷ ۷ ۷˘ ̃ ۸/ ̑ ض˘. ݘ` ݜ` ק˘ ˘ أ

```
// ۷ ۷ ۷ ۷ ۸ ۷ ۷ ۷ ۷ & ۷ ۷ ṇ ۷ ۷ ۷ ۷
//
#ifdef SF_BUILD_DEBUG
//
// ۷ ۷ ۷ ۷ ۸ ۷̉ ۱ ۷ ۱ ۷ ۷ ۷ ۷ ۱ ۷̉ DOM ۱ ۷ ṇ ݣ ۃ˘ ۷ ۱ ṇ ۷˘.
//
// #define SF_XML_DOCBUILDER_TRACE
//
// ȸ ݕ `DOM ۱ ۷ ṇ˘ ˘̉ ˘ غ ى ۸ ۷´ ۷ ۷ ۷˘.
// (ⴰⴷ: ۷ ק´ ۷ ا ̈ ۱̉ ۷ ۱̉ ݘ ˘ ﺒ ۱. ݘ` )
//
// #define SF_XML_DOCBUILDER_DOM_TREE_DUMP
//
#endif  // #ifdef SF_BUILD_DEBUG
```

3

Scaleform [illegible] expat [illegible] XML [illegible] XML_Support.h [illegible] GFx::XML::Parser [illegible] Scaleform XML [illegible] XML_Parser.h [illegible] GFx::XML::ParserHandler [illegible] SAX2 [illegible]

```
namespace Scaleform { namespace GFx { namespace XML {
//
// [illegible] XML[illegible]
//
// [illegible]
// [illegible]
// [illegible]
// XML[illegible]
//
//
class Parser : public RefCountBaseNTS<Parser, Stat_Default_Mem>
{
  public:
    virtual ~Parser() {}

  // [illegible]
    virtual bool    ParseFile(const char* pfilename, FileOpenerBase* pfo,
                              ParserHandler* pphandler) = 0;
    virtual bool    ParseString(const char* pdata, UPInt len,
                                ParserHandler* pphandler) = 0;
};
}}} //SF::GFx::XML
```

[illegible] XML [illegible] ParseFile [illegible] ParseString [illegible] DOM [illegible] GFx::XML::ParserLocator [illegible] GFx::XML::ParserHandler [illegible]

```
namespace Scaleform { namespace GFx { namespace XML {
//
// SAX2[illegible]
//
// DOM[illegible] SAX2[illegible]
// [illegible]
// [illegible]
class ParserHandler : public RefCountBase<ParserHandler, StatMV_XML_Mem>
{
  public:
    ParserHandler() {}
    virtual ~ParserHandler() {}

  // [illegible]
    virtual void        StartDocument() = 0;
    virtual void        EndDocument() = 0;

  // [illegible]
    virtual void        StartElement(const StringRef& prefix,
                                     const StringRef& localname,
                                     const ParserAttributes& atts) = 0;
    virtual void        EndElement(const StringRef& prefix,
                                   const StringRef& localname) = 0;

  // [illegible]
    virtual void        PrefixMapping(const StringRef& prefix,
                                      const StringRef& uri) = 0;

  // [illegible]
    virtual void        Characters(const StringRef& text) = 0;

  // [illegible]
    virtual void        IgnorableWhitespace(const StringRef& ws) = 0;

  // [illegible]
    virtual void        SkippedEntity(const StringRef& name) = 0;

  // GFx::XML::Parser [illegible]
  // [illegible] GFx::XML::ParserHandler [illegible]
  // [illegible] xmlversion [illegible]
  // [illegible]
    virtual void    SetDocumentLocator(const ParserLocator* plocator) = 0;

  // [illegible]
    virtual void        Comment(const StringRef& text) = 0;

  // ErrorHandler [illegible]
    virtual void        Error(const ParserException& exception) = 0;
    virtual void        FatalError(const ParserException& exception) = 0;
    virtual void        Warning(const ParserException& exception) = 0;

};
}}} //SF::GFx::XML
```

4

4.1 ActionScript にカスタム *XML* ノード プロパティが存在しない

```
// ٦ ٧ ı ٩ ٦ ٧˜ ﻬﺟ˘
temp = temp.prevSibling;
// ٦ ٧ ٧ ٦̉ ﻴﻣ6 ˜ ﺮﺿ˘
trace(temp.attributes.someProperty)
```

Scaleform ˋ someValue ٧ ١ لا ˜ ˘ ٲ

4.2 ActionScript XML.status プロパティが存在しない

٦ ٧ ٧ ٦̉ ٧ ṇ ٧ ṇ ٩̈ ٧ ٩ ٧̉ ٦ ٩ ṇ ٧ ṇ 1˜ ḭ ActionScript 2.0 XML̉ ٦ ٩ ṇ ٧ ṇ 1´ ٧ ٧ ٧ ٩ ٦˘. ˋ ק´ ٧˜˘ ˜ ´ ΰ ١ ﻢﺷﻬﻣ ᾱ ٧ ٧ ٧˘. ˋ. ḭ ̃ɔ̉ ٧ ٩ ٧ ٦̉ ᾱ ﺦﻓ لا ˜ , ˜ ˋ ˋ ˋ ٲ

ActionScript ٦ ٩ ṇ ٧ ṇ 1 :

0 ٦ ٩ ṇ´ ˋ ; ̑ ﺬﺨ̉ ₃ δ´ ש ﺞﻬﺑ ˋ ˜ ˋ ˋ ٲ

-2 CDATA ٧ ٦ ٦ ٩ ٧ ٧ .. ٧̈́ ´ ﻚﻬﺑ ˋ ˘ ך˜ , ˜ ٲ

-3 XML ﺶﻟ ٥ ٧ .. ٧̈́ ´ ﻚﻬﺑ ˋ ˘ ך˜ , ˜ ٲ

-4 DOCTYPE ﺶﻟ ٥ ٧ .. ٧̈́ ´ ﻚﻬﺑ ˋ ˘ ך˜ , ˜ ٲ

-5 ٧ ٩ ٧ ٦ ٧ .. ٧̈́ ´ ﻚﻬﺑ ˋ ˘ ך˜ , ˜ ٲ

-6 XML ٦ ٩ ٩ ٧ ٦̉ ﻙ ﻩ´ ₃ δ ٧ ט̣ ˜ ˋ ˋ ٲ

-7 ٩ ٩ ٧ ٧ ΰ ﺽ ˋ ˘ ך˜ ˘ ٲ

-8 ﻴﻣ6 ڑ ٧ .. ٧̈́ ´ ﻚﻬﺑ ˋ ˘ ך˜ , ˜ ٲ

-9˝ ı ٧ ٦ˋ ﻚﻬﺑ ٧ ٦ ٧ ١ ﻢﻫ ˋ ˜ , ˜ ˋ ˋ ˋ ٲ

-10 ١ ﻢﻫ˘. ˝ ı ٧ ٦̉ ´ ך ﻚﻬﺑ ٧ ٦ ٧ ף ١ لا ˜ ˋ ˋ ٲ

Expat פ. ActionScript ˋ̉ ٧ ٦ ٧ ٩ ٦ Ḳ

```
//
// XML_ERROR_NONE            = 0
// XML_ERROR_INVALID_TOKEN   = 0 (例: XML.parse("http://www.google.com"))
// XML_ERROR_UNCLOSED_CDATA_SECTION = -2
// XML_ERROR_UNCLOSED_TOKEN  = -3
// XML_ERROR_INVALID_TOKEN   = -4
// XML_ERROR_INVALID_TOKEN   = -5
// XML_ERROR_UNCLOSED_TOKEN  = -8
// XML_ERROR_NO_ELEMENTS     = -9
// XML_ERROR_TAG_MISMATCH    = -10
//
```

[illegible] *Scaleform::XML::DOMBuilder* [illegible] XML [illegible] *GFx::XML::ParserLocator* [illegible]

4.3 ActionScript XML.docTypeDecl プロパティが存在しない

Flash® [illegible] ActionScript [illegible] XML [illegible] DOCTYPE [illegible] XML.docTypeDecl [illegible] DTD [illegible] Flash [illegible] Scaleform [illegible]