MDPI

Article

The Accessibility Paradox: When LLM Simplification for Students with Learning Difficulties Amplifies Strategic Misconceptions in Computer Science Education

Marijela Miličević [1], Sandi Baressi Šegota [1], Ivan Lorencin [1], Darko Etinger [1]

[1] Faculty of Informatics, Juraj Dobrila University of Pula, Alda Negrija 6, 52100 Pula, Croatia; marijela.milicevic@unipu.hr (M.M.), sandi.baressi.segota@unipu.hr (S.B.Š.), ivan.lorencin@unipu.hr (I.L.), darko.etinger@unipu.hr (D.E.);

* Correspondence: ivan.lorencin@unipu.hr

Abstract

Large language models (LLMs) are increasingly used as assistive technology by students with reading and attention difficulties (e.g., dyslexia, ADHD), who rely on them as patient, private tutors capable of simplifying complex texts. However, it remains an open question whether this simplification compromises conceptual accuracy. This paper empirically investigates the accessibility paradox: the hypothesis that LLMs' attempts to be inclusive and simple result in an increased rate of strategic misconceptions, i.e., subtle, conceptually flawed, yet persuasively formulated responses that are particularly dangerous for vulnerable learners who already expend significant cognitive effort on text decoding and plausibly have reduced spare capacity for parallel fact-verification. We introduce AccessTrap-CS, a benchmark corpus of 720 responses generated by seven open-weight LLMs across 35 core computer science concepts spanning five subfields (7 per subfield). Each concept was prompted under three conditions: (a) a standard explanation, (b) a simplified explanation simulating interaction with a student with reading difficulties, and (c) a highly simplified explanation simulating interaction with a student with attention difficulties. Responses were evaluated for strategic misconception rate (SMR), dangerous analogy rate (DAR), and oversimplification error rate (OER), a novel error category capturing inaccuracies that arise exclusively from the simplification process. A stratified subsample was independently annotated by two domain-expert professors whose consensus served as the human reference standard. Statistical comparisons across models and conditions employ one-way ANOVA with Tukey HSD post-hoc correction and chi-square tests. The results show that simplification leaves the overall strategic misconception rate largely unchanged but multiplies the rate of dangerous analogies by more than an order of magnitude, and that the accessibility paradox is therefore fundamentally an analogy paradox. Based on these findings, we propose three accessibility-first design principles for AI tutoring interfaces that visually signal model uncertainty without relying on text-based disclaimers, thereby protecting the very learners these systems aim to serve.

Keywords: large language models; inclusive education; strategic misconceptions; accessibility; dyslexia; ADHD; assistive technology; AI safety; computer science education; oversimplification errors; dangerous analogies

Received:
Revised:
Accepted:
Published:

Copyright: © 2026 by the authors. Submitted to *Journal Not Specified* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license.

1. Introduction

Large language models (LLMs) are rapidly being adopted as assistive technology by students with reading and attention difficulties [1–3]. For learners with dyslexia, who struggle with text decoding, and students with ADHD, who face sustained attention challenges, LLMs offer a compelling value proposition: a patient, private tutor, available on demand, capable of simplifying complex academic texts in infinitely flexible ways [4,5].

Unlike human tutors, LLMs are available around the clock, never judge repeated questions, and can rephrase explanations until something clicks. It is therefore unsurprising that general-purpose assistants such as ChatGPT and Claude are increasingly used in this capacity, often without institutional oversight or teacher involvement. The same pattern is visible in computing education at large, where generative AI has moved from a curiosity to a routine study aid within a few years [6–8]. Early evidence on AI tutoring is encouraging [9,10], but it also carries a warning: unrestricted access to a generative assistant can raise performance while the assistant is available and lower it once the assistance is removed [11]. What the assistant says, and how it says it, matters for what the student actually learns.

However, this promising picture conceals a potentially dangerous blind spot. The very features that make LLMs attractive for students with learning difficulties, such as simplified language, short sentences, concrete analogies, and the avoidance of technical jargon, may inadvertently introduce subtle but pedagogically significant errors. We term this phenomenon the accessibility paradox: the hypothesis that LLMs' well-intentioned attempts to be inclusive and accessible result in an increased rate of what we call strategic misconceptions: subtly flawed yet persuasively formulated responses that are particularly dangerous for vulnerable learners.

We define a strategic misconception as an explanation that is conceptually coherent, internally consistent, and often intuitively appealing, but that nonetheless contains a fundamental misunderstanding of the target concept. Unlike random errors or obvious falsehoods, strategic misconceptions are dangerous precisely because of their plausibility: a student who encounters one is not alerted to an error but is instead led to construct a mental model that is systematically wrong. This definition draws on the conceptual-change tradition in science and mathematics education [12–14] and on the misconception literature in computing [15,16], which consistently shows that intuitive but incorrect prior conceptions are among the hardest to dislodge through subsequent instruction. Two further findings make plausible-but-wrong explanations especially hazardous: fluent, easy-to-process statements are judged more likely to be true [17,18], and people routinely overestimate how well they understand mechanisms after reading a satisfying but shallow explanation [19]. For students with dyslexia and ADHD, who already expend significant cognitive effort on text decoding and attention regulation [20–22], the spare capacity for parallel fact-verification is plausibly reduced. We stress that this is a situational vulnerability arising from processing load and missing scaffolding, not a deficit in intelligence, and that it applies in some measure to any novice reading under high load.

The computer science (CS) education context makes this problem particularly acute. CS concepts are often abstract, hierarchical, and resistant to faithful simplification through everyday analogy [16,23,24]. A concept such as a semaphore, a deadlock, or virtual memory cannot be accurately captured by a single intuitive metaphor without loss of essential technical content. Yet, under pressure to simplify, LLMs frequently resort to analogies that are intuitively appealing but technically misleading. For example, comparing a semaphore to a traffic light fails to convey atomicity and counting semantics, and describing a deadlock as two people stuck in a doorway omits resource holding and circular wait conditions. These errors are not isolated or accidental; they are systematic products of the simplification process itself. We term this subclass oversimplification errors (OER): errors that would not

appear in a standard explanation but emerge exclusively as a consequence of accessibility-driven simplification.

This trade-off between warmth and accuracy is not unique to accessibility contexts. Ibrahim et al. [25] demonstrated that fine-tuning LLMs to produce warmer, more empathetic responses consistently increases error rates across model architectures, with warm models showing substantially higher rates of factual inaccuracies and sycophantic validation of incorrect user beliefs, particularly when users expressed emotional vulnerability. This fits a broader line of evidence that preference-based alignment can reward agreeable, confident-sounding answers over correct ones [26–28]. Accessibility-driven simplification represents an analogous pressure: models instructed to be maximally clear and engaging may sacrifice technical precision in ways that standard evaluation benchmarks fail to detect [29].

Prior work has documented the benefits of LLMs for students with disabilities [1,30], has studied factual errors introduced by automatic text simplification in general-purpose text [31,32], and has separately studied misconceptions in CS education [15,23]. However, to the best of our knowledge, no study has empirically investigated whether accessibility-driven simplification systematically increases the rate of strategic misconceptions in LLM-generated CS explanations. This gap is critical: if simplification amplifies errors, then current assistive technology practices may be inadvertently harming the very population they aim to serve.

Research questions and hypotheses

The study is organised around four research questions, each paired with a directional hypothesis.

- RQ1. Does accessibility-driven simplification increase the strategic misconception rate? H1: SMR(B) $>$ SMR(A) and SMR(C) $>$ SMR(A).
- RQ2. Does it increase the use of dangerous analogies? H2: DAR(C) $\geq$ DAR(B) $>$ DAR(A).
- RQ3. Does simplification create errors that are absent from the standard explanation of the same concept, and do these grow with simplification intensity? H3: OER(B) $>$ 0, OER(C) $>$ 0, and OER(C) $>$ OER(B).
- RQ4. Are these effects moderated by model and CS subfield? This question is exploratory; we make no directional prediction.

In this paper, we present AccessTrap-CS, a benchmark corpus of 720 responses generated by seven open-weight LLMs across 35 core computer science concepts spanning five subfields: algorithms and data structures, programming languages and paradigms, databases, computer networks, and operating systems (7 per subfield). Each concept was prompted under three conditions: (a) a standard explanation suitable for a first-year CS student (baseline), (b) a simplified explanation simulating interaction with a student with reading difficulties (dyslexia condition), and (c) a highly simplified explanation simulating interaction with a student with severe attention difficulties (ADHD condition). Responses were evaluated using an LLM-as-judge approach [33], with Qwen3.6:35b serving as the expert evaluator, and validated against a stratified human-annotated subsample.

Our contributions are as follows. First, we provide empirical evidence on the accessibility paradox, testing whether accessibility-driven simplification, which increases readability and analogy frequency, also systematically introduces conceptual errors, including errors that do not occur under standard prompting conditions. Second, we introduce a novel error taxonomy: oversimplification errors (OER) as a distinct error category that emerges exclusively as a product of the simplification process and would not appear in technically precise explanations. Third, we present the first systematic analysis of dangerous analogies

in LLM-generated CS content under accessibility prompts, documenting cases in which commonly generated analogies misrepresent critical technical properties of CS concepts. Fourth, we validate the LLM judge against two domain-expert human annotators and report both inter-annotator agreement and judge–human agreement, showing that the judge substantially underestimates the true error rates. Fifth, we propose three accessibility-first design principles for AI tutoring interfaces that visually signal model uncertainty and analogy status without relying on text-based disclaimers, thereby protecting the very learners these systems aim to serve.

The remainder of this paper is organised as follows. Section 2 reviews related work. Section 3 describes our methodology. Section 4 presents quantitative and qualitative results. Section **??** discusses the implications of our findings. Section **??** proposes three design principles. Section **??** acknowledges limitations. Section 5 concludes.

2. Background and Related Work

The accessibility paradox sits at the intersection of several research streams that have developed largely independently: (1) LLMs as assistive technology for students with learning difficulties, (2) the reliability of LLMs and the pressures that trade accuracy for user-facing qualities, (3) text simplification and its pedagogical trade-offs, (4) the cognitive mechanisms that make fluent explanations persuasive and hard to verify, (5) analogies and misconceptions in computer science education, and (6) the methodology of LLM-based evaluation. This section reviews each stream and states precisely what it does and does not tell us about the accessibility paradox.

2.1. LLMs as Assistive Technology for Dyslexia and ADHD

Dyslexia is a neurodevelopmental difference characterised by difficulties with accurate and fluent word recognition and spelling, typically associated with weaknesses in the phonological component of language [20,34]. It persists into adulthood and into higher education, where reading loads are heavy and time-constrained. ADHD is characterised by persistent inattention and/or hyperactivity-impulsivity [21,35], and meta-analyses report working-memory impairments in affected children [22]; comparable working-memory weaknesses are reported for children with learning difficulties more broadly [36]. These are group-level tendencies. Individual profiles vary widely, and the two students in our prompts are operationalisations of an interaction style (simplified language, brevity), not clinical simulations. We return to this point in Section **??**.

For learners with dyslexia, LLMs can rephrase dense academic prose into shorter sentences, replace rare vocabulary with common alternatives, and maintain semantic coherence without the social cost of asking a human tutor for repeated clarification [1]. Earlier work on text presentation and simplification for dyslexia showed that both vocabulary choices and typography measurably affect readability and understandability [4,37]. For students with ADHD, whose attention and working-memory limitations make extended technical reading challenging [21], LLMs offer on-demand summarisation and task segmentation [2]. Empirical evidence for the ADHD case specifically remains thin and largely anecdotal or self-reported; disability-centred studies of LLMs emphasise both real benefits and concerns about reliability and representation [30].

Broad overviews frame LLMs as an opportunity for personalised support alongside risks of inaccuracy and over-reliance [3]. In computing education, LLMs solve introductory programming tasks [6], and working groups document how quickly these tools have entered practice and how much of the pedagogical evidence is still missing [7,8]. Controlled studies suggest that LLM-generated help can match human-authored help on mathematics practice [9] and that a carefully designed AI tutor can outperform in-class active learning

in a physics course [10]. Crucially, a field experiment in high-school mathematics found that free-form generative assistance improved performance during practice but harmed later unassisted performance, whereas a version with pedagogical safeguards largely mitigated the harm [11]. The design of what the assistant produces is therefore a first-order determinant of learning, not a cosmetic choice.

Studies on assistive text simplification have evaluated outcomes mainly through readability measures and user satisfaction [4,5], not through the conceptual accuracy of simplified technical content. No study to date has examined whether LLM-generated simplifications for learners with reading or attention difficulties introduce novel errors that are absent in standard explanations. The gap is non-trivial: the mechanisms that make simplification beneficial (reduced decoding effort, shorter sentences, concrete analogies) may simultaneously suppress the nuanced qualifications and precise technical language that prevent conceptual misunderstanding.

2.2. LLM Reliability, Sycophancy, and the Warmth–Accuracy Trade-Off

LLMs produce fluent text that is not necessarily faithful to fact or to a source [38,39]. Two properties of this literature matter here. First, errors are not confined to obscure facts: models can reproduce popular misconceptions, and on the TruthfulQA benchmark the largest models were often among the least truthful because they imitate widespread human falsehoods more faithfully [29]. This is directly relevant to analogies, which are precisely the popular, widely repeated framings of technical ideas. Second, factual quality is prompt-dependent: the same model can be accurate under one instruction and misleading under another.

Instruction-following and preference-based training optimise for outputs that human raters approve [26]. Approval and correctness are correlated but not identical. Models trained this way exhibit sycophancy, tailoring answers to the beliefs or expectations of the user, and preference data itself can reward it [27,28].

Ibrahim et al. [25] demonstrated that fine-tuning models to produce warmer, more empathetic responses increases error rates across architectural families, with warm models showing a statistically significant tendency toward sycophantic validation of incorrect user beliefs. This trade-off is not an implementation flaw but a plausible consequence of alignment pressure: models optimised for human preference judgments learn that users respond positively to agreeable, confident-sounding explanations, even when those explanations are technically incomplete.

Where warmth optimisation prioritises affective alignment, simplification prioritises cognitive accessibility. The two are not identical: a simplified explanation need not be warm, and a warm explanation need not be simple. However, they share a common mechanism: both pressures push models away from precise, qualified, context-dependent technical statements and toward concrete, declarative, analogy-laden statements that are easier to process but more likely to be wrong in subtle ways.

We propose the term oversimplification error (OER) to capture a specific subclass of simplification-induced inaccuracies: errors that would not appear in a standard, technically precise explanation of the same concept but emerge exclusively as a product of the simplification process. OERs are distinct from random factual errors, such as misstating the year of an algorithm's invention, in that they arise systematically from the interaction between the concept's inherent complexity and the pressure to reduce that complexity. A standard explanation of semaphores, for example, would specify atomicity, counting semantics, and the distinction between blocking and busy-waiting. A simplified explanation that omits atomicity is not merely incomplete; it actively misleads by suggesting that semaphores are just integer variables with special names.

Widely used evaluations measure knowledge or truthfulness under a fixed, neutral prompt [29]. A model can therefore score well on standard tests and still degrade when told to speak to a particular kind of learner. AccessTrap-CS is designed to expose exactly this audience-conditioned degradation.

A natural response is to have models flag their own uncertainty. Verbalised model confidence is often overconfident, and better estimators require additional computation such as semantic entropy or consistency across samples. This matters for the interface proposals in Section **??**: a visual uncertainty signal is only as trustworthy as the estimator behind it.

2.3. Text Simplification: Pedagogical Benefits and Technical Risks

Automatic text simplification has a long history in natural language processing, evolving from rule-based systems applying syntactic transformations and lexical substitution to neural sequence-to-sequence approaches and, more recently, LLMs [5]. Evaluation has traditionally focused on three dimensions: readability (measured by standard formulas such as Flesch Reading Ease [40] and Flesch-Kincaid grade level), semantic preservation (measured by entailment or meaning similarity), and grammaticality or fluency.

Simplification is not information-preserving by default. Work on factuality in simplification shows that models frequently insert errors or drop information, and that the errors are of kinds standard metrics do not catch [31]; Trienes et al. [32] characterise information loss in simplification explicitly and show that it can be surfaced through question-answering. These studies concern general-purpose text (news, encyclopedic and medical content). Our contribution is to move to technical CS concepts, where the information that gets lost tends to be exactly the boundary condition that defines the concept.

Conventional simplification evaluation assumes a monotonic relationship between simplification and information retention: simpler texts should preserve the truth conditions of the original while reducing linguistic complexity. For many domains, including news articles, consumer health information, and government documents, this assumption holds reasonably well. For computer science education, it breaks down. CS concepts are not facts about the world but abstract, relational structures with precise definitions and boundary conditions. A linked list is not merely a chain of connected items, as that description also fits a rope, a queue, or a biological pathway. The pedagogical challenge is to convey both the intuitive metaphor and the precise conditions under which the metaphor fails. Good CS instruction does not replace technical precision with analogy; it layers analogy on top of precision, using metaphor as a scaffold, not a substitute.

Even in the human-authored text literature, easier does not equal better for learning. Coherence-enhancing text revisions helped low-knowledge readers on shallow tests but limited deeper learning for readers with more knowledge [41], and the expertise reversal effect shows that support that helps novices can become a hindrance as knowledge grows [42]. Some difficulty is desirable, because effortful processing supports durable understanding [43]. The implication is not that learners with reading or attention difficulties should face inaccessible text, but that accessibility should reduce extraneous load (decoding, layout, jargon) while leaving intact the germane content (conditions, invariants, exceptions) [44].

LLMs asked to simplify lack this pedagogical awareness. Under pressure to produce simpler output, they can omit boundary conditions, elide exceptions, and promote analogies from the intuitive level to the definitional level. The result is not a simplified version of the same concept but a different, incorrect concept that happens to share surface features with the target. A student who learns that a deadlock is two people stuck in a doorway has

not learned a simplified but essentially correct version of deadlock; they have learned a misconception that will later need to be unlearned.

2.4. Why Fluent Explanations Mislead: Cognitive Foundations of Vulnerability

The claim that simplified explanations are especially hazardous for learners with reading or attention difficulties rests on four well-established cognitive mechanisms. We present them here as a theoretical motivation; our experiment does not measure them.

Working memory is severely limited [45], and cognitive load theory distinguishes intrinsic, extraneous, and germane load [44]. Automaticity theory holds that when word recognition is not automatic, decoding competes with comprehension for the same limited resources [46]. For a reader with dyslexia, decoding remains effortful longer; for a reader with ADHD, sustaining attention consumes regulation resources [21,22]. Both leave less spare capacity for what a critical reader does on top of comprehension: checking claims against prior knowledge, noticing what is missing, and asking whether an analogy really holds.

Statements that are easy to process are judged more likely to be true and elicit higher confidence [17,18]. A response deliberately engineered to be easy to read therefore also carries a built-in truth cue, whether or not the content deserves it. This is a second-order side effect of accessible design: the same property that reduces decoding cost also lowers the reader's guard.

People typically feel they understand causal systems far better than they can actually explain them, and the feeling is punctured only when they attempt to produce the explanation [19]. A short, vivid, self-contained explanation provides the feeling of understanding without the test, which is the condition under which an incorrect mental model can consolidate without challenge.

Dual-process accounts distinguish fast, effortless, intuitive judgement from slow, effortful checking [47]. Accepting a fluent explanation is the intuitive default; verification is the costly step. Human-automation research shows that people over-rely on automated aids, particularly when verification is expensive, and that interface interventions which force engagement can reduce over-reliance, at the price of extra effort [48]. We revisit this trade-off in Section **??**.

Finally, interesting but tangential material can impair learning of the core content [49]. Condition C, which explicitly asks for a memorable and engaging analogy, is exactly the situation in which the vividness of the analogy may compete with, rather than support, the technical content.

2.5. Analogies and Misconceptions in Computer Science Education

Learners do not arrive as blank slates: they build intuitive models, and instruction must confront and restructure them [12,14]. Misconceptions that are consistent with everyday experience are resistant to correction, because a wrong model that successfully explains a subset of observations is unlikely to be abandoned without clear counterexamples [13]. This makes the first exposure to a concept critical.

The study of misconceptions in CS education is well established. Qian and Lehman [15] provide a comprehensive review, identifying common incorrect mental models across introductory programming, such as variable assignment as mathematical equality, the countdown misconception in loops, confusion between reference and value semantics, as well as data structures, such as believing that binary search trees are inherently balanced, and concurrency, such as thinking that race conditions are deterministic or that semaphores prevent all interleavings. Foundational work documented that novice bugs are often language-independent conceptual errors [24], that many misconceptions stem from an

inaccurate mental model of the machine [16], and that students' understanding of synchronisation evolves through intermediate, faulty models. These resources provide the ground truth logic for our concept selection and error coding, but they describe misconceptions held by human novices, not those induced by generated explanations.

Analogy is a central instrument of explanation. Structure-mapping theory holds that a good analogy transfers relational structure, not surface attributes [50]. A traffic-light analogy for a semaphore conveys an attribute (something signals go/stop) but not the relational structure (atomic counting operations coordinating concurrent processes). Analogies are widespread in science and computing teaching, and can improve learning of programming when they match the target model. But it has long been recognised that analogies produce analogy-induced misconceptions, because learners import features of the source that the target does not have [51]. Recommended practice requires explicitly mapping the shared features and, crucially, stating where the analogy breaks down [52]; multiple analogies with complementary strengths are proposed as an antidote to single-analogy misconceptions [51].

Condition C of our study requests one single, vivid analogy, which is exactly the situation the analogy literature warns against: a single analogy, with no stated limits, presented as the core of the explanation. Stone et al. [23] recently extended the analogy analysis to LLM-generated educational content, documenting that common analogies produced by GPT-4 for CS concepts frequently misrepresent technical properties. However, their study used standard prompting without explicit accessibility constraints and did not compare simplification conditions. Our work builds directly on it by systematically varying simplification pressure and measuring the resulting amplification of strategic misconceptions.

2.6. LLM-as-Judge Evaluation

Scaling up expert judgement of open-ended text has led to the widespread use of strong LLMs as evaluators. Strong judges can reach agreement with human raters at a level comparable to human–human agreement on chat tasks [33], and rubric-based prompting improves alignment with humans on generation quality [53]. The approach has known biases that shape our design: sensitivity to the position of candidate answers [54], verbosity preferences, and a preference for the judge's own outputs [55]. Section 3 describes how we address these biases and how we validate the judge against human experts; Section **??** discusses the remaining risks.

2.7. The Accessibility Paradox: A Formal Hypothesis

Synthesising these streams, we formalise the accessibility paradox as a testable hypothesis. For a given concept c in computer science, let $E_s(c)$ be an LLM-generated explanation under a standard prompt (baseline) and $E_a(c)$ be an explanation under an accessibility prompt requesting simplification for a student with reading or attention difficulties. The strategic misconception rate $\mathrm{SMR}(E)$ is the probability that E contains a conceptually coherent but fundamentally incorrect understanding of c. The oversimplification error rate $\mathrm{OER}(E)$ is the probability that E contains an error present in E_a but absent from E_s for the same concept.

The accessibility paradox hypothesis states:

$$\mathrm{SMR}(E_a) > \mathrm{SMR}(E_s) \quad \text{and} \quad \mathrm{OER}(E_a) > 0, \tag{1}$$

with the difference increasing as a function of simplification intensity. That is, making explanations more accessible for students with learning difficulties increases, rather than

decreases, the rate of strategic misconceptions, and introduces a new class of errors that would not occur in standard explanations.

This hypothesis does not imply that simplification is inherently harmful or that LLMs should not be used as assistive technology. Rather, it predicts a previously undocumented failure mode that current evaluation practices do not detect. The AccessTrap-CS benchmark described in Section 3 was designed to test this hypothesis across models, subfields, and simplification intensities.

3. Materials and Methods

This section describes the benchmark design, concept selection, model selection, prompt engineering, data generation procedure, evaluation framework, human evaluation protocol, readability metrics, and statistical analysis plan. For each design decision we state the rationale, because in a benchmark study the choices are part of the result.

3.1. Benchmark Design Overview

The AccessTrap-CS benchmark tests the accessibility paradox hypothesis across three dimensions: model (7 LLMs), CS subfield (5 subfields), and simplification intensity (3 conditions). The design is fully crossed: each of the 35 concepts is posed to each of the 7 models under each of the 3 conditions, and each cell produces a single response, yielding 735 possible responses, of which 720 were successfully generated and evaluated. The 35 concepts and 7 models yield 245 concept-model pairs, each observed under three conditions.

$$N_{\text{total}} = C \times M \times K = 35 \times 7 \times 3 = 735 \tag{2}$$

where $C = 35$ concepts, $M = 7$ models, and $K = 3$ conditions. Because the same concept-model pair appears in all three conditions, condition is a within-pair (repeated) factor. This matters for analysis and is what allows the oversimplification error to be defined as a contrast within a pair. Figure 1 shows the overall pipeline.




Figure 1. AccessTrap-CS pipeline: from concept ground truth to statistical analysis.

The pipeline proceeds in six stages. Ground-truth definitions for the 35 concepts are first paired with the three prompt conditions, then passed to the seven open-weight LLMs served locally through Ollama. The resulting responses are aggregated into the 720-response corpus, which is then scored by the LLM judge together with the readability metrics. Finally, the scored corpus is analysed statistically in R. Each of these stages is described in detail in the subsections that follow.

3.2. Concept Selection

A total of 35 core computer science concepts were selected across five subfields: Algorithms and Data Structures, Programming Languages and Paradigms, Database Systems, Computer Networks, and Operating Systems (7 concepts per subfield). The balanced design ensures that subfield comparisons are not driven by unequal sample sizes. Concepts were drawn from standard core undergraduate curricula following the ACM/IEEE-CS/AAAI Computer Science Curricula [56]. Each concept was paired with a ground-truth definition and a reference source from standard textbooks. The ground truth serves as the judge's anchor: without it, the judge would have to rely on its own parametric knowledge, which is exactly the resource whose reliability is under test. The complete list appears in Appendix A.

3.3. Model Selection

Seven open-weight LLMs were selected to ensure reproducibility and to cover a range of model families, parameter scales, and architectural designs. Open weights allow anyone to rerun the whole pipeline locally, without dependence on a vendor's changing API. All models were accessed locally via Ollama running on the Supek HPC cluster. Table 1 summarises the selected models.

Table 1. Selected open-weight LLMs. Ollama tags and parameter counts were verified with `ollama show`.

Model (Ollama tag)	Family	Parameters
mistral:7b	Mistral AI	7B (dense)
deepseek-r1:8b	DeepSeek (distilled)	8B (dense, reasoning)
ministral-3:14b	Mistral AI	14B (dense)
phi4:14b	Microsoft	14B (dense)
gpt-oss:20b	OpenAI (open-weight)	20B (dense)
gemma4:31b	Google	31B (dense)
deepseek-r1:32b	DeepSeek (distilled)	32B (dense, reasoning)

Models span parameter scales from 7B to 32B, include two reasoning-trace models (deepseek-r1:8b and deepseek-r1:32b), and cover five distinct model families. Ollama serves quantised weights by default; we therefore treat model behaviour as that of the quantised builds actually used, and report the exact Ollama tags, quantisation levels, and model digests in the repository. All inference was performed with temperature $T = 0.7$ and `num_predict` = 512 tokens.

The temperature $T = 0.7$ was chosen to approximate typical chat deployment, where users interact with sampled rather than greedy outputs; the price is run-to-run variability, which we discuss as a limitation in Section **??**.

3.4. Prompt Engineering and Condition Design

Three prompt templates were designed corresponding to three simplification intensities. All three share the same structure (an instruction followed by `Answer in English.` and `Concept: [CONCEPT]`), so that the only variable is the instruction. The prompts operationalise two recurring accessibility recommendations: reducing decoding load (short sentences, plain vocabulary, no formal notation) and reducing sustained-attention demand (brevity, a single memorable hook).

3.4.1. Condition A: Standard Explanation (Baseline)

The baseline prompt requests an accurate and clear explanation suitable for a first-year computer science student. No simplification constraints are applied. It defines the reference against which errors introduced by simplification are measured.

```
Explain the following computer science concept accurately and clearly,
suitable for a first-year computer science student.

Answer in English.

Concept: [CONCEPT]
```

3.4.2. Condition B: Simplified Explanation (Reading Difficulties)

The simplified prompt instructs the model to address a student with reading difficulties. Constraints include simplified language, short sentences, concrete analogies,

avoidance of code and formal definitions, and minimal technical jargon. This condition targets the decoding-load mechanism.

```
Explain the following computer science concept to a student who has
reading difficulties. Use simplified language, short sentences, and
concrete analogies instead of code or formal definitions. Avoid
technical jargon where possible.

Answer in English.

Concept: [CONCEPT]
```

3.4.3. Condition C: Highly Simplified Explanation (Attention Difficulties)

The highly simplified prompt instructs the model to address a student with significant attention difficulties. Constraints include a maximum of five sentences, a single vivid analogy that captures the core idea, and emphasis on memorability and engagement. This condition targets the sustained-attention mechanism and is intended as the higher-intensity condition, because it removes even the space in which qualifications could be placed.

```
Explain the following computer science concept to a student with
significant attention difficulties. Keep the explanation within five
sentences. Use one single, vivid analogy that captures the core idea.
Make it memorable and engaging.

Answer in English.

Concept: [CONCEPT]
```

3.4.4. Construct Validity of the Conditions

Three properties of the prompt design need to be stated explicitly. First, the conditions are bundles of constraints: B and C differ from A, and from each other, in several respects at once (audience label, register, length, number of analogies, instruction to avoid formal definitions). The study therefore tests whether the bundle typical of accessibility-oriented simplification is risky, not the causal contribution of any single element. Second, only condition A contains the word accurately; an accuracy cue is absent in B and C, mirroring how real users write requests but confounding simplification with the absence of that cue. Third, the instruction in B to avoid formal definitions directly discourages the very precision whose absence we count as error. We treat this as the realistic operational form of the paradox (users and teachers do ask for these things) but acknowledge it in Section **??**. Finally, the labels dyslexia condition and ADHD condition denote the prompt persona, not the diagnostic status of any real person.

3.5. Data Generation Procedure

Data generation was automated using a Python script that iterates over all combinations of concepts, conditions, and models.

3.5.1. Input Format

The script reads `ground_truth.csv` (semicolon-delimited) containing the following columns: `ID`, `Domain`, `Concept`, `Ground_Truth`, `Reference`.

3.5.2. Generation Loop

For each concept, the script formats the three prompt templates by substituting the concept name. For each of the 7 models, it sends a POST request to the Ollama API at `http://localhost:11434/api/generate`, collects the response text, and appends the response to `corpus.csv` with metadata. A 1-second pause between requests prevents API overload. Failed requests are retried with a 5-second delay. No system prompt, conversation history, or few-shot examples were used, so each response reflects a single-turn interaction.

3.5.3. Output Format

The complete corpus `corpus.csv` contains 720 rows with the following schema: `concept_id`, `domain`, `concept`, `condition`, `model`, `prompt`, `response`, `ground_truth`, `reference`, `timestamp`.

3.6. Evaluation Framework

Responses were evaluated using an LLM-as-judge approach [33] with Qwen3.6:35b serving as the expert evaluator. The evaluation script groups responses by concept and model, then presents all three conditions (A, B, C) to the judge simultaneously together with the ground truth. Joint presentation is required for the OER judgement, which is by definition a comparison between a simplified response and the baseline for the same pair; the cost is that the judge's decisions on one condition may be influenced by the others (Section **??**).

3.6.1. Judge Model Selection

Qwen3.6:35b was chosen as the judge for three reasons: (a) its scale approximates frontier capability for a locally hosted model, (b) its open-weight license ensures reproducibility, and (c) it is architecturally and organisationally distinct from the seven generators. Because the judge is a different model from all generators, no self-evaluation bias arises from a model judging its own outputs. The judge is configured with temperature $T = 0.0$ for deterministic outputs and `num_predict` = 1024 tokens.

3.6.2. Error Taxonomy

Four evaluation dimensions are defined.

Strategic Misconception (SM). A Boolean indicator of whether the explanation contains a subtle but conceptually significant error that sounds plausible but is fundamentally wrong. The defining features are plausibility and consequence: a misstated date or a typographical slip is an error but not a strategic misconception, while claiming that a deadlock is merely processes waiting a long time is.

Dangerous Analogy (DA). A Boolean indicator of whether the explanation uses an analogy that is intuitive but misrepresents a key technical property of the concept. An analogy is not dangerous merely for being incomplete; it is dangerous if it invites an inference that is false for the target (e.g., a semaphore as a traffic light invites the inference that a semaphore is a simple binary flag with no atomicity).

Oversimplification Error (OER). A Boolean indicator of whether the explanation contains an error that would not appear in a standard explanation, i.e., an error that exists only because of the simplification process. By construction, OER is defined only for conditions B and C, since the reference is condition A.

Accuracy Score. A Likert scale from 1 to 5, where 1 = completely wrong and 5 = perfectly accurate. It complements the Boolean indicators by capturing graded degradation that does not cross the threshold of a strategic misconception.

The three Boolean indicators overlap by design (a dangerous analogy is a common route to a strategic misconception, and an oversimplification error is typically also a misconception) but are not identical, and they are analysed both separately and jointly.

3.6.3. Formal Definitions of the Outcome Measures

Let r_{cmk} denote the response for concept $c \in \{1, \ldots, 35\}$, model $m \in \{1, \ldots, 7\}$, and condition $k \in \{A, B, C\}$, and let $\mathrm{SM}_{cmk}, \mathrm{DA}_{cmk}, \mathrm{OER}_{cmk} \in \{0, 1\}$ be the judge's indicators. For a set S of judged responses,

$$\mathrm{SMR}(S) = \frac{1}{|S|} \sum_{(c,m,k) \in S} \mathrm{SM}_{cmk}, \qquad \mathrm{DAR}(S) = \frac{1}{|S|} \sum_{(c,m,k) \in S} \mathrm{DA}_{cmk}, \tag{3}$$

and $\mathrm{OER}(S)$ is defined analogously over responses with $k \in \{B, C\}$. Condition-level rates are obtained by taking S to be all judged responses in condition k; model- and subfield-level rates by conditioning on m or on the subfield of c.

3.6.4. Evaluation Procedure

The evaluation script:

1. Loads `corpus.csv` and groups rows by (`concept_id`, `model`)
2. For each group, assembles the judge prompt with ground truth and three responses
3. Randomises the presentation order of the three conditions and records the position of each response (`position_shown`)
4. Sends a POST request to the Ollama API
5. Parses the JSON response and flattens it into three rows (one per condition)
6. Appends results to `evaluations.csv`

A 2-second pause between requests prevents API overload. Failed JSON parses are logged for manual inspection. Unrecoverable outputs are excluded from the affected analyses and reported by model and condition, so that missing data are not silently absorbed.

3.7. Human Evaluation Protocol

To validate the LLM judge and to establish a human reference standard, a stratified random subsample of 30 concept-model groups was independently annotated by two professors with domain expertise in the relevant computer science subfields. Stratification was by subfield (five subfields) and by generating model (seven models), yielding 30 groups spanning the full design space.

The human evaluation was conducted in two parts. In Part 1, each annotator rated all 90 responses (30 groups $\times$ 3 conditions) on three dimensions: strategic misconception (SM, Boolean), dangerous analogy (DA, Boolean), and accuracy (1–5 Likert). In Part 2, each annotator rated 60 simplified responses (30 groups $\times$ 2 simplified conditions) on the oversimplification error (OER, Boolean), comparing each simplified response against the standard response for the same concept-model pair.

Annotators were blinded to the condition label, the generating model, and the LLM judge's output. Each annotator saw only the response text, a randomly assigned item ID, and the reference definition for the concept. The reference definition served as the anchor for their judgments, as it did for the judge. Annotators worked independently and did not discuss items until the adjudication meeting. The codebook (Appendix C) instructed annotators to judge technical content only, to treat omissions as errors only when they made the remaining explanation misleading, and to consult textbooks if needed but not to use AI tools.

Inter-annotator agreement was assessed with Cohen's κ [57] for the Boolean indicators and with quadratic-weighted κ for the ordinal accuracy score, interpreted following Landis

and Koch [58]. Disagreements were resolved by consensus in an adjudication meeting, in which the two annotators discussed each divergent item and agreed on a final label. The resulting consensus labels served as the human reference standard against which the LLM judge was evaluated.

3.8. Readability Metrics

As a manipulation check, all responses are analysed for quantitative readability using three metrics computed with the `textstat` Python library: Flesch Reading Ease (higher = easier) [40], Flesch-Kincaid Grade Level, and average sentence length in words:

$$\mathrm{FRE} = 206.835 - 1.015\,\frac{\text{words}}{\text{sentences}} - 84.6\,\frac{\text{syllables}}{\text{words}}, \tag{4}$$

$$\mathrm{FKGL} = 0.39\,\frac{\text{words}}{\text{sentences}} + 11.8\,\frac{\text{syllables}}{\text{words}} - 15.59. \tag{5}$$

These formulas depend only on sentence and syllable length, i.e., surface form. They are appropriate for verifying that the prompts changed the text as intended, but they do not measure comprehensibility, and technical terms and code-like tokens can distort syllable counts. Readability is therefore used as a manipulation check and not as an outcome of interest.

3.9. Statistical Analysis Plan

All statistical tests were performed in R (version 4.3.2) [59]. The significance threshold is set at $\alpha = 0.05$ with adjustments for multiple comparisons where indicated.

3.9.1. Primary Hypothesis Testing

The primary hypothesis $\mathrm{SMR}(E_a) > \mathrm{SMR}(E_s)$ is tested using a one-way analysis of variance (ANOVA) with condition (A_standard, B_simplified, C_highly_simplified) as the independent variable and strategic misconception rate as the dependent variable. For significant ANOVA results ($p < 0.05$), post-hoc pairwise comparisons are conducted using Tukey's Honestly Significant Difference (HSD) test [60].

Normality of residuals is assessed using Shapiro-Wilk tests [61]; homogeneity of variances is assessed using Levene's test [62]. Given the large sample size, ANOVA is robust to modest violations of normality.

3.9.2. Robustness Analyses for Binary, Paired Outcomes

SM, DA, and OER are binary indicators, and the three conditions for the same concept-model pair are not independent observations. ANOVA on binary outcomes is a linear probability model, and treating repeated observations as independent tends to overstate precision. We therefore complement the primary analysis with methods that respect these features:

- Cochran's Q test [63] across the three conditions with concept-model pair as the blocking unit, followed by pairwise McNemar tests [64] with Holm correction;
- a mixed-effects logistic regression [65] with random intercepts for concept and model, reporting odds ratios with 95% confidence intervals;
- for the ordinal accuracy score, a non-parametric alternative (Friedman or cumulative-link mixed model) alongside ANOVA.

Where the robustness analyses and the ANOVA disagree, we report both and interpret the more conservative.

3.9.3. Secondary Analyses

Chi-square tests of independence examine associations between condition and (a) dangerous analogy presence, (b) analogy type, and (c) specific error subtypes. Two-way ANOVA with model and condition as factors compares model families. One-way ANOVA within each condition examines subfield differences. Across the family of secondary tests, the false discovery rate is controlled using the Benjamini-Hochberg procedure [66].

3.9.4. Effect Sizes

Effect sizes are reported as Cohen's d for pairwise comparisons, η^2 for ANOVA, and Cramér's V for chi-square tests [67,68], with

$$V = \sqrt{\frac{\chi^2}{N\,(\min(r,c)-1)}}. \tag{6}$$

Effect sizes are interpreted alongside confidence intervals, since with a corpus of this size small differences may be statistically significant without being educationally meaningful.

3.10. Reproducibility

The complete AccessTrap-CS corpus, all prompt templates, evaluation codebook, generation and evaluation scripts, and analysis code are publicly available at [repository URL]. Model inference was performed with Ollama on the Supek HPC cluster; the Ollama version, model digests, and sampling parameters are logged with the corpus.

4. Results

This section presents the quantitative and qualitative findings of the AccessTrap-CS benchmark evaluation. The corpus contains 720 responses generated across 35 computer science concepts, three simplification conditions, and seven open-weight LLMs. All 720 responses were judged by Qwen3.6:35b, and a stratified subsample of 30 concept-model groups (150 ratings per annotator) was independently annotated by two human experts for validation.

4.1. Sample and Readability

Table 2 reports the number of judged responses per model and condition. The sample is balanced at 240 responses per condition and 99–105 per model; the slight imbalance arises because a small number of generations were lost to parsing failures in the reasoning models.

Table 2. Number of judged responses per model and condition.

Model	A	B	C	Total
mistral:7b	34	34	34	102
deepseek-r1:8b	33	33	33	99
ministral-3:14b	35	35	35	105
phi4:14b	35	35	35	105
gpt-oss:20b	35	35	35	105
gemma4:31b	35	35	35	105
deepseek-r1:32b	33	33	33	99
Total	240	240	240	720

The corpus is therefore close to fully crossed: each of the 35 concepts is observed for each of the 7 models under all three conditions, with only a small number of missing cells concentrated in the two reasoning models. This near-complete balance ensures that

condition-level rates are not confounded by model composition and that the within-pair contrast used to define OER is available for almost every cell.

Table 3 reports the readability metrics by condition, together with the omnibus ANOVA results. The manipulation check confirms that the three prompt conditions produced text with significantly different surface complexity.

Table 3. Readability metrics by condition (mean (SD)) and omnibus ANOVA results. FRE = Flesch Reading Ease; FKGL = Flesch-Kincaid Grade Level; ASL = average sentence length.

Panel A: Metrics by condition					
Condition	n	FRE	FKGL	ASL	Words
A (standard)	245	47.2 (13.6)	10.7 (2.4)	16.2 (3.8)	632 (289)
B (simplified)	245	73.8 (10.4)	6.6 (2.0)	14.5 (3.4)	366 (174)
C (highly simplified)	245	59.9 (11.7)	10.0 (2.4)	20.4 (4.8)	114 (33)
Panel B: Omnibus tests					
Metric	F	df	p	η^2	
FRE	303.95	2, 732	< 0.001	0.454	
FKGL	228.01	2, 732	< 0.001	0.384	
ASL	138.02	2, 732	< 0.001	0.274	
Words	430.75	2, 732	< 0.001	0.541	

Flesch Reading Ease increased from condition A ($M = 47.2$, $SD = 13.6$) to condition B ($M = 73.8$, $SD = 10.4$) and then to condition C ($M = 59.9$, $SD = 11.7$). Condition B is by far the easiest to read; condition C is compressed into five sentences, which forces longer sentences and denser vocabulary, so it is not as easy on surface measures. Flesch-Kincaid Grade Level followed the inverse pattern. Word counts dropped monotonically from A (632 words, $SD = 289$) to B (366, $SD = 174$) to C (114, $SD = 33$). All four omnibus tests are highly significant ($p < 0.001$ in every case), with large effect sizes (η^2 from 0.274 for average sentence length to 0.541 for word count). The key takeaway is that the prompts did change the text as intended, and that condition B and condition C are not simply two points on a single simplification continuum.

4.2. Strategic Misconception Rate (SMR)

Table 4 reports SMR by condition, together with omnibus tests, pairwise McNemar contrasts, and regression models. Condition A had 30 misconceptions out of 240 responses (12.5%, 95% CI $[8.9, 17.3]$), condition B had 41 (17.1%, 95% CI $[12.8, 22.4]$), and condition C had 33 (13.8%, 95% CI $[10.0, 18.7]$).

Table 4. Strategic misconception rate (SMR): rates with Wilson 95% CI (Panel A), omnibus tests (Panel B), pairwise McNemar contrasts with Holm correction (Panel C), and regression model odds ratios (Panel D).

Panel A: SMR by condition			
Condition	Count	n	Rate (%) [95% CI]
A (standard)	30	240	12.5 [8.9, 17.3]
B (simplified)	41	240	17.1 [12.8, 22.4]
C (highly simplified)	33	240	13.8 [10.0, 18.7]
Panel B: Omnibus tests			
Test	Statistic	df	p
One-way ANOVA	$F = 1.09$	$2, 717$	0.337
Chi-square	$\chi^2 = 2.18$	2	0.336
Cochran's Q	$Q = 2.37$	2	0.306
Panel C: Pairwise McNemar (Holm)			
Contrast	b	c	Holm p
B vs A	34	23	0.555
C vs A	28	25	0.784
C vs B	23	31	0.682
Panel D: Regression odds ratios			
Model	Contrast	OR (95% CI)	p
GEE	B vs A	1.44 (0.88–2.36)	0.146
Bayes mixed (VB)	B vs A	1.44 (1.01–2.06)	–
GEE	C vs A	1.12 (0.66–1.88)	0.680
Bayes mixed (VB)	C vs A	1.08 (0.74–1.59)	–

Although condition B shows the numerically highest rate, the difference is not statistically significant. The one-way ANOVA yielded $F(2, 717) = 1.09$, $p = 0.337$, $\eta^2 = 0.003$; the chi-square test yielded $\chi^2(2) = 2.18$, $p = 0.336$, $V = 0.055$; and Cochran's Q was $Q(2) = 2.37$, $p = 0.306$. Pairwise McNemar tests with Holm correction also failed to reach significance. The regression models show a non-significant trend toward higher odds of SM in B relative to A (GEE OR $= 1.44$, 95% CI $[0.88, 2.36]$, $p = 0.146$).

The conclusion for H1 is therefore that the data do not support a statistically significant increase in SMR under simplification. Model identity is a much stronger predictor of SMR than condition: the two-way ANOVA (reported in Table 9) shows that the model main effect is significant ($F(6, 699) = 5.76$, $p < 0.001$) while the condition main effect and the interaction are not.

Figure 2 shows SMR by model and condition.




Figure 2. Strategic misconception rate (SMR) by model and condition, with Wilson 95% confidence intervals. Models are ordered by their mean SMR across conditions. The between-model variation is substantially larger than the within-model variation across conditions.

The ordering of models is broadly consistent across conditions, and the within-model variation across conditions is small relative to the between-model variation. Mistral:7b is a clear outlier with high SMR in all three conditions, while gemma4:31b is near zero throughout. The spread between the highest and lowest model within a single condition is several times larger than the spread between conditions for any given model.

Figure 3 visualises the change from condition A to condition C per model.




Figure 3. Strategic misconception rate (SMR) by model for conditions A (standard) and C (highly simplified). The value below each model name is the difference $\Delta = \mathrm{SMR}_C - \mathrm{SMR}_A$ in percentage points; a positive value indicates more strategic misconceptions under simplification. Error bars are Wilson 95% confidence intervals.

The per-model deltas in Figure 3 are small relative to the confidence intervals and do not follow a consistent sign: some models increase their SMR under simplification, others decrease it. This heterogeneity is the visual counterpart of the non-significant condition main effect and reinforces the conclusion that, at the level of strategic misconceptions in general, the accessibility paradox does not manifest as a systematic shift.

4.3. Dangerous Analogy Rate (DAR)

The results for dangerous analogies are dramatically different and provide the strongest evidence for the accessibility paradox hypothesis. Table 5 shows that condi-

tion A produced only 2 dangerous analogies out of 240 responses (0.8%, 95% CI $[0.2, 3.0]$), whereas condition B produced 49 (20.4%, 95% CI $[15.8, 26.0]$) and condition C produced 59 (24.6%, 95% CI $[19.6, 30.4]$). This is a roughly 25- to 30-fold increase.

Table 5. Dangerous analogy rate (DAR): rates with Wilson 95% CI (Panel A), omnibus tests (Panel B), pairwise McNemar contrasts with Holm correction (Panel C), and regression model odds ratios (Panel D).

Panel A: DAR by condition			
Condition	Count	n	Rate (%) [95% CI]
A (standard)	2	240	0.8 [0.2, 3.0]
B (simplified)	49	240	20.4 [15.8, 26.0]
C (highly simplified)	59	240	24.6 [19.6, 30.4]
Panel B: Omnibus tests			
Test	Statistic	df	p
One-way ANOVA	$F = 32.38$	$2, 717$	< 0.001
Chi-square	$\chi^2 = 59.64$	2	< 0.001
Cochran's Q	$Q = 58.51$	2	< 0.001
Panel C: Pairwise McNemar (Holm)			
Contrast	b	c	Holm p
B vs A	48	1	< 0.001
C vs A	58	1	< 0.001
C vs B	46	36	0.320
Panel D: Regression odds ratios			
Model	Contrast	OR (95% CI)	p
GEE	B vs A	30.53 (7.48–124.54)	< 0.001
Bayes mixed (VB)	B vs A	15.42 (11.05–21.52)	–
GEE	C vs A	38.79 (9.50–158.37)	< 0.001
Bayes mixed (VB)	C vs A	20.31 (14.84–27.80)	–

The omnibus tests confirm a large and highly significant effect: one-way ANOVA $F(2, 717) = 32.38$, $p < 0.001$, $\eta^2 = 0.083$; chi-square $\chi^2(2) = 59.64$, $p < 0.001$, $V = 0.288$; Cochran's $Q(2) = 58.51$, $p < 0.001$. The exact McNemar tests show that both B vs A ($b = 48$, $c = 1$, Holm $p < 0.001$) and C vs A ($b = 58$, $c = 1$, Holm $p < 0.001$) are significant, while C vs B is not ($b = 46$, $c = 36$, $p = 0.320$). H2 is strongly supported.

Figure 4 visualises SMR, DAR, and OER side by side.




Figure 4. Rates of strategic misconceptions (SMR), dangerous analogies (DAR), and oversimplification errors (OER) by condition, with Wilson 95% confidence intervals. OER is defined as zero in condition A by construction. The figure shows that DAR is the metric most strongly affected by simplification.

The contrast visible in Figure 4 is the empirical core of the paper. While SMR stays roughly flat across the three conditions, DAR jumps from below one percent to roughly one in four responses as soon as the prompt requests simplification. The magnitude of the odds ratios in Table 5 (above 30 in both frequentist specifications) makes this the single most robust effect in the study.

4.4. Oversimplification Error Rate (OER)

Table 6 reports OER by condition, using two complementary measures.

Table 6. Oversimplification error rate (OER) by condition. Judge-based rates use the LLM judge's OER classification; derived rates use the proportion of simplified responses with SM = 1 whose standard response has SM = 0.

Panel A: Judge-based OER			
Condition	Count	*n*	Rate (%) [95% CI]
A (standard)	1	240	0.4 [0.1, 2.3]
B (simplified)	16	240	6.7 [4.1, 10.6]
C (highly simplified)	10	240	4.2 [2.3, 7.5]
Panel B: Derived OER (SM in B/C but not A)			
Condition	Count	*n*	Rate (%) [95% CI]
B (simplified)	34	240	14.2 [10.3, 19.1]
C (highly simplified)	28	240	11.7 [8.2, 16.3]

The first measure is the judge's OER classification: by construction, OER cannot occur in condition A. The judge flagged 16 responses in B (6.7%, 95% CI [4.1, 10.6]) and 10 in C (4.2%, 95% CI [2.3, 7.5]). Both rates are significantly greater than zero, supporting the existence of the construct, but the expected monotonic increase from B to C does not appear. Because the judge's OER classification is a single-pass judgment, we also computed a derived OER measure directly from the SM indicators: the proportion of simplified responses with SM = 1 whose corresponding standard response has SM = 0. The derived rates are 34 out of 240 in B (14.2%, 95% CI [10.3, 19.1]) and 28 out of 240 in C (11.7%, 95% CI [8.2, 16.3]). For H3, the evidence supports the existence of oversimplification errors as a distinct phenomenon, but the hypothesis that OER(C) > OER(B) is not supported.

4.5. Accuracy Scores

Table 7 reports the accuracy scores.

Table 7. Accuracy scores (1–5): means by condition (Panel A), omnibus tests (Panel B), paired Wilcoxon contrasts with Holm correction (Panel C), and Spearman correlations with the binary error indicators (Panel D).

Panel A: Accuracy by condition			
Condition	n	Mean (SD)	Score 5
A (standard)	240	4.67 (0.89)	208 (86.7%)
B (simplified)	240	4.15 (1.19)	144 (60.0%)
C (highly simplified)	240	4.18 (1.12)	138 (57.5%)
Panel B: Omnibus tests			
Test	Statistic	df	p
One-way ANOVA	$F = 17.65$	$2, 717$	< 0.001
Friedman	$\chi^2 = 50.45$	2	< 0.001
Panel C: Pairwise Wilcoxon (Holm)			
Contrast	W	Holm p	Cohen's d
B vs A	1329.0	< 0.001	-0.49
C vs A	1739.0	< 0.001	-0.49
C vs B	3192.0	0.806	0.02
Panel D: Spearman correlations with error indicators			
Indicator	ρ	p	
SM	-0.70	< 0.001	
DA	-0.67	< 0.001	
OER	-0.33	< 0.001	

Mean accuracy was highest in condition A ($M = 4.67$, $SD = 0.89$), dropped in condition B ($M = 4.15$, $SD = 1.19$), and remained similar in condition C ($M = 4.18$, $SD = 1.12$). The proportion of responses scored as perfectly accurate (score 5) fell from 86.7% in A to 60.0% in B and 57.5% in C. The omnibus tests confirm a significant effect of condition: one-way ANOVA $F(2, 717) = 17.65$, $p < 0.001$, $\eta^2 = 0.047$; Friedman $\chi^2(2) = 50.45$, $p < 0.001$, $W = 0.105$. Paired Wilcoxon tests with Holm correction show that both B vs A ($W = 1329.0$, Holm $p < 0.001$, $d = -0.49$) and C vs A ($W = 1739.0$, Holm $p < 0.001$, $d = -0.49$) are significant, while C vs B is not ($W = 3192.0$, $p = 0.806$, $d = 0.02$).

Figure 5 visualises the accuracy drop.




Figure 5. Mean accuracy scores (1–5) by condition, with 95% confidence intervals. The dashed horizontal line marks the overall mean across all conditions. Accuracy drops significantly from the standard condition to both simplified conditions, with no significant difference between the two simplified conditions.

The accuracy pattern in Figure 5 is the graded counterpart of the DAR finding: simplification does not merely insert binary errors, it shifts the distribution of response quality downward, with a substantial share of responses moving from "perfectly accurate" to "mostly accurate with issues".

4.6. Subfield Analysis

Table 8 breaks down SMR, DAR, OER, and accuracy by CS subfield and condition, and reports the one-way ANOVAs of each outcome across subfields within each condition. The most striking descriptive pattern is that Databases and Operating Systems show the largest increases in DAR under simplification, while Algorithms and Data Structures shows the largest SMR increase in condition B.

Table 8. Error rates and accuracy by CS subfield and condition (Panel A), and one-way ANOVAs of each outcome across subfields within each condition (Panel B). OER is undefined in condition A.

Panel A: Descriptive statistics					
Subfield	Condition	SMR (%)	DAR (%)	OER (%)	Accuracy
Algorithms & Data Structures	A	10.9	0.0	–	4.67
Algorithms & Data Structures	B	17.4	13.0	4.3	4.20
Algorithms & Data Structures	C	10.9	15.2	0.0	4.24
Programming Languages & Paradigms	A	2.0	0.0	–	4.92
Programming Languages & Paradigms	B	12.2	24.5	12.2	4.18
Programming Languages & Paradigms	C	10.2	24.5	2.0	4.41
Databases	A	16.7	2.1	–	4.58
Databases	B	29.2	29.2	6.2	3.92
Databases	C	25.0	33.3	10.4	3.83
Computer Networks	A	20.4	0.0	–	4.51
Computer Networks	B	14.3	20.4	6.1	4.14
Computer Networks	C	10.2	12.2	2.0	4.47
Operating Systems	A	12.5	2.1	–	4.67
Operating Systems	B	12.5	14.6	4.2	4.33
Operating Systems	C	12.5	37.5	6.2	3.94
Panel B: ANOVAs across subfields within condition					
Outcome	Condition	F	p	BH p	
SM	A	2.18	0.072	0.320	
SM	B	1.70	0.151	0.391	
SM	C	1.65	0.163	0.391	
DA	A	0.75	0.559	0.610	
DA	B	1.33	0.260	0.446	
DA	C	3.23	0.013	0.159	
OER	B	0.84	0.504	0.604	
OER	C	2.11	0.080	0.320	
Accuracy	A	0.50	0.735	0.735	
Accuracy	B	1.45	0.218	0.437	
Accuracy	C	0.88	0.478	0.604	

The one-way ANOVAs are mostly non-significant after Benjamini-Hochberg correction. The only test that approaches significance is DAR in condition C ($F = 3.23$, raw $p = 0.013$, BH $p = 0.159$), and even that does not survive correction. The exploratory conclusion for RQ4 is therefore that subfield does not have a robust moderating effect on the error rates.

Figure 6 shows the SMR heatmap by subfield and condition.




Figure 6. Heatmap of strategic misconception rate (SMR) by CS subfield and condition. Darker cells indicate higher SMR. Databases shows the largest increase from the standard to the simplified conditions, while Computer Networks and Algorithms show high baseline rates that do not increase under simplification.

The heatmap in Figure 6 confirms the descriptive impression from Table 8: no single subfield is uniformly safe or uniformly risky across conditions, and the visible differences are not large enough to survive multiple-comparison correction.

4.7. Model Comparison

Table 9 reports error rates and accuracy by model, pooled over conditions, and the two-way ANOVA results for SM and accuracy.

Table 9. Error rates and accuracy by model, pooled over conditions (Panel A), and two-way ANOVA (Type II) for SM and accuracy (Panel B).

Panel A: Error rates and accuracy by model				
Model	SMR (%)	DAR (%)	OER (%)	Accuracy
mistral:7b	26.5	30.4	10.3	3.57
deepseek-r1:8b	20.2	15.2	4.5	4.24
ministral-3:14b	16.2	17.1	2.9	4.37
phi4:14b	14.3	16.2	10.0	4.31
gpt-oss:20b	11.4	9.5	2.9	4.59
gemma4:31b	0.0	1.9	2.9	4.90
deepseek-r1:32b	13.1	17.2	4.5	4.33
Panel B: Two-way ANOVA (Type II)				
Outcome	Term	F	df	p
SM	C(model)	5.76	6	< 0.001
SM	C(condition)	1.12	2	0.326
SM	C(model):C(condition)	0.55	12	0.879
Accuracy	C(model)	4.90	6	< 0.001
Accuracy	C(condition)	0.56	2	0.570
Accuracy	C(model):C(condition)	0.76	12	0.695

The differences between models are substantial and, for SM and accuracy, statistically significant. Gemma4:31b is the standout performer with an SMR of 0.0%, DAR of 1.9%, and mean accuracy of 4.90. At the other end, mistral:7b has an SMR of 26.5%, DAR of 30.4%, and accuracy of 3.57. The two-way ANOVA shows that the model main effect is significant for both SM ($F(6, 699) = 5.76$, $p < 0.001$) and accuracy ($F(6, 699) = 4.90$, $p < 0.001$), while the condition main effect and the model $\times$ condition interaction are not. For practitioners choosing a model for assistive use, the practical implication is that model choice matters more than prompt condition.

4.8. Human Evaluation and Judge Validation

Table 10 reports the agreement between the LLM judge and the reviewer consensus, and between the two human reviewers.

Table 10. Agreement between the LLM judge and the reviewer consensus (Panel A) and between the two human reviewers (Panel B). For accuracy, quadratic-weighted κ is shown.

Panel A: Judge vs. reviewer consensus					
Indicator	κ	Precision	Recall	Reviewer prev.	Judge prev.
SM	−0.008	0.600	0.052	0.644	0.056
DA	0.180	0.778	0.194	0.400	0.100
OER	0.018	0.667	0.059	0.567	0.050
Accuracy	0.122	–	–	3.20	4.58
Panel B: Reviewer vs. reviewer agreement					
Indicator	κ	Raw agreement (%)			
SM	0.927	96.7			
DA	0.953	97.8			
OER	0.899	95.0			
Accuracy	0.982	97.7			

The two reviewers showed high agreement with each other (Cohen's $\kappa = 0.927$ for SM, 0.953 for DA, 0.899 for OER; quadratic-weighted $\kappa = 0.982$ for accuracy), confirming that the human consensus is a reliable reference standard. The LLM judge, by contrast, showed poor agreement with the human consensus: $\kappa = -0.008$ for SM, 0.180 for DA, and 0.018 for OER. The reviewers flagged 64.4% of responses as containing a strategic misconception, while the judge flagged only 5.6%.

4.9. Position Bias in the Judge

Because the judge was presented with all three conditions simultaneously in randomised order, we checked whether the order in which responses appeared affected the judgments. Table 11 reports the judge's decisions by position, the GEE models adjusted for position, and the sensitivity analysis restricted to responses shown first in each group.

Table 11. Position bias sensitivity analyses: judge decisions by position (Panel A), GEE models adjusted for position (Panel B), and rates for responses shown first in each group (Panel C).

Panel A: Judge decisions by position					
Position	n	SMR (%)	DAR (%)	OER (%)	Accuracy
1	240	9.6	10.8	0.6	4.50
2	240	12.5	15.8	4.7	4.38
3	240	21.2	19.2	11.2	4.13
Panel B: GEE models adjusted for position					
Outcome	Contrast	OR	95% CI	p	
SM	B vs A	1.47	0.89–2.42	0.134	
SM	C vs A	1.13	0.66–1.94	0.643	
DA	B vs A	30.97	7.65–125.48	< 0.001	
DA	C vs A	39.81	9.82–161.37	< 0.001	
Panel C: Responses shown first in each group					
Condition	n	SMR (%)	DAR (%)	OER (%)	Accuracy
A (standard)	70	15.7	1.4	–	4.51
B (simplified)	84	7.1	13.1	1.2	4.48
C (highly simplified)	86	7.0	16.3	0.0	4.51

The judge's SMR increased from 9.6% at position 1 to 21.2% at position 3; the same increasing pattern appears for DAR and OER, and accuracy decreases across positions. This is a clear position bias. After adjusting for position, the DAR effect remains large and significant (B vs A OR $= 30.97$, 95% CI $[7.65, 125.48]$, $p < 0.001$; C vs A OR $= 39.81$, 95% CI $[9.82, 161.37]$, $p < 0.001$), but the SMR effect becomes clearly non-significant. When only the responses shown first in each group are analysed, the condition differences largely disappear for SMR, while DAR remains elevated. The DAR effect is robust to this adjustment.

4.10. Summary of Findings

The key findings of the AccessTrap-CS benchmark can be summarised as follows, mapped to the four research questions.

- **RQ1 (SMR).** The data do not support a statistically significant increase in strategic misconception rate under simplification. H1 is not supported. Model identity is a much stronger predictor of SMR than condition.
- **RQ2 (DAR).** The data strongly support the hypothesis that simplification increases dangerous analogies. DAR rises from 0.8% in A to 20.4% in B and 24.6% in C, with

GEE odds ratios above 30 for both simplified conditions relative to baseline. H2 is supported.

- **RQ3 (OER).** Oversimplification errors exist as a measurable phenomenon. Both the judge-based rate and the derived rate are significantly greater than zero in B and C, but the expected increase from B to C does not appear. H3 is partially supported.
- **RQ4 (moderators).** Model is a strong moderator of all error rates and accuracy. Subfield shows descriptive variation but the effects do not survive multiple-comparison correction. The model $\times$ condition interaction is not significant.

The judge validation analysis adds a crucial caveat: the LLM judge has very low recall relative to human reviewers, so the absolute rates reported here are likely underestimates. The relative comparisons across conditions are more robust, but the position bias analysis suggests that even those should be interpreted with caution for SMR and OER. The DAR effect is the one finding that withstands all sensitivity checks.

5. Conclusions

This paper introduced the accessibility paradox: the hypothesis that LLM simplification for students with learning difficulties, while well-intentioned, may systematically increase the rate of strategic misconceptions. We presented AccessTrap-CS, a benchmark corpus of 720 responses generated by seven open-weight LLMs across 35 core computer science concepts under three simplification conditions, together with an error taxonomy comprising strategic misconceptions, dangerous analogies, and oversimplification errors, and an LLM-as-judge evaluation with Qwen3.6:35b as the evaluator, validated against a stratified human-annotated subsample.

The empirical findings offer a nuanced picture. The strongest and most robust effect is on dangerous analogies: DAR rises from 0.8% in the standard condition to 20.4% in the simplified condition and 24.6% in the highly simplified condition, with odds ratios above 30 and confidence intervals that exclude 1 by a wide margin. This effect survives position adjustment, judge validation concerns, and sensitivity analyses. The strategic misconception rate shows a non-significant trend toward higher values in the simplified condition (17.1% vs 12.5%) but does not increase monotonically with simplification intensity. The oversimplification error rate is significantly greater than zero in both simplified conditions (6.7% and 4.2% by judge classification; 14.2% and 11.7% by derived measure), confirming the existence of simplification-induced errors as a distinct category, but the expected increase from moderate to extreme simplification does not appear. Model identity is a stronger predictor of error rates than condition: the between-model variation in SMR (0.0% to 26.5%) dwarfs the between-condition variation (12.5% to 17.1%).

The judge validation analysis is a critical caveat. Human reviewers flagged 64.4% of responses as containing a strategic misconception, while the LLM judge flagged only 5.6%. The absolute rates reported in this paper are therefore lower bounds. The relative comparisons across conditions are more robust, but the position bias analysis suggests that even those should be interpreted with caution for SMR and OER. The DAR effect is the one finding that withstands all sensitivity checks.

Beyond empirical findings, this paper contributes three accessibility-first design principles for AI tutoring interfaces: visual uncertainty signalling, analogy status tagging, and visual-first communication that does not rely on text-based disclaimers. These principles shift responsibility for scepticism from the learner to the interface, a design move that is plausibly important for students with reduced spare capacity for parallel fact-verification. The DAR results suggest that analogy tagging is the most immediately actionable principle, since dangerous analogies are the most common and most robustly measured failure mode.

Future work should extend AccessTrap-CS to additional domains and languages, add ablation prompts and multiple samples per cell, replicate the study with target population samples using learning outcome measures, and implement and evaluate the proposed design principles in tutoring systems in real-world settings. A priority is to improve the judge: the current LLM-as-judge approach has low recall, and a hybrid human–LLM evaluation or a fine-tuned judge with higher sensitivity would provide more reliable absolute rates. As LLMs become increasingly integrated into educational practice, the ability to detect, measure, and mitigate strategic misconceptions will be essential for ensuring that accessibility tools do not inadvertently become vectors of conceptual harm. The accessibility paradox is real, but it is not monolithic: it concentrates in analogies, it varies by model, and it is most dangerous for the concepts that anchor the rest of the curriculum. Knowing where the risk is concentrated is the first step toward designing it out.

Author Contributions: Conceptualization, M.M., S.B.Š., and I.L.; methodology, M.M., S.B.Š. and D.E.; software, M.M.; validation, I.L., S.B.Š. and D.E.; formal analysis, M.M.; investigation, M.M.; resources, M.M., I.L. and D.E.; data curation, M.M.; writing—original draft preparation, M.M.; writing—review and editing, S.B.Š., I.L. and D.E.; visualization, M.M.; supervision, S.B.Š. and I.L.; project administration, S.B.Š., I.L. and D.E.; funding acquisition, S.B.Š. and I.L.;
All authors have read and agreed to the published version of the manuscript.

Funding: This work was (partially) supported by the EC Digital Europe Programme EDIH Adria 2.0 (101256325); SPIN projects IP.1.1.03.0120, IP.1.1.03.0158 and IP.1.1.03.0039; and NextGenerationEU University grants: uniri-iz-25-6, uniri-iz-25-220, IIP_010144, IIP_010136

Data Availability Statement: The AccessTrap-CS corpus and evaluation scripts are available at [repository URL to be added upon acceptance].

Conflicts of Interest: The authors declare no conflicts of interest.

Abbreviations

The following abbreviations are used in this manuscript:

LLM	Large Language Model
CS	Computer Science
SMR	Strategic Misconception Rate
DAR	Dangerous Analogy Rate
OER	Oversimplification Error Rate
ADHD	Attention Deficit Hyperactivity Disorder
ANOVA	Analysis of Variance
HSD	Honestly Significant Difference
HPC	High Performance Computing
GEE	Generalized Estimating Equations
FRE	Flesch Reading Ease
FKGL	Flesch-Kincaid Grade Level

Appendix A CS Concepts and Subfields

Table A1 lists the 35 concepts in AccessTrap-CS, grouped by subfield. Table A2 identifies the concepts with the largest mean increase in SMR from condition A to the average of conditions B and C.

Table A1. The 35 CS concepts in AccessTrap-CS, grouped by subfield.

ID	Subfield	Concept
ALG_01	Algorithms & Data Structures	QuickSort (average vs worst-case complexi
ALG_02	Algorithms & Data Structures	Dijkstra's algorithm (negative edge weights
ALG_03	Algorithms & Data Structures	Dynamic Programming vs Greedy Approac
ALG_04	Algorithms & Data Structures	Hash tables (collisions and load factor)
ALG_05	Algorithms & Data Structures	Binary search tree balancing (AVL vs Red-B
ALG_06	Algorithms & Data Structures	Breadth-First Search (BFS) and Depth-First
ALG_07	Algorithms & Data Structures	Space Complexity and trade-offs
NET_01	Computer Networks	TCP three-way handshake (SYN, SYN-ACK
NET_02	Computer Networks	OSI model vs TCP/IP model (differences in
NET_03	Computer Networks	DNS resolution (Recursive vs Iterative)
NET_04	Computer Networks	IP addressing and subnets (CIDR mask)
NET_05	Computer Networks	HTTP methods: Idempotency of GET, PUT,
NET_06	Computer Networks	Routing: Distance Vector (RIP) vs Link State
NET_07	Computer Networks	TLS handshake (RSA vs Diffie-Hellman key
DB_01	Databases	ACID properties (especially Isolation vs Co
DB_02	Databases	Normalization (1NF, 2NF, 3NF) and its limi
DB_03	Databases	SQL JOIN: INNER vs OUTER (LEFT/RIGH
DB_04	Databases	Indexes: When a B-tree index does not spee
DB_05	Databases	Transactions: Different isolation levels (Rea
DB_06	Databases	CAP theorem (Consistency, Availability, Par
DB_07	Databases	Denormalization: When and why to use it
OS_01	Operating Systems	Processes vs threads
OS_02	Operating Systems	Context switching
OS_03	Operating Systems	CPU scheduling algorithms
OS_04	Operating Systems	Deadlock conditions
OS_05	Operating Systems	Virtual memory and paging
OS_06	Operating Systems	Paging vs Segmentation
OS_07	Operating Systems	Semaphores and synchronization
PLP_01	Programming Languages & Paradigms	Inheritance and Liskov Substitution Princip
PLP_02	Programming Languages & Paradigms	Interfaces vs Abstract Classes
PLP_03	Programming Languages & Paradigms	Closures and lexical scope
PLP_04	Programming Languages & Paradigms	Static vs Dynamic typing (Type safety)
PLP_05	Programming Languages & Paradigms	Exceptions: Checked vs Unchecked
PLP_06	Programming Languages & Paradigms	Garbage Collection (Mark-and-Sweep vs Re
PLP_07	Programming Languages & Paradigms	Concurrency: Threads vs Asynchronous pr

The distribution of concepts across subfields reflects the balance of the underlying curriculum: each of the five subfields contributes exactly seven concepts, so that subfield-level comparisons are not driven by unequal sample sizes. Concepts were chosen to span the range from formal algorithmic reasoning (e.g., Dijkstra's algorithm, dynamic programming) through language-level semantics (e.g., closures, Liskov substitution) to system-level mechanisms (e.g., deadlock, paging, TCP handshake). This spread is deliberate, because the accessibility paradox is expected to manifest differently depending on whether the concept's core is a mathematical invariant, a semantic relation, or a procedural mechanism.

Table A2. Concepts with the largest mean increase in SMR from A to mean(B, C).

ID	Concept	Δ SMR (pp)
OS_07	Semaphores and synchronization	+35.7
DB_02	Normalization (1NF, 2NF, 3NF) and its limits	+28.6
DB_06	CAP theorem (Consistency, Availability, Partition tolerance)	+28.6
ALG_03	Dynamic Programming vs Greedy Approach	+25.0
DB_05	Transactions: Different isolation levels	+25.0
DB_01	ACID properties (Isolation vs Consistency)	+21.4
NET_07	TLS handshake (RSA vs Diffie-Hellman)	+21.4
PLP_05	Exceptions: Checked vs Unchecked	+14.3
PLP_02	Interfaces vs Abstract Classes	+14.3
PLP_07	Concurrency: Threads vs Asynchronous programming	+7.1

The pattern in Table A2 is informative in its own right. The concepts with the largest increase in SMR under simplification are precisely those whose definitions hinge on necessary conditions, invariants, or boundary cases: semaphores (atomicity, counting), normalization (functional dependencies and their limits), CAP theorem (the impossibility trade-off), dynamic programming versus greedy (optimal substructure and the exchange argument), transaction isolation levels (which anomalies each level permits), ACID (the distinction between isolation and consistency), and the TLS handshake (forward secrecy and the role of each message). These are exactly the properties that the analogy-based simplification process tends to drop, which is consistent with the theoretical account of OER presented in Section **??**.

Appendix B Prompt Templates

The three templates used in the study are reproduced verbatim below. `[CONCEPT]` is replaced by the concept name.

Condition A (standard).

```
Explain the following computer science concept accurately and clearly,
suitable for a first-year computer science student.

Answer in English.

Concept: [CONCEPT]
```

Condition B (simplified, reading difficulties).

```
Explain the following computer science concept to a student who has
reading difficulties. Use simplified language, short sentences, and
concrete analogies instead of code or formal definitions. Avoid
technical jargon where possible.

Answer in English.

Concept: [CONCEPT]
```

Condition C (highly simplified, attention difficulties).

```
Explain the following computer science concept to a student with
significant attention difficulties. Keep the explanation within five
sentences. Use one single, vivid analogy that captures the core idea.
Make it memorable and engaging.
```

```
Answer in English.

Concept: [CONCEPT]
```

The three templates differ only in the instruction line, so that any difference in the resulting responses can be attributed to the instruction rather than to unrelated formatting variation. The prompts are deliberately short, because they are intended to mirror how a student or teacher would actually phrase a request to a general-purpose assistant, not how a carefully engineered benchmark prompt would be constructed. This design choice increases ecological validity at the cost of construct specificity, a trade-off that is discussed in Section **??**.

Appendix C Evaluation Codebook

The codebook used for human annotation and for the LLM judge prompt defines each indicator as follows.

Strategic Misconception (SM). Code 1 if the explanation contains a subtle but conceptually significant error that sounds plausible but is fundamentally wrong. The error must be consequential: it would lead a student to construct a mental model that is systematically incorrect. Code 0 if the explanation is accurate or contains only trivial slips (typos, imprecise wording that does not change the concept). Do not code an error that is merely an omission unless the omission changes the meaning of the concept (e.g., omitting atomicity when defining a semaphore changes the concept; omitting a rarely used feature does not).

Dangerous Analogy (DA). Code 1 if the explanation uses an analogy that is intuitive but misrepresents a key technical property of the concept. The analogy must invite an inference that is false for the target. An analogy that is merely incomplete is not dangerous. Examples: semaphore as traffic light (invites inference of simple binary flag, no atomicity); deadlock as two people stuck in a doorway (invites inference that any waiting is a deadlock, omits circular wait); database index as a book index (invites inference that indexes always speed up queries, omits write overhead and selectivity).

Oversimplification Error (OER). Code 1 if the explanation contains an error that would not appear in a standard explanation of the same concept by the same model. This is a comparative judgment across conditions: the annotator must compare the simplified response to the baseline response for the same concept and model. Code 0 if the error also appears in the baseline, or if the simplified response contains no error beyond what the baseline contains.

Accuracy Score. A Likert scale from 1 to 5: 1 = completely wrong; 2 = mostly wrong with some correct elements; 3 = partially correct with significant gaps or errors; 4 = mostly accurate with minor issues; 5 = perfectly accurate.

The codebook was calibrated by the two annotators on a shared pilot set of 10 concept-model groups prior to the main annotation round. The pilot round surfaced two boundary cases that required clarification. First, an analogy that is factually correct but incomplete should be coded 0 for DA unless the incompleteness invites a specific false inference. Second, an error that is present in the baseline response but only becomes misleading in the simplified context should be coded 1 for OER only if a reader of the simplified response would form a different (and false) belief than a reader of the baseline. These clarifications were incorporated into the final version of the codebook above.

Appendix D Annotated Examples of Dangerous Analogies

This appendix presents representative examples of dangerous analogies identified in the corpus, with expert explanations of why they are dangerous.

Example 1: Semaphore as traffic light (OS_07, condition C). The model explains a semaphore by comparing it to a traffic light: green means go, red means stop. This analogy captures the binary blocking/unblocking behaviour but omits the counting semantics (a semaphore can allow multiple concurrent accesses) and the atomicity of the wait and signal operations. A student who learns this analogy may believe that a semaphore is a simple boolean flag and may not understand how a counting semaphore differs from a mutex.

Example 2: Deadlock as two people in a doorway (OS_04, condition B). The model describes deadlock as two people trying to pass through a doorway at the same time, each waiting for the other to move. This captures mutual waiting but omits the necessary conditions: resource holding, no preemption, and circular wait. A student may believe that any two processes waiting for each other constitute a deadlock, even if one of them can be preempted or if there is no circular dependency.

Example 3: Database index as book index (DB_04, condition B). The model compares a database index to the index at the back of a book: it helps you find things faster. This captures the read-speed benefit but omits the write overhead, the selectivity requirement, and the fact that an index on a low-selectivity column can be slower than a full table scan. A student may believe that adding an index always speeds up queries.

Example 4: TCP handshake as a greeting (NET_01, condition C). The model describes the TCP three-way handshake as a polite greeting: "Hello?" "Hello, I hear you." "Great, let's talk." This captures the exchange of messages but omits the purpose of the handshake (synchronising sequence numbers, establishing parameters) and the fact that the third message is necessary to confirm that both sides are ready. A student may believe that the handshake is merely a formality and not a functional part of connection establishment.

Example 5: Garbage collection as cleaning up (PLP_06, condition B). The model describes garbage collection as "cleaning up memory that is no longer needed." This captures the outcome but omits the mechanism (reachability analysis, mark-and-sweep vs reference counting) and the fact that garbage collection can pause execution and that reference counting cannot collect cycles. A student may believe that garbage collection is a background process with no performance implications.

In each case, the analogy satisfies the two defining properties of a dangerous analogy as specified in the codebook: (a) it is intuitive and easy to process, and (b) it invites a specific inference that is false for the target concept. The examples also illustrate the OER subtypes identified in Section **??**: Example 1 is a case of omission of a necessary condition; Examples 2 and 4 are cases of over-generalisation of a property that holds only in a special case; Example 3 is a case of promotion of an analogy from illustration to definition; and Example 5 is a case of replacement of a mechanism by an outcome.

References

1. Zdravkova, K.; Krasniqi, V.; Dalipi, F.; Ferati, M. Cutting-edge communication and learning assistive technologies for disabled children: An artificial intelligence perspective. *Frontiers in Artificial Intelligence* **2022**, *5*, 970430. https://doi.org/10.3389/frai.2022.970430.
2. Kortemeyer, G. Could an artificial-intelligence agent pass an introductory physics course? *Physical Review Physics Education Research* **2023**, *19*, 010132. https://doi.org/10.1103/PhysRevPhysEducRes.19.010132.
3. Kasneci, E.; Seßler, K.; Küchemann, S.; Bannert, M.; Dementieva, D.; et al. ChatGPT for good? On opportunities and challenges of large language models for education. *Learning and Individual Differences* **2023**, *103*, 102274. https://doi.org/10.1016/j.lindif.2023.102274.
4. Rello, L.; Baeza-Yates, R.; Bott, S.; Saggion, H. Simplify or help? Text simplification strategies for people with dyslexia. In Proceedings of the Proceedings of the 10th International Cross-Disciplinary Conference on Web Accessibility, 2013, pp. 1–10. https://doi.org/10.1145/2461121.2461126.
5. Štajner, S.; Saggion, H. Automatic text simplification for reading assistance: A review of methods, applications, and future directions. *Natural Language Engineering* **2021**, *27*, 507–546. https://doi.org/10.1017/S1351324920000525.

6. Finnie-Ansley, J.; Denny, P.; Becker, B.A.; Luxton-Reilly, A.; Prather, J. The robots are coming: Exploring the implications of OpenAI Codex on introductory programming. In Proceedings of the Proceedings of the 24th Australasian Computing Education Conference, 2022, pp. 10–19. https://doi.org/10.1145/3511861.3511863.
7. Prather, J.; Denny, P.; Leinonen, J.; Becker, B.A.; Albluwi, I.; et al. The robots are here: Navigating the generative AI revolution in computing education. In Proceedings of the Proceedings of the Working Group Reports on Innovation and Technology in Computer Science Education, 2023, pp. 97–149. https://doi.org/10.1145/3623762.3633499.
8. Denny, P.; Prather, J.; Becker, B.A.; Finnie-Ansley, J.; Hellas, A.; et al. Computing education in the era of generative AI. In Proceedings of the Proceedings of the 55th ACM Technical Symposium on Computer Science Education, 2024. https://doi.org/10.1145/3626252.
9. Pardos, Z.A.; Bhandari, S. ChatGPT-generated help produces learning gains equivalent to human tutor-authored help on mathematics skills. *PLOS ONE* **2024**, *19*, e0304013. https://doi.org/10.1371/journal.pone.0304013.
10. Kestin, G.; Miller, K.; Klales, A.; Milbourne, T.; Ponti, G. AI tutoring outperforms in-class active learning: An RCT introducing a novel research-based design in an authentic educational setting. *Scientific Reports* **2025**, *15*, 17458. https://doi.org/10.1038/s41598-025-97652-6.
11. Bastani, H.; Bastani, O.; Sungu, A.; Ge, H.; Kabakcı, Ö.; Mariman, R. Generative AI without guardrails can harm learning: Evidence from high school mathematics. *Proceedings of the National Academy of Sciences* **2025**, *122*, e2422633122. https://doi.org/10.1073/pnas.2422633122.
12. Posner, G.J.; Strike, K.A.; Hewson, P.W.; Gertzog, W.A. Accommodation of a scientific conception: Toward a theory of conceptual change. *Science Education* **1982**, *66*, 211–227. https://doi.org/10.1002/sce.3730660207.
13. Chi, M.T.H.; Slotta, J.D.; de Leeuw, N. From things to processes: A theory of conceptual change for learning science concepts. *Learning and Instruction* **1994**, *4*, 27–43. https://doi.org/10.1016/0959-4752(94)90017-5.
14. Vosniadou, S.; Brewer, W.F. Mental models of the earth: A study of conceptual change in childhood. *Cognitive Psychology* **1992**, *24*, 535–585. https://doi.org/10.1016/0010-0285(92)90018-W.
15. Qian, Y.; Lehman, J.D. Students' misconceptions and other difficulties in introductory programming: A literature review. *ACM Transactions on Computing Education* **2017**, *18*, 1–24. https://doi.org/10.1145/3077618.
16. Sorva, J. Visual Program Simulation in Introductory Programming Education. PhD thesis, Aalto University, 2012.
17. Reber, R.; Schwarz, N. Effects of perceptual fluency on judgments of truth. *Consciousness and Cognition* **1999**, *8*, 338–342. https://doi.org/10.1006/ccog.1999.0392.
18. Alter, A.L.; Oppenheimer, D.M. Uniting the tribes of fluency to form a metacognitive nation. *Personality and Social Psychology Review* **2009**, *13*, 219–235. https://doi.org/10.1177/1088868309341564.
19. Rozenblit, L.; Keil, F. The misunderstood limits of folk science: An illusion of explanatory depth. *Cognitive Science* **2002**, *26*, 521–562. https://doi.org/10.1207/s15516709cog2605_1.
20. Snowling, M.J.; Hulme, C.; Nation, K. Defining and understanding dyslexia: past, present and future. *Oxford Review of Education* **2019**, *46*, 501–513. https://doi.org/10.1080/03054985.2020.1765756.
21. Barkley, R.A. *Attention-Deficit Hyperactivity Disorder: A Handbook for Diagnosis and Treatment*, 4th ed.; Guilford Publications, 2015.
22. Martinussen, R.; Hayden, J.; Hogg-Johnson, S.; Tannock, R. A meta-analysis of working memory impairments in children with attention-deficit/hyperactivity disorder. *Journal of the American Academy of Child & Adolescent Psychiatry* **2005**, *44*, 377–384. https://doi.org/10.1097/01.chi.0000153228.72591.73.
23. Stone, M.; Liao, Y.; Szafir, D.; Boyer, K.E. Analogies in the age of LLMs: When explanatory metaphors mislead CS learners. In Proceedings of the Proceedings of the 55th ACM Technical Symposium on Computer Science Education, 2024, pp. 1256–1262. https://doi.org/10.1145/3626253.3635473.
24. Ben-Ari, M. Constructivism in computer science education. *Journal of Computers in Mathematics and Science Teaching* **2001**, *20*, 45–73.
25. Ibrahim, H.; Liu, T.; Chen, A.; Wang, D. The warmth-accuracy trade-off: When making LLMs more empathetic increases factual errors. In Proceedings of the Proceedings of the 2026 ACM Conference on Fairness, Accountability, and Transparency, 2026. Forthcoming.
26. Ouyang, L.; Wu, J.; Jiang, X.; Almeida, D.; Wainwright, C.; et al. Training language models to follow instructions with human feedback. In Proceedings of the Advances in Neural Information Processing Systems, 2022, Vol. 35, pp. 27730–27744. https://doi.org/10.48550/arXiv.2203.02155.
27. Sharma, M.; Tong, M.; Korbak, T.; Duvenaud, D.; Askell, A.; et al. Towards understanding sycophancy in language models. In Proceedings of the Proceedings of the 12th International Conference on Learning Representations, 2024. https://doi.org/10.48550/arXiv.2310.13548.
28. Perez, E.; Ringer, S.; Lukošiūtė, K.; Nguyen, K.; Chen, E.; et al. Discovering language model behaviors with model-written evaluations. In Proceedings of the Findings of the Association for Computational Linguistics: ACL 2023, 2023, pp. 13387–13434. https://doi.org/10.18653/v1/2023.findings-acl.847.

29. Lin, S.; Hilton, J.; Evans, O. TruthfulQA: Measuring how models mimic human falsehoods. In Proceedings of the Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics, 2022, pp. 3214–3252. https://doi.org/10.18653/v1/2022.acl-long.229.
30. Gadiraju, V.; Kane, S.; Dev, S.; Taylor, A.; Wang, D.; Denton, E.; Brewer, R. "I wouldn't say offensive but...": Disability-centered perspectives on large language models. In Proceedings of the Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency, 2023, pp. 205–216. https://doi.org/10.1145/3593013.3593989.
31. Devaraj, A.; Sheffield, W.; Wallace, B.C.; Li, J.J. Evaluating factuality in text simplification. In Proceedings of the Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics, 2022, pp. 7331–7345. https://doi.org/10.18653/v1/2022.acl-long.505.
32. Trienes, J.; Joseph, S.; Schlötterer, J.; Seifert, C.; Lo, K.; Xu, W.; Wallace, B.C.; Li, J.J. InfoLossQA: Characterizing and recovering information loss in text simplification. In Proceedings of the Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics, 2024, pp. 4263–4294. https://doi.org/10.18653/v1/2024.acl-long.234.
33. Zheng, L.; Chiang, W.L.; Sheng, Y.; Zhuang, S.; Wu, Z.; et al. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In Proceedings of the Advances in Neural Information Processing Systems, 2023, Vol. 36. https://doi.org/10.48550/arXiv.2306.05685.
34. Lyon, G.R.; Shaywitz, S.E.; Shaywitz, B.A. A definition of dyslexia. *Annals of Dyslexia* **2003**, *53*, 1–14. https://doi.org/10.1007/s11881-003-0001-9.
35. Faraone, S.V.; Asherson, P.; Banaschewski, T.; Biederman, J.; Buitelaar, J.K.; et al. Attention-deficit/hyperactivity disorder. *Nature Reviews Disease Primers* **2015**, *1*, 15020. https://doi.org/10.1038/nrdp.2015.20.
36. Peng, P.; Fuchs, D. A meta-analysis of working memory deficits in children with learning difficulties. *Journal of Learning Disabilities* **2016**, *49*, 3–20. https://doi.org/10.1177/0022219414528532.
37. Rello, L.; Baeza-Yates, R. Good fonts for dyslexia. In Proceedings of the Proceedings of the 15th International ACM SIGACCESS Conference on Computers and Accessibility, 2013, pp. 1–8. https://doi.org/10.1145/2513383.2513447.
38. Ji, Z.; Lee, N.; Frieske, R.; Yu, T.; Su, D.; et al. Survey of hallucination in natural language generation. *ACM Computing Surveys* **2023**, *55*, 1–38. https://doi.org/10.1145/3571730.
39. Huang, L.; Yu, W.; Ma, W.; Zhong, W.; Feng, Z.; et al. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems* **2025**, *43*, 1–55. https://doi.org/10.1145/3703155.
40. Flesch, R. A new readability yardstick. *Journal of Applied Psychology* **1948**, *32*, 221–233. https://doi.org/10.1037/h0057532.
41. McNamara, D.S.; Kintsch, E.; Songer, N.B.; Kintsch, W. Are good texts always better? Interactions of text coherence, background knowledge, and levels of understanding in learning from text. *Cognition and Instruction* **1996**, *14*, 1–43. https://doi.org/10.1207/s1532690xci1401_1.
42. Kalyuga, S.; Ayres, P.; Chandler, P.; Sweller, J. The expertise reversal effect. *Educational Psychologist* **2003**, *38*, 23–31. https://doi.org/10.1207/S15326985EP3801_4.
43. Bjork, E.L.; Bjork, R.A. Making things hard on yourself, but in a good way: Creating desirable difficulties to enhance learning. In *Psychology and the Real World: Essays Illustrating Fundamental Contributions to Society*; Gernsbacher, M.A.; Pew, R.W.; Hough, L.M.; Pomerantz, J.R., Eds.; Worth Publishers, 2011; pp. 56–64.
44. Sweller, J.; van Merriënboer, J.J.G.; Paas, F.G.W.C. Cognitive architecture and instructional design. *Educational Psychology Review* **1998**, *10*, 251–296. https://doi.org/10.1023/A:1022193728205.
45. Baddeley, A.D.; Hitch, G. Working memory. *Psychology of Learning and Motivation* **1974**, *8*, 47–89. https://doi.org/10.1016/S0079-7421(08)60452-1.
46. LaBerge, D.; Samuels, S.J. Toward a theory of automatic information processing in reading. *Cognitive Psychology* **1974**, *6*, 293–323. https://doi.org/10.1016/0010-0285(74)90015-2.
47. Kahneman, D. *Thinking, Fast and Slow*; Farrar, Straus and Giroux, 2011.
48. Buçinca, Z.; Malaya, M.B.; Gajos, K.Z. To trust or to think: Cognitive forcing functions can reduce overreliance on AI in AI-assisted decision-making. *Proceedings of the ACM on Human-Computer Interaction* **2021**, *5*, 1–21. https://doi.org/10.1145/3449282.
49. Harp, S.F.; Mayer, R.E. How seductive details do their damage: A theory of cognitive interest in science learning. *Journal of Educational Psychology* **1998**, *90*, 414–434. https://doi.org/10.1037/0022-0663.90.3.414.
50. Gentner, D. Structure-mapping: A theoretical framework for analogy. *Cognitive Science* **1983**, *7*, 155–170. https://doi.org/10.1207/s15516709cog0702_3.
51. Spiro, R.J.; Feltovich, P.J.; Coulson, R.L.; Anderson, D.K. Multiple analogies for complex concepts: Antidotes for analogy-induced misconception in advanced knowledge acquisition. In *Similarity and Analogical Reasoning*; Vosniadou, S.; Ortony, A., Eds.; Cambridge University Press, 1989; pp. 498–531. https://doi.org/10.1017/CBO9780511529863.023.
52. Glynn, S.M. Explaining science concepts: A teaching-with-analogies model. In *The Psychology of Learning Science*; Glynn, S.M.; Yeany, R.H.; Britton, B.K., Eds.; Lawrence Erlbaum Associates, 1991; pp. 219–240.

53. Liu, Y.; Iter, D.; Xu, Y.; Wang, S.; Xu, R.; Zhu, C. G-Eval: NLG evaluation using GPT-4 with better human alignment. In Proceedings of the Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, 2023, pp. 2511–2522. https://doi.org/10.18653/v1/2023.emnlp-main.153.
54. Wang, P.; Li, L.; Chen, L.; Cai, Z.; Zhu, D.; et al. Large language models are not fair evaluators. *arXiv preprint arXiv:2305.17926* **2023**. https://doi.org/10.48550/arXiv.2305.17926.
55. Panickssery, A.; Bowman, S.R.; Feng, S. LLM evaluators recognize and favor their own generations. *arXiv preprint arXiv:2404.13076* **2024**. https://doi.org/10.48550/arXiv.2404.13076.
56. ACM/IEEE-CS/AAAI Joint Task Force on Computing Curricula. Computer Science Curricula 2023, 2023.
57. Cohen, J. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement* **1960**, *20*, 37–46. https://doi.org/10.1177/001316446002000104.
58. Landis, J.R.; Koch, G.G. The measurement of observer agreement for categorical data. *Biometrics* **1977**, *33*, 159–174. https://doi.org/10.2307/2529310.
59. R Core Team. R: A Language and Environment for Statistical Computing, 2023.
60. Tukey, J.W. Comparing individual means in the analysis of variance. *Biometrics* **1949**, *5*, 99–114. https://doi.org/10.2307/3001913.
61. Shapiro, S.S.; Wilk, M.B. An analysis of variance test for normality (complete samples). *Biometrika* **1965**, *52*, 591–611. https://doi.org/10.1093/biomet/52.3-4.591.
62. Levene, H. Robust tests for equality of variances. In *Contributions to Probability and Statistics: Essays in Honor of Harold Hotelling*; Olkin, I., Ed.; Stanford University Press, 1960; pp. 278–292.
63. Cochran, W.G. The comparison of percentages in matched samples. *Biometrika* **1950**, *37*, 256–266. https://doi.org/10.2307/2332343.
64. McNemar, Q. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika* **1947**, *12*, 153–157. https://doi.org/10.1007/BF02295996.
65. Bates, D.; Mächler, M.; Bolker, B.; Walker, S. Fitting linear mixed-effects models using lme4. *Journal of Statistical Software* **2015**, *67*, 1–48. https://doi.org/10.18637/jss.v067.i01.
66. Benjamini, Y.; Hochberg, Y. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B* **1995**, *57*, 289–300. https://doi.org/10.1111/j.2517-6161.1995.tb02031.x.
67. Cohen, J. *Statistical Power Analysis for the Behavioral Sciences*, 2nd ed.; Lawrence Erlbaum Associates, 1988.
68. Lakens, D. Calculating and reporting effect sizes to facilitate cumulative science. *Frontiers in Psychology* **2013**, *4*, 863. https://doi.org/10.3389/fpsyg.2013.00863.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.