

# Package ‘HazReg’

December 19, 2025

**Type** Package

**Title** Parametric hazard-based regression models

**Version** 0.1.0

**Author** F. Javier Rubio

**Maintainer** F. Javier Rubio <fxrubio@gmail.com>

**Description** The HazReg R package implements the following parametric hazard-based regression models for survival data, in the overall and relative survival frameworks.

**License** What license is it under?

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.3

**Imports** numDeriv, matrixStats

## Contents

chew . . . . .	2
chgamma . . . . .	3
chggamma . . . . .	3
chllogis . . . . .	4
chlnorm . . . . .	4
chpgw . . . . .	5
chweibull . . . . .	5
CH_TVC . . . . .	6
Conf_Int . . . . .	7
dggamma . . . . .	7
dpgw . . . . .	8
GEHMLE . . . . .	8
GHMLE . . . . .	9
hew . . . . .	10
hgamma . . . . .	11
hggamma . . . . .	11
hllogis . . . . .	12
hlnorm . . . . .	12
HMLE_TVC . . . . .	13
hpgw . . . . .	15
hweibull . . . . .	15

pggamma . . . . .	16
qew . . . . .	16
qggamma . . . . .	17
qllogis . . . . .	17
qpgw . . . . .	18
rggamma . . . . .	18
rpgw . . . . .	19
sggamma . . . . .	19
simGH . . . . .	20
sim_TVC . . . . .	21
spgw . . . . .	22
SPred_TVC . . . . .	22
SPred_TVC_i . . . . .	23
<b>Index</b>	<b>25</b>

---

chew	<i>Power Exponentiated Weibull (EW) cumulative hazard function.</i> <i><a href="https://rpubs.com/FJRubio/EWD">https://rpubs.com/FJRubio/EWD</a></i>
------	---

---

## Description

Power Exponentiated Weibull (EW) cumulative hazard function. <https://rpubs.com/FJRubio/EWD>

## Usage

```
chew(t, sigma, nu, gamma)
```

## Arguments

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

## Value

the value of the EW cumulative hazard function

---

chgamma	<i>Gamma (G) cumulative hazard function.</i>
---------	--

---

**Description**

Gamma (G) cumulative hazard function.

**Usage**

```
chgamma(t, shape, scale)
```

**Arguments**

t	: positive argument
shape	: shape parameter
scale	: scale parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the Weibull hazard function

---

chggamma	<i>Generalised Gamma (GG) cumulative hazard function. <a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
----------	---

---

**Description**

Generalised Gamma (GG) cumulative hazard function. <https://rpubs.com/FJRubio/GG>

**Usage**

```
chggamma(t, sigma, nu, gamma)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

the value of the GG cumulative hazard function

---

chllogis	<i>Log-logistic (LL) cumulative hazard function.</i>
----------	--

---

**Description**

Log-logistic (LL) cumulative hazard function.

**Usage**

```
chllogis(t, mu, sigma)
```

**Arguments**

t	: positive argument
mu	: mean parameter in the log scale
sigma	: scale parameter in the log scale

**Value**

the value of the LL cumulative hazard function

---

chlnorm	<i>Lognormal (LN) cumulative hazard function.</i>
---------	---

---

**Description**

Lognormal (LN) cumulative hazard function.

**Usage**

```
chlnorm(t, mu, sigma)
```

**Arguments**

t	: positive argument
mu	: mean parameter in the log scale
sigma	: scale parameter in the log scale

**Value**

the value of the LN cumulative hazard function

---

chpgw	<i>Power Generalised Weibull (PGW) cumulative hazard function.</i> <i><a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a></i>
-------	--

---

**Description**

Power Generalised Weibull (PGW) cumulative hazard function. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
chpgw(t, sigma, nu, gamma)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

the value of the PGW cumulative hazard function

---

chweibull	<i>Weibull (W) cumulative hazard function.</i>
-----------	--

---

**Description**

Weibull (W) cumulative hazard function.

**Usage**

```
chweibull(t, sigma, nu)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter

**Value**

the value of the Weibull cumulative hazard function

---

CH_TVC	<i>Compute the Cumulative Hazard for a Proportional Hazards or Accelerated Failure Model (2- and 3-parameter baseline)</i>
--------	--

---

### Description

Computes the cumulative hazard  $H(t \mid x(t))$  at multiple time points for each individual under a proportional hazards (PH) model or Accelerated Failure Time (AFT) model with a two-parameter or three-parameter parametric baseline hazard.

### Usage

```
CH_TVC(df, beta, theta, chfun, hstr)
```

### Arguments

df	A data frame containing: <ul style="list-style-type: none"> <li>• ‘time’: numeric vector of time points.</li> <li>• Covariate columns named with prefix “des” (e.g., ‘des1’, ‘des2’, ...), representing <math>x(t)</math>.</li> </ul>
beta	Numeric vector of regression coefficients.
theta	Numeric baseline parameters of the cumulative hazard.
chfun	A function computing the baseline cumulative hazard: ‘chfun(time, theta[1], theta[2])’ or ‘chfun(time, theta[1], theta[2], theta[3])’.
hstr	Hazard structure ("PH" or "AFT")

### Details

The PH model assumes

$$H(t \mid x(t)) = H_0(t; a_0, b_0, c_0) \exp(x(t)^\top \beta).$$

In the AFT model, event time is rescaled as

$$H(t \mid x(t)) = H_0(t \exp(x(t)^\top \beta); a_0, b_0, c_0).$$

### Value

A numeric vector with the cumulative hazard evaluated at each time point in ‘df’.

---

Conf_Int	<i>Function to calculate the normal confidence intervals. The parameters indicated with "index" are transformed to the real line using log().</i>
----------	---

---

### Description

Function to calculate the normal confidence intervals. The parameters indicated with "index" are transformed to the real line using log().

### Usage

```
Conf_Int(FUN, MLE, level = 0.95, index = NULL)
```

### Arguments

FUN	: minus log-likelihood function to be used to calculate the confidence intervals
MLE	: maximum likelihood estimator of the parameters of interest
level	: confidence level
index	: position of the positive parameters under the original parameterisation

### Value

a list containing the upper and lower conf.int limits, the transformed MLE, and std errors

---

dggamma	<i>Generalised Gamma (GG) probability density function. <a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
---------	---

---

### Description

Generalised Gamma (GG) probability density function. <https://rpubs.com/FJRubio/GG>

### Usage

```
dggamma(t, sigma, nu, gamma, log = FALSE)
```

### Arguments

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log:	log scale (TRUE or FALSE)

### Value

the value of the GG probability density function

---

dpgw	<i>Power Generalised Weibull (PGW) probability density function.</i> <i><a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a></i>
------	--

---

**Description**

Power Generalised Weibull (PGW) probability density function. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
dpgw(t, sigma, nu, gamma, log = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the PGW probability density function

---

GEHMLE	<i>Relative (Net) Survival models Log likelihood and MLE for the GH excess hazards model. Baseline hazards: Lognormal, Log-logistic, Gamma, PGW, EW, GG</i>
--------	---

---

**Description**

Relative (Net) Survival models Log likelihood and MLE for the GH excess hazards model. Baseline hazards: Lognormal, Log-logistic, Gamma, PGW, EW, GG

**Usage**

```
GEHMLE(
  init,
  times,
  status,
  hp,
  hstr = NULL,
  dist = NULL,
  des = NULL,
  des_t = NULL,
  method = "Nelder-Mead",
  maxit = 100
)
```



**Arguments**

<code>init</code>	: initial point for optimisation step under the parameterisation ( $\log(\text{scale})$ , $\log(\text{shape1})$ , $\log(\text{shape2})$ , $\alpha$ , $\beta$ ) for scale-shape1-shape2 models or ( $\mu$ , $\log(\text{scale})$ , $\alpha$ , $\beta$ ) for log-location scale models.
<code>times</code>	: times to event
<code>status</code>	: vital status indicators (TRUE or 1 = observed, FALSE or 0 = censored)
<code>hp</code>	: population hazard (for all individuals)
<code>hstr</code>	: hazard structure: No covariates ("baseline"), AFT model with PGW baseline hazard ("AFT"), PH model with PGW baseline hazard ("PH"), AH model with PGW baseline hazard ("AH"), GH model with PGW baseline hazard ("GH") *GH is not available with Weibull dist
<code>dist</code>	: distribution for the baseline hazard: Power Generalised Weibull ("PGW") Generalised Gamma ("GenGamma") Exponentiated Weibull ("EW") Weibull ("Weibull") Gamma ("Gamma") LogNormal ("LogNormal") LogLogistic ("LogLogistic")
<code>des</code>	: design matrix for hazard-level effects
<code>des_t</code>	: design matrix for time-level effects (it is recommended not to use splines here)
<code>method</code>	: "nlminb" or optimisation method to be used in optim (see ?optim)
<code>maxit</code>	: maximum number of iterations in optim or nlminb

**Value**

It returns the output from optim or nlminb for the selected model and the negative log likelihood function

---

GHMLE	<i>GHMLE function: Hazard Regression Models with a parametric baseline hazard</i>
-------	---

---

**Description**

GHMLE function: Hazard Regression Models with a parametric baseline hazard

**Usage**

```
GHMLE(
  init,
  times,
  status,
  hstr = NULL,
  dist = NULL,
  des = NULL,
  des_t = NULL,
  method = "Nelder-Mead",
  maxit = 100
)
```

**Arguments**

<code>init</code>	: initial point for optimisation step under the parameterisation ( $\log(\text{scale})$ , $\log(\text{shape1})$ , $\log(\text{shape2})$ , $\alpha$ , $\beta$ ) for scale-shape1-shape2 models or ( $\mu$ , $\log(\text{scale})$ , $\alpha$ , $\beta$ ) for log-location scale models.
<code>times</code>	: times to event
<code>status</code>	: vital status indicators (TRUE or 1 = observed, FALSE or 0 = censored)
<code>hstr</code>	: hazard structure: No covariates ("baseline"), AFT model with PGW baseline hazard ("AFT"), PH model with PGW baseline hazard ("PH"), AH model with PGW baseline hazard ("AH"), GH model with PGW baseline hazard ("GH") *GH is not available with Weibull dist
<code>dist</code>	: distribution for the baseline hazard: Power Generalised Weibull ("PGW") Generalised Gamma ("GenGamma")) Exponentiated Weibull ("EW") Weibull ("Weibull") Gamma ("Gamma") LogNormal ("LogNormal") LogLogistic ("LogLogistic")
<code>des</code>	: design matrix for hazard-level effects
<code>des_t</code>	: design matrix for time-level effects (it is recommended not to use splines here)
<code>method</code>	: "nlminb" or optimisation method to be used in optim (see ?optim)
<code>maxit</code>	: maximum number of iterations in optim or nlminb

**Value**

It returns the output from optim or nlminb for the selected model and the negative log likelihood function

---

<code>hew</code>	<i>Power Exponentiated Weibull (EW) hazard function.</i> <a href="https://rpubs.com/FJRubio/EWD">https://rpubs.com/FJRubio/EWD</a>
------------------	---

---

**Description**

Power Exponentiated Weibull (EW) hazard function. <https://rpubs.com/FJRubio/EWD>

**Usage**

```
hew(t, sigma, nu, gamma, log = FALSE)
```

**Arguments**

<code>t</code>	: positive argument
<code>sigma</code>	: scale parameter
<code>nu</code>	: shape parameter
<code>gamma</code>	: shape parameter
<code>log</code> :	log scale (TRUE or FALSE)

**Value**

the value of the EW hazard function

---

hgamma	<i>Gamma (G) hazard function.</i>
--------	-----------------------------------

---

**Description**

Gamma (G) hazard function.

**Usage**

```
hgamma(t, shape, scale, log = FALSE)
```

**Arguments**

t	: positive argument
shape	: shape parameter
scale	: scale parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the Gamma hazard function

---

hggamma	<i>Generalised Gamma (GG) hazard function.</i> <i><a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
---------	--

---

**Description**

Generalised Gamma (GG) hazard function. <https://rpubs.com/FJRubio/GG>

**Usage**

```
hggamma(t, sigma, nu, gamma, log = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the GG hazard function

---

hllogis	<i>Log-logistic (LL) hazard function.</i>
---------	---

---

**Description**

Log-logistic (LL) hazard function.

**Usage**

```
hllogis(t, mu, sigma, log = FALSE)
```

**Arguments**

t	: positive argument
mu	: mean parameter in the log scale
sigma	: scale parameter in the log scale
log:	log scale (TRUE or FALSE)

**Value**

the value of the LL hazard function

---

hlnorm	<i>Lognormal (LN) hazard function.</i>
--------	--

---

**Description**

Lognormal (LN) hazard function.

**Usage**

```
hlnorm(t, mu, sigma, log = FALSE)
```

**Arguments**

t	: positive argument
mu	: mean parameter in the log scale
sigma	: scale parameter in the log scale
log:	log scale (TRUE or FALSE)

**Value**

the value of the LN hazard function

HMLE\_TVC

*Maximum Likelihood Estimation for Parametric Hazard Models with Time-Varying Covariates***Description**

'HMLE\_TVC()' fits parametric survival models in the presence of **time-varying covariates**, using maximum likelihood estimation.

The function supports:

\* **Proportional Hazards (PH)** models with time-varying covariates \* Fully parametric baseline hazards (2-parameter or 3-parameter)

\* **Accelerated Failure Time (AFT)** models with time-varying covariates \* Fully parametric baseline hazards (2-parameter or 3-parameter)

The likelihood is constructed from the cumulative hazard differences across observation intervals for each individual, using a counting-process representation.

For each individual, the data must contain several rows: one per time-varying covariate measurement, along with the corresponding time.

**Usage**

```
HMLE_TVC(
  init,
  df,
  status,
  hstr = NULL,
  dist = NULL,
  method = "Nelder-Mead",
  maxit = 100
)
```

**Arguments**

<code>init</code>	: initial point for optimisation step under the parameterisation (log(scale), log(shape1), log(shape2), beta) for scale-shape1-shape2 models or (mu, log(scale), beta) for log-location scale models.
<code>df</code>	A data frame in <b>long format</b> , containing one row per individual per covariate-measurement time. Required columns: * <code>ID</code> — individual identifier * <code>time</code> — time at which the covariates are measured * <code>des*</code> — covariate columns used in the model (e.g., <code>des1</code> , <code>des2</code> , ...) The last row for each ID represents the individual's event/censoring time, even if the event time does not coincide with a measurement time.
<code>status</code>	vector of event indicators (1 = event at the final time; 0 = censored)
<code>hstr</code>	Hazard structure ("PH" or "AFT")
<code>dist</code>	: distribution for the baseline hazard: Power Generalised Weibull ("PGW") Generalised Gamma ("GenGamma") Exponentiated Weibull ("EW") Weibull ("Weibull") Gamma ("Gamma") LogNormal ("LogNormal") LogLogistic ("LogLogistic")

method	Optimisation method for the likelihood. Either "nlminb" or a valid 'optim()' method.
maxit	Maximum number of optimisation iterations.

## Details

## Likelihood formulation for PH models

For each individual  $i$ , let  $t_{i1} < t_{i2} < \dots < t_{iK_i}$  denote the \*observation / measurement times\*.

The cumulative hazard contribution over interval  $(t_{ij-1}, t_{ij})$  is:

$$\Delta H_{ij} = [H_0(t_{ij}) - H_0(t_{ij-1})] \exp(x_{ij}^\top \beta),$$

where  $x_{ij}$  is the vector of covariates measured at time  $t_{ij}$ .

The full log-likelihood is:

$$\ell = \sum_i \left( - \sum_j \Delta H_{ij} + \delta_i \log [h_0(T_i) \exp(x_{iK}^\top \beta)] \right),$$

where:

\*  $\Delta H_{ij}$  comes from cumulative hazard increments \*  $(T_i = t_{iK})$  is the final event or censoring time \*  $\delta_i$  is the event indicator \* hazard and cumulative hazard are computed based on 'dist'

The function internally: 1. Splits the data by ID 2. Computes cumulative hazard at all measurement times 3. Computes increments  $\Delta H_{ij}$  for each ID 4. Constructs the likelihood 5. Optimises over  $\beta$  and baseline parameters

## Value

A list containing:

\* The full output from 'optim()' or 'nlminb()' \* The **negative log-likelihood function** used for optimisation \* A vector giving, for each ID, the cumulative hazard increments used in the likelihood

Returned invisibly where appropriate.

## Data structure

The input data frame must contain:

\* varying number of rows per ID \* strictly increasing 'time' within each ID \* last row containing the event/censoring time

Covariates must be named as 'des1', 'des2', etc.

---

hpgw	<i>Power Generalised Weibull (PGW) hazard function.</i> <i><a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a></i>
------	---

---

**Description**

Power Generalised Weibull (PGW) hazard function. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
hpgw(t, sigma, nu, gamma, log = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the PGW hazard function

---

hweibull	<i>Weibull (W) hazard function.</i>
----------	-------------------------------------

---

**Description**

Weibull (W) hazard function.

**Usage**

```
hweibull(t, sigma, nu, log = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
log:	log scale (TRUE or FALSE)

**Value**

the value of the Weibull hazard function

---

pgamma	<i>Generalised Gamma (GG) cumulative distribution function.</i> <i><a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
--------	---

---

**Description**

Generalised Gamma (GG) cumulative distribution function. <https://rpubs.com/FJRubio/GG>

**Usage**

```
pgamma(t, sigma, nu, gamma, log.p = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log.p:	log scale (TRUE or FALSE)

**Value**

the value of the GG cumulative distribution function

---

qew	<i>Power Exponentiated Weibull (EW) quantile function.</i> <i><a href="https://rpubs.com/FJRubio/EWD">https://rpubs.com/FJRubio/EWD</a></i>
-----	--

---

**Description**

Power Exponentiated Weibull (EW) quantile function. <https://rpubs.com/FJRubio/EWD>

**Usage**

```
qew(p, sigma, nu, gamma)
```

**Arguments**

p	: probability. A value in (0,1)
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

the value of the EW quantile function



---

qggamma	<i>Generalised Gamma (GG) quantile function.</i> <i><a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
---------	--

---

**Description**

Generalised Gamma (GG) quantile function. <https://rpubs.com/FJRubio/GG>

**Usage**

```
qggamma(p, sigma, nu, gamma)
```

**Arguments**

p	: probability. A value in (0,1)
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

the value of the GG quantile function

---

qllogis	<i>Log-logistic (LL) quantile function.</i>
---------	---

---

**Description**

Log-logistic (LL) quantile function.

**Usage**

```
qllogis(p, mu, sigma)
```

**Arguments**

p	: probability. A value in (0,1)
mu	: mean parameter in the log scale
sigma	: scale parameter in the log scale

**Value**

the value of the LL quantile function

---

qp <sub>gw</sub>	<i>Power Generalised Weibull (PGW) quantile function.</i> <i><a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a></i>
------------------	---

---

**Description**

Power Generalised Weibull (PGW) quantile function. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
qpgw(p, sigma, nu, gamma)
```

**Arguments**

p	: probability. A value in (0,1)
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

the value of the PGW quantile function

---

rggamma	<i>Generalised Gamma (GG) random number generation.</i> <i><a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
---------	---

---

**Description**

Generalised Gamma (GG) random number generation. <https://rpubs.com/FJRubio/GG>

**Usage**

```
rggamma(n, sigma, nu, gamma)
```

**Arguments**

n	: number of observations
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

generates random deviates

---

rpgw	<i>Power Generalised Weibull (PGW) random number generation.</i> <i><a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a></i>
------	--

---

**Description**

Power Generalised Weibull (PGW) random number generation. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
rpgw(n, sigma, nu, gamma)
```

**Arguments**

n	: number of observations
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter

**Value**

generates random deviates

---

sgamma	<i>Generalised Gamma (GG) survival function.</i> <i><a href="https://rpubs.com/FJRubio/GG">https://rpubs.com/FJRubio/GG</a></i>
--------	--

---

**Description**

Generalised Gamma (GG) survival function. <https://rpubs.com/FJRubio/GG>

**Usage**

```
sgamma(t, sigma, nu, gamma, log.p = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log.p:	log scale (TRUE or FALSE)

**Value**

the value of the GG survival function

---

simGH	<i>simGH function: Function to simulate times to event from a model with a GH structure for different parametric baseline hazards. Distributions: LogNormal, LogLogistic, GenGamma, Gamma, Weibull, PGW, EW. See: <a href="https://github.com/FJRubio67/HazReg">https://github.com/FJRubio67/HazReg</a></i>
-------	---

---

## Description

simGH function: Function to simulate times to event from a model with a GH structure for different parametric baseline hazards. Distributions: LogNormal, LogLogistic, GenGamma, Gamma, Weibull, PGW, EW. See: <https://github.com/FJRubio67/HazReg>

## Usage

```
simGH(
  seed,
  n,
  des = NULL,
  des_h = NULL,
  des_t = NULL,
  theta,
  beta_h = NULL,
  beta_t = NULL,
  beta = NULL,
  hstr,
  baseline
)
```

## Arguments

seed	: seed for simulation
n	: sample size (number of individuals)
des	: Design matrix for AFT, PH, and AH models
des_h	: Design matrix for GH model (hazard scale)
des_t	: Design matrix for GH model (time scale)
theta	: parameters of the baseline hazard
beta_h	: regression parameters multiplying the hazard for GH model
beta_t	: regression parameters multiplying the time scale for GH model
beta	: regression parameters for AFT, PH, and AH models
hstr	: hazard structure (AH, AFT, PH, GH)
baseline	: baseline hazard distribution

## Value

a vector containing the simulated times to event

sim\_TVC

*Simulate Event Times from a Time-Varying Covariates Survival Model***Description**

Simulates event times from a survival model with time-varying covariates using the probability integral transform. The function supports proportional hazards (PH) and accelerated failure time (AFT) models with parametric baseline hazards.

**Usage**

```
sim_TVC(seed, df, chfun, hstr, theta, beta)
```

**Arguments**

seed	Integer random seed for reproducibility.
df	A data frame containing the longitudinal covariate information with: <ul style="list-style-type: none"> <li>• ID: individual identifier.</li> <li>• time: observation times for covariate measurements.</li> <li>• Covariate columns named with prefix "des" (e.g., des1, des2, ...).</li> </ul> Covariates are assumed to be piecewise constant between observation times.
chfun	A function computing the baseline cumulative hazard, e.g. <code>chfun(time, ...)</code> .
hstr	Character string specifying the hazard structure. Either "PH" for proportional hazards or "AFT" for accelerated failure time models.
theta	Numeric vector of baseline hazard parameters. The length of theta determines whether a two- or three-parameter baseline is used.
beta	Numeric vector of regression coefficients corresponding to the time-varying covariates.

**Details**

For each individual  $i$ , a uniform random variable  $U_i \sim \text{Unif}(0, 1)$  is generated. If the survival probability at the last observed time  $t_{\max,i}$  satisfies

$$S_i(t_{\max,i}) > U_i,$$

the individual is right-censored at  $t_{\max,i}$ . Otherwise, the event time  $T_i$  is obtained by solving

$$S_i(t) = U_i$$

for  $t \in (0, t_{\max,i}]$ , where  $S_i(t)$  is the individual-specific survival function accounting for time-varying covariates.

The survival function is evaluated via `SPred_TVC` and `SPred_TVC_i`, ensuring consistency with the underlying cumulative hazard specification.

The simulation assumes that covariates are left-continuous and piecewise constant over time. Event times are generated conditional on the observed covariate history up to the last follow-up time for each individual.

This function is suitable for simulation studies involving time-varying covariates under parametric PH or AFT models.

**Value**

A list with components:

- time: numeric vector of simulated event or censoring times.
- status: event indicator (1 = event, 0 = right-censored).

**See Also**

[CH\\_TVC](#), [SPred\\_TVC](#), [SPred\\_TVC\\_i](#)

---

spgw	<i>Power Generalised Weibull (PGW) survival function.</i> <a href="http://rpubs.com/FJRubio/PGW">http://rpubs.com/FJRubio/PGW</a>
------	--

---

**Description**

Power Generalised Weibull (PGW) survival function. <http://rpubs.com/FJRubio/PGW>

**Usage**

```
spgw(t, sigma, nu, gamma, log.p = FALSE)
```

**Arguments**

t	: positive argument
sigma	: scale parameter
nu	: shape parameter
gamma	: shape parameter
log.p:	log scale (TRUE or FALSE)

**Value**

the value of the PGW survival function

---

SPred_TVC	<i>Compute the Survival Function for a Proportional Hazards or Accelerated Failure Model (2- and 3-parameter baseline)</i>
-----------	--

---

**Description**

Computes the survival function  $\exp(-H(t | x(t)))$  at the last time point for each individual under a proportional hazards (PH) model or Accelerated Failure Time (AFT) model with a two-parameter or three-parameter parametric baseline hazard.

**Usage**

```
SPred_TVC(df, beta, theta, chfun, hstr)
```

**Arguments**

df	A data frame containing: <ul style="list-style-type: none"> <li>• ‘time’: numeric vector of time points.</li> <li>• Covariate columns named with prefix “des” (e.g., ‘des1’, ‘des2’, ...), representing <math>x(t)</math>.</li> </ul>
beta	Numeric vector of regression coefficients.
theta	Numeric baseline parameters of the cumulative hazard.
chfun	A function computing the baseline cumulative hazard: ‘chfun(time, theta[1], theta[2])’ or ‘chfun(time, theta[1], theta[2], theta[3])’.
hstr	Hazard structure ("PH" or "AFT")

**Details**

The PH model assumes

$$H(t \mid x(t)) = H_0(t; a_0, b_0, c_0) \exp(x(t)^\top \beta).$$

In the AFT model, event time is rescaled as

$$H(t \mid x(t)) = H_0(t \exp(x(t)^\top \beta); a_0, b_0, c_0).$$

**Value**

A numeric vector with the survival function evaluated at the last time point in ‘df’.

---

SPred_TVC_i	<i>Compute the Individual Survival Function at an Arbitrary Time Point for a Proportional Hazards or Accelerated Failure Model (2- and 3-parameter baseline)</i>
-------------	--

---

**Description**

Computes the individual-specific survival function  $S_i(t) = \exp\{-H_i(t \mid x_i(t))\}$  at a user-specified time point  $t$  for a given individual  $i$ , under a proportional hazards (PH) model or an accelerated failure time (AFT) model with time-varying covariates.

**Usage**

```
SPred_TVC_i(df, i, t, beta, theta, chfun, hstr)
```

**Arguments**

df	A data frame containing: <ul style="list-style-type: none"> <li>• ‘ID’: individual identifier.</li> <li>• ‘time’: numeric vector of observation times.</li> <li>• Covariate columns named with prefix “des” (e.g., ‘des1’, ‘des2’, ...), representing the time-varying covariate process <math>x_i(t)</math>.</li> </ul>
i	Integer specifying the individual for whom the survival function is to be evaluated.

t	Numeric value giving the time point at which the survival function is evaluated. Must lie within the observation window of individual 'i'.
beta	Numeric vector of regression coefficients.
theta	Numeric baseline parameters of the cumulative hazard.
chfun	A function computing the baseline cumulative hazard: 'chfun(time, theta[1], theta[2])' or 'chfun(time, theta[1], theta[2], theta[3])'.
hstr	Character string specifying the hazard structure: "'PH'" for proportional hazards or "'AFT'" for accelerated failure time.

### Details

The cumulative hazard for individual  $i$  is defined as:

$$H_i(t \mid x_i(t)) = \int_0^t h_0(u; a_0, b_0, c_0) \exp\{x_i(u)^\top \beta\} du$$

for the PH model, and

$$H_i(t \mid x_i(t)) = H_0(t \exp\{x_i(t)^\top \beta\}; a_0, b_0, c_0)$$

for the AFT model.

Time-varying covariates are assumed to be piecewise constant between the observation times provided in 'df'. If the evaluation time 't' does not coincide with an observed time point for individual 'i', the covariate values are taken to be those at the most recent time strictly less than 't'.

This function relies on 'CH\_TVC()' to compute the cumulative hazard over the observed time grid augmented with the evaluation time 't'. The cumulative hazard is then extracted at time 't', and the survival function is obtained as  $\exp\{-H_i(t)\}$ .

The resulting survival function is continuous in time but may exhibit changes in slope at covariate change points, reflecting the piecewise-constant nature of the time-varying covariates.

### Value

A numeric scalar giving the survival probability  $S_i(t)$  for individual 'i' at time 't'.

### See Also

[CH\\_TVC](#), [SPred\\_TVC](#)



# Index

CH\_TVC, [6](#), [22](#), [24](#)  
chew, [2](#)  
chgamma, [3](#)  
chggamma, [3](#)  
chllogis, [4](#)  
chlnorm, [4](#)  
chpgw, [5](#)  
chweibull, [5](#)  
Conf\_Int, [7](#)  
  
dggamma, [7](#)  
dpgw, [8](#)  
  
GEHMLE, [8](#)  
GHMLE, [9](#)  
  
hew, [10](#)  
hgamma, [11](#)  
hggamma, [11](#)  
hllogis, [12](#)  
hlnorm, [12](#)  
HMLE\_TVC, [13](#)  
hpgw, [15](#)  
hweibull, [15](#)  
  
pggamma, [16](#)  
  
qew, [16](#)  
qggamma, [17](#)  
qllogis, [17](#)  
qpgw, [18](#)  
  
rggamma, [18](#)  
rpgw, [19](#)  
  
sggamma, [19](#)  
sim\_TVC, [21](#)  
simGH, [20](#)  
spgw, [22](#)  
SPred\_TVC, [21](#), [22](#), [22](#), [24](#)  
SPred\_TVC\_i, [21](#), [22](#), [23](#)