WikiRace

Remember this is a competition, do your best!

---

1 What you submit

You submit a public GitHub repository that holds only your player project, the folder `player/` of the WikiRace repository. The root of your repository is the content of that folder, with all its files and the same structure. The rest of the WikiRace repository (`platform/`, `deploy/`, `docs/`) is not part of your submission.

```
.formatter.exs
.gitignore
Dockerfile
README.md
bin/connect.exs
lib/player/application.ex
lib/player/crawler.ex
lib/wiki_race/crawler.ex
lib/wiki_race/harness.ex
lib/wiki_race/status.ex
mix.exs
mix.lock
test/test_helper.exs
test/wiki_race/contract_test.exs
```

You may add files and folders under `lib/` and `test/`. The platform clones your repository at a tag, builds a release from its root, and copies it to both player virtual machines. Before each match, the platform starts your crawler on one of them, in a new Erlang node.
The platform clones a PUBLIC repository. A private repository cannot be cloned, so your submission cannot be raced.

2 Steps

1. Choose a name for your group. The dashboard and the standings show it during the tournament. Mention it: in the README or in the BN submission, you choose where, I just need to know what the name of your group is.

2. Create a public GitHub repository.

3. Turn your `player/` folder into a repository of its own and push it. The folder `my-crawler` is any new folder outside your copy of WikiRace.

   ```
   cp -r wiki_race/player my-crawler
   cd my-crawler
   git init -b main
   git add .
   git commit -m "Crawler"
   git remote add origin https://github.com/<you>/<your-repo>.git
   git push -u origin main
   ```

   The `.gitignore` of the template keeps `_build/` and `deps/` out of the repository.

4. Do not change the files and settings listed in Section 3.

5. Check that the release builds from the root of your repository. The platform builds it with Elixir 1.20 and Erlang/OTP 28.

```
MIX_ENV=prod mix deps.get
MIX_ENV=prod mix release
```

6. Tag the commit you submit and push the tag.

```
git tag -a final -m "Final submission"
git push origin final
```

7. Submit your group name, the HTTPS URL of the repository (the one of step 3), the tag name (`final`), and the commit hash. The following command prints the hash of the tagged commit.

```
git rev-list -n 1 final
```

3 What you must not change

The application name. `mix.exs` declares `app: :player`. The platform runs your release as `bin/player`, so it cannot start a release with another name.

The contract. The files in `lib/wiki_race/` stay as they are in the template. The platform calls your crawler through them.

The dependencies. Your crawler depends only on `req` and `floki`, as in the template. Commit `mix.lock` so that the platform builds with the versions you tested.

The node name and the cookie. Do not set them in `rel/env.sh.eex`, in `rel/vm.args.eex`, or in your code with `Node.start/2` or `Node.set_cookie/1`. The platform sets both each time it starts your crawler.

4 The tag

The platform clones your repository at the tag and prints the commit it cloned for each group. That commit is compared with the hash you submit, and it is the commit that is graded. Do not move the tag or push it again after the deadline.