

ITA0448 – STATISTICS WITH R PROGRAMMING

Lab manual Day 1

S. Dhanush kumar

192121154

BASIC OPERATIONS IN R

1. Write The Commands To Perform Basic Arithmetic In R.

Program:

```
a<-16
```

```
b<-3
```

```
add<-a+b
```

```
sub=a-b
```

```
multi=a*b
```

```
division=a/b
```

```
integer_division=a%/%b
```

```
exponent=a^b
```

```
print(paste("addition of two numbers 16 and 3 is:",add))
```

```
print(paste("Subtracting Number 3 from 16 is : ", sub))
```

```
print(paste("Multiplication of two numbers 16 and 3 is : ", multi))
```

```
print(paste("Division of two numbers 16 and 3 is : ", division))
```

```
print(paste("Integer Division of two numbers 16 and 3 is : ", Integer_Division))
```

```
print(paste("Exponent of two numbers 16 and 3 is : ", exponent))
```

output:

```
> a<-16
> b<-3
> add<-a+b
> sub=a-b
> multi=a*b
> division=a/b
> integer_division=a%/%b
> exponent=a^b
>
> print(paste("addition of two numbers 16 and 3 is:",add))
[1] "addition of two numbers 16 and 3 is: 19"
> print(paste("Subtracting Number 3 from 16 is : ", sub))
[1] "Subtracting Number 3 from 16 is : 13"
> print(paste("Multiplication of two numbers 16 and 3 is : ", multi))
[1] "Multiplication of two numbers 16 and 3 is : 48"
> print(paste("Division of two numbers 16 and 3 is : ", division))
[1] "Division of two numbers 16 and 3 is : 5.333333333333333"
> print(paste("Integer Division of two numbers 16 and 3 is : ", Integer_Division))
```

2. Display a String on R Console.**program**

```
print("hello, world!")
```

```
> print("hello, world!")
```

Output:

```
[1] "hello, world!"
```

3.Declare Variables In R And Also Write The Commands For Retrieving The Value Of The Stored Variables In R Console.**Program:**

```
#assignment using equal operator.
```

```
var.1=c(0,1,2,3)
```

```
#assignment using leftward operator.
```

```
var.2<-c("learn","R")
```

```
#assgnment using rightward operator.
```

```
c(TRUE,1)-> var.3
```

```
print(var.1)
```

```
cat("var.1 is", var.1,"\n")
```

```
cat("var.2 is", var.2,"\n")
```

```
cat("var.3 is", var.3,"\n")
```

output:

```
> #assignment using equal operator.
```

```
> var.1=c(0,1,2,3)
```

```
>

> #assignment using leftward operator.

> var.2<-c("learn","R")

>

> #assgnment using rightward operator.

> c(TRUE,1)-> var.3

>

> print(var.1)

[1] 0 1 2 3

> cat("var.1 is", var.1,"\n")

var.1 is 0 1 2 3

> cat("var.2 is", var.2,"\n")

var.2 is learn R

> cat("var.3 is", var.3,"\n")

var.3 is 1 1
```

4. Write R script to calculate the area of Rectangle.

Program:

```
length <- 5

width <- 10

area <- length * width

cat("the area of the rectangle is",area,"\n")
```

output:

```
> length <- 5  
> width <- 10  
>  
> area <- length * width  
>  
> cat("the area of the rectangle is",area,"\n")  
the area of the rectangle is 50
```

5. Write Commands In R Console To Determine The Type Of Variable

program

```
x <- "ms dhoni"  
typeof(x)
```

```
x <- 5  
typeof(x)
```

output:

```
> x <- "ms dhoni"  
> typeof(x)  
[1] "character"  
>  
> x <- 5  
> typeof(x)  
[1] "double"
```

**6.Enumerate The Process To Check Whether A Given Input Is Numeric , Integer ,
Double, Complex in R.**

Program

```
x <- 3.14
```

```
is.numeric(x)
```

```
x <- 5L
```

```
is.integer(x)
```

```
x <- 343.3
```

```
is.double(x)
```

```
x <- 2+4i
```

```
is.complex(x)
```

output:

```
> x <- 3.14
```

```
> is.numeric(x)
```

```
[1] TRUE
```

```
>
```

```
> x <- 5L
```

```
> is.integer(x)
```

```
[1] TRUE
```

```
>  
> x <-343.3  
> is.double(x)  
[1] TRUE  
>  
> x <- 2+4i  
> is.complex(x)  
[1] TRUE
```

7. Illustration of Vector Arithmetic.

Program:

```
v1<-c(1,2,3)  
v2<-c(4,5,6)
```

```
# vector addition
```

```
v3<- v1+v2  
print(v3)
```

```
# vector sub  
v4 <- v1-v2  
print(v4)
```

```
#vector mul
```

```
v5 <- v1 * v2
```

```
print(v5)
```

output:

```
> v1<-c(1,2,3)
```

```
> v2<-c(4,5,6)
```

```
>
```

```
> # vector addition
```

```
>
```

```
> v3<- v1+v2
```

```
> print(v3)
```

```
[1] 5 7 9
```

```
>
```

```
> # vector sub
```

```
> v4 <- v1-v2
```

```
> print(v4)
```

```
[1] -3 -3 -3
```

```
>
```

```
> #vector mul
```

```
>
```

```
> v5 <- v1 * v2
```

```
> print(v5)
```

```
[1] 4 10 18
```


8. Write an R Program to Take Input From User.

Input name as "Jack" and age as 17.

The program should display the output as

"Hai , Jack next year you will be 18 years old"

Program:

```
# Prompt the user to enter their name and age
```

```
name <- readline(prompt = "Please enter your name: ")
```

```
age <- readline(prompt = "Please enter your age: ")
```

```
# Convert the age to a numeric value
```

```
age <- as.numeric(age)
```

```
# Add one to the age to calculate the next year's age
```

```
next_year_age <- age + 1
```

```
# Display the message to the user
```

```
message(paste("Hi,", name, "next year you will be", next_year_age, "years old."))
```

output:

```
>"Hi,", name, "next year you will be", next_year_age, "years old."
```

DATA STRUCTURES IN R

1) Perform Matrix Addition & Subtraction in R

Program:

```
# Create two matrices
mat1 <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
mat2 <- matrix(c(5, 6, 7, 8), nrow = 2, ncol = 2)

# Add the matrices
mat_sum <- mat1 + mat2

# Subtract the matrices
mat_diff <- mat1 - mat2

# Print the results
print(mat_sum)
print(mat_diff)
```

Output:

```
> # Create two matrices
> mat1 <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
> mat2 <- matrix(c(5, 6, 7, 8), nrow = 2, ncol = 2)
>
> # Add the matrices
> mat_sum <- mat1 + mat2
>
> # Subtract the matrices
> mat_diff <- mat1 - mat2
>
> # Print the results
> print(mat_sum)
      [,1] [,2]
[1,]   6  10
[2,]   8  12
> print(mat_diff)
      [,1] [,2]
[1,]  -4  -4
[2,]  -4  -4
>

>
```

2) Perform Scalar multiplication and matrix multiplication in R

Program:

```
# Create a matrix

mat <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)


# Perform scalar multiplication

scalar_mult <- 2 * mat


# Perform matrix multiplication

mat_mult <- mat %*% mat


# Print the results

print(scalar_mult)

print(mat_mult)
```

output:

```
> # Create a matrix
> mat <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
>
> # Perform scalar multiplication
> scalar_mult <- 2 * mat
>
> # Perform matrix multiplication
> mat_mult <- mat %*% mat
```

```
>
> # Print the results
> print(scalar_mult)
  [,1] [,2]
[1,]  2  6
[2,]  4  8
> print(mat_mult)
  [,1] [,2]
[1,]  7 15
[2,] 10 22
>
```

```
>
```

3) Find Transpose of matrix in R.

Program:

```
# Create a matrix
```

```
mat <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
```

```
# Find the transpose of the matrix
```

```
mat_transpose <- t(mat)
```

```
# Print the results
```

```
print(mat)
```

```
print(mat_transpose)
```

output:

```
> # Create a matrix
> mat <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
>
```

```

> # Find the transpose of the matrix
> mat_transpose <- t(mat)
>
> # Print the results
> print(mat)
      [,1] [,2]
[1,]    1    3
[2,]    2    4
> print(mat_transpose)
      [,1] [,2]
[1,]    1    2
[2,]    3    4
>

```

```

>

```

4) Perform the operation of combining matrices in R using cbind() and rbind() functions.

Program:

```

# Create two matrices

```

```

mat1 <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)

```

```

mat2 <- matrix(c(5, 6, 7, 8), nrow = 2, ncol = 2)

```

```

# Combine the matrices horizontally (column-wise)

```

```

mat_combined1 <- cbind(mat1, mat2)

```

```

# Combine the matrices vertically (row-wise)

```

```

mat_combined2 <- rbind(mat1, mat2)

```

```

# Print the results

```

```

print(mat_combined1)

```

```
print(mat_combined2)
```

output:

```
> # Create two matrices
> mat1 <- matrix(c(1, 2, 3, 4), nrow = 2, ncol = 2)
> mat2 <- matrix(c(5, 6, 7, 8), nrow = 2, ncol = 2)
>
> # Combine the matrices horizontally (column-wise)
> mat_combined1 <- cbind(mat1, mat2)
>
> # Combine the matrices vertically (row-wise)
> mat_combined2 <- rbind(mat1, mat2)
>
> # Print the results
> print(mat_combined1)
      [,1] [,2] [,3] [,4]
[1,]    1    3    5    7
[2,]    2    4    6    8
> print(mat_combined2)
      [,1] [,2]
[1,]    1    3
[2,]    2    4
[3,]    5    7
[4,]    6    8
>

>
```

5) Deconstruct a matrix in R

Program:

```
# Create a matrix
```

```
mat <- matrix(c(1, 2, 3, 4, 5, 6), nrow = 2, ncol = 3)
```

```
# Extract the elements of the matrix
```

```
elements <- mat[1:6]
```

```
# Extract the rows of the matrix
```

```
rows <- mat[c(1, 2), ]
```

```
# Extract the columns of the matrix
```

```
columns <- mat[, c(2, 3)]
```

```
# Print the results
```

```
print(mat)
```

```
print(elements)
```

```
print(rows)
```

```
print(columns)
```

output:

```
> # Create a matrix
> mat <- matrix(c(1, 2, 3, 4, 5, 6), nrow = 2, ncol = 3)
>
> # Extract the elements of the matrix
> elements <- mat[1:6]
>
> # Extract the rows of the matrix
> rows <- mat[c(1, 2), ]
>
> # Extract the columns of the matrix
> columns <- mat[, c(2, 3)]
>
> # Print the results
> print(mat)
  [,1] [,2] [,3]
[1,]  1  3  5
[2,]  2  4  6
> print(elements)
[1] 1 2 3 4 5 6
> print(rows)
  [,1] [,2] [,3]
[1,]  1  3  5
[2,]  2  4  6
> print(columns)
  [,1] [,2]
[1,]  3  5
[2,]  4  6
```

```
[1,] 3 5  
[2,] 4 6  
>
```

6) Perform array manipulation in R .

Program:

```
# Create the vectors with different length
```

```
vector1 <- c(1, 2, 3)
```

```
vector2 <- c(10, 15, 3, 11, 16, 12)
```

```
# taking this vector as input
```

```
result <- array(c(vector1, vector2), dim = c(3, 3, 2))
```

```
print(result)
```

output:

```
# Create the vectors with different length
```

```
> vector1 <- c(1, 2, 3)
```

```
> vector2 <- c(10, 15, 3, 11, 16, 12)
```

```
>
```

```
> # taking this vector as input
```

```
> result <- array(c(vector1, vector2), dim = c(3, 3, 2))
```

```
> print(result)
```

```
., 1
```

```
      [,1] [,2] [,3]  
[1,]  1  10  11  
[2,]  2  15  16  
[3,]  3   3  12
```

```
., 2
```



```
      [,1] [,2] [,3]  
[1,]    1   10   11  
[2,]    2   15   16  
[3,]    3    3   12
```

>

>

7) Perform calculations across array elements in an array using the apply() function.

Program:

```
# Create a matrix
```

```
mat <- matrix(1:9, nrow = 3)
```

```
# Apply the sum function to each row of the matrix
```

```
row_sums <- apply(mat, 1, sum)
```

```
# Print the row sums
```

```
print(row_sums)
```

```
# Create a matrix
```

```
mat <- matrix(rnorm(16), nrow = 4)
```

```
# Apply the mean function to each column of the matrix
```

```
col_means <- apply(mat, 2, mean)
```

```
# Print the column means
```

```
print(col_means)
```

output

```
> # Create a matrix
> mat <- matrix(1:9, nrow = 3)
>
> # Apply the sum function to each row of the matrix
> row_sums <- apply(mat, 1, sum)
>
> # Print the row sums
> print(row_sums)
[1] 12 15 18
> # Create a matrix
> mat <- matrix(rnorm(16), nrow = 4)
>
> # Apply the mean function to each column of the matrix
> col_means <- apply(mat, 2, mean)
>
> # Print the column means
> print(col_means)
[1] 0.05163526 0.22976812 -0.05427408 0.05352512
>
>
```

8) Demonstrate Factor data structure in R.

Program:

```
# Create a vector of categorical data

grades <- c("A", "B", "A", "C", "B", "B", "A")

# Convert the vector to a factor

grades_factor <- factor(grades)

# Print the levels of the factor
```

```
print(levels(grades_factor))
```

```
# Print the counts of each level
```

```
print(table(grades_factor))
```

```
# Rename the levels of the factor
```

```
levels(grades_factor) <- c("Excellent", "Good", "Fair")
```

```
# Print the renamed levels
```

```
print(levels(grades_factor))
```

```
# Print the counts of each renamed level
```

```
print(table(grades_factor))
```

output:

```
> # Create a vector of categorical data
> grades <- c("A", "B", "A", "C", "B", "B", "A")
>
> # Convert the vector to a factor
> grades_factor <- factor(grades)
>
> # Print the levels of the factor
> print(levels(grades_factor))
[1] "A" "B" "C"
>
> # Print the counts of each level
> print(table(grades_factor))
grades_factor
A B C
3 3 1
>
> # Rename the levels of the factor
> levels(grades_factor) <- c("Excellent", "Good", "Fair")
>
> # Print the renamed levels
> print(levels(grades_factor))
[1] "Excellent" "Good"      "Fair"
>
```

```

> # Print the counts of each renamed level
> print(table(grades_factor))
grades_factor
Excellent    Good    Fair
          3      3      1
>

```

```

>

```

9) Create a data frame and print the structure of the data frame in R.

Program:

```

# Create a data frame with two columns

```

```

df <- data.frame(name = c("Alice", "Bob", "Charlie"), age = c(25, 30, 35))

```

```

# Print the structure of the data frame

```

```

str(df)

```

output

```

> # Create a data frame with two columns
> df <- data.frame(name = c("Alice", "Bob", "Charlie"), age = c(25, 30, 35))
>
> # Print the structure of the data frame
> str(df)
'data.frame':      3 obs. of  2 variables:
 $ name: chr  "Alice" "Bob" "Charlie"
 $ age : num  25 30 35
>

```

```

>

```

10) Demonstrate the creation of S3 class in R.

Program:

```
# Define a custom S3 class
```

```
myclass <- function(x) {  
  class(x) <- c("myclass", class(x))  
  x  
}
```

```
# Create an object of the custom class
```

```
myobject <- myclass(5)
```

```
# Print the class of the object
```

```
class(myobject)
```

```
# Define a method for the custom class
```

```
print.myclass <- function(x, ...) {  
  cat("This is an object of class 'myclass':\n")  
  print(as.numeric(x))  
}
```

```
# Call the method on the object
```

```
print(myobject)
```

output

```
> # Define a custom S3 class  
> myclass <- function(x) {  
+   class(x) <- c("myclass", class(x))  
+   x  
+ }
```

```

>
> # Create an object of the custom class
> myobject <- myclass(5)
>
> # Print the class of the object
> class(myobject)
[1] "myclass" "numeric"
>
> # Define a method for the custom class
> print.myclass <- function(x, ...) {
+   cat("This is an object of class 'myclass':\n")
+   print(as.numeric(x))
+ }
>
> # Call the method on the object
> print(myobject)
This is an object of class 'myclass':
[1] 5
>

```

```

>

```

11) Demonstrate the creation of S4 class in R.

Program:

```

# Define a custom S4 class

setClass("Person",

  representation(

    name = "character",

    age = "numeric"

  )

)

# Create an object of the custom class

person <- new("Person", name = "Alice", age = 25)

```

```
# Print the object
```

```
person
```

```
# Define a method for the custom class
```

```
setMethod("print", "Person",
```

```
  function(x) {
```

```
    cat("Name: ", x@name, "\n")
```

```
    cat("Age: ", x@age, "\n")
```

```
  }
```

```
)
```

```
# Call the method on the object
```

```
print(person)
```

output

```
> # Define a custom S4 class
```

```
> setClass("Person",
```

```
+   representation(
```

```
+     name = "character",
```

```
+     age = "numeric"
```

```
+   )
```

```
+ )
```

```
>
```

```
> # Create an object of the custom class
```

```
> person <- new("Person", name = "Alice", age = 25)
```

```
>
```

```
> # Print the object
```

```
> person
```

```
An object of class "Person"
```

```
Slot "name":
```

```
[1] "Alice"
```

```
Slot "age":
```

```
[1] 25
```

```

>
> # Define a method for the custom class
> setMethod("print", "Person",
+   function(x) {
+     cat("Name: ", x@name, "\n")
+     cat("Age: ", x@age, "\n")
+   }
+ )
>
> # Call the method on the object
> print(person)
Name: Alice
Age: 25
>

```

```

>

```

12) Demonstrate the creation of Reference class in R by defining a class called students with fields – Name, Age , GPA. Also illustrate how the fields of the object can be accessed using the \$ operator. Modify the Name field by reassigning the name to Paul.

Program:

```

# Define a Reference Class called "students"

students <- setRefClass("students",

  fields = list(

    Name = "character",

    Age = "numeric",

    GPA = "numeric"

  )

)

# Create an object of the Reference Class

s <- students(Name = "John", Age = 20, GPA = 3.5)

```



```
# Access fields using the $ operator
```

```
s$Name # "John"
```

```
s$Age # 20
```

```
s$GPA # 3.5
```

```
# Modify the Name field
```

```
s$Name <- "Paul"
```

```
s$Name # "Paul"
```

output:

```
> # Define a Reference Class called "students"
> students <- setRefClass("students",
+       fields = list(
+           Name = "character",
+           Age = "numeric",
+           GPA = "numeric"
+       )
+ )
>
> # Create an object of the Reference Class
> s <- students(Name = "John", Age = 20, GPA = 3.5)
>
> # Access fields using the $ operator
> s$Name # "John"
[1] "John"
> s$Age # 20
[1] 20
> s$GPA # 3.5
[1] 3.5
>
> # Modify the Name field
> s$Name <- "Paul"
> s$Name # "Paul"
[1] "Paul"
>
>
```