PERMEABLE INFRASTRUCTURE FOR PEDESTRIAN ROUTES

AP-Series Cut Sheet

WHAT IT IS

Flexus™ AP-Series is an architectural porous pavement system engineered for pedestrian environments where permeability, refined natural aesthetics, and continuous underfoot performance are required. Constructed as a 50:50 (by volume) specialty aggregate and recycled tire rubber matrix, bonded with a single-component moisture-cure polyurethane binder, the AP-Series delivers a firm, textured walking surface with architectural finish quality and integrated drainage capacity. Available in 1.5 in, 2.0 in, and 2.5 in installed lifts.

SYSTEM SUMMARY

Installed thickness: 1.5 in, 2.0 in, 2.5 in

Surface Finish: Textured, matte, stone-forward

Aggregate to rubber: 50:50 (by volume)

Binder System: Single-component moisture-cure polyurethane

Binder Content: Minimum 11 percent (by weight)

Installation Type: Poured-in-place, continuous

INTENDED USE

Pedestrian walking paths and trails

Park circulation routes

Public pedestrian spaces

LIMITATIONS

Pedestrian use only

Not designed for vehicular, emergency, or maintenance equipment

Final performance dependent on site conditions, substrate preparation, and construction

COLOR AND FINISH

Flexus™ AP-Series is available in natural specialty-aggregate palettes with a matte, low-gloss, stone-forward appearance intended to blend with landscape and natural settings. Representative palettes include Sand Dune, Coastal Granite, Charcoal Earth, and Natural Trail.

WHY AP-SERIES

Architectural finish quality with exposed natural aggregate

Integrated permeability within a continuous surface. An infiltration rate is not published; ASTM C1701 testing is in progress.

A bonded aggregate and recycled tire rubber matrix

Designed specifically for refined landscape environments

When properly installed over a compliant subbase, the surface may support ADA slope conditions, with a recommended maximum cross slope of 2 percent. Final compliance is the responsibility of the project designer.

DATA STATUS

In testing: ASTM C1701, E303, F1551 / D412, G154, C501, D2859. No results published.

Available on request: AP-Series leach report, EPA 1311 TCLP and 1312 SPLP, RCRA 8 metals, non-detect; reproduce in full only.

> All information contained herein is subject to change without notice. Installation conditions: 50°F (10°C) and rising, not more than 104°F (40°C); dry substrate; single-component moisture-cure binder. See the installation guide.

Flexus™
Permeable Infrastructure for Pedestrian Routes

(770) 742-6016 info@flexusco.com

© 2026 Flexus Materials Ltd Co

Atlanta, Georgia