Flexus™

AP-Series

Permeable Infrastructure for Pedestrian Routes

AP-Series Cut Sheet

Permeable Infrastructure for Pedestrian Routes



WHAT IT IS

Flexus™ AP-Series is an architectural porous pavement system engineered for pedestrian environments where permeability, refined natural aesthetics, and continuous underfoot performance are required. Constructed as a 50:50 (by volume) specialty aggregate and recycled tire rubber matrix, bonded with a moisture-cured polyurethane structural binder, the AP-Series delivers a firm, textured walking surface with architectural finish quality and integrated drainage capacity. Available in 1.5", 2.0", and 2.5" installed lifts.

SYSTEM SUMMARY

- Minimum Installed Thickness: 1.5", 2.0", 2.5"
- Surface Finish: Textured, matte, stone-forward
- Rock / Rubber Ratio: 50:50 (by volume)
- Binder System: Moisture-cured polyurethane
- Binder Content: Minimum 11% (by weight)
- Installation Type: Poured-in-place, continuous

INTENDED USE

- Pedestrian walking paths and trails
- Park circulation routes
- Public pedestrian spaces

LIMITATIONS

- Pedestrian use only
- Not designed for vehicular, emergency, or maintenance equipment
- Final performance dependent on site conditions, substrate preparation, and construction

COLOR & FINISH

- Flexus™ AP-Series is available in natural specialty-aggregate palettes with a matte, low-gloss, stone-forward appearance intended to blend with landscape and natural settings.

  Representative palettes include:
  - Sand Dune
  - Coastal Granite
  - Charcoal Earth
  - Natural Trail

WHY AP-Series

- Architectural finish quality with exposed natural aggregate
- Integrated permeability within a continuous surface
- Engineered aggregate-to-elastomer matrix for pedestrian resilience
- Designed specifically for refined landscape environments

All information contained herein is subject to change without notice.

© 2026 Flexus Materials Ltd Co. All rights reserved.