Module Fabrication Document

Layer Stack Legend



Material	Layer	Thickness	Dielectric	Type	Gerber
	F.Paste			Paste Mask	
	F.Silkscreen		Direct Printing	Legend	GBR
	F.Mask	0.02mm	Solder Resist	Solder Mask	GBR
Copper	**L1 (Sig, PWR)**	**0.07mm (2.00oz)**		**Signal**	**GBR**
Core		1.48mm	FR4_7628	Dielectric	
Copper	**L6 (Sig, PWR)**	**0.07mm (2.00oz)**		**Signal**	**GBR**
	B.Mask	0.02mm	Solder Resist	Solder Mask	GBR
	B.Silkscreen		Direct Printing	Legend	GBR
	B.Paste			Paste Mask	

Total thickness: 1.66mm
Note: external layer thicknesses are specified after plating

Top Fabrication (Scale 1:1)



Impedance Table

Transmission Line	Impedance [ohms]	Tolerance [ohms]	Layer	Trace Width [mm]	Gap [mm]	Ref. Layers
Edge-Coupled Coated Microstrip	100	±10 %	L1	0.2032	0.28	L2

FABRICATION NOTES (UNLESS OTHERWISE SPECIFIED)

1) FABRICATE PER IPC-6012A CLASS 2.

2) OUTLINE DEFINED IN SEPARATE GERBER FILE WITH "Edge_Cuts.GBR" SUFFIX.

   DIMENSIONS OF CIRCUMSIZED RECTANGLE SHOWN ON THIS DRAWING FOR REFERENCE ONLY.

3) SEE SEPARATE DRILL FILES WITH ".DRL" SUFFIX FOR HOLE LOCATIONS.

   SELECTED HOLE LOCATIONS SHOWN ON THIS DRAWING FOR REFERENCE ONLY.

4) SURFACE FINISH: IMMERSION GOLD

5) SOLDERMASK ON BOTH SIDES OF THE BOARD SHALL BE LPI, COLOR BLACK.

6) SILK SCREEN LEGEND TO BE APPLIED PER LAYER STACKUP USING YELLOW NON-CONDUCTIVE EPOXY INK.

7) ALL VIAS ARE TENTED ON BOTH SIDES UNLESS SOLDERMASK OPENED IN GERBER.

8) VENDOR SHOULD FOLLOW ROHS COMPLIANT PROCESS AND Pb FREE FOR MANUFACTURING

9) PCB MATERIAL REQUIREMENTS:

   A. FLAMMABILITY RATING MUST MEET OR EXCEED UL94V-0 REQUIREMENTS.
   B. Tg 170 C OR EQUIVALENT.
   C. EQUIVALENT MATERIAL SHALL BE RoHS COMPLIANT, HALOGEN FREE AND APPROVED BY FR.

10) DESIGN GEOMETRY MINIMUM FEATURE SIZES:

BOARD SIZE	81.800 × 47.200 mm
BOARD THICKNESS	1.660 mm
TRACE WIDTH	1.000 mm
TRACE TO TRACE	0.200 mm
MIN. HOLE (PTH)	0.800 mm
MIN. HOLE (NPTH)	N/A mm
ANNULAR RING	0.320 mm
COPPER TO HOLE	0.254 mm
COPPER TO EDGE	0.250 mm
HOLE TO HOLE	0.254 mm

11) REFER TO IMPEDANCE TABLE FOR IMPEDANCE CONTROL REQUIREMENTS.

12) CONFIRM SPACE WIDTHS AND SPACINGS.

All dimensions are in millimeters unless otherwise specified.

Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
	Board Name: **Module**		Project Name: **Alixp Step up module 12 to 450 V**	
Sheet Title: Top Fabrication (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
Sheet Path:		Reviewer:	Size: **A4**	Sheet: **1** of **7**

Module Fabrication Document



Bottom Fabrication (Scale 1:1)

All dimensions are in millimeters unless otherwise specified.

	Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: **Module**		Project Name: **Alixp Step up module 12 to 450 V**	
	Sheet Title: Bottom Fabrication (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: **A4**	Sheet: **2** of **7**

Module Fabrication Document

Drill Table

Symbol	Count	Hole Size	Plated	Hole Shape	Drill Layer Pair	Hole Type
×	2	0.80mm (31.50mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Via
○	52	0.80mm (31.50mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
+	16	0.90mm (35.43mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
□	4	1.00mm (39.37mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
◇	6	1.20mm (47.24mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
⊠	4	1.30mm (51.18mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
✳	4	1.70mm (66.93mils)	PTH	Round	L1 (Sig, PWR) - L6 (Sig, PWR)	Pad
	Total 88					

Drill Drawing L1 - L2 (Scale 1:1)



	Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: **Module**		Project Name: **Alixp Step up module 12 to 450 V**	
	Sheet Title: Drill Drawing (L1 - L2)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: **A4**	Sheet: **3** of **7**

Module Fabrication Document

Top Test Points (Scale 1:1)

Ref.	Net	X [mm]	Y [mm]

Ref.	Net	X [mm]	Y [mm]



All dimensions are in millimeters unless otherwise specified.

	Comments:	Company: FR	Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: **Module**	Project Name: **Alixp Step up module 12 to 450 V**	
	Sheet Title: Top Test Points (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13 / Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: **A4** / Sheet: **4** of **7**

Module Fabrication Document

Bottom Test Points (Scale 1:1)

Ref.	Net	X [mm]	Y [mm]



All dimensions are in millimeters unless otherwise specified.

	Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: **Module**		Project Name: **Alixp Step up module 12 to 450 V**	
	Sheet Title: Bottom Test Points (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: **A4**	Sheet: **5** of **7**

Module Fabrication Document

L1 (Sig, PWR) (Scale 1:1)



	Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: **Module**		Project Name: **Alixp Step up module 12 to 450 V**	
	Sheet Title: L1 (Sig, PWR) (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: **A4**	Sheet: **6** of **7**

Module Fabrication Document

L6 (Sig, PWR) (Scale 1:1)



	Comments:	Company: FR		Variant: PRELIMINARY	Git Hash: 12f9779
		Board Name: Module		Project Name: Alixp Step up module 12 to 450 V	
	Sheet Title: L6 (Sig, PWR) (Scale 1:1)	File Name: StepUp_module_12to450V.kicad_pcb	Designer: FR	Date: 2024-04-13	Revision: + (Unreleased)
	Sheet Path:		Reviewer:	Size: A4	Sheet: 7 of 7