

Desk controller


Table of contents

- 1 Root_sch
- 2 System_overview
- 3 Interface_Power_supply
- 4 Interface_servomotor
- 5 Interface_Limit_switches
- 6 Block_diagram
- 7 DCDC_converter_3V3
- 8 Microcontroller
- 9 Servomotor_interface
- 10 Limit_switch_interface
- 11 Touch_TFT
- 12

Change history

1.0.0	07/10/2026	First release
1.0.0	08/10/2026	Fix R1234 value due to issue xyz etc etc etc. Update C14 to 10 nF to reduce roll-off frequency.
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD
1.0.0	TBD	TBD

System overview



File: System_overview.kicad_sch



Desk controller


Notes

This is a comment 1 field - potentially not used
This is a comment 2 field - potentially not used
This is a comment 3 field - potentially not used
This is a comment 4 field - potentially not used

Sheet: Root
File: ktest.kicad_sch

Rev: 0.0.1	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date: 2026-10-06	RLs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 1/11

System overview



This sheet shows the overall system and the interfaces to external components. External components are shown for system context only and are not part of this schematic. Only the "DESIGNED SUBSYSTEM" is covered by this schematic.

[Return to front sheet](#)



Desk controller

Notes

Sheet: System overview	
File: System_overview.kicad_sch	
Rev:	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date:	RLs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 2/11

DC power supply

Interface specification

Barrel connector (Dell type, with ID pin)

Pin

- 1 Supply - 19.5 V, 3 A (inner shell)
- 2 ID (internal pin)
- 3 GND (outer shell)
- SH Shield

Return to front sheet



Desk controller

Notes

Sheet: DC power supply	
File: Interface_Power_supply.kicad_sch	
Rev:	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date:	RLs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 3/11

Servomotor

Interface specification

JST B6B-XH-A / JST XHP-6 connector

Pin	Description
1	Encoder B output (VCC)
2	Encoder A output (VCC)
3	GND
4	VCC (3.3 - 5V)
5	Motor B (3 A, 12-24 V)
6	Motor A (3 A, 12-24 V)

Return to front sheet



Desk controller

Notes

Sheet: Servomotor	
File: Interface_servomotor.kicad_sch	
Rev:	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date:	RLs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 4/11

Interface specification

JST B4B XH A / JST XHP-4 connector


- Pin Description
- 1 Bottom limit switch (Normally open, switch closes to GND)
 - 2 GND
 - 3 GND
 - 4 Top limit switch (Normally open, switch closes to GND)

Return to front sheet



Desk controller	Sheet: Limit switches	
	File: Interface_Limit_switches.kicad_sch	
	Rev:	Drwn: FLR
	Mat: Concept	Rev'd: FLR
	Date:	RLs'd: FLR
Notes	Dwg: NA	Size: A4
	Generated with KiCad	Page: 5/11

Block diagram






Return to front sheet



Desk controller		Sheet: Block diagram	
Notes		File: Block_diagram.kicad_sch	
		Rev:	Drwn: FLR
		Mat: Concept	Rev'd: FLR
		Date:	RLs'd: FLR
		Dwg: NA	Size: A4
		Generated with KiCad	Page: 6/11

DCDC converter 3V3

Block interface



J8 is fitted to a small "standalone" PCB which will then be soldered into the "main" PCB. This standalone PCB + connector are what make the "DC barrel assy" used in position.

Return to front sheet





Desk controller

Notes


Sheet: DCDC converter 3V3	
File: DCDC_converter_3V3.kicad_sch	
Rev:	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date:	Rs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 7/11

Block interface




Microcontroller

USB interface (serial comms port)



SWD header



Return to front sheet



Desk controller

Notes

Sheet: Microcontroller

File: Microcontroller.kicad_sch

Rev:

Mat: Concept

Date:

Dwg: NA

Generated with KiCad

Drwn: FLR

Rev'd: FLR



RLs'd: FLR

Size: A4

Page: 8/11

Servomotor interface

Block interface



Return to front sheet



Desk controller

Notes

Sheet: Servomotor interface

File: Servomotor_interface.kicad_sch

Rev:

Mat: Concept

Date:

Dwg: NA

Generated with KiCad

Drwn: FLR

Rev'd: FLR



RLs'd: FLR

Size: A4

Page: 9/11

Limit switch interface

Block interface



Return to front sheet





Desk controller

Notes

Sheet: Limit switch interface	
File: Limit_switch_interface.kicad_sch	
Rev:	Drwn: FLR
Mat: Concept	Rev'd: FLR
Date:	RLs'd: FLR
Dwg: NA	Size: A4
Generated with KiCad	Page: 10/11

Touch TFT

Block interface



TFT1
TFT_2.4in_320x240



The display will not be directly soldered to the PCB. Instead, generic 2.54 mm pitch sockets J2 and J3 will be used as connectors.

Return to front sheet



Desk controller

Notes

Sheet: Touch TFT

File: Touch_TFT.kicad_sch

Rev:

Mat: Concept

Date:

Dwg: NA

Generated with KiCad

Drwn: FLR

Rev'd: FLR

RLs'd: FLR

Size: A4

Page: 11/11