Booleans

https://csci-1301.github.io/about#authors

February 20, 2023 (05:13:40 PM)

Contents

1	Trut	th Tables			
2	Precedence and Order of Evaluation				
	2.1	Reading and Understanding			
	2.2	Computing Simple Boolean Expressions			
	2.3	Computing Expressions Involving Booleans and Numerical Values			

This lab serves multiple goals:

- To help you manipulate boolean values,
- To practice boolean operators,
- To understand the concept of precedence,
- To practice simple mental calculations.

1 Truth Tables

1. Copy and paste the following code into the Main method of a new project:

- 2. Compile and execute it. This should display to the screen the truth tables¹ for conjunction (and, &&) and negation (not, !).
- 3. Make sure you understand both the code and its output.
- 4. After the truth table for the negation, write code to display the truth tables for three binary operators:

¹https://en.wikipedia.org/wiki/Truth_table

- a) the disjunction (or, $|\cdot|$),
- b) the identity (equality, ==), and
- c) the difference (inequality, !=).

Normally, copying the truth table for the conjunction and using the find-and-replace feature of your IDE should make this a quick and easy task.

5. You can make sure you completed this exercise correctly by checking that your output matches the truth tables on Wikipedia for disjunction² and equality³. To check the inequality truth table, compare your output against the table for exclusive disjunction⁴. Exclusive disjunction (XOR) is conceptually different than inequality but has the same truth table.

2 Precedence and Order of Evaluation

2.1 Reading and Understanding

If you read the documentation on operator precedence⁵, you will see that operators are evaluated in a particular order. This order is also given in our notes⁶.

For instance, ! true | | false && 3 * 2 == 6 will be evaluated as

Operation	Result	Op.	
! true false && 3 * 2 == 6	\Rightarrow	false false && 3 * 2 == 6	!
false false && 3 * 2 == 6	\Rightarrow	false false && 6 == 6	*
false false && 6 == 6	\Rightarrow	false false && true	==
false false && true	\Rightarrow	false false	&&
false false	\Rightarrow	false	11

Note that an expression like !3 > 2 does not make any sense: C# would try to take the negation of 3 (since ! has higher precedence than >), but you cannot negate the truth value of an integer! Along the same lines, an expression like false * true does not make sense; you can not multiply booleans (what would be "true times false"?)! Similarly, 3 % false will cause an error; can you see why? These are all examples of "illegal" expressions.

2.2 Computing Simple Boolean Expressions

Evaluate the following expressions. Try to do this "by hand," and write your answers down on paper.

```
true && false || true
!true && false
false || true && !false
false == !true || false
!(true || false || true && true)
```

- !(true || false) && (true && !false)
- !true || false && (true && !false)
- true != !(false || true)

 $^{^2} https://en.wikipedia.org/wiki/Truth_table\#Logical_disjunction_(OR)$

 $^{^3} https://en.wikipedia.org/wiki/Truth_table\#Logical_equality$

⁴https://en.wikipedia.org/wiki/Truth_table#Exclusive_disjunction

 $^{^5} https://docs.microsoft.com/en-us/dotnet/csharp/language-reference/operators/\#operator-precedence$

 $^{^6} labs/Booleans/../../book.html\#precedence-of-operators-1$

2.3 Computing Expressions Involving Booleans and Numerical Values

For each of the following expressions, decide if it is "legal" or not. If it is, give the result of its evaluation.

- 3 > 2
- 2 == 4
- 3 >= 2 != false
- 3 > false
- true && 3 + 5 * 8 == 43
- 3 + true != false