

Polypropylene Case Process Pressure Gauge (PP)

The Polypropylene Case (PP) process pressure gauge is offered with a welded bourdon tube and socket design to ensure safety and a longer life than other comparable gauges. Meeting EN 837-1 standard, the PP process gauge has been engineered to meet market requirements of extremely corrosive-resistance while ensuring personnel safety and long product life.

The material used to make the gauges is suitable for chemically aggressive environments. The tried and tested bourdon tube system can be offered in special material such as monel, and is reliable under adverse operating conditions.

It has solid front design features, a burst-proof baffle wall interposed between the bourdon tube and window, to ensure that the bourdon tube which is subjected to high process pressures is isolated from the viewing area of the gauge. Coupled with a laminated safety glass and blowout back, these gauges are specially designed to protect the operating personnel from any adverse effects of extreme pressure impluses.



Available in

Nominal sizes	115 mm
Ranges	-760 mmHg to 0 and 0 to 0.6 upto 700 kg/sq.cm

Special Features

- Compliance to latest EN837-1
- Polypropylene case with SS 316L measuring system
- Overpressure limit 125 % of FSD
- Ingress protection to IP65
- Dry or liquid filled version
- CE marking as per PED 97/23/EC
- Solid front design

Industrial Applications

- Chemical and Fertiliser
- Pharmaceutical
- Food processing
- Water treatment plants
- Aluminium and Steel
- Refineries
- Petrochemical

Standard Product Specifications	
Standards	Description
Reference standard	EN 837 - 1
Mounting	Direct bottom / surface bottom
Connection	½" NPT (M)
Case & Bezel	Polypropylene
Bourdon	SS 316L
Socket	SS 316L
Movement	SS 304
Dial	Aluminum, white background with black marking
Pointer	Aluminum, black color micrometer with zero adjustable
Accuracy	±1% of FS (standard)
Overpressure limit	As per EN standard
	From 0 to 100 Kg/Sq.cm, 125% of maximum scale value
	From 100 to 600 Kg/Sq.cm, 115% of maximum scale value
	From 600 Kg/Sq.cm to 1600 Kg/Sq.cm 110% of maximum scale value
Window	Safety laminated shatterproof glass
Protection	IP65
Blow off disc	Reinforced polypropylene (for dry gauge)
	SS 304 (For fillable gauge)
Gasket and Filling Plug	Neoprene
Ambient temperature	-25°C to 65°C
Process temperature	Max. 150°C (for dry gauge)
	Max. 65°C (for glycerin filled gauges)
Technical specifications, MOC are subject to change without prior notice	

Direct Bottom Mounting

→ Parameters

	A	B	C	D	E	F
Dial Size ↓	115	Ø128	141.5	68	13	Ø140 Ø8

Pressure Ranges

Standard Pressure Range										
Code	Kg/Sq.cm (Code A)	Bar (Code B)	Code	KPA (Code C)	Code	Dual Scale kg/Sq.cm & Psi (Code D)	Dual Scale Kg/Sq.cm & Bar (Code E)	Code	Dual Scale kg/Sq.cm & Psi (Code D)	Dual Scale Kg/Sq.cm & Bar (Code E)
AA	-1 + 0	-1 + 0	AR	-100 + 0	BI	-1 + 0/-15 + 0	-1 + 0/-15 + 0	CI	0 + 210/0 + 3000	0 + 210/0 + 3000
AB	0 + 0.6	0 + 0.6	AL	0 + 60	BK	0 + 1/0 + 15	0 + 1/0 + 15	CJ	0 + 280/0 + 4000	0 + 280/0 + 4000
AC	0 + 1	0 + 1	AM	0 + 100	BL	0 + 1.6/0 + 23	0 + 1.6/0 + 23	CK	0 + 420/0 + 6000	0 + 420/0 + 6000
AD	0 + 1.6	0 + 1.6	AN	0 + 160	BZ	0 + 2.1/0 + 30	0 + 2.1/0 + 30	CL	0 + 700/0 + 10000	0 + 700/0 + 10000
AE	0 + 2.5	0 + 2.5	AO	0 + 250	CA	0 + 4.2/0 + 60	0 + 4.2/0 + 60			
AF	0 + 4	0 + 4	AP	0 + 400	BO	0 + 6.0/0 + 86	0 + 6.0/0 + 86			
AG	0 + 6	0 + 6	AQ	0 + 600	CB	0 + 7.0/0 + 100	0 + 7.0/0 + 100			
AH	0 + 10	0 + 10	AY	0 + 1000	BP	0 + 10/0 + 150	0 + 10/0 + 143			
AI	0 + 16	0 + 16	AZ	0 + 1600	CC	0 + 14.0/0 + 200	0 + 14.0/0 + 200			
AJ	0 + 25	0 + 25	BA	0 + 2500	BQ	0 + 16.0/0 + 230	0 + 16.0/0 + 230			
AK	0 + 40	0 + 40	BB	0 + 4000	CD	0 + 21.0/0 + 300	0 + 21.0/0 + 300			
AL	0 + 60	0 + 60	BC	0 + 6000	CE	0 + 28.0/0 + 400	0 + 28.0/0 + 400			
AM	0 + 100	0 + 100	BD	0 + 10000	CF	0 + 42.0/0 + 600	0 + 42.0/0 + 600			
AN	0 + 160	0 + 160	BE	0 + 16000	CG	0 + 70.0/0 + 1000	0 + 70.0/0 + 1000			
AO	0 + 250	0 + 250	BF	0 + 25000	BU	0 + 100/0 + 1500	0 + 100/0 + 1500			
AP	0 + 400	0 + 400	BG	0 + 40000	CH	0 + 140/0 + 2000	0 + 140/0 + 2000			
AQ	0 + 600	0 + 600	BH	0 + 60000	BV	0 + 160/0 + 2300	0 + 160/0 + 2300			

Compound Pressure Range											
Code	mmHg / Kg/Sq.cm (Code F)	mmHg/Bar (Code G)	Code	Kg/Sq.cm (Code A)	Bar (Code B)	Code	Dual Scale in Hg+Psi / mmHg+Kg/ Sq.cm (Code H)	Dual Scale in Hg + Psi / mmHg+ Bar (Code I)	Code	Dual Scale inHg+Psi/ Kg/Sq.cm (Code J)	Dual Scale inHg + Psi/Bar (Code K)
CM	-760 + 1.5	-760 + 1.5	CU	-1 + 1.5	-1 + 1.5	DC	-30 + 20/-760 + 1.5	-30 + 20/-760 + 1.5	FA	-30 + 20/-1 + 1.5	-30 + 20/-1 + 1.5
CN	-760 + 3.0	-760 + 3.0	CV	-1 + 3.0	-1 + 3.0	DD	-30 + 42/-760 + 3.0	-30 + 42/-760 + 3.0	FB	-30 + 42/-1 + 3.0	-30 + 42/-1 + 3.0
CO	-760 + 5.0	-760 + 5.0	CW	-1 + 5.0	-1 + 5.0	DE	-30 + 70/-760 + 5.0	-30 + 70/-760 + 5.0	FC	-30 + 70/-1+ 5.0	-30 + 70/-1+ 5.0
CP	-760 + 6.0	-760 + 6.0	CX	-1 + 6.0	-1 + 6.0	DF	-30 + 85/-760 + 6.0	-30 + 85/-760 + 6.0	FD	-30 + 85/-1 + 6.0	-30 + 85/-1 + 6.0
CQ	-760 + 7.0	-760 + 7.0	CY	-1 + 7.0	-1 + 7.0	DG	-30 + 100/- 760 + 7.0	-30 + 100/- 760 + 7.0	FE	-30 + 100/-1 + 7.0	-30 + 100/-1 + 7.0
CR	-760 + 9.0	-760 + 9.0	CZ	-1 + 9.0	-1 + 9.0	DH	-30 + 125/- 760 + 9.0	-30 + 125/- 760 + 9.0	FF	-30 + 125/-1 + 9.0	-30 + 125/-1 + 9.0
CS	-760 + 15.0	-760 + 15.0	DA	-1 + 15.0	-1 + 15.0	DI	-30 + 210/- 760 + 15.0	-30 + 210/- 760 + 15.0	FG	-30 + 210/-1 + 15.0	-30 + 210/-1 + 15.0
CT	-760 + 24.0	-760 + 24.0	DB	-1 + 24.0	-1 + 24.0	DJ	-30 + 340/- 760 + 24.0	-30 + 340/- 760 + 24.0	FH	-30 + 340/-1 + 24.0	-30 + 340/-1 + 24.0

Ordering Information

Configuration Generation Code

Model	PP	**	*	*	*	*	**	*
Dial Size								
115 mm	J							
Mountings								
Direct bottom	1							
Connection Size								
1/4"	A							
3/8"	B							
1/2"	C							
M20X1.5P	1							
Connection Type								
NPT (M)	A							
BSP (M)	B							
BSPT (M)	C							
Metric thread (M)	M							
Range								
Refer to Std. Pressure Range Table								
Engineering Unit*								
Kg/sq.cm	A							
Bar	B							
Kpa	C							
Dual scale Kg/sq.cm-Psi	D							
Dual scale Bar-Psi	E							

Case and Bezel
Polypropylene (standard)

Bourdon and Socket
SS316L (standard)
Monel

Movement
SS304 (standard)
SS316
Jelly cap movement

Pointer
Micrometer pointer (standard)
Knife Edge Pointer

Window
Toughened glass (standard)
Safety laminated Shatterproof glass

Tests and Certificates
Five point calibration certificate (standard)
Oxygen service (for dry version)
NABL traceability certificates
CE marking (As Per PED (97/23/EC))
Material test certificates for wetted parts
Helium leak test
NACE conformity for wetted parts
Dye penetration testing
Special requirement – please specify

Optional Features
Accuracy 0.5% of FS
Over range protection of 150% of FS
Integral dampening screw
Internal over pressure stop
Internal vacuum stop
Tag marking on dial
SS tag plate
Case filling – glycerin upto 65°C
Custom designed dial
Special requirement – please specify
Case filling – silicon oil -40°C to 200°C

Ordering example : PPJ1CAAHB-0000 (Standard)



Forbes Marshall
Krohne Marshall
Forbes Marshall Arca
Codel International
Forbes Solar
Forbes Vyncke
Forbes Marshall Steam Systems

Plot No. A-19/2 & T-4/2, I.D.A
Nacharam, Hyderabad - 500 076
Tel : +91-40-27179223, 27171909,
27170732
Fax : +91-40-27173235

Email : sales-gauges@forbesmarshall.com, ccmidc@forbesmarshall.com

All contents herein are the property of Forbes Marshall Private Limited ("FMPL") or Forbes Marshall Steam Systems Private Limited ("FMSSPL"), as the case may be, and having protection under the intellectual property rights. Any reproduction, distribution or disclosure without prior written permission is prohibited. Information in this document is subject to change without notice.

B-85, Phase II, Chakan Indl Area
Sawardari, Chakan, Tal. Khed
Dist. Pune - 410 501. INDIA
Tel : 91(0)2135-393400

A-34/35, MIDC H Block
Pimpri, Pune - 411 018. INDIA.
Tel : 91(0)20-27442020, 39851199
Fax : 91(0)20-27442040

CIN No.: U28996PN1985PTC037806
www.forbesmarshall.com