Minimal rational interpolation for

time-harmonic Maxwell's equations

June 24, 2022 Fabio Matti

Primer

To locally approximate

$$u:\mathbb{C}\ni\omega\mapsto u(\omega)$$

Primer

To locally approximate

$$\mathbf{u}: \mathbb{C} \ni \boldsymbol{\omega} \mapsto \mathbf{u}(\boldsymbol{\omega})$$

compute

$$\mathbf{u}(\omega_1), \mathbf{u}(\omega_2), \dots, \mathbf{u}(\omega_S)$$

(Snapshots)

Primer 1

To locally approximate

$$\mathbf{u}: \mathbb{C} \ni \boldsymbol{\omega} \mapsto \mathbf{u}(\boldsymbol{\omega})$$

compute

$$\mathbf{u}(\omega_1), \mathbf{u}(\omega_2), \dots, \mathbf{u}(\omega_S)$$
 (Snapshots)

and build

$$\tilde{\mathbf{u}}(\omega) = \frac{\mathbf{P}(\omega)}{q(\omega)}$$
 (Rational surrogate)

such that

$$\tilde{\mathbf{u}}(\omega) \approx \mathbf{u}(\omega)$$

close to $\omega_1, \omega_2, \ldots, \omega_S$.

► Problem formulation

- ► Problem formulation
- ► Finite element method

- ► Problem formulation
- ► Finite element method
- ► Minimal rational interpolation

- ► Problem formulation
- ► Finite element method
- ► Minimal rational interpolation
- ► Example applications

- ▶ Problem formulation
- ► Finite element method
- ► Minimal rational interpolation
- ► Example applications
- ► Conclusion and outlook

Time-harmonic vector potential $\mathbf{u}(\mathbf{x},t) = \mathbf{u}(\mathbf{x}) \exp(i\omega t)$.

$$\mathbf{B} = \nabla \times \mathbf{u}$$

$$\boldsymbol{E} = -i\boldsymbol{\omega}\boldsymbol{u}$$

(Electric field)

Time-harmonic vector potential $\mathbf{u}(\mathbf{x},t) = \mathbf{u}(\mathbf{x}) \exp(i\omega t)$.

$$\mathbf{B} = \nabla \times \mathbf{u}$$
 (Magnetic field)
 $\mathbf{E} = -\mathrm{i}\omega\mathbf{u}$ (Electric field)

Maxwell's equation

$$\nabla \times (\mu^{-1}B) - \vartheta_t(\varepsilon E) = j$$

Time-harmonic vector potential $\mathbf{u}(\mathbf{x}, t) = \mathbf{u}(\mathbf{x}) \exp(i\omega t)$.

$$\mathbf{B} = \nabla \times \mathbf{u}$$
 (Magnetic field)
 $\mathbf{E} = -\mathrm{i}\omega\mathbf{u}$ (Electric field)

Maxwell's equation

$$\nabla \times (\mu^{-1}\mathbf{B}) - \partial_{\mathsf{t}}(\epsilon \mathbf{E}) = \mathbf{j}$$

Time-harmonic potential equation

$$\nabla \times (\mu^{-1}\nabla \times \mathbf{u}) - \varepsilon \omega^2 \mathbf{u} = \mathbf{j}$$
 (1)

$$H_{curl}(\Omega)=\{\boldsymbol{v}:\Omega\to\mathbb{C}^3,\text{ such that }\boldsymbol{v}\in L_2(\mathbb{C})^3,\ \nabla\times\boldsymbol{v}\in L_2(\mathbb{C})^3\}$$

$$\mathsf{H}_{\text{curl}}(\Omega) = \{ v : \Omega \to \mathbb{C}^3, \text{ such that } v \in \mathsf{L}_2(\mathbb{C})^3, \ \nabla \times v \in \mathsf{L}_2(\mathbb{C})^3 \}$$

Weak formulation of the time-harmonic potential equation

Find $\mathbf{u} \in \mathsf{H}_{\mathrm{curl}}(\Omega)$, such that

$$\int_{\Omega} \langle \mu^{-1} \nabla \times \mathbf{u}, \nabla \times \mathbf{v} \rangle - \omega^{2} \int_{\Omega} \varepsilon \langle \mathbf{u}, \mathbf{v} \rangle = \int_{\Omega} \langle \mathbf{j}, \mathbf{v} \rangle + \int_{\partial \Omega} \langle \mathbf{g}, \mathbf{v} \rangle$$
 (2)

for all $\mathbf{v} \in \mathsf{H}_{\text{curl}}$, where $\mathbf{g} = (\mu^{-1} \nabla \times \mathbf{u}) \times \mathbf{n}$.

Perfectly conducting boundary

$$\mathbf{u} \times \mathbf{n} = \mathbf{0}$$
, on Γ_D

Perfectly conducting boundary

$$\mathbf{u} \times \mathbf{n} = \mathbf{0}$$
, on Γ_{D}

Inlet, i.e. **B** is given along Γ_N

$$\mathbf{g} = (\mu^{-1}\mathbf{B}) \times \mathbf{n}$$
, on Γ_N

Perfectly conducting boundary

$$\mathbf{u} \times \mathbf{n} = \mathbf{0}$$
, on Γ_{D}

Inlet, i.e. **B** is given along Γ_N

$$\mathbf{g} = (\mu^{-1}\mathbf{B}) \times \mathbf{n}$$
, on Γ_{N}

Imperfectly conducting boundary

$$\mathbf{g} = i\omega\lambda(\mathbf{n} \times \mathbf{u}) \times \mathbf{n}$$
, on Γ_{I}

TODO

Rational surrogate

$$\tilde{\mathbf{u}}(\omega) = \sum_{i=1}^{S} \frac{\mathbf{p}_{i}}{\omega - \omega_{i}} / \sum_{i=1}^{S} \frac{\mathbf{q}_{i}}{\omega - \omega_{i}}$$

in barycentric coordinates with support points $\omega_1, \omega_2, \dots, \omega_3$.

Rational surrogate

$$\tilde{\mathbf{u}}(\omega) = \sum_{i=1}^{S} \frac{\mathbf{p}_{i}}{\omega - \omega_{i}} / \sum_{i=1}^{S} \frac{q_{i}}{\omega - \omega_{i}}$$

in barycentric coordinates with support points $\omega_1, \omega_2, \ldots, \omega_3$. Interpolation property

$$\tilde{\mathbf{u}}(\omega_i) = \mathbf{u}(\omega_i), \ \forall i \in \{1, 2, \dots, S\}$$

1. Compute the Gramian matrix \underline{G} with $g_{ij} = \langle \mathbf{u}(\omega_i), \mathbf{u}(\omega_j) \rangle$, $i, j \in \{1, 2, \dots, S\}$

- 1. Compute the Gramian matrix \underline{G} with $g_{ij} = \langle \mathbf{u}(\omega_i), \mathbf{u}(\omega_j) \rangle$, $i, j \in \{1, 2, ..., S\}$
- 2. Compute the singular value decomposition $G = \underline{V} \underline{\Sigma} \underline{V}^H$

- 1. Compute the Gramian matrix \underline{G} with $g_{ij} = \langle \mathbf{u}(\omega_i), \mathbf{u}(\omega_j) \rangle$, $i, j \in \{1, 2, ..., S\}$
- 2. Compute the singular value decomposition $G = V \Sigma V^{H}$
- 3. Define $\mathbf{q} = (q_1, q_2, \dots, q_S)^T = \underline{\mathbf{V}}[:, S]$

- 1. Compute the Gramian matrix $\underline{\mathbf{G}}$ with $g_{ij} = \langle \mathbf{u}(\omega_i), \mathbf{u}(\omega_j) \rangle$, $i, j \in \{1, 2, \dots, S\}$
- 2. Compute the singular value decomposition $G = V \Sigma V^H$
- 3. Define $\mathbf{q} = (q_1, q_2, \dots, q_S)^T = \underline{\mathbf{V}}[:, S]$
- 4. Define $\tilde{\mathbf{u}}(\omega) = \mathbf{P}(\omega)/Q(\omega)$ with $\mathbf{P}(\omega) = \sum_{j=1}^{S} \frac{q_j \mathbf{u}(\omega_j)}{\omega \omega_j}$ and $Q(\omega) = \sum_{j=1}^{S} \frac{q_j}{\omega \omega_j}$

1. Define $\Omega_{test} = \{\omega_1, \omega_2, \dots, \omega_M\}$ as candidate support points

- 1. Define $\Omega_{test} = \{\omega_1, \omega_2, \dots, \omega_M\}$ as candidate support points
- 2. Build surrogate $\tilde{\mathbf{u}}_t$ with initial support points $\omega_1, \omega_2, \cdot, \omega_t \in \Omega_{test}$

- 1. Define $\Omega_{test} = \{\omega_1, \omega_2, \dots, \omega_M\}$ as candidate support points
- 2. Build surrogate $\tilde{\mathbf{u}}_t$ with initial support points $\omega_1, \omega_2, \cdot, \omega_t \in \Omega_{test}$
- 3. Iteratively add a new support point $\omega_{t+1} = \text{argmin}_{\omega \in \Omega_{test}} |Q_t(\omega)| \text{ to build } \tilde{\mathbf{u}}_{t+1} \text{ based on } \mathbf{u}(\omega_1), \mathbf{u}(\omega_2), \dots, \mathbf{u}(\omega_{t+1})$

- 1. Define $\Omega_{test} = \{\omega_1, \omega_2, \dots, \omega_M\}$ as candidate support points
- 2. Build surrogate $\tilde{\mathbf{u}}_t$ with initial support points $\omega_1, \omega_2, \cdot, \omega_t \in \Omega_{test}$
- 3. Iteratively add a new support point $\omega_{t+1} = \operatorname{argmin}_{\omega \in \Omega_{test}} |Q_t(\omega)|$ to build $\tilde{\mathbf{u}}_{t+1}$ based on $\mathbf{u}(\omega_1), \mathbf{u}(\omega_2), \dots, \mathbf{u}(\omega_{t+1})$
- 4. Stop when relative error $\|u_{t+1} \tilde{u}_{t+1}\|/\|u_{t+1}\|$ is small enough

Householder, sequential

Norms

We want to find ω , such that


$$0 = Q(\omega) = \sum_{i=1}^{S} \frac{q_i}{\omega - \omega_i}$$


Equivalently eigenvalue problem


$$\mathbf{A}\mathbf{w} = \omega \mathbf{B}\mathbf{w}$$


with

$$\underline{\mathbf{A}} = \begin{pmatrix} 0 & q_1 & q_2 & \dots & q_S \\ 1 & \omega_1 & & & & \\ 1 & & \omega_2 & & & \\ \vdots & & & \ddots & & \\ 1 & & & & \omega_S \end{pmatrix} \text{ and } \underline{\mathbf{B}} = \begin{pmatrix} 0 & & & & \\ & 1 & & & & \\ & & 1 & & & \\ \vdots & & & \ddots & & \\ & & & & 1 \end{pmatrix}$$











Dual-mode circular waveguide filter







- xyxy

Conclusion and outlook

- **▶** xy
- **▶** xy
- ► DMCWF exact dimensions and reference