BGCE First Milestone Meeting

BGCE Project: CAD – Integrated Topology Optimization

S. Joshi, J.C. Medina, F. Menhorn, S. Reiz, *B. Rüth, E. Wannerberg*, A. Yurova

Technische Universität München August 5, 2015





ШП

Contents

- 1. Workflow Overview
- 2. Schedule & Deadlines
- 3. CAD to Optimized Surface
 - 3.1 CAD To STL
 - 3.2 STL To Voxels
 - 3.3 Boundary conditions
 - 3.4 Topology Optimization
 - 3.5 Surface Extraction
- 4. Optimized Surface to CAD
 - 4.1 B-Spline Fitting
- 5. Summary
- 6. Outlook





CAD design






STL Interface






Voxelization








TPD input file - Specification of loads and fixtures








Topology optimization








Optimized output geometry







Post-processing: Parametrization, Feature recognition








Schedule & Deadlines

Original schedule:








Schedule & Deadlines

Current state:







CAD to STL

- Create original CAD geometry in CAD program
- Most CAD programs offer: Export to STL...

Picture







From STL To Voxels

- Common Versatile Multi-purpose Library for C++ (CVMLCPP)
 - Takes .stl file and returns a binary file with the given voxel size
- Custom script to read binary file and output it as ascii.vtk










From STL To Voxels

- Common Versatile Multi-purpose Library for C++ (CVMLCPP)
 - Takes .stl file and returns a binary file with the given voxel size
- Custom script to read binary file and output it as ascii.vtk








From STL To Voxels

- Common Versatile Multi-purpose Library for C++ (CVMLCPP)
 - Takes .stl file and returns a binary file with the given voxel size
- Custom script to read binary file and output it as ascii.vtk









Load and fixture specification

Boundary conditions required - how to specify?


- Current state: Manual specification
- Idea 1: Metafile before Voxelization step







- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually









- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually










- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually










- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually










- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually










- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually









- ToPy for topology optimization
- Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually









- ToPy for topology optimization
- · Custom script for generating .tpd file
 - Takes binary output from CVMLCPP and generates ToPy input
 - Sets non-voxel cells to passive elements
 - Adds boundary conditions manually










From Voxel to Mesh Geometry

- Extract isosurface from voxel information
- Algorithms: Marching Cubes, Dual Contouring, Extended Models










Surface Extraction

Contour Filtering using Implicit Modelling





Problem: Holes are not taken into account







Decimation

- Fine mesh to a coarser mesh through Decimation- Reduction of number of triangles. (Upper: 50% Lower: 90%)
- Smoothing step is needed in between









Current status

· What do we have so far?





Current status

- What do we have so far?
- What if we try to pass it to an engineer?





How to make CAD understand our data?





B–Spline


$$\vec{S}(u,v) = \sum_{i,j=1}^{n,m} \vec{C}_{i,j} N_i^p(u) N_j^p(v),$$

where p – degree of the B–Spline surface and n, m – number of control points in each direction.

B-Splines

- offer great flexibility for handling arbitrary shapes
- are CAD-standard


Engineers are working with CAD







B–Spline Fitting




Goal:

Find B-Spline representation of our data!

$$\vec{S}(u_{\alpha},v_{\alpha})pprox \vec{P}_{lpha}$$



B–Spline Fitting



Goal:

Find B-Spline representation of our data!

$$\vec{S}(u_{\alpha},v_{\alpha})pprox \vec{P}_{lpha}$$



B-spline fitting: Least squares

The task:

Find control points $C_{i,j}$, such that the B–Spline surface

$$\vec{S}(u, v) = \sum_{i,j=1}^{n,m} \vec{C}_{i,j} N_i^p(u) N_j^p(v)$$

approximates our dataset of points $\{\vec{P}_{\alpha}\}$.

This leads to minimization problem:

$$\vec{S}(u_{\alpha}, v_{\alpha}) \approx \vec{P}_{\alpha} \forall \alpha \leftrightarrow \min_{\vec{C}_{i,j} \in \mathbb{R}^3} \sum_{\alpha} \parallel \vec{P}_{\alpha} - \vec{S}(u_{\alpha}, v_{\alpha}) \parallel_2$$





B-spline fitting: Least squares (cont.)

Resulting system looks like:

$$\sum_{i,j=1}^{n,m} \vec{C}_{i,j} N_i^{\rho} (u_{\alpha}) N_j^{\rho} (v_{\alpha}) \approx \vec{P}_{\alpha} \quad \forall \alpha$$


Or, in matrix-vector form:

$$AC \approx P$$

Our system matrix A depends on $\{u_{\alpha}, v_{\alpha}\}$



B-Spline Fitting pipeline according to Becker, Schäfer, Jameson






B–Spline Fitting: Open questions

- How to distribute our data into patches?
- How to parameterize obtained patches?
- How to connect several patches after fitting?



B-Spline Fitting pipeline according to M. Eck & H. Hoppe









B–Spline Fitting: Parameter correction

The task:

For *fixed* control points $C_{i,j}$, find an optimal parametrization $\{u_{\alpha}, v_{\alpha}\}$.









What is done?

- First part of the pipeline from CAD model to optimized voxel model:
 - CAD to STL with e.g. FreeCAD
 - STI to Voxels with CVMI CPP
 - Voxels to ToPy input with custom script
 - Topology optimized geometry with ToPy
 - (*) Surface reconstruction with VTKToolbox
- B–spline fitting
 - Automatic patch selection
 - Parametrization of obtained patches
 - √ B–spline fitting using least squares
 - (b) Smooth connection of patches

 - Conversion back to CAD.





What is next?

- Automation of the first part of the pipeline
- Integration of boundary conditions handling
- Implementation of remaining B-spline fitting steps (based on work of M.Eck & H.Hoppe)
- Further research on algorithms considering voxel geometry