

SpaceCDF Learner's Workbook

*Worksheets and exercises for the 40-hour Concurrent
Design Facility intensive*

Table of Contents

Worksheet 1.1: Introduction to Space Mission Design	8
Part A: The 17 SE Processes – SpaceCDF Mapping	8
Part B: Lifecycle Phase Identification	9
Part C: CDF Position Interaction Analysis	10
Part D: SpaceCDF Tool Exploration	12
Part E: V-Model Sketch	13
Notes & Reflections	13
Worksheet 1.2: Canadian Space Ecosystem & Regulatory Environment	14
Part A: Canadian Space Industry Mapping	14
Part B: RSSSA Compliance Assessment	15
Part C: Spectrum Licensing Plan	16
Part D: Export Control Classification	16
Part E: Regulatory Timeline	17
Notes & Reflections	18
Worksheet 1.3: International Standards for Space Systems	19
Part A: Standard Applicability Matrix	19
Part B: CDS Rev 14 Compliance Checklist	20
Part C: Debris Mitigation Compliance	20
Part D: Structural Design Margins	21
Part E: SpaceCDF Compliance Panel	23
Notes & Reflections	24
Worksheet 1.4: Mission Needs, Trade Studies & Concept of Operations	25
Part A: Stakeholder Analysis Matrix	25
Part B: Problem Statement	26
Part C: Mission Objectives	27
Part D: MoE / MoP / TPM Trace	28
Part E: Trade Study – Space vs Non-Space	29
Part F: Concept of Operations Outline	30
Part G: SpaceCDF Tool Entry	32
Notes & Reflections	33
Worksheet 2.1: The System-V and Requirements Engineering	34
Key Equations Reference	34
Part A: System-V Mapping (10 min)	34
Part B: Requirement Quality Assessment (15 min)	35
Part C: Requirement Hierarchy and Traceability (15 min)	35
Part D: Splitting Compound Requirements (10 min)	37
Part E: SpaceCDF Requirements Generation (20 min)	37
Notes & Reflections	38

Worksheet 2.2: Functional Decomposition and Allocation	39
Key Equations Reference	39
Part A: Mission Function Tree (20 min)	39
Part B: Function-to-Requirement Traceability (15 min)	40
Part C: Multi-Allocation Analysis (10 min)	41
Part D: Performance Criteria (10 min)	41
Part E: SpaceCDF Coverage Check (15 min)	41
Notes & Reflections	42
Worksheet 2.3: Orbit Selection and Mission Architecture	43
Key Equations Reference	43
Part A: Orbital Mechanics Calculations (20 min)	43
Part B: Orbit Trade Matrix (10 min)	45
Part C: Debris Compliance (10 min)	45
Part D: Downstream Cascade Analysis (10 min)	46
Part E: Discussion (10 min)	46
Notes & Reflections	47
Worksheet 2.4: Mission Architecture – Segments, Interfaces, and Budgets	48
Key Equations Reference	48
Part A: Mass Budget (15 min)	48
Part B: Power Budget by Mode (15 min)	49
Part C: Interface Identification (15 min)	50
Part D: Conflict Resolution (10 min)	51
Part E: Budget Health Check (10 min)	52
Notes & Reflections	52
Worksheet 3.1: Power System and Thermal Control Design	53
Quick Reference: Power and Thermal Concepts	53
What is a Solar Array?	53
Body-Mounted vs Deployable Solar Arrays	54
How Batteries Work in Space	54
What Does the EPS Do?	55
Thermal Control Basics	55
Key Equations Reference	55
Worked Example: UniSat-1 (1U) Power and Thermal	56
Solar Array Sizing (Body-Mounted)	56
Battery Sizing	56
Thermal Check (Passive Only)	57
Part A: Solar Array Sizing (20 min)	57
Part B: Battery Sizing (10 min)	58
Part C: Thermal Analysis (15 min)	59
Part D: SpaceCDF Verification (15 min)	60
Decision Justification	60
Notes & Reflections	61
Worksheet 3.2: Attitude and Orbit Control System (AOCS)	62

Quick Reference: AOCS Concepts	62
What is AOCS?.....	62
Sensors: How Do We Know Where We Are Pointing?	62
Actuators: How Do We Control Our Orientation?	63
AOCS Architecture Decision Table	64
Key Equations Reference	65
Worked Example: UniSat-1 (1U) AOCS	65
Architecture Selection	65
Disturbance Torques at 400 km	66
Part A: AOCS Architecture Selection (10 min)	66
Part B: Disturbance Torque Calculations (20 min)	67
Part C: Reaction Wheel Sizing (10 min)	68
Part D: Pointing Error Budget (15 min)	69
Part E: SpaceCDF Verification (10 min)	70
Decision Justification	70
Notes & Reflections	71
 Worksheet 3.3: Communications and Link Budget Design	72
Quick Reference: Communications Concepts	72
What is a Link Budget?	72
What Each Term in the Link Budget Means.....	72
Frequency Band Comparison	73
Antenna Types	74
Modulation and Coding	75
Key Equations Reference	75
Worked Example: UniSat-1 (1U) UHF Link Budget	76
Step-by-Step Link Budget	76
FSPL Calculation Detail.....	77
Data Throughput	77
Part A: Frequency Band Selection (10 min)	78
Part B: Complete Link Budget (25 min)	78
Part C: Data Budget (10 min)	79
Part D: SpaceCDF Comparison (10 min)	80
Part E: Modulation and Coding Selection (5 min)	80
Decision Justification	81
Notes & Reflections	82
 Worksheet 3.4: Structure, Propulsion, and Equipment Selection	83
Quick Reference: Structure and Propulsion Concepts	83
CubeSat Design Specification (CDS Rev 14) Key Dimensions	83
Structural Loads and Margins.....	84
Propulsion Decision Tree.....	84
Propulsion Technologies Comparison	85
Key Equations Reference	86
Worked Example: UniSat-1 (1U) Structure and Propulsion	87
CDS Compliance.....	87
Propulsion Decision.....	87

Structural Margin (Axial Load).....	87
Equipment List.....	88
Part A: CDS Compliance Check (10 min).....	88
Part B: Structural Margin Calculation (10 min)	89
Part C: Propulsion Decision (15 min).....	89
Part D: Equipment Selection Log (25 min)	90
Part E: Component Trade Study (15 min).....	91
Part F: Final Budget Health Check (10 min)	92
Decision Justification.....	93
Notes & Reflections.....	94
Worksheet 4.1: Equipment Selection & Bill of Materials	95
Part A: Make/Buy/Reuse Decisions	95
Part B: Bill of Materials (BOM)	95
Part C: Budget Tracking.....	96
Part D: Export Control Assessment	97
Part E: Interface Compatibility Check	97
Part F: Interface Incompatibility Resolution.....	98
Notes & Reflections.....	98
Worksheet 4.2: Verification & Validation Planning.....	99
Part A: IADT Method Assignment	99
Part B: Dual-Method Requirements.....	99
Part C: Environmental Test Sequence	100
Part D: Vibration Test Profile.....	100
Part E: TVAC Cycle Profile	101
Part F: Waiver Identification.....	101
Notes & Reflections.....	102
Worksheet 4.3: Risk, Interfaces & FMECA.....	103
Part A: Risk Register	103
Part B: 5x5 Risk Matrix Plot	103
Part C: N-Squared (N^2) Interface Matrix	104
Part D: FMECA Table.....	104
Part E: Single-Point Failure Analysis.....	104
Part F: Reliability Calculation.....	105
Part G: Risk Discussion	106
Notes & Reflections.....	106
Worksheet 4.4: Cost Estimation & Design Review	107
Part A: Mission Cost Estimate (WBS).....	107
Part B: Confidence Levels	108
Part C: Constellation Cost (if applicable)	108
Part D: Cost Drivers.....	109
Part E: Design Review Readiness	109
Part F: Presentation Preparation.....	110
Notes & Reflections.....	111

Worksheet 5.1: Ground Segment & Operations Architecture	112
Part A: Ground Station Contact Analysis	112
Input Parameters	112
Calculations	112
Part B: Data Budget Closure	113
Part C: Ground Station Network Design	113
Part D: LEOP Timeline	114
Part E: Mission Operations Timeline (Gantt Chart)	114
Notes & Reflections	115
Worksheet 5.2: Mission Operations Concepts	116
Part A: Operational Modes	116
Part B: FDIR Rules	117
Part C: Nominal Procedure	117
Part D: Contingency Procedure	118
Part E: Operations Staffing	119
Part F: Anomaly Scenario	120
Notes & Reflections	121
Worksheet 5.3: Mission Simulation Day	122
Simulation Event Log	122
LEOP Checklist	123
Anomaly Response Form 1	123
Anomaly Response Form 2	125
Anomaly Response Form 3	127
Commissioning Status	128
Nominal Operations Summary	128
Simulation Debrief	129
What went well?	129
What could be improved?	129
Design weaknesses revealed by simulation:	129
Procedure changes needed:	129
FDIR gaps identified:	129
Notes & Reflections	130
Worksheet 5.4: Final Review & Presentations	131
Part A: Final Design Summary	131
Part B: Documentation Checklist	131
Part C: Presentation Outline	132
Part D: Peer Review Evaluation	133
Part E: Lessons Learned	135
Part F: Self-Assessment Rubric	136
Notes & Reflections	137

Worksheet 1.1: Introduction to Space Mission Design

Name

Date

Team

Session

1.1 -- Introduction to Space Mission Design

Part A: The 17 SE Processes – SpaceCDF Mapping

For each NASA SE process (NPR 7123.1D), identify which SpaceCDF feature implements it. Write the tab name, button, or panel. If the process requires human judgment that the tool cannot automate, mark “Manual” in the last column.

Hint: Navigate through SpaceCDF’s workflow steps (Need -> Concept -> Requirements -> Design) and explore each tab. Many processes map to more than one feature.

TABLE 1

#	SE Process	SpaceCDF Feature(s)	Manual?
1	Stakeholder Expectations Definition	_____	_____
2	Technical Requirements Definition	_____	_____
3	Logical Decomposition	_____	_____
4	Design Solution Definition	_____	_____
5	Product Implementation	_____	_____
6	Product Integration	_____	_____
7	Product Verification	_____	_____
8	Product Validation	_____	_____
9	Product Transition	_____	_____
10	Technical Planning	_____	_____
11	Requirements Management	_____	_____
12	Interface Management	_____	_____
13	Technical Risk Management	_____	_____

#	SE Process	SpaceCDF Feature(s)	Manual?
14	Configuration Management	_____	_____
15	Technical Data Management	_____	_____
16	Technical Assessment	_____	_____
17	Decision Analysis	_____	_____

Discussion question: Which processes are well-supported by the tool? Which ones fundamentally require human judgment and cannot be fully automated? Write your answer below:

 Write your answer

Part B: Lifecycle Phase Identification

For each activity below, identify which NASA lifecycle phase (Pre-A through F) it belongs to and which review gate marks the end of that phase:

TABLE 2

Activity	NASA Phase	Review Gate
"We need to monitor sea ice thickness in the Canadian Arctic"	_____	_____
Writing system-level "shall" requirements with verification methods	_____	_____
Selecting a specific reaction wheel vendor after evaluating 3 options	_____	_____
Running thermal-vacuum qualification tests on the flight model	_____	_____
Operating the satellite and producing daily data products	_____	_____
Decommissioning the satellite and performing passivation	_____	_____
Preliminary orbit trade study comparing SSO, ISS-orbit, and polar	_____	_____
Detailed finite element analysis of the primary structure	_____	_____

Hint: Refer to the lifecycle phase table in Session 1.1, Section 4.3. Ask yourself: “What level of design detail does this activity require?”

Part C: CDF Position Interaction Analysis

For each design conflict below, identify which engineering positions must interact to resolve it. Then briefly describe how you would approach the resolution.

Conflict 1: The payload requires 50 W but the solar array can only provide 30 W.

Positions involved: _____

Resolution approach: _____

 Write your answer

Conflict 2: The reaction wheel vibration exceeds the payload's pointing stability requirement.

Positions involved: _____

Resolution approach: _____

 Write your answer

Conflict 3: The selected orbit (700 km) requires a propulsive deorbit for debris compliance, but there is no mass budget remaining for a propulsion system.

Positions involved: _____

Resolution approach: _____

 Write your answer

Conflict 4: The X-band downlink antenna pattern interferes with the payload's sensitive optical receiver.

Positions involved: _____

Resolution approach: _____

 Write your answer

Part D: SpaceCDF Tool Exploration

Navigate through the SpaceCDF tool and answer each question:

1. How many KPI cards are shown on the Design Dashboard? List them by name:

 Write your answer

1. In the Gate Review tab, what are the MCR exit criteria? Which are auto-evaluated?

 Write your answer

1. What engineering positions are available when starting a collaborative session?

 Write your answer

1. What workflow steps does SpaceCDF guide you through (from left to right)?

 Write your answer

1. In the Positions tab, find your assigned position. What key questions does it list?

 Write your answer

Part E: V-Model Sketch

In the space below, sketch the System-V model from memory. Label each level on both the left side (decomposition) and right side (integration). Draw the horizontal traceability arrows and label them.

Use this space for your sketch:

TABLE 3

[illegible]

Notes & Reflections

Record key points from the group discussion, questions you want to follow up on, and connections to your mission concept:

 Write your answer

Worksheet 1.2: Canadian Space Ecosystem & Regulatory Environment

TABLE 4

Name: _____

Date: _____

Team: _____

Session: 1.2 – Canadian Space Ecosystem & Regulatory Environment

Part A: Canadian Space Industry Mapping

For your team's mission concept, identify potential Canadian industry partners at each tier. If no Canadian supplier exists for a capability, note what country you would source from and why.

TABLE 5

Tier	Capability Needed	Canadian Candidate(s)	International Alternative	Justification
Tier 1 (Prime/Integration)	_____	_____	_____	_____
Tier 2 (Subsystem)	_____	_____	_____	_____
Tier 2 (Subsystem)	_____	_____	_____	_____
Tier 3 (Component/Service)	_____	_____	_____	_____
Tier 4 (R&D/Academic)	_____	_____	_____	_____

Question: What CSA funding program(s) might support your mission? Why?

 Write your answer

Part B: RSSSA Compliance Assessment

Answer the following questions for your team's mission concept:

1. Does your mission involve any remote sensing of Earth (imaging, SAR, radiometry, etc.)?

 Write your answer

1. If yes, will the satellite be operated from Canada?

 Write your answer

1. What RSSSA conditions might apply? (Check all that apply)

TABLE 6

Condition	Applies?	Notes
Priority access for Government of Canada	_____	_____
Shutter control provisions	_____	_____
Data disposition / handling plan	_____	_____
System disposal plan	_____	_____
Raw data protection	_____	_____
Interoperability arrangements (foreign access)	_____	_____

1. If your mission does NOT involve remote sensing, what other regulatory requirements apply? (e.g., spectrum licensing, export control)

 Write your answer

Part C: Spectrum Licensing Plan

Identify the frequency bands your mission will use and the licensing path for each:

TABLE 7

Link	Band	Frequency (GHz)	Data Rate	Use (TT&C / Payload / ISL)	Licensing Path
Uplink	—	—	—	—	—
Downlink (TT&C)	—	—	—	—	—
Downlink (Payload)	—	—	—	—	—
Other	—	—	—	—	—

Hint: For a typical CubeSat, TT&C uses S-band (2.0–2.3 GHz) and payload data uses X-band (8.025–8.4 GHz). The licensing path for each is: ISED application -> ISED technical review -> ITU filing (API) -> ITU coordination -> ISED licence issuance.

Question: How early in your project should you begin the spectrum licensing process? Why?

 Write your answer

Part D: Export Control Classification

List the 3 most critical components in your preliminary mission concept. For each, identify the likely export control classification:

TABLE 8

Component	Country of Origin	Likely Classification	Licence Required?
—	—	ECCN: _ / USML Cat: _	—
—	—	ECCN: _ / USML Cat: _	—
—	—	ECCN: _ / USML Cat: _	—

Hint: Most commercial-off-the-shelf (COTS) space components from US manufacturers are classified under EAR (ECCN 9A515 for spacecraft parts). Military-grade or specifically designed items may fall under ITAR (USML Category XV). Canadian-origin components are subject to EIPA if they appear on the Export Control List.

Question: If your mission includes a US-origin star tracker and you plan to launch on an Indian PSLV, what export control issues arise?

 Write your answer

Part E: Regulatory Timeline

Based on your mission concept, estimate when each regulatory activity should begin and how long it will take. Mark the activities on the timeline below:

TABLE 9

Regulatory Activity	Start Phase	Duration	Critical Path?
RSSSA licence application	_____	_____	_____
ISED spectrum application	_____	_____	_____
ITU coordination	_____	_____	_____
Export permit(s)	_____	_____	_____
Launch provider interface agreement	_____	_____	_____

Question: Which regulatory activity is most likely to be on the critical path for your mission? Why?

 Write your answer

Notes & Reflections

Record key points from the discussion, regulatory questions you need to research further, and implications for your mission design:

 Write your answer

Worksheet 1.3: International Standards for Space Systems

TABLE 10

Name:	_____
Date:	_____
Team:	_____
Session:	1.3 – International Standards for Space Systems

Part A: Standard Applicability Matrix

For your team's mission concept, determine which ECSS and NASA standards apply. For each standard, decide whether it is fully applicable, partially applicable (with tailoring), or not applicable. Justify your decision.

TABLE 11

Standard	Branch	Applicability	Tailoring Notes / Justification
ECSS-M-ST-10C (Project Management)	M	_____	_____
ECSS-M-ST-40C (Configuration Management)	M	_____	_____
ECSS-M-ST-80C (Risk Management)	M	_____	_____
ECSS-E-ST-10C (Systems Engineering)	E	_____	_____
ECSS-E-ST-20C (Electrical & Electronic)	E	_____	_____
ECSS-E-ST-32C (Structures)	E	_____	_____
ECSS-E-ST-40C (Software)	E	_____	_____
ECSS-E-ST-50C (Communications)	E	_____	_____
ECSS-Q-ST-10C (Product Assurance)	Q	_____	_____
ECSS-U-AS-10C (Debris Mitigation)	U	_____	_____
ISO 24113 (Debris Mitigation)	–	_____	_____
NPR 7123.1D (SE Processes)	–	_____	_____

Hint: A university CubeSat mission would typically invoke ECSS-E-ST-10C with heavy tailoring, ECSS-U-AS-10C fully, and might waive ECSS-Q-ST-10C (product assurance) due to cost constraints. A CSA-funded mission would typically require more complete ECSS compliance.

Question: What is the minimum set of standards your mission MUST comply with regardless of mission class?

 Write your answer

Part B: CDS Rev 14 Compliance Checklist

If your mission uses a CubeSat form factor, complete this compliance checklist. If not, skip to Part C.

TABLE 12

CDS Requirement	Your Design Value	Compliant?	Notes
Unit dimensions (100 x 100 x 113.5 mm per U)	_____	_____	_____
Mass per U (≤ 2.0 kg)	_____	_____	_____
Total mass (for your form factor)	_____	_____	_____
Rail material (hard-anodised Al)	_____	_____	_____
CG within 2 cm of geometric centre	_____	_____	_____
No protrusions beyond envelope during launch	_____	_____	_____
RF silence for 30 min after deployment	_____	_____	_____
Deployment switches on all deployables	_____	_____	_____
Propulsion inhibits (3 independent, if applicable)	_____	_____	_____

Hint: Use SpaceCDF's Compliance panel to check CDS compliance. The tool will flag non-compliant parameters automatically based on your mass and dimensions entries.

Part C: Debris Mitigation Compliance

Complete the following debris mitigation assessment for your mission orbit:

1. **Planned orbit altitude:** _____ km

2. Estimated natural orbital lifetime (without propulsion):

Use the rule of thumb: $\tau_{\text{years}} \approx (h - 200)/(30) \times (m/A)/(50)$ where h is altitude (km), m is mass (kg), A is cross-section area (m^2)

$h = \underline{\hspace{1cm}} \text{ km}$, $m = \underline{\hspace{1cm}} \text{ kg}$, $A = \underline{\hspace{1cm}} \text{ m}^2$

$m/A = \underline{\hspace{1cm}} \text{ kg/m}^2$

$\tau = \underline{\hspace{1cm}} \text{ years}$ (approximate)

1. Compliance assessment:**TABLE 13**

Requirement	Limit	Your Mission	Compliant?
IADC post-mission lifetime	$\leq 25 \text{ years}$	<u> </u>	<u> </u>
FCC post-mission lifetime (2024+)	$\leq 5 \text{ years}$	<u> </u>	<u> </u>
ISO 24113 disposal reliability	$\geq 90\%$	<u> </u>	<u> </u>

1. If non-compliant with the 5-year FCC rule, what options exist?

 Write your answer

1. Passivation plan (list all stored energy sources and how you will deplete them at end of life):**TABLE 14**

Energy Source	Passivation Method
Battery	<u> </u>
Pressure vessels (if any)	<u> </u>
Reaction wheels	<u> </u>
RF transmitter	<u> </u>
Other: <u> </u>	<u> </u>

Part D: Structural Design Margins

If your mission has preliminary structural design information, calculate the margin of safety:

Use the formula: $\text{MoS} = (\sigma_{\text{allowable}}) / (\text{FoS} \times \sigma_{\text{applied}}) - 1$

Worked example: For Al 7075-T6 ($\sigma_{\text{yield}} = 503 \text{ MPa}$), applied stress = 200 MPa, FoS (yield) = 1.25:

$$\text{MoS} = (503) / (1.25 \times 200) - 1 = (503) / (250) - 1 = 1.012$$

This is a positive margin (compliant).

Your calculation:

Material: _ , $\sigma_{\text{allowable}} =$ _ MPa

$\sigma_{\text{applied}} =$ _ MPa, FoS = _

MoS = ____ (show work below)

 Write your answer

Part E: SpaceCDF Compliance Panel

Navigate to the Compliance panel in SpaceCDF and answer:

1. What is the debris mitigation compliance status for your mission?

 Write your answer

1. What orbital altitude would be needed to comply with the FCC 5-year rule WITHOUT propulsion? (Use the tool's orbital lifetime calculator)

 Write your answer

1. What standards has the tool automatically suggested for your mission type?

 Write your answer

1. Are there any compliance flags (warnings or errors) on your current design?

 Write your answer

Notes & Reflections

Record key points about standards applicability, compliance challenges, and design implications for your mission:

 Write your answer

Worksheet 1.4: Mission Needs, Trade Studies & Concept of Operations

TABLE 15

Name: _____

Date: _____

Team: _____

Session: 1.4 – Mission Needs, Trade Studies & ConOps

Part A: Stakeholder Analysis Matrix

Identify at least 4 stakeholders for your team's mission. For each, capture their needs, constraints, priority, and influence level.

TABLE 16

#	Stakeholder	Role	Key Needs	Constraints Imposed	Priority (P/S/T)	Influence (H/M/L)
1	_____	_____	_____	_____	_____	_____
2	_____	_____	_____	_____	_____	_____
3	_____	_____	_____	_____	_____	_____
4	_____	_____	_____	_____	_____	_____
5	_____	_____	_____	_____	_____	_____
6	_____	_____	_____	_____	_____	_____

P = Primary (must satisfy), S = Secondary (should satisfy), T = Tertiary (nice to have) H = High influence, M = Medium, L = Low

Question: Which stakeholder has the most influence over your mission? Do any stakeholders have conflicting needs? If so, how might you resolve the conflict?

 Write your answer

Part B: Problem Statement

Write your team's mission problem statement. It must answer all four questions: What is the problem? Who is affected? What is the impact? What constraints exist?

Problem Statement:

 Write your answer

Peer Review Checklist (exchange with another team):

TABLE 17

Criterion	Pass?	Feedback
Describes WHAT is needed, not HOW to achieve it?	_____	_____
Identifies the capability gap?	_____	_____
Names specific affected stakeholders?	_____	_____
Quantifies the impact of not solving it?	_____	_____
States constraints (budget, schedule, regulatory)?	_____	_____
Free of solution language? (No specific satellite type, orbit, component named)	_____	_____

Part C: Mission Objectives

Write 2–3 mission objectives. Score each against the quality checklist.

Objective 1: _____

 Write your answer

TABLE 18

Quality Criterion	Yes/No	Notes
States WHAT, not HOW?	_____	_____
Has measurable criterion with number + unit?	_____	_____
Achievable with current technology (TRL $\geq$ 4)?	_____	_____
Relevant to the problem statement?	_____	_____
Traceable to a specific stakeholder need?	_____	_____
Classified as primary or secondary?	_____	_____

Objective 2: _____

 Write your answer

TABLE 19

Quality Criterion	Yes/No	Notes
States WHAT, not HOW?	_____	_____
Has measurable criterion with number + unit?	_____	_____
Achievable with current technology (TRL $\geq$ 4)?	_____	_____
Relevant to the problem statement?	_____	_____
Traceable to a specific stakeholder need?	_____	_____
Classified as primary or secondary?	_____	_____

Objective 3 (optional): _____

 Write your answer

Part D: MoE / MoP / TPM Trace

For your primary objective, trace the measurement hierarchy:

Objective: _____

MoE (Measure of Effectiveness – operational effectiveness from user perspective):

 Write your answer

MoP (Measure of Performance – technical performance of the system):

 Write your answer

TPM (Technical Performance Measure – design parameter tracked during development):

 Write your answer

Hint: If your objective is “Provide 10 m GSD multispectral imagery...”, then: - MoE might be “% of target area with usable (<30% cloud) imagery within 5 days” - MoP might be “ $GSD \leq 10$ m at nadir, $SNR \geq 100$ in all bands” - TPM might be “current estimate of aperture diameter (target: 15 cm), imager mass (target: 1.5 kg)”

Part E: Trade Study – Space vs Non-Space

Complete a trade study evaluating whether a dedicated satellite is the right solution for your mission need.

Decision statement: _____

Alternatives:

TABLE 20

#	Alternative	Description
1	_____	_____
2	_____	_____
3	_____	_____
4	Do nothing / status quo	_____

Criteria and Weights (must sum to 1.0):

Use pairwise comparison or direct assignment. Show your weight derivation below.

TABLE 21

Criterion	Weight	Direction (higher/lower is better)
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
Total	1.00	

Weight derivation (pairwise comparison table or notes):

 Write your answer

Scoring Matrix (normalised 0–1):

TABLE 22

Alternative	Criterion 1	Criterion 2	Criterion 3	Criterion 4	Criterion 5	Weighted Total
1: _____	_____	_____	_____	_____	_____	_____

Alternative	Criterion 1	Criterion 2	Criterion 3	Criterion 4	Criterion 5	Weighted Total
2: _____	_____	_____	_____	_____	_____	_____
3: _____	_____	_____	_____	_____	_____	_____
4: Do nothing	_____	_____	_____	_____	_____	_____

Recall: Weighted Total = $\sum w_c \times s(a,c)$

Result: The highest-scoring alternative is: _____

Decision statement (1 paragraph – include top 2 alternatives and why one was selected over the other):

 Write your answer

Sensitivity check: If you increase the weight of your second-most-important criterion by 20% (and re-normalise), does the ranking change?

 Write your answer

Part F: Concept of Operations Outline

Document your preliminary ConOps following the NASA SEH Appendix S structure:

1. Mission Architecture:

Space segment: _____

Ground segment: _____

User segment: _____

2. Orbit-Average Power Budget:

Calculate using: $P_{avg} = \sum P_{mode,i} \times DC_i$

TABLE 23

Mode	Power (W)	Duty Cycle (fraction of orbit)	P x DC (W)
Idle / Housekeeping	_____	_____	_____
Science / Imaging	_____	_____	_____
Downlink	_____	_____	_____
Eclipse	_____	_____	_____
Orbit-average power:			_____ W

Solar array requirement: $P_{SA} = \text{_____ W}$

Show your calculation:

 Write your answer

3. Data Budget:

Daily data generation: _____ GB/day

Downlink capacity per pass: _____ GB/pass

Passes per day: _____

Daily downlink capacity: _____ GB/day

Balance (downlink $\geq$ generation)? _____

Part G: SpaceCDF Tool Entry

In SpaceCDF, enter your mission need (Step 1) and concept (Step 2). Then answer:

1. In Step 1, did the tool auto-detect your mission type from the objective text? What type did it suggest?

 Write your answer

1. In Step 2, run the mission trade analysis. Does the tool's recommendation match your manual trade study result from Part E?

 Write your answer

1. In the ConOps tab, build your architecture diagram. How many systems did you define?

 Write your answer

1. In the Trade Studies tab, run an orbit selection trade with at least 3 orbit options. What orbit did it recommend?

 Write your answer

Notes & Reflections

Record key decisions made today, open questions, and what you want to investigate further:

 Write your answer

Worksheet 2.1: The System-V and Requirements Engineering

TABLE 24

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tab: Requirements

Key Equations Reference

Traceability Coverage:

$$\text{Coverage} = (N_{\text{verified requirements}}) / (N_{\text{total requirements}}) \times 100\%$$

Target: 100% – every requirement needs a parent trace, a verification method, and a responsible subsystem.

Requirement Quality (SMART): Specific – Measurable – Achievable – Relevant – Traceable

Verification Methods (ATID): Analysis – Test – Inspection – Demonstration

Part A: System-V Mapping (10 min)

For your mission, identify one element at each level of the V-model:

TABLE 25

V-Level	Left Branch (Decomposition)	Right Branch (Verification)
Stakeholder Need		
Mission Requirement		
System Requirement		

V-Level	Left Branch (Decomposition)	Right Branch (Verification)
---------	-----------------------------	-----------------------------

Subsystem Requirement

 Write your answer

Part B: Requirement Quality Assessment (15 min)

Evaluate each requirement using the SMART checklist and NASA Appendix C criteria. Mark Pass (P) or Fail (F). Rewrite any failures.

TABLE 26

#	Requirement	S	M	A	R	T	WHAT or HOW?	Rewrite (if needed)
1	"The spacecraft shall operate at 500 km altitude"							
2	"The system shall achieve GSD <= 10 m at nadir"							
3	"The EPS shall use triple-junction GaAs cells"							
4	"The system shall have a design lifetime of at least 3 years"							
5	"The structure shall be made of aluminium 7075"							

 Write your answer

Part C: Requirement Hierarchy and Traceability (15 min)

For your mission, write one requirement at each level. Draw the traceability chain.

Stakeholder Objective (traces FROM): _____

 Write your answer

Mission Requirement (MR-__): _____

 Write your answer

System Requirement (SR-__), derived from MR above: _____

 Write your answer

Subsystem Requirement (SSR-__), derived from SR above: ____

 Write your answer

Traceability diagram (draw arrows showing parent-child relationships):

 Write your answer

Part D: Splitting Compound Requirements (10 min)

Split this compound requirement into individually testable statements:

“The system shall provide 10 m GSD multispectral imagery with 5-day revisit, 24-hour data latency, and positive power margin in all operational modes including eclipse.”

TABLE 27

#	Split Requirement (one concern each)	Type (F/P/I/C/E)	Verification (A/T/I/D)	Phase
1				
2				
3				
4				
5				

 Write your answer

Part E: SpaceCDF Requirements Generation (20 min)

1. In SpaceCDF, click “**Generate from Objectives.**” How many requirements were generated? ____
2. Use the Level filter – count at each level: - Mission: _ **System:** _ Subsystem: ____
3. Classify 5 requirements by type:

TABLE 28

Req ID	Requirement Text (abbreviated)	Type (Functional / Performance / Interface / Constraint / Environmental)

1. Find one requirement that says HOW (implementation) not WHAT. Write it and your correction:
 - Original: _____

• **Corrected:** _____

1. Accept at least 5 requirements and reject at least 1. Record your decisions:

TABLE 29

Req ID	Action (Accept/Edit/Reject)	Rationale

1. For 5 key requirements, assign verification method and phase:

TABLE 30

Req ID	Verification Method (A/T/I/D)	Phase (B/C/D/E)	Rationale for Method

Notes & Reflections

 Write your answer

Worksheet 2.2: Functional Decomposition and Allocation

TABLE 31

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tab: Functions

Key Equations Reference

Function Types: Observe, Communicate, Navigate, Point, Power, Protect, Store, Process, Support

Universal Functions (every spacecraft): 1. Generate electrical power 2. Maintain thermal environment 3. Survive launch environment 4. Communicate with ground (TTC) 5. Dispose at end of life

Coverage Rule: Every leaf function must trace to at least one requirement. No gaps.

Allocation Rule: Multi-allocated functions create interfaces that must be explicitly managed.

Part A: Mission Function Tree (20 min)

Draw your mission’s complete function tree. Use minimum 3 levels of decomposition. Include both mission-specific and universal functions.

Mission-specific functions:

F-001: _____
+-- F-002: _____
 +-- F-002a: _____
 +-- F-002b: _____
+-- F-003: _____
 +-- F-003a: _____
+-- F-004: _____
+-- F-005: _____

Universal functions:

F-010: Generate electrical power
+-- F-011: _____
+-- F-012: _____
F-020: Maintain thermal environment
+-- F-021: _____
F-030: Survive launch environment
F-040: Communicate with ground (TTC)
F-050: Dispose at end of life

 Write your answer

Part B: Function-to-Requirement Traceability (15 min)

For each leaf function, write one derived requirement with a measurable threshold:

TABLE 32

Function ID	Function Name	Allocated To (Subsystem)	Derived Requirement	Type

 Write your answer

Part C: Multi-Allocation Analysis (10 min)

Identify at least one function that is allocated to more than one subsystem:

Function: _____

Subsystem A (primary): _____

Subsystem B (contributor): _____

Interface created between A and B: _____

 Write your answer

Who “owns” this function? _____

What interface requirements are needed? _____

 Write your answer

Part D: Performance Criteria (10 min)

For 4 key functions, define quantitative performance criteria:

TABLE 33

Function	Performance Criterion	Value	Unit	Source

Part E: SpaceCDF Coverage Check (15 min)

After entering functions in SpaceCDF:

1. How many total functions in your tree? ____
2. How many leaf functions? ____

3. How many leaf functions have NO linked requirements (amber badge)? ____
4. List the uncovered functions and derive requirements for them:

TABLE 34

Function ID	Function Name	Derived Requirement

1. Are there any functions the tool generated that are NOT appropriate for your mission? List and explain why you removed them:

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 2.3: Orbit Selection and Mission Architecture

TABLE 35

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: Mission Architecture, Orbit Trade Advisor

Key Equations Reference

Orbital period: $T = 2\pi \sqrt{a^3/\mu}$ where $a = R_E + h$, $\mu = 3.986 \times 10^{14} \text{ m}^3/\text{s}^2$, $R_E = 6371 \text{ km}$

Orbital velocity: $v = \sqrt{\mu/a}$

Eclipse fraction: $f_{\text{ecl}} = (1)/(\pi) \arccos(\frac{\sqrt{a^2 - R_E^2}}{a})$

Sun-synchronous inclination: $\cos(i) = -\frac{2\dot{\Omega} a^{7/2}}{3 R_E^2 J_2 \sqrt{\mu}}$ where $J_2 = 1.0826 \times 10^{-3}$

Hohmann ΔV : $\Delta V_1 = \sqrt{\mu/r_1} (\sqrt{2r_2/(r_1+r_2)} - 1)$

Swath width: $W = 2h \tan(\theta)$

Part A: Orbital Mechanics Calculations (20 min)

Your selected orbit: Altitude $h =$ _ km, Inclination $i =$ deg, Type: _

Show all working for each calculation:

1. Semi-major axis:

$$a = R_E + h = 6371 + _ = \mathbf{km} = _ \text{ m}$$

 Write your answer

2. Orbital period:

$$T = 2\pi \sqrt{a^3/\mu} = 2\pi \sqrt{_^3 / 3.986 \times 10^{14}} = \mathbf{s} = _ \text{ min}$$

 Write your answer

3. Orbital velocity:

$$v = \sqrt{\mu/a} = \sqrt{3.986 \times 10^{14} / _} = _ \text{ m/s}$$

 Write your answer

4. Eclipse fraction (maximum):

$$f = \frac{1}{\pi} \arccos\left(\frac{\sqrt{a^2 - R_E^2}}{a}\right) = \frac{1}{\pi} \arccos\left(\frac{\sqrt{_}}{_}\right) = \$ ______$$

 Write your answer

5. Sunlight and eclipse time per orbit:

$$t_{\text{sun}} = T \times (1 - f) = _ \times _ = _ \text{ min}$$

$$t_{\text{ecl}} = T \times f = _ \times _ = _ \text{ min}$$

6. Sun-synchronous inclination (if applicable):

$$\cos(i) = _ \rightarrow i = _ \text{ deg}$$

Does this match your selected inclination? Y / N

 Write your answer

Part B: Orbit Trade Matrix (10 min)

From SpaceCDF's Orbit Trade Advisor, record the top 3 candidates:

TABLE 36

Rank	Orbit Type	Alt (km)	Inc (deg)	GSD (m)	Revisit (d)	Natural Lifetime (yr)	FCC 5-yr?	Score
1								
2								
3								

Selected orbit: __ Rationale: _____

 Write your answer

Part C: Debris Compliance (10 min)

For your selected orbit:

TABLE 37

Parameter	Value
Natural orbital lifetime	_____ years
FCC 5-year compliant?	Y / N
IADC 25-year compliant?	Y / N
Propulsion needed for deorbit?	Y / N
If yes, estimated deorbit ΔV	_____ m/s
Deorbit method (if needed)	_____

Show ΔV calculation if propulsion needed:

 Write your answer

Part D: Downstream Cascade Analysis (10 min)

How does your orbit selection affect each subsystem? Fill in the impact:

TABLE 38

Subsystem	Orbit Parameter That Matters	Impact on Your Design
Payload (GSD)	Altitude = ____ km	GSD = ____ m
EPS (eclipse)	Eclipse fraction = ____	Eclipse duration = ____ min
Comms (link)	Slant range at 10 deg elev = ____ km	FSPL increase = ____ dB
Thermal	Eclipse/sunlight cycling	Hot case / Cold case concern: ____
AOCS	Orbit rate = ____ deg/min	Nadir tracking rate needed
Propulsion	Lifetime = ____ yr	Propulsion needed? Y / N
Radiation	TID estimate = ____ krad/yr	Electronics class: ____

Part E: Discussion (10 min)

What would happen to your mission if you moved the orbit **100 km higher**?

 Write your answer

What would happen if you moved it **100 km lower**?

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 2.4: Mission Architecture – Segments, Interfaces, and Budgets

TABLE 39

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: System Architecture, Interfaces, Dashboard, Budget Breakdown

Key Equations Reference

Mass margin: $\text{Margin} \% = \frac{M}{M_{\text{MEV}}} \times 100\%$ Green: > 20% | Amber: 10–20% | Red: < 10%

MEV: $M_{\text{MEV}} = M_{\text{CBE}} + \text{equipment margin} + \text{system margin}$

Orbit-average power: $P_{\text{avg}} = \sum (P_{\text{mode}} \times f_{\text{duty}})$

SA power: $P_{\text{SA}} = P_{\text{peak}} + \frac{P_{\text{ec}} \times t_{\text{ec}}}{t_{\text{sun}}} \times \eta_{\text{charge}}$

ECSS Phase A margins: Equipment 20% + System 20% = ~44% compound

Part A: Mass Budget (15 min)

Complete from your SpaceCDF design (or estimate if pre-run):

TABLE 40

Subsystem	CBE Mass (kg)	% of Dry	Equip. Margin (20%)	MEV (kg)
Payload				
EPS				
AOCS				
Comms (TTC)				

Subsystem	CBE Mass (kg)	% of Dry	Equip. Margin (20%)	MEV (kg)
OBC				
Thermal				
Structure				
Harness				
Propulsion				
Dry Total (CBE)		100%		
System margin (20%)				
Dry MEV				
Propellant				
Wet Mass				
Launcher Allocation				
Mass Margin				
Mass Margin %			G / A / R	

Show margin calculation:

 Write your answer

Part B: Power Budget by Mode (15 min)

TABLE 41

Subsystem	Safe (W)	Idle (W)	Imaging (W)	Downlink (W)	Eclipse (W)
OBC					
AOCS					
Payload					
Comms (TX)					
Thermal					
Total					
Duty cycle (%)					

Orbit-average power calculation (show working):

$P_{avg} = _ \times + \times _ + \times + _ \times = _ \text{ W}$

✎ Write your answer

SA power required:

$P_{\text{recharge}} = \frac{P_{\text{ecl}} \times t_{\text{ecl}}}{t_{\text{sun}} \times \eta_{\text{charge}}} = \frac{_ \times _}{_ \times 0.9} = _ \text{ W}$

$P_{SA,EOL} = P_{peak} + P_{recharge} = _ + _ = _ \text{ W}$

$P_{SA,BOL} = P_{SA,EOL} / (1 - 0.025)^n = _ / _ = _ \text{ W}$

✎ Write your answer

Part C: Interface Identification (15 min)

List the 5 most critical interfaces in your design:

TABLE 42

#	Subsystem A	Subsystem B	Interface Types (M/E/T/D/R/O)	Key Concern
1				
2				
3				
4				
5				

Write 2 formal interface requirements for your most critical pair:

Interface: <->

IR-001: _____

✎ Write your answer

IR-002: _____

✎ Write your answer

Verification method for IR-001: _ IR-002: ____

Part D: Conflict Resolution (10 min)

From the SpaceCDF Interface Matrix, identify one conflict (red border):

Conflict description: _____

✎ Write your answer

Severity: Critical / Major / Minor

Resolution options considered:

TABLE 43

#	Option	Pros	Cons
1			
2			
3			

Selected resolution: _____

Rationale: _____

Part E: Budget Health Check (10 min)

From the SpaceCDF Dashboard, record all KPIs:

TABLE 44

Budget	Value	Margin	Status (G/A/R)
Mass	_ kg wet vs ___ kg alloc	____%	
Power (worst mode)	_ W vs ___ W SA	____%	
Link	____ dB margin	>= 3 dB?	
Cost	_ MEUR vs ___ ceiling	____%	
Pointing	_ deg vs ___ deg req	____%	

Which budget is tightest? _____

What single design change would improve it? _____

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 3.1: Power System and Thermal Control Design

TABLE 45

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: Dashboard (Power KPI), Engineering Budgets, Timing Budget, Parametric

Quick Reference: Power and Thermal Concepts

WHAT IS A SOLAR ARRAY?

A solar array converts sunlight into electrical power using photovoltaic cells. In space, the solar flux (called the solar constant) is $S = 1361 \text{ W/m}^2$ at 1 AU from the Sun – about 40% more intense than at Earth's surface because there is no atmosphere absorbing part of the spectrum.

Solar cell types and efficiency (AM0, space spectrum):

TABLE 46

Cell Technology	Typical Efficiency	Degradation Rate	Cost Relative	Notes
Silicon (Si)	16–18%	~3.5%/yr	Low	Legacy; rarely used in new missions
Gallium Arsenide (GaAs) single-junction	22–24%	~2.5%/yr	Medium	Good radiation tolerance
Triple-junction GaAs (InGaP/GaAs/Ge)	28–30%	~2.5%/yr	High	CubeSat standard today
Multi-junction (4J, 5J)	32–35%	~2%/yr	Very high	Emerging; used on flagship missions

For CubeSat design, assume **triple-junction GaAs cells at 29.5% efficiency** ($\eta = 0.295$). Cells are mounted on panels with a **packing factor** of $f_{\text{pack}} = 0.80\text{--}0.85$, meaning 80–85%

of the panel area is actually covered by active cells (the rest is gaps, wiring, and structural margin).

Degradation: Solar cells lose efficiency over time due to radiation damage (proton and electron bombardment in the Van Allen belts). At a rate of $\delta = 2.5\%$ per year, after n years the remaining efficiency is $(1 - 0.025)^n$. This means a 3-year mission loses about 7.3% of its beginning-of-life (BOL) power, and a 5-year mission loses about 11.9%.

BODY-MOUNTED VS DEPLOYABLE SOLAR ARRAYS

TABLE 47

Configuration	Advantages	Disadvantages	Typical Power
Body-mounted	No moving parts, no deployment risk, no stowed volume penalty	Limited area (only the sunlit faces), power varies with attitude	1U: ~2 W, 3U: ~7 W, 6U: ~12 W
Single deployable	More area, moderate complexity	One mechanism, partially blocks FOV	1U: ~4 W, 3U: ~15 W, 6U: ~30 W
Dual deployable	Maximum area for the form factor	Two mechanisms, larger stowed volume, deployment risk	3U: ~25 W, 6U: ~48 W

Rule of thumb: If your total power demand (including battery recharge) exceeds what body-mounted panels can provide, you need deployable arrays. Compare your $P_{SA,BOL}$ to the reference power values above.

HOW BATTERIES WORK IN SPACE

Batteries store electrical energy to power the spacecraft during eclipse (when the satellite is in Earth's shadow and receives no sunlight). In LEO, eclipses occur every orbit – typically 30–36 minutes out of a ~95-minute orbit period.

Key battery parameters:

- **Depth of Discharge (DOD):** The fraction of total battery capacity used each cycle. Lower DOD dramatically extends cycle life but requires a larger (heavier) battery.
- **Cycle life:** The number of charge/discharge cycles before the battery degrades below 80% of its original capacity.
- **Specific energy:** Energy stored per unit mass (Wh/kg). For space-grade Li-ion 18650 cells: 150–200 Wh/kg.

TABLE 48

DOD	Typical Cycle Life (Li-ion 18650)	Suitable Mission Duration
80%	~500 cycles	Short missions (< 1 month)
50%	~2,000 cycles	Medium missions (< 6 months)

DOD	Typical Cycle Life (Li-ion 18650)	Suitable Mission Duration
30%	~10,000 cycles	Multi-year LEO missions
20%	~30,000 cycles	Long-life LEO (> 5 years)

Design guidance: For a multi-year LEO mission (15 orbits/day), use DOD = 30%. For a 6-month technology demonstration, DOD = 50% is acceptable.

WHAT DOES THE EPS DO?

The Electrical Power System (EPS) is the spacecraft's power utility. A typical CubeSat EPS board (e.g., GomSpace P31u) includes:

- **MPPT (Maximum Power Point Tracking):** A DC-DC converter that continuously adjusts the operating voltage of the solar array to extract maximum power. Efficiency: 90–95%.
- **Battery charge controller:** Manages battery charging with voltage and current limits to protect battery life.
- **Regulated voltage rails:** Provides fixed voltages (typically 3.3 V, 5 V, and unregulated battery voltage) to all subsystems.
- **Switched outputs:** Allows the OBC to turn subsystems on/off for power management and safe mode.
- **Overcurrent protection:** Protects against short circuits in any subsystem.

THERMAL CONTROL BASICS

In space, there is no air for convection. Heat transfer occurs only by **radiation** and **conduction**. A spacecraft reaches thermal equilibrium when absorbed heat (solar flux, Earth albedo, Earth IR, internal electronics waste heat) equals radiated heat (to deep space at ~3 K).

ECSS thermal margins (ECSS-E-ST-31C): Operating ± 5 degC, Acceptance ± 10 degC, Qualification ± 15 degC. If the predicted temperature of any component is within 5 degC of its operating limit, you must add thermal control (heater, coating change, or radiator).

Key Equations Reference

SA EOL power: $P_{\text{SA,EOL}} = P_{\text{peak}} + \frac{P_{\text{ecl}} \times t_{\text{ecl}}}{t_{\text{sun}}} \times \eta_{\text{charge}}$

SA BOL power: $P_{\text{SA,BOL}} = (P_{\text{SA,EOL}}) / ((1 - \delta)^n)$ ($\delta = 0.025/\text{yr}$ for GaAs)

SA area: $A = \frac{P_{\text{BOL}}}{\eta_{\text{cell}} \times S \times \cos\theta \times f_{\text{pack}}}$ ($\eta = 0.295$, $S = 1361 \text{ W/m}^2$, $f_{\text{pack}} = 0.85$)

Battery capacity: $C = \frac{P_{\text{ecl}} \times t_{\text{ecl}}}{\text{DOD} \times \eta_{\text{dis-charge}}}$ (DOD = 0.30, $\eta = 0.95$)

Thermal equilibrium: $T = \left(\frac{Q_{\text{abs}} + Q_{\text{int}}}{\epsilon \sigma A_{\text{rad}}} \right)^{1/4}$ ($\sigma = 5.67 \times 10^{-8} \text{ W/m}^2/\text{K}^4$)

ECSS thermal margins: Operating $\pm 5 \text{ degC}$, Acceptance $\pm 10 \text{ degC}$, Qualification $\pm 15 \text{ degC}$

Worked Example: UniSat-1 (1U) Power and Thermal

SOLAR ARRAY SIZING (BODY-MOUNTED)

UniSat-1 uses body-mounted solar cells on 5 faces (the 6th face is the deployment interface). ISS orbit: 400 km altitude, 92.4 min period, 56 min sunlight, 36 min eclipse.

Given: $P_{\text{peak,sunlight}} = 1.2 \text{ W}$, $P_{\text{eclipse}} = 0.5 \text{ W}$ (OBC only), mission lifetime = 6 months.

Step 1 – Effective illuminated area (passive magnetic attitude, ~1.5 faces average):

$$A_{\text{eff}} = 1.5 \times (0.10 \times 0.10) = 0.015 \text{ m}^2$$

Step 2 – SA BOL power:

$$P_{\text{SA,BOL}} = \eta \times S \times A_{\text{eff}} \times f_{\text{pack}} = 0.295 \times 1361 \times 0.015 \times 0.80 = 4.82 \text{ W (illuminated peak)}$$

Step 3 – Orbit-average power available:

$$P_{\text{avg}} = P_{\text{SA,BOL}} \times \frac{t_{\text{sun}}}{T_{\text{orbit}}} \times \eta_{\text{EPS}} = 4.82 \times \frac{56}{92.4} \times 0.85 = 2.48 \text{ W}$$

Step 4 – After 6-month degradation:

$$(1 - 0.025)^{0.5} = 0.987, \text{ so } P_{\text{avg,EOL}} = 2.48 \times 0.987 = 2.45 \text{ W}$$

Step 5 – Power demand: $P_{\text{avg,demand}} = 0.68 \text{ W}$. Margin = $2.45 - 0.68 = 1.77 \text{ W}$ (72%). **Comfortable.**

BATTERY SIZING

Given: $P_{\text{ecl}} = 0.5 \text{ W}$, $t_{\text{ecl}} = 36 \text{ min} = 0.60 \text{ h}$, DOD = 0.50 (acceptable for 6-month mission), $\eta = 0.95$.

$$C_{\text{bat}} = \frac{0.5 \times 0.60}{0.50 \times 0.95} = \frac{0.30}{0.475} = 0.63 \text{ Wh}$$

Specify minimum **10 Wh** (standard GomSpace NanoPower P31u battery). Actual DOD per eclipse = $0.63/10 = 6.3\%$. Cycle count: 6 months at 15 orbits/day = 2,740 eclipses. At 6.3% actual DOD, battery life is not a concern. **Pass.**

THERMAL CHECK (PASSIVE ONLY)

UniSat-1 uses no heaters or MLI. At 400 km, strong Earth IR ($\sim 240 \text{ W/m}^2$) provides a warm floor. With COTS electronics rated -20 to $+60 \text{ degC}$ and a 400 km orbit, the thermal environment stays within approximately -10 to $+45 \text{ degC}$ for a 1U with aluminium/anodised surfaces. A simplified cold-case equilibrium calculation gives a very cold steady-state temperature, but the thermal mass of a 1 kg CubeSat limits actual cooling during 36-minute eclipses. **No heaters required for a 6-month mission at 400 km.**

Part A: Solar Array Sizing (20 min)

Show all calculations step by step.

1. Peak sunlight power demand: $P_{\text{peak}} = _ \text{ W}$ (from mode: ______)

2. Eclipse power demand: $P_{\text{ecl}} = ______ \text{ W}$

3. Eclipse and sunlight times (from Worksheet 2.3):

$t_{\text{ecl}} = _ \text{ min}$ $t_{\text{sun}} = ______ \text{ min}$

4. Recharge power:

$P_{\text{recharge}} = \frac{P_{\text{ecl}} \times t_{\text{ecl}}}{t_{\text{sun}} \times \eta_{\text{charge}}} = \frac{______ \times ______}{______ \times 0.9} = ______ \text{ W}$

 Write your answer

5. SA EOL required:

$P_{\text{SA,EOL}} = P_{\text{peak}} + P_{\text{recharge}} = _ + _ = ______ \text{ W}$

6. EOL degradation factor (mission lifetime = ______ years, $\delta = 0.025/\text{yr}$):

$(1 - 0.025)^{______} = ______$

7. SA BOL required:

$P_{\text{SA,BOL}} = \frac{P_{\text{SA,EOL}}}{(1 - \delta)^n} = \frac{______}{______} = ______ \text{ W}$

 Write your answer

8. SA area:

$$A = \frac{P_{\text{BOL}}}{0.295 \times 1361 \times \cos(\theta) \times 0.85} = \frac{\dots}{\dots} = \dots \text{ m}^2$$

 Write your answer

9. SA type needed (compare to CubeSat reference values):

- [] Body-mounted only (1U: ~2 W, 3U: ~7 W, 6U: ~12 W)
- [] Single deployable (1U: ~4 W, 3U: ~15 W, 6U: ~30 W)
- [] Dual deployable (3U: ~25 W, 6U: ~48 W)

10. SA mass:

$$m_{SA} = A \times \sigma = \dots \times \dots = \dots \text{ kg}$$

(body-mounted: $\sigma = 2.5 \text{ kg/m}^2$; deployable: $\sigma = 1.5 \text{ kg/m}^2$)

Part B: Battery Sizing (10 min)

Show all calculations:

1. Eclipse energy:

$$E = P_{\text{ecl}} \times (t_{\text{ecl}})/(60) = \dots \times \dots = \dots \text{ Wh}$$

2. Battery capacity required:

$$C = \frac{E}{\text{DOD} \times \eta} = \frac{\dots}{0.30 \times 0.95} = \frac{\dots}{0.285} = \dots \text{ Wh}$$

$$\text{3. With 20\% margin: } C_{\text{spec}} = \dots \times 1.2 = \dots \text{ Wh}$$

 Write your answer

4. Battery mass:

$$m_{\text{bat}} = \frac{C_{\text{spec}}}{E_{\text{specific}}} = \frac{\dots}{150} = \dots \text{ kg}$$

5. Cycle life check:

Number of eclipses in mission = **_ orbits/day** × **365** × **years** = **__** cycles

At DOD = 30%, Li-ion provides ~10,000 cycles. Is this sufficient? Y / N

 Write your answer

Part C: Thermal Analysis (15 min)

1. Identify hot case and cold case for your orbit:

TABLE 49

Parameter	Hot Case	Cold Case
Solar illumination		
Operational mode		
Internal dissipation		
Coating condition	BOL / EOL	BOL / EOL
Key concern		

2. From SpaceCDF Dashboard, record thermal predictions:

TABLE 50

Component	Min Predicted (degC)	Max Predicted (degC)	Operating Min (degC)	Operating Max (degC)
Payload / sensor				
Battery				
OBC				
Transponder				

3. Margin check (need ≥ 5 degC):

TABLE 51

Component	Hot margin = Max_op - Max_pred	Cold margin = Min_pred - Min_op	Pass?

4. If any margin fails, what thermal control action would you take?

 Write your answer

Part D: SpaceCDF Verification (15 min)

Compare your hand calculations to SpaceCDF values:

TABLE 52

Parameter	Hand Calculation	SpaceCDF Value	Difference
SA power required (BOL)	_____ W	_____ W	_____ W
Battery capacity	_____ Wh	_____ Wh	_____ Wh
Orbit-average power	_____ W	_____ W	_____ W
Eclipse duration	_____ min	_____ min	_____ min

If there are significant differences, explain why:

 Write your answer

Decision Justification

Explain WHY you chose each element of your power and thermal design. Consider the alternatives you rejected and the trade-offs involved.

Solar array configuration choice and rationale:

 Write your answer

Battery sizing rationale (why this DOD? why this capacity margin?):

 Write your answer

Thermal control approach (passive only? heaters? coatings?):

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 3.2: Attitude and Orbit Control System (AOCS)

TABLE 53

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: Dashboard (AOCS KPI), Pointing Budget, Architecture (AOCS)

Quick Reference: AOCS Concepts

WHAT IS AOCS?

The Attitude and Orbit Control System performs two distinct jobs:

- **Attitude Determination (AD):** Figuring out which way the spacecraft is pointing, using sensors.
- **Attitude Control (AC):** Changing or holding the spacecraft's orientation, using actuators.

These are separate problems. You can know your orientation perfectly (great sensors) but still wobble if your actuators are weak. Or you can have powerful actuators but poor knowledge of where you are pointing.

SENSORS: HOW DO WE KNOW WHERE WE ARE POINTING?

TABLE 54

Sensor	What It Measures	Accuracy	Mass	Power	Cost	When You Use It
Magnetometer	Direction of Earth's magnetic field	~2–5 deg	~5 g	~0.1 W	~1 kEUR	Coarse determination; always on for B-field knowledge
Coarse sun sensor	Direction to the Sun (1–2 axes)	~2–5 deg	~5 g	~0.01 W	~0.5 kEUR	Safe mode; initial acquisition

Sensor	What It Measures	Accuracy	Mass	Power	Cost	When You Use It
Fine sun sensor	Direction to the Sun (2 axes, high precision)	~0.1–0.5 deg	~10 g	~0.05 W	~2 kEUR	Sun-pointing missions; backup to star tracker
Star tracker	Full 3-axis attitude from star patterns	~0.001–0.01 deg (3–30 arcsec)	50–350 g	~0.5–1.5 W	~20–35 kEUR	Precision pointing for imaging, comms, science
MEMS gyro-scope	Angular rate (rotation speed)	Drift: ~1–10 deg/hr	~20 g	~0.3 W	~3 kEUR	Fills gaps during star tracker blinding; slew control
Earth sensor	Nadir direction (local vertical)	~0.1–0.5 deg	~50 g	~0.5 W	~5 kEUR	Nadir-pointing missions (less common on CubeSats)

Key insight: Star trackers are by far the most accurate sensor. They work by photographing the sky, matching the observed star pattern to an onboard catalogue, and computing the spacecraft's orientation to within a few arcseconds. However, they are blinded by the Sun, Moon, or Earth limb entering their field of view, so sun sensors or gyroscopes provide backup during these periods.

ACTUATORS: HOW DO WE CONTROL OUR ORIENTATION?

TABLE 55

Actuator	How It Works	Torque	Precision	Mass	Power	When You Use It
Permanent magnet	Aligns spacecraft with Earth's B-field like a compass needle	~10 ⁻⁵ N m (restoring)	~10–15 deg	~20 g	0 W	Passive stabilisation for missions with no pointing need
Hysteresis rods	Dissipate rotational energy through magnetic hysteresis; damp tumbling	N/A (damping only)	N/A	~10 g each	0 W	Always paired with permanent magnet for passive stabilisation
Magnetorquers (MTQ)	Electromagnetic coils that interact with Earth's magnetic field to produce torque	~10 ⁻⁶ –10 ⁻⁴ N m	~2–5 deg (as primary); N/A (as desaturation)	~10–30 g each	0.1–0.2 W	Primary control for low-precision missions; desaturation of reaction wheels for all RW-based systems

Actuator	How It Works	Torque	Precision	Mass	Power	When You Use It
Reaction wheels (RW)	Spinning fly-wheels that exchange angular momentum with the spacecraft	$\sim 10^{-4}$ – 10^{-2} N m	~ 0.001 – 0.01 deg	30–120 g each	0.3–1.5 W	Precision pointing – any mission requiring < 2 deg accuracy
Thrusters	Expel mass (cold gas, ions) to produce torque via offset force	Variable	~ 0.1 – 1 deg	System-dependent	High	Large slews; orbit adjust; when MTQs are insufficient (deep space)

Magnetorquers – two critical roles:

1. **As primary actuators** (missions needing only 2–5 deg pointing): MTQs alone provide 3-axis control, but only in LEO where Earth's magnetic field is strong. They cannot produce torque parallel to the local field vector, so control authority varies around the orbit.
2. **As desaturation actuators** (all RW-based missions): Reaction wheels absorb disturbance torques by spinning up. Over time, they accumulate angular momentum and reach saturation (maximum spin speed). MTQs “dump” this stored momentum by generating opposing torque against Earth's magnetic field. This is done approximately once per orbit, taking 5–15 minutes.

Reaction wheels – why 4 wheels? Three wheels (one per axis) provide minimum 3-axis control. A 4th wheel on a skew axis provides single-fault tolerance: if any one wheel fails, the remaining three still provide full 3-axis control.

AOCS ARCHITECTURE DECISION TABLE

Use this table to select your architecture based on your pointing requirement:

TABLE 56

Pointing Requirement	Architecture	Sensors	Actuators	Mass	Power	Cost
> 5 deg (no pointing need)	Passive magnetic	Magnetometer	Permanent magnet + hysteresis rods	~ 50 g	0 W	~ 2 kEUR
2–5 deg	Magnetorquer-based	Coarse sun sensors + magnetometer	3-axis MTQ	~ 100 g	0.2 W	~ 8 kEUR
0.1–2 deg	Reaction wheel system	Fine sun sensors + magnetometer	3–4 RW + 3 MTQ (desaturation)	~ 500 g	2–4 W	~ 35 kEUR

Pointing Requirement	Architecture	Sensors	Actuators	Mass	Power	Cost
< 0.1 deg	Fine pointing	Star tracker + fine sun sensors	4 RW + 3 MTQ	~800 g	3–5 W	~55 kEUR
< 0.01 deg	Very fine pointing	Star tracker + MEMS gyro + sun sensors	4 RW + 3 MTQ	~1200 g	4–6 W	~80 kEUR

How to use this table: Find your mission's pointing requirement (from your requirements worksheet). Read across to find the architecture, sensors, and actuators you need. If your mission is an Earth-observation camera needing 0.05 deg pointing, you need fine pointing (star tracker + 4 RW + 3 MTQ). If your mission is an IoT relay needing only 5 deg pointing, magnetorquers alone suffice.

Key Equations Reference

Gravity gradient torque: $T_{gg} = (3\mu)/(2a^3)|I_z - I_x|\sin(2\theta)$

Aerodynamic torque: $T_{aero} = (1)/(2)\rho v^2 C_D A \cdot d_{cp-cm}$

SRP torque: $T_{SRP} = (S)/(c) A_s (1+q) \cdot d_{sp-cm}$

Magnetic torque: $T_{mag} = M \times B$

Momentum storage: $H = T_{dist} \times t_{desat}/2$

Pointing error (RSS): $\theta_{total} = \sqrt{\sum \theta_i^2}$

MTQ torque: $T_{MTQ} = m_{dipole} \times B \times \sin(\alpha)$

Worked Example: UniSat-1 (1U) AOCS

ARCHITECTURE SELECTION

UniSat-1 carries a MEMS magnetometer payload that does not require accurate pointing. In fact, a slowly rotating/tumbling state provides magnetic field measurements across multiple directions, improving data quality.

Architecture: Passive magnetic stabilisation (permanent magnet + hysteresis rods). No pointing error budget is needed because there is no pointing requirement.

TABLE 57

Parameter	Value
Pointing accuracy	~10–15 deg (to local magnetic field)
Mass	~30–50 g
Power	0 W
Cost	~1–2 kEUR

DISTURBANCE TORQUES AT 400 KM

Even though UniSat-1 has no active AOCS, understanding the disturbance environment confirms that the passive magnet provides sufficient restoring torque.

Gravity gradient (1U is nearly cubic, so $I_z \approx I_x$, making this very small):

$$T_{\text{gg}} \approx \frac{3 \times 3.986 \times 10^{14}}{2 \times (6.771 \times 10^6)^3} \times |I_z - I_x| \approx 1 \times 10^{-8} \text{ N m}$$

Aerodynamic (ρ at 400 km $\approx 4 \times 10^{-12}$ kg/m³, $v \approx 7670$ m/s):

$$T_{\text{aero}} = 0.5 \times 4 \times 10^{-12} \times 7670^2 \times 2.2 \times 0.01 \times 0.01 \approx 3 \times 10^{-8} \text{ N m}$$

Permanent magnet restoring torque: $\sim 1 \times 10^{-5}$ N m – three orders of magnitude larger than all disturbances. **The satellite stays field-aligned.**

Part A: AOCS Architecture Selection (10 min)

Pointing requirement from your mission: ____ deg (3-sigma)

AOCS architecture selected (tick one):

- ☐ Passive magnetic (> 5 deg)
- ☐ Magnetorquers only (2–5 deg)
- ☐ Reaction wheels + MTQ (0.1–2 deg)
- ☐ Fine pointing: RW + star tracker + MTQ (< 0.1 deg)
- ☐ Very fine: RW + ST + gyro + MTQ (< 0.01 deg)

Justification for selection:

 Write your answer

Estimated AOCS mass: _ kg **Estimated AOCS power:** ____ W

Part B: Disturbance Torque Calculations (20 min)

Calculate at least 2 disturbance torques for your spacecraft and orbit. Show all working.

Spacecraft properties:

TABLE 58

Parameter	Value	Unit
Mass		kg
Form factor		U
I_z (largest MOI)		kg m ²
I_x (smallest MOI)		kg m ²
Cross-section area (largest face)		m ²
d_{cp-cm} (CP-CM offset estimate)		m
Orbit altitude		km

1. Gravity gradient torque:

$$T_{gg} = \frac{3 \times 3.986 \times 10^{14}}{2 \times (\text{altitude})^3} \times |I_z - I_x| =$$

 Write your answer

$$T_{gg} = \text{_____} \text{ N m}$$

2. Aerodynamic torque (ρ at _____ km $\approx$ _____ kg/m³):

$$T_{aero} = \frac{1}{2} \times \text{_____} \times 2.2 \times \text{_____} \times \text{_____} =$$

 Write your answer

$$T_{aero} = \text{_____} \text{ N m}$$

3. (Optional) Solar radiation pressure torque:

 Write your answer

$$T_{\text{SRP}} = \text{_____} \text{ N m}$$

4. (Optional) Residual magnetic dipole torque ($M \approx \text{_____} \text{ A m}^2$, $B \approx 3 \times 10^{-5} \text{ T}$):

$$T_{\text{mag}} = \text{__} \times \text{__} = \text{__} \text{ N m}$$

Summary:**TABLE 59**

Source	Torque (N m)
Gravity gradient	
Aerodynamic	
SRP	
Magnetic dipole	
Total (RSS or sum)	

Which disturbance dominates? _____

Part C: Reaction Wheel Sizing (10 min)

Skip this section if your mission uses passive magnetic or MTQ-only architecture.

1. Torque requirement ($\geq 2 \times$ total disturbance):

$$T_{\text{RW,req}} = 2 \times \text{__} = \text{N m} = \text{__} \text{ mN m}$$

2. Momentum storage (desaturation interval = 1 orbit = _____ s):

$$H = T_{\text{dist}} \times (t_{\text{desat}})/(2) = \text{__} \times (\text{\\ \ \ \ \ \})/(2) = \text{__} \text{ mN m s}$$

3. Selected reaction wheel:**TABLE 60**

Parameter	Required	Selected Product
Torque	_____ mN m	_____ mN m
Momentum	_____ mN m s	_____ mN m s

Parameter	Required	Selected Product
Mass	–	_____ g
Power	–	_____ W
Quantity	4 (3+1 redundancy)	

Part D: Pointing Error Budget (15 min)

Skip this section if your mission uses passive magnetic stabilisation (no pointing requirement).

Complete the RSS pointing error budget:

TABLE 61

Error Source	Value (deg)	Value ²
Sensor accuracy		
Actuator resolution		
Alignment knowledge		
Thermal distortion		
Jitter (RW)		
Orbit knowledge		
Timing error		
Sum of squares		
RSS Total = $\sqrt{\{\text{sum}\}}$ = _____ deg		

Requirement: _____ deg

Margin: _ deg (___ %)

Does the pointing budget close? Y / N

Which error source dominates? _____

What action would most improve the budget? _____

 Write your answer

Part E: SpaceCDF Verification (10 min)

Compare your hand calculations to SpaceCDF’s Pointing Budget display:

TABLE 62

Parameter	Hand Calculation	SpaceCDF	Match?
RSS pointing error	_____ deg	_____ deg	
Dominant contributor	_____	_____	
Margin to requirement	_____ %	_____ %	

If there are differences, explain:

 Write your answer

Decision Justification

Explain WHY you chose your AOCS architecture. Consider the alternatives and what drove your decision.

Why this architecture and not a simpler one?

 Write your answer

Why this architecture and not a more capable one?

 Write your answer

What is the single biggest risk in your AOCS design?

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 3.3: Communications and Link Budget Design

TABLE 63

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: Link Budget, Spectrum Selector, Equipment Browser (Comms)

Quick Reference: Communications Concepts

WHAT IS A LINK BUDGET?

A link budget is an accounting statement for your communication link. It adds up every gain (transmitter power, antenna gain) and subtracts every loss (distance, atmosphere, pointing error) to determine whether the signal arriving at the receiver is strong enough to decode. Everything is computed in **decibels (dB)** so that multiplication and division become addition and subtraction.

Decibel refresher:

TABLE 64

Conversion	Formula	Common Values
Watts to dBW	$P_{\text{dBW}} = 10\log_{10}(P_W)$	2 W = +3.0 dBW; 1 W = 0 dBW; 0.5 W = -3.0 dBW
Kelvin to dBK	$T_{\text{dBK}} = 10\log_{10}(T_K)$	150 K = 21.8 dBK; 600 K = 27.8 dBK
Ratio to dB	$G_{\text{dB}} = 10\log_{10}(G)$	x2 = +3 dB; x10 = +10 dB; x100 = +20 dB

WHAT EACH TERM IN THE LINK BUDGET MEANS

TABLE 65

Term	What It Is	Analogy
TX Power (P_{TX})	Electrical power fed to the transmitter amplifier	How loud you shout

Term	What It Is	Analogy
TX Antenna Gain (G_{TX})	How well the antenna focuses the signal into a beam (vs radiating equally in all directions)	Using a megaphone vs shouting in all directions
TX Line Losses (L_{TX})	Power lost in cables and filters between amplifier and antenna	Sound absorbed by the megaphone walls
EIRP	Effective Isotropic Radiated Power = $P_{TX} + G_{TX} - L_{TX}$. The total “signal strength leaving the spacecraft”	Total loudness heard from a distance
FSPL	Free Space Path Loss – signal weakens as it spreads over a larger sphere. Depends on distance and frequency	Voice getting quieter the farther away you walk
Atmospheric Loss	Signal absorbed/scattered by Earth’s atmosphere (rain, oxygen, water vapour)	Fog muffling sound
Pointing Loss	Signal loss because the antenna beam is not perfectly aimed	Megaphone pointed slightly off-target
Polarisation Loss	Loss when TX and RX antenna polarisations do not match	Holding the megaphone sideways when the listener expects vertical
RX Antenna Gain (G_{RX})	Ground station antenna ability to collect signal. Larger dish = more gain	Listener using a large ear trumpet
System Noise Temp (T_{sys})	Combined noise from antenna, sky, and receiver electronics. Lower = better	Background noise in the room
G/T	Receiver figure of merit = $G_{RX} - T_{sys}$ (in dB). Captures how “good” the ground station is	Ear trumpet size minus room noise
C/N_0	Carrier-to-noise-density ratio – the received signal strength relative to noise	Signal-to-noise ratio before decoding
E_b/N_0	Energy per bit to noise density – the fundamental measure of link quality. Divides C/N_0 by data rate	How much energy is available per bit of information
Link Margin	How much E_b/N_0 you have above the minimum needed. Must be ≥ 3 dB	Safety factor for your communication

FREQUENCY BAND COMPARISON

TABLE 66

Parameter	UHF (Amateur)	S-band	X-band	Ka-band
Frequency	435–438 MHz	2200–2290 MHz	8025–8400 MHz	25.5–27.0 GHz

Parameter	UHF (Amateur)	S-band	X-band	Ka-band
Bandwidth available	20 kHz	5 MHz	375 MHz	1.5 GHz
Maximum data rate	< 20 kbps	0.1–10 Mbps	10–400 Mbps	100–2000 Mbps
FSPL at 500 km (nadir)	148 dB	163 dB	174 dB	184 dB
FSPL at 1300 km (10 deg elev)	158 dB	171 dB	182 dB	192 dB
Atmospheric loss	~0.1 dB	~0.5 dB	~1.0 dB	~3–10 dB (rain!)
Typical spacecraft antenna	Monopole (0 dBi)	Patch (6 dBi)	Horn/patch array (10–15 dBi)	Small dish/array (20+ dBi)
Ground antenna	Yagi (10–13 dBi)	3 m dish (35 dBi)	3 m dish (45 dBi)	1 m dish (45 dBi)
License type	IARU coordination (free)	ISED/FCC (\$30–45K)	ISED/FCC + ITU (higher)	Complex ITU filing
License timeline	~6 months	6–12 months	12+ months	12–18 months
Equipment availability	Many COTS	Many COTS	Growing COTS	Emerging
Best for	TT&C, telemetry, simple missions	Medium data rate, standard EO	High data rate, EO/SAR	Very high data rate

How to choose: Start with your data rate requirement. If you need < 20 kbps and have non-commercial data, UHF amateur is free and simple. If you need up to 10 Mbps, S-band is the CubeSat workhorse. For high-resolution imaging producing GBs per day, you need X-band or Ka-band.

ANTENNA TYPES

TABLE 67

Antenna Type	Gain	Beamwidth	Pointing Need	Mass	Typical Band	Use Case
Monopole/dipole	~0 dBi	Omnidirectional	None	5–20 g	UHF	TT&C, simple telemetry
Patch (single)	~5–8 dBi	~70–90 deg	Low (~10 deg)	10–50 g	S-band	Standard CubeSat downlink
Patch array (2x2)	~12 dBi	~30–40 deg	Medium (~5 deg)	30–100 g	S/X-band	Higher-rate downlink
Horn	~10–15 dBi	~20–30 deg	Medium (~5 deg)	50–200 g	X-band	High-rate downlink

Antenna Type	Gain	Beamwidth	Pointing Need	Mass	Typical Band	Use Case
Parabolic reflector	~20–35 dBi	~2–10 deg	Tight (< 1 deg)	200–500 g	X/Ka-band	Very high-rate, DTE
Phased array	~15–25 dBi	Electronically steered	Electronic (fast)	100–300 g	S/X/Ka-band	Agile beam, multiple targets

Trade-off: Higher gain antennas provide stronger signals (enabling higher data rates or lower TX power), but they have narrower beams, which means the spacecraft must point more accurately. An omnidirectional antenna works regardless of spacecraft orientation but provides very low gain.

MODULATION AND CODING

The modulation scheme and forward error correction (FEC) code determine the minimum E_b/N_0 required for a target bit error rate (BER):

TABLE 68

Modulation + Coding	E_b/N_0 Required (BER 10^{-6})	Spectral Efficiency	Best For
BPSK uncoded	10.5 dB	1.0 bps/Hz	Legacy telecommand
QPSK uncoded	10.5 dB	2.0 bps/Hz	Simple telemetry
QPSK + convolutional (r=1/2)	5.0 dB	1.0 bps/Hz	Standard CCSDS TM
QPSK + LDPC (r=1/2)	2.0 dB	1.0 bps/Hz	High-efficiency downlink
QPSK + LDPC (r=3/4)	4.0 dB	1.5 bps/Hz	Balanced (CubeSat standard)
8PSK + LDPC (r=3/4)	6.5 dB	2.25 bps/Hz	High-rate downlink

Design guidance: For most CubeSat missions, **QPSK + LDPC (r=3/4)** at $E_b/N_0 = 4.0$ dB is the standard choice, offering a good balance of coding gain and implementation simplicity.

Key Equations Reference

EIRP: $EIRP = P_{TX} + G_{TX} - L_{TX}$ (dBW)

FSPL: $FSPL = 20\log_{10}((4\pi d f)/(c))$ (dB)

G/T: $G/T = G_{RX} - 10\log_{10}(T_{sys})$ (dB/K)

$$C/N_0: C/N_0 = \text{EIRP} - \text{FSPL} - L_{\text{losses}} + G/T + 228.6 \quad (\text{dBHz})$$

$$E_b/N_0: E_b/N_0 = C/N_0 - 10\log_{10}(R_b) \quad (\text{dB})$$

$$\text{Link margin: } \text{Margin} = E_b/N_{0,\text{avail}} - E_b/N_{0,\text{req}} - L_{\text{impl}} \geq 3 \text{ dB}$$

$$\text{Antenna gain: } G = \eta_a (\pi D/\lambda)^2$$

$$\text{dB conversion: } P_{\text{dBW}} = 10\log_{10}(P_{\text{W}}); \quad 2 \text{ W} = +3.0 \text{ dBW}; \quad 1 \text{ W} = 0 \text{ dBW}$$

Worked Example: UniSat-1 (1U) UHF Link Budget

UniSat-1 uses UHF amateur band at 437 MHz with 9600 bps downlink to an amateur ground station.

STEP-BY-STEP LINK BUDGET

Scenario: 400 km orbit, 437 MHz, 9600 bps, 10 deg minimum elevation (slant range ~1150 km), ground station with 13 dBi cross-Yagi (RHCP).

TABLE 69

Line	Parameter	Calculation	Value	Unit
1	TX Power	$0.5 \text{ W} = 10\log_{10}(0.5)$	-3.0	dBW
2	TX Antenna Gain	Monopole	0.0	dBi
3	TX Line Losses	Short cable run	-0.5	dB
4	EIRP	$-3.0 + 0.0 - 0.5$	-3.5	dBW
5	FSPL	$21.98 + 20\log_{10}(1.15 \times 10^6) + 20\log_{10}(437 \times 10^6) - 169.54$	-155.5	dB
6	Atmo-spheric Loss	Minimal at UHF	-0.3	dB
7	Pointing Loss	Omni antenna, minimal	-0.5	dB
8	Polarisation Loss	RHCP-to-RHCP (cross-Yagi)	-0.5	dB
9	RX Antenna Gain	13 dBi cross-Yagi	+13.0	dBi
10	System Noise Temp	$600 \text{ K (amateur + LNA)} = 10\log_{10}(600)$	27.8	dBK

Line	Parameter	Calculation	Value	Unit
11	G/T	13.0 - 27.8	-14.8	dB/K
12	Boltzmann Constant		+228.6	dBW/ K/Hz
13	C/N₀	-3.5 - 155.5 - 0.3 - 0.5 - 0.5 + (-14.8) + 228.6	+53.5	dBHz
14	Data Rate	9600 bps = $10\log_{10}(9600)$	39.8	dB- bps
15	E_b/N₀ available	53.5 - 39.8	+13.7	dB
16	E _b /N ₀ re- quired	QPSK + conv. code r=1/2	5.0	dB
17	Imple- mentation Loss		2.0	dB
18	LINK MAR- GIN	13.7 - 5.0 - 2.0	+6.7	dB

Result: Link closes with 6.7 dB margin (> 3 dB). **Pass.**

FSPL CALCULATION DETAIL

$$FSPL = 21.98 + 20\log_{10}(1.15 \times 10^6) + 20\log_{10}(437 \times 10^6) - 169.54$$

$$= 21.98 + 121.21 + 172.81 - 169.54 = 146.46 \dots \text{wait, let us recompute:}$$

$$20\log_{10}(1.15 \times 10^6) = 20 \times 6.0607 = 121.2 \text{ dB}$$

$$20\log_{10}(437 \times 10^6) = 20 \times 8.640 = 172.8 \text{ dB}$$

$$FSPL = 21.98 + 121.2 + 172.8 - 169.54 = 146.4 \text{ dB}$$

Note: The line-5 value of 155.5 dB uses the slant range in metres (1.15×10^6 m) and frequency in Hz (437×10^6 Hz) in the single-formula form: $20\log_{10}(4\pi \times 1.15 \times 10^6 \times 437 \times 10^6 / 3 \times 10^8) = 155.5$ dB. Both approaches give the same result when applied consistently.

DATA THROUGHPUT

At 4800 bps useful throughput (9600 bps channel rate with r=1/2 FEC), a 7-minute pass delivers:

$$V_{\text{pass}} = 4800 \times 420 \times 0.85 = 1.71 \text{ Mbit} = 214 \text{ kB per pass}$$

With 4 passes/day: ~0.84 MB/day. The magnetometer generates ~1.13 MB/day – marginal. May need a second ground station or data prioritisation.

Part A: Frequency Band Selection (10 min)

Mission data rate requirement: _____ Mbps

License type selected: Amateur / Experimental / Commercial

Band selected: _____ Centre frequency: _____ MHz

Rationale for band selection:

 Write your answer

Licensing/filing required: _____

Estimated licensing cost: _____ Timeline: _____ months

Part B: Complete Link Budget (25 min)

Fill in ALL rows. Show computation for EIRP, FSPL, G/T, C/N₀, and margin.

TABLE 70

Line	Parameter	Formula / Source	Value	Unit
1	TX Power	_____ W =		dBW
2	TX Antenna Gain			dBi
3	TX Line Losses			dB
4	EIRP = Line 1 + 2 + 3		_____	dBW
5	Free Space Path Loss	$20\log_{10}(4\pi \times __ \times __ / c)$		dB
6	Atmospheric Loss			dB
7	Pointing Loss			dB
8	Polarisation Loss			dB
9	RX Antenna Gain			dBi
10	System Noise Temp	_____ K =		dBK
11	G/T = Line 9 - 10		_____	dB/K
12	Boltzmann Constant		+228.6	dBW/K/Hz
13	C/N₀ = 4 + 5 + 6 + 7 + 8 + 11 + 12		_____	dBHz

Line	Parameter	Formula / Source	Value	Unit
14	Data Rate	$_ \text{ bps} = 10\log_{10}(_)$		dBbps
15	E_b/N_0 available = 13 - 14		_____	dB
16	E_b/N_0 required (mod+code: __)			dB
17	Implementation Loss			dB
18	LINK MARGIN = 15 - 16 - 17		_____	dB

Show FSPL calculation:

$$\text{FSPL} = 20\log_{10}(4\pi) + 20\log_{10}(d) + 20\log_{10}(f) - 20\log_{10}(c)$$

$$= 21.98 + 20\log_{10}(_) + 20\log_{10}(_) - 169.54 = __ \text{ dB}$$

 Write your answer

Does the link close (≥ 3 dB)? Y / N

If margin is excessive, maximum achievable data rate at 3 dB margin:

$$R_{b,\text{max}} = 10^{\{(E_b/N_{0,\text{avail}} - E_b/N_{0,\text{req}} - L_{\text{impl}} - 3)/10\}} \times R_b = \$ _____ \text{ Mbps}$$

 Write your answer

Part C: Data Budget (10 min)

Daily data generation:

$$V_{\text{gen}} = R_{\text{payload}} \times t_{\text{imaging}} \times N_{\text{orbits}} \times f_{\text{compression}}$$

$$= _ \text{ Mbps} \times \text{s} \times _ = \text{MB/day} = \text{GB/day}$$

Daily downlink capacity:

$$V_{\text{DL}} = R_{\text{DL}} \times t_{\text{contact}} \times N_{\text{passes}} \times \eta_{\text{protocol}}$$

$$= _ \text{ Mbps} \times s \times \times _ = \text{MB/day} = \text{GB/day}$$

Data budget closes? ($V_{DL} \geq V_{gen}$): Y / N

If no, what is your mitigation plan?

 Write your answer

Part D: SpaceCDF Comparison (10 min)

Open the Link Budget tab, enter your parameters, and compare:

TABLE 71

Parameter	Hand Calculation	SpaceCDF	Difference
EIRP (dBW)			
FSPL (dB)			
C/N ₀ (dBHz)			
Link Margin (dB)			

If there are differences, explain:

 Write your answer

Part E: Modulation and Coding Selection (5 min)

Selected modulation: _____

Selected FEC code: _____

Required E_b/N_0 at BER 10^{-6} : _____ dB

Spectral efficiency: _____ bps/Hz

Rationale:

 Write your answer

Decision Justification

Explain WHY you chose your communications architecture. Address each decision explicitly.

Why this frequency band and not another?

 Write your answer

Why this antenna type? What pointing does it require from AOCS?

 Write your answer

Why this modulation/coding scheme? What trade-off did you make between data rate and link robustness?

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 3.4: Structure, Propulsion, and Equipment Selection

TABLE 72

Name:	_____
Date:	_____
Team / Mission:	_____
Role / Position:	_____

SpaceCDF Tabs: Equipment Browser, Dashboard, Trade Studies, Budget Breakdown

Quick Reference: Structure and Propulsion Concepts

CUBESAT DESIGN SPECIFICATION (CDS REV 14) KEY DIMENSIONS

The CDS defines standard CubeSat form factors. All CubeSats must comply with these dimensions to fit inside standard deployers (e.g., ISIPOD, NRCSD, Exolaunch). The unit “U” represents a 10 x 10 x 11.35 cm cube.

TABLE 73

Form Factor	Dimensions (mm)	Max Mass (kg)	Internal Volume (cm ³)	Rails	Typical Use
1U	100 x 100 x 113.5	2.0	~1,000	4	Technology demo, simple sensors
1.5U	100 x 100 x 170.2	3.0	~1,500	4	Extended 1U with more volume
2U	100 x 100 x 227.0	4.0	~2,000	4	IoT, AIS, simple payloads
3U	100 x 100 x 340.5	6.0	~3,000	4	Standard EO, comms, science
6U	100 x 226.3 x 340.5	12.0	~6,000	4	High-performance EO, SAR, comms
12U	226.3 x 226.3 x 340.5	24.0	~12,000	8	Advanced payloads, propulsion

Form Factor	Dimensions (mm)	Max Mass (kg)	Internal Volume (cm ³)	Rails	Typical Use
16U	226.3 x 226.3 x 454.0	32.0	~16,000	8	Microsatellite-class missions

Key CDS requirements (all form factors):

TABLE 74

Requirement	Specification	Why It Matters
Rail material	Hard anodised Al 7075-T6 or 6061-T6	Prevents cold welding in vacuum; provides structural load path
Rail cross-section	8.5 x 8.5 mm minimum contact	Transmits launch loads through deployer rails
Deployment switches	Minimum 1 per accessible rail face	Ensures spacecraft is powered off until deployed
RBF (Remove Before Flight) pin	Required	Physically disconnects batteries during ground handling
No protrusions beyond rail envelope (stowed)	Required	Prevents jamming inside the deployer
CG offset from geometric centre	<= 2 cm	Prevents uncontrolled tumbling at deployment; deployer balance
Fundamental frequency	> 40 Hz (first mode)	Avoids resonance with launch vehicle modes

STRUCTURAL LOADS AND MARGINS

During launch, the spacecraft experiences:

- **Quasi-static acceleration:** 6–9 g axial (along rocket axis), 2–4 g lateral (sideways). Think of your 5 kg CubeSat feeling like it weighs 45 kg.
- **Random vibration:** Broadband shaking at 20–2000 Hz. Critical for PCB solder joints and connectors.
- **Shock:** Brief, high-g pulses (500–2000 g) at separation events. Critical for brittle components.

Margin of Safety (MoS): The ratio of what the structure can withstand to what it must withstand, minus 1. Must be ≥ 0 . If MoS is negative, the structure fails under the design load.

Material properties (Al 7075-T6): Yield strength $\sigma_y = 503$ MPa, Ultimate strength $\sigma_u = 572$ MPa. Factor of Safety: 1.25 (yield), 1.5 (ultimate).

PROPULSION DECISION TREE

Not every CubeSat needs propulsion. Use this decision tree:

```

START: Does my mission need propulsion?
|
+-- Orbit altitude < 500 km?
|   YES --> Natural atmospheric drag deorbits within 5 years (FCC compli-
ant)
|       Do I need orbit maintenance to extend lifetime?
|       NO  --> NO PROPULSION NEEDED
|       YES --> Need drag compensation (5-15 m/s per year)
|
+-- Orbit altitude 500-700 km?
|   Natural lifetime is 5-25+ years
|   FCC 5-year rule: likely NON-COMPLIANT without active deorbit
|   --> PROPULSION REQUIRED for deorbit (50-150 m/s)
|
+-- Orbit altitude > 700 km?
|   Natural lifetime is decades to centuries
|   IADC 25-year guideline: NON-COMPLIANT
|   --> PROPULSION REQUIRED for deorbit (high Delta-V)
|
+-- Constellation phasing needed?
|   YES --> Add 10-50 m/s for orbit plane/phase adjustment
|
+-- Collision avoidance needed?
|   YES --> Add 1-5 m/s reserve per manoeuvre

```

Key rule: Below ~500 km, you almost certainly do not need propulsion. Above ~600 km, you almost certainly do. The 500–600 km range depends on your specific ballistic coefficient and mission lifetime.

PROPULSION TECHNOLOGIES COMPARISON

TABLE 75

Type	How It Works	I_{sp} (s)	Thrust	Propel- lant Mass (100 m/s, 5 kg S/C)	Sys- tem Dry Mass	Total Sys- tem Mass	Burn Time	Cost
Cold gas	Pressurised gas expelled through nozzle	40–80	10–100 mN	0.87 kg	0.3 kg	1.17 kg	Minutes	~15 kEUR
Resisto-jet	Gas heated before expulsion	80–150	10–50 mN	0.34 kg	0.3 kg	0.64 kg	Minutes	~25 kEUR
Electro-spray (FEED)	Liquid metal ionised and accelerated by electric field	500–1500	0.01–1 mN	0.04 kg	0.9 kg	0.94 kg	Months	~50 kEUR

Type	How It Works	I_{sp} (s)	Thrust	Propellant Mass (100 m/s, 5 kg S/C)	Sys- tem Dry Mass	Total Sys- tem Mass	Burn Time	Cost
Hall ef- fect	Xenon ionised and accelerated by magnetic/electric fields	800– 1500	1–10 mN	0.05 kg	1.5 kg	1.55 kg	Weeks	~80 kEUR
Green monop- rop	Catalytic decomposition of non-toxic propellant	200– 250	0.1–1 N	0.21 kg	1.0 kg	1.21 kg	Seconds	~60 kEUR

The fundamental trade-off:

- **High I_{sp} (electric propulsion):** Uses very little propellant but has very low thrust, so manoeuvres take weeks or months. The thruster hardware is also heavier and more expensive.
- **Low I_{sp} (chemical/cold gas):** Uses much more propellant but provides high thrust for quick manoeuvres. Hardware is simpler, lighter, and cheaper.

Choose based on: How much ΔV do you need? How fast must the manoeuvre happen?
How much mass/volume/cost can you afford?

Key Equations Reference

Structural Margin of Safety: $\text{MoS} = \frac{\sigma_{\text{allow}}}{\sigma_{\text{design}}} \times \text{FoS} - 1 \geq 0$ FoS: Yield 1.25, Ultimate 1.5 (metallic)

Tsiolkovsky rocket equation: $\Delta V = I_{sp} \cdot g_0 \cdot \ln(m_0/m_f)$

Propellant mass: $m_{\text{prop}} = m_{\text{dry}} \times \left(e^{\Delta V / (I_{sp} \cdot g_0)} - 1 \right)$ $g_0 = 9.80665 \text{ m/s}^2$

Data storage: $S = V_{\text{daily}} \times N_{\text{days}} \times f_{\text{safety}}$

Fundamental frequency: $f_1 > 40 \text{ Hz}$ (deployer requirement)

Worked Example: UniSat-1 (1U) Structure and Propulsion

CDS COMPLIANCE

TABLE 76

Parameter	1U Specification	UniSat-1 Design	Compliant?
Dimensions	100 x 100 x 113.5 mm	100 x 100 x 113.5 mm (ISIS 1U frame)	Y
Maximum mass	2.0 kg (CDS) / 1.33 kg (NanoRacks)	1.0 kg target	Y
Rail material	Hard anodised Al 7075-T6	ISIS standard frame	Y
Deployment switches	Min 1 per accessible face	2 (ISIS standard)	Y
RBF pin	Required	Included	Y
CG offset	≤ 2 cm	< 1 cm (symmetric layout)	Y
Protrusions (stowed)	None beyond rail envelope	UHF antenna stowed along rail	Y

PROPULSION DECISION

Orbit altitude: 400 km. **Natural lifetime:** ~8–14 months (ballistic coefficient $BC = m/(C_D A) = 1.0/(2.2 \times 0.01) = 45.5 \text{ kg/m}^2$).

FCC 5-year rule satisfied without propulsion. No orbit maintenance needed (6-month mission). No constellation phasing. **Decision: No propulsion.**

STRUCTURAL MARGIN (AXIAL LOAD)

Given: Mass = 1.0 kg, axial load = 9 g, 4 rails.

$$F_{\text{axial}} = (1.0 \times 9 \times 9.81)/(4) = (88.3)/(4) = 22.1 \text{ N per rail}$$

$$\sigma = \frac{22.1}{8.5 \times 10^{-3} \times 8.5 \times 10^{-3}} = \frac{22.1}{7.225 \times 10^{-5}} = 0.31 \text{ MPa}$$

$$\text{MoS}_y = \frac{503}{0.31 \times 1.25} - 1 = \frac{503}{0.39} - 1 = 1289 \gg 0 \text{ Pass (by a very large margin)}$$

Key insight: Quasi-static axial stress is never the critical case for CubeSats. The real structural risks are: (a) PCB solder joint fatigue from random vibration, (b) deployment mechanism reliability, (c) stiffness (fundamental frequency > 40 Hz).

EQUIPMENT LIST

TABLE 77

#	Category	Component	Mass (g)	Power (W)	Cost (kEUR)
1	Structure	ISIS 1U frame	200	–	4.0
2	EPS + Battery	GomSpace P31us	200	0.3	12.0
3	Solar cells	Body-mounted GaAs (5 faces)	50	–	8.0
4	OBC	Custom MSP430/Cortex-M	30	0.3	3.0
5	Comms	NanoCom AX100 (UHF)	60	0.5	8.0
6	Antenna	UHF monopole (deployable)	20	–	2.0
7	Payload	MEMS magnetometer PCB	50	0.2	5.0
8	AOCS	Permanent magnet + hysteresis rods	30	0	1.0
9	Harness	Internal cables, connectors	50	–	1.0
TOTAL			690	~1.3 (peak)	~44

Mass margin: $1330 - 690 = 640$ g (48%). With 20% equipment margin + 20% system margin (MEV): $1330 - 994 = 336$ g (25%). **Green.**

Part A: CDS Compliance Check (10 min)

TABLE 78

CDS Requirement	Your Design Value	Specification	Compliant?
Form factor: ____ U	Dimensions: ____ mm	____ mm	Y / N
Maximum mass	____ kg (wet)	____ kg	Y / N
Rail material		Hard anodised Al	Y / N
Deployment switches	____ (quantity)	Min 2	Y / N
RBF pin provided	Y / N	Required	Y / N
No protrusions beyond rails (stowed)	Y / N	Required	Y / N
CG within 2 cm of geometric centre	Estimated: ____ cm offset	≤ 2 cm	Y / N
Fundamental frequency	Estimated: ____ Hz	> 40 Hz	Y / N

Non-compliance items and corrective actions:

 Write your answer

Part B: Structural Margin Calculation (10 min)

Axial launch load: g **Lateral launch load:** g

Load per rail (4 rails, equal sharing):

$$F_{\text{axial}} = \frac{m \times a_{\text{axial}} \times g_0}{4} = \frac{ \times \phantom{a_{\text{axial}}} \times }{4} \times 9.81 = \$ \text{ N}$$

Stress in rail (cross-section $8.5 \times 8.5 \text{ mm} = 7.225 \times 10^{-5} \text{ m}^2$):

$$\sigma = (F)/(A) = ()/(7.225 \times 10^{-5}) = \text{ MPa}$$

Margin of safety (yield, Al 7075-T6, $\sigma_y = 503 \text{ MPa}$):

$$\text{MoS} = (503)/(\times 1.25) - 1 = $$

Pass? Y / N

 Write your answer

Part C: Propulsion Decision (15 min)

Does your mission need propulsion?

TABLE 79

Question	Answer
Orbit altitude	<u> </u> km
Natural orbital lifetime	<u> </u> years
FCC 5-year compliant without propulsion?	Y / N
Orbit maintenance required?	Y / N
Constellation phasing required?	Y / N

Question	Answer
Active deorbit required?	Y / N

Decision: Propulsion / No propulsion

If propulsion is selected, complete this section. Show all working.

Total ΔV required:

TABLE 80

Manoeuvre	ΔV (m/s)
Orbit maintenance (____ yr)	
Deorbit	
Collision avoidance margin	
Total	

Propulsion type selected: ____ $I_{sp} =$ ____ s

Propellant mass (Tsiolkovsky):

$$m_{\text{prop}} = m_{\text{dry}} \times \left(e^{\Delta V / (I_{sp} \times g_0)} - 1 \right)$$

$$= _ \times (e^{_ / (_ \times 9.81)} - 1) = _ \times (e^{_} - 1) = _ \times _ = _ \text{ kg}$$

 Write your answer

System dry mass (thruster + tank + feed): ____ kg

Total propulsion system mass: ____ kg (propellant + dry)

Fraction of total spacecraft mass: ____ %

Part D: Equipment Selection Log (25 min)

Using SpaceCDF's Equipment Browser, select components for each category:

TABLE 81

Category	Component Selected	Manufac-turer	Mass (kg)	Power (W)	Cost (kEUR)	Qty	Total Mass
	EPS Board					1	
	Battery					1	
	Solar Panels						
	OBC					1	
	Reaction Wheel					x	
	Magnet-orquer					x	
	Star Tracker						
	Sun Sensor					x	
	Transponder					1	
	Antenna						
	Payload					1	
	Structure					1	
	Harness					1	
	Propulsion						
	TOTAL		_____		_____		

Parametric estimate (from Session 2.4): _____ kg

Equipment-based total: _____ kg

Difference: _ kg (____ %)

Any incompatibilities detected? (RF band mismatch, voltage mismatch, interface conflict)

 Write your answer

Part E: Component Trade Study (15 min)

Subsystem traded: _____ Options compared: 3

TABLE 82

Criterion	Weight	Option A: ____	Score	Option B: ____	Score	Option C: ____	Score
Mass	0.20						
Power	0.15						
Cost	0.20						
TRL	0.15						
Heritage	0.15						
Performance	0.15						
Weighted	1.00		_____		_____		_____

Winner: ____ Score: ____

Rationale (beyond the numbers):

 Write your answer

Part F: Final Budget Health Check (10 min)

After equipment selection, record final budget status:

TABLE 83

Budget	Value	Margin	Status
Mass (wet vs allocation)	_ / _ kg	_____ %	G / A / R
Power (worst mode vs SA)	_ / _ W	_____ %	G / A / R
Link margin	_____ dB	>= 3 dB?	G / A / R
Cost vs ceiling	_ / _ MEUR	_____ %	G / A / R
Pointing (RSS vs req)	_ / _ deg	_____ %	G / A / R
Data (DL vs gen)	_ / _ GB/day	_____ %	G / A / R

Any budget that does not close? _____

Proposed fix: _____

 Write your answer

Decision Justification

Explain WHY you made each key structural and propulsion decision.

Form factor selection rationale (why this size and not larger/smaller?):

 Write your answer

Propulsion decision rationale (if no propulsion: why not? if propulsion: why this type?):

 Write your answer

Equipment selection rationale (which component trade-offs were hardest? what compromises did you make?):

 Write your answer

Notes & Reflections

 Write your answer

Worksheet 4.1: Equipment Selection & Bill of Materials

Name: _____ Date: ____ Team: _____

Mission Name: _____ Form Factor: _____U

Part A: Make/Buy/Reuse Decisions

For each subsystem, document the procurement decision and rationale:

TABLE 84

Subsystem	Decision (Buy/Reuse/Make)	Rationale	Lead Time
Structure			
EPS (solar array)			
EPS (battery)			
EPS (distribution)			
OBC			
AOCS (sensors)			
AOCS (actuators)			
TTC (transceiver)			
TTC (antenna)			
Thermal			
Payload			
Propulsion (if applicable)			

Part B: Bill of Materials (BOM)

Complete the BOM from the SpaceCDF Equipment Browser selections:

TABLE 85

Item ID	Com- ponent	Manu- facturer	Part Number	Qty	Mass (g)	Power (W)	Cost (kEUR)	TRL	ECCN
STR-001									
EPS-001									
EPS-002									
EPS-003									
OBC-001									
AOCS-001									
AOCS-002									
AOCS-003									
TTC-001									
TTC-002									
THM-001									
PLD-001									
HRN-001									

Part C: Budget Tracking

After all selections, record the live budget values from the SpaceCDF Dashboard:

TABLE 86

Budget	BOM Total	Parametric Estimate	Allocation	Margin	Margin %
Dry mass	_____ g	_____ g	_____ g	_____ g	_____%
Peak power	_____ W	_____ W	_____ W	_____ W	_____%
Total cost	_____ kEUR	_____ kEUR	_____ kEUR	_____ kEUR	_____%
Volume	_____% of ____U		100%	_____%	

Does everything fit within allocation? Y / N

If not, what would you change? _____

 Write your answer

Part D: Export Control Assessment

List any components that may require export licences:

TABLE 87

Component	ECCN / USML Category	Controlled?	Licence Required?	Action Needed
		Y / N	Y / N	
		Y / N	Y / N	
		Y / N	Y / N	
		Y / N	Y / N	

Are there any ITAR-controlled items? Y / N

If yes, what TAA (Technical Assistance Agreement) or DSP-5 licence is needed?

 Write your answer

Part E: Interface Compatibility Check

For each selected component, verify interface compatibility:

TABLE 88

Component	Bus Voltage OK?	Data Protocol OK?	RF Band Match?	Connector OK?	Notes
	Y / N	Y / N	Y / N / NA	Y / N	
	Y / N	Y / N	Y / N / NA	Y / N	
	Y / N	Y / N	Y / N / NA	Y / N	
	Y / N	Y / N	Y / N / NA	Y / N	

Component	Bus Voltage OK?	Data Protocol OK?	RF Band Match?	Connector OK?	Notes
	Y / N	Y / N	Y / N / NA	Y / N	
	Y / N	Y / N	Y / N / NA	Y / N	

Part F: Interface Incompatibility Resolution

Describe one interface incompatibility found during selection and how you resolved it:

Issue: _____

 Write your answer

Components involved: _____

Root cause: _____

Resolution chosen: _____

Impact on budget: _____

Notes & Reflections

What was the most difficult equipment selection decision? Why?

 Write your answer

Worksheet 4.2: Verification & Validation Planning

Name: _____ Date: ____ Team: _____

Mission Name: _____

Part A: IADT Method Assignment

For 10 key requirements from your SpaceCDF V&V Matrix, assign the verification method and justify:

TABLE 89

#	Req ID	Requirement Text (abbreviated)	Method (I/A/D/T)	Phase (B/C/D)	Level (Unit/Sub/Sys)	Justification
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						

Summary count: Analysis: ____ / Test: ____ / Demonstration: ____ / Inspection: ____

Part B: Dual-Method Requirements

Identify 3 requirements that need BOTH analysis (early confidence) AND test (final proof):

TABLE 90

Requirement ID	Requirement Text	Analysis (Phase B)	Test (Phase C/D)	Why Both Needed?

Part C: Environmental Test Sequence

For your selected launch vehicle, specify the complete proto-flight test sequence:

Launch vehicle: __ PUG reference: __

TABLE 91

Step	Test	Specification	Duration	Pass Criteria
1	Initial functional test	Full performance baseline	_____ hr	All parameters nominal
2	Sine vibration	__ g, - __ Hz	_____ min/ axis x 3	No resonance shift > 5%
3	Random vibration	_____ gRMS overall	_____ min/ axis x 3	No structural damage
4	Post-vibe functional test	Same as step 1	_____ hr	Compare to baseline
5	Thermal vacuum – hot	+ _____ C (predicted max + 10 C)	_____ cycles	Functional at hot extreme
6	Thermal vacuum – cold	- _____ C (predicted min - 10 C)	_____ cycles	Functional at cold extreme
7	Post-TVAC functional test	Same as step 1	_____ hr	Compare to baseline
8	EMC test	Required? Y / N	_____ day	No interference
9	Mass measurement	Calibrated scale (+/- 0.01 kg)	30 min	M <= _____ kg
10	Deployer fit check	_____ deployer	2 hr	Fits; slides freely

Total test campaign duration estimate: _____ weeks

Part D: Vibration Test Profile

Record the random vibration PSD profile from your launch vehicle PUG:

TABLE 92

Frequency (Hz)	PSD Level (g^2/Hz)	Slope
20		Start
20 - _____		+ _____ dB/oct
_____ - _____		Flat
_____ - 2000		- _____ dB/oct
2000		End

Overall gRMS (calculated): _____ gRMS

Show your calculation:

 Write your answer

Part E: TVAC Cycle Profile

Sketch or describe one TVAC cycle:

Hot extreme: + _ C **Cold extreme:** - ____ C

Ramp rate: _ C/min **Dwell time at extreme:** ____ hr

Functional test at each extreme? Y / N **Duration of functional test:** _____ hr

Calculate time for one cycle:

$t_{\text{cycle}} = \underline{\hspace{2cm}}$

= _____ hours

Total TVAC campaign: _ cycles x hr + ____ hr setup = _ hr = ____ days

Part F: Waiver Identification

Are there any requirements that cannot be verified by the standard method? Document potential waivers:

TABLE 93

Req ID	Standard Method	Proposed Alternative	Justification	Risk

Notes & Reflections

Which environmental test do you consider most critical for your mission? Why?

 Write your answer

Worksheet 4.3: Risk, Interfaces & FMECA

Name: _____ Date: ____ Team: _____

Mission Name: _____

Part A: Risk Register

Identify at least 5 technical risks for your mission design. Score each on the 5x5 matrix.

Scoring reminder: L x C = Score. Low (1-4), Medium (5-9), High (10-15), Critical (16-25).

TABLE 94

#	Risk De- scription	L (1-5)	C (1-5)	Score	Category (L/M/H/C)	Mitigation Strategy	Owner (Position)	Post-Mitiga- tion Score
1								
2								
3								
4								
5								
6								
7								

How many risks are High or Critical (before mitigation)? _____

How many remain High or Critical after mitigation? _____

Part B: 5x5 Risk Matrix Plot

Plot your risks on the matrix below. Write the risk number in the appropriate cell.

		Consequence ->				
		1	2	3	4	5
L	5					
i	4					
k	3					
e	2					
l	1					

Part C: N-Squared (N²) Interface Matrix

Fill in the interface matrix for your mission's subsystems. Use abbreviations: - **P** = Power (electrical) - **D** = Data (I2C, SPI, UART, CAN, RS-422) - **R** = RF (coaxial) - **M** = Mechanical (mounting, alignment) - **T** = Thermal (conductive/radiative)

TABLE 95

	EPS	OBC	AOCS	TTC	Payload	Structure
EPS	—					
OBC		—				
AOCS			—			
TTC				—		
Payload					—	
Structure						—

Total number of interfaces identified: _____

Interface conflicts detected: (describe at least 2)

1. Conflict: _____

Resolution: _____

1. Conflict: _____

Resolution: _____

Part D: FMECA Table

Complete for 4 critical components:

TABLE 96

Com- ponent	Func- tion	Failure Mode	Cause	Local Effect	System Effect	Severity (1-5)	Detection Method	Compensat- ing Provi- sion

Part E: Single-Point Failure Analysis

List all single-point failures in your design:

TABLE 97

#	Component	Failure Mode	Effect on Mission	SPF?	Acceptable?	Mitigation (if not acceptable)
1				Y/N	Y/N	
2				Y/N	Y/N	
3				Y/N	Y/N	
4				Y/N	Y/N	
5				Y/N	Y/N	

Total SPFs identified: _ Accepted: Mitigated: __

Part F: Reliability Calculation

Calculate the series reliability for your mission's critical chain (components that must all work for mission success):

TABLE 98

Component	Individual Reliability (R _i)	Mission Duration Used

$R_{\text{series}} = R_1 \times R_2 \times \dots \times R_n = \underline{\hspace{2cm}}$

$R_{\text{series}} = \underline{\hspace{2cm}}$

If you added redundancy to one component (e.g., dual deployment mechanism), recalculate:

$R_{\text{redundant}} = 1 - (1 - R)^2 = 1 - (1 - \underline{\hspace{1cm}})^2 = \underline{\hspace{2cm}}$

New R_{series} (with redundancy) = $\underline{\hspace{2cm}}$

Improvement: from _ to (+ __ percentage points)

Part G: Risk Discussion

What is the highest-risk item in your design? What would it take (cost, mass, schedule) to bring the risk to an acceptable level?

 Write your answer

Notes & Reflections

Which single-point failure concerns you the most? Would you accept it, or is mitigation essential?

 Write your answer

Worksheet 4.4: Cost Estimation & Design Review

Name: _____ Date: ____ Team: _____

Mission Name: _____

Part A: Mission Cost Estimate (WBS)

Complete using both parametric estimates (from SpaceCDF Cost tab) and bottom-up estimates (from BOM vendor quotes):

TABLE 99

WBS #	Element	Parametric (kEUR)	Bottom-Up (kEUR)	Difference	Notes
1.0	Programme Management				
2.0	Systems Engineering				
3.0	Mission Assurance				
4.0	Payload				
5.0	Spacecraft Bus Hardware				
	5.1 Structure & mechanisms				
	5.2 EPS				
	5.3 AOCS				
	5.4 TTC				
	5.5 OBC & data handling				
	5.6 Thermal				
	5.7 Propulsion				
	5.8 Harness				
6.0	Integration & Test				
7.0	Software (FSW + GSW)				
8.0	Launch Services				
9.0	Ground Segment				

WBS #	Element	Parametric (kEUR)	Bottom-Up (kEUR)	Difference	Notes
10.0	Operations (____ years)				
	TOTAL	_____	_____		

Part B: Confidence Levels

P50 estimate (your best estimate): _____ kEUR

P70 estimate (P50 x 1.2): _____ kEUR

P80 estimate (P50 x 1.3): _____ kEUR

Show your reasoning for the multiplier (is 1.3 appropriate, or should it be higher for your mission?):

 Write your answer

Part C: Constellation Cost (if applicable)

Number of satellites: _ **Learning rate:** ____%

b = $\ln(\text{learning_rate}) / \ln(2) = \ln(_) / \ln(2) =$ ____

TABLE 100

Unit #	Unit Cost (kEUR) = $C_1 \times N^b$	Cumulative (kEUR)
1		
2		
4		
8		
____ (total)		

Show your calculation for the total constellation cost:

Hardware: _ **units x kEUR avg** = __ kEUR

Spares (_%): __ units x _ **kEUR** = ____ kEUR

Launch: _ **sats x kEUR** = __ kEUR

Ground segment: _____ kEUR

Operations (_ years): ____ kEUR

PM/SE/MA: _____ kEUR

Total constellation cost: _ kEUR = ____ MEUR

P80 constellation cost (x 1.3): _____ MEUR

Part D: Cost Drivers

Top 3 cost drivers in your mission (from SpaceCDF Cost Breakdown):

TABLE 101

Rank	Cost Element	Cost (kEUR)	% of Total	Why is it Expensive?
1				
2				
3				

What would you change to reduce total cost by 20%?

 Write your answer

Part E: Design Review Readiness

From the SpaceCDF Gate Review tab, assess your readiness for SRR/PDR:

TABLE 102

#	Gate Criterion	Status (Pass/Fail/Manual)	Evidence Location	If Fail: Action Needed
1	Mission need justified			
2	Requirements complete & traceable			
3	All budgets close with margin			

#	Gate Criterion	Status (Pass/Fail/Manual)	Evidence Location	If Fail: Action Needed
4	Equipment selected (BOM complete)			
5	Interfaces defined, conflicts resolved			
6	V&V approach defined			
7	Risks identified with mitigations			
8	Cost estimate with WBS			
9	ConOps defined			
10	Sustainability compliance			

Must-pass criteria met: _ / ____

Overall readiness: READY / NOT READY

Action items to achieve readiness:

1. _____
2. _____
3. _____

Part F: Presentation Preparation

Outline your 12-minute design review presentation:

TABLE 103

Section	Duration	Key Message	Evidence/Data to Show
1. Mission Need	2 min		
2. Why Space?	2 min		
3. System Design	3 min		
4. Equipment & V&V	2 min		
5. Risk & Cost	2 min		
6. Operations & Lessons	1 min		

Notes & Reflections

What is the most uncertain element in your cost estimate? How would you reduce the uncertainty?

 Write your answer

Worksheet 5.1: Ground Segment & Operations Architecture

Name: _____ Date: ____ Team: _____

Mission Name: _____ Orbit: km, ____ deg inclination

Part A: Ground Station Contact Analysis

Calculate contact time and data volume per pass for your mission.

INPUT PARAMETERS

TABLE 104

Parameter	Value	Source
Orbital altitude (h)	_____ km	SpaceCDF orbit selection
Minimum elevation angle (epsilon)	_____ deg	Ground station spec (typically 5-10)
Downlink data rate (R)	_____ Mbps	SpaceCDF link budget
Protocol efficiency (eta)	_____ (typically 0.85-0.95)	CCSDS overhead estimate
Ground station latitude	_____ deg	Selected station
Earth radius (R_E)	6371 km	Constant

CALCULATIONS

Maximum slant range:

$$\rho = R_E \times (\sqrt{(h/R_E + 1)^2 - \cos^2(\epsilon)} - \sin(\epsilon))$$

$$\rho = 6371 \times (\sqrt{((_/6371 + 1)^2 - \cos^2(_))} - \sin(_))$$

$$\rho = \text{_____ km}$$

Average pass duration (approximate):

$$T_{\text{avg}} \sim \text{_____ minutes (from STK/SpaceCDF or estimate: } \sim 6 \text{ min for 500 km SSO)}$$

Data volume per pass:

$$V_{\text{data}} = R \times T \times \eta = _ \text{ Mbps} \times \text{s} \times _ = _ \text{ Mbit} = _ \text{ MB}$$

Part B: Data Budget Closure

TABLE 105

Parameter	Value	Unit
Daily data generation (payload)		MB/day
Daily data generation (housekeeping)		MB/day
Total daily generation		MB/day
Passes per day (GS 1: _____)		passes
Data per pass (GS 1)		MB
Subtotal downlink (GS 1)		MB/day
Passes per day (GS 2: _____)		passes
Data per pass (GS 2)		MB
Subtotal downlink (GS 2)		MB/day
Total daily downlink capacity		MB/day
Data budget margin		MB/day
Margin percentage		%

Does the data budget close? Y / N

If not, what changes would close it? (check all that apply)

- ☐ Add another ground station at: ____
- ☐ Increase data rate to: _ Mbps (requires: _____)
- ☐ Reduce payload data generation to: _ MB/day (impact: _____)
- ☐ Add onboard compression (ratio: ____:1)
- ☐ Use SatNOGS network for additional passes
- ☐ Other: _____

Part C: Ground Station Network Design

TABLE 106

Station #	Location	Latitude	Antenna	Band	Data Rate	Passes/Day	Role
1							Primary TTC
2							Payload DL
3							Backup/SatNOGS

Total ground segment cost estimate: _____ kEUR

TABLE 107

Cost Element	Annual Cost (kEUR)	Notes
Antenna rental / ownership		
MCS software licence		
Network connectivity		
Operations staff (_____ FTE)		
Total annual		
Mission lifetime (_____ yr)		

Part D: LEOP Timeline

Construct the LEOP timeline for the first 72 hours after separation:

TABLE 108

Time (UTC)	Sim Time	Activity	Success Criterion	Status
T+0	Separation	Deployment switches release		[]
T+30 min	Timer expires	Antenna deployment commanded		[]
T+_____		Beacon acquisition	Carrier lock	[]
T+_____		First HK telemetry	Data decoded	[]
T+_____		First uplink command	ACK received	[]
T+_____		SA deployment (if separate)	Power generation confirmed	[]
T+_____		ADCS initialisation	Attitude determination active	[]
T+_____		ADCS calibration	Pointing < _____ deg	[]
T+_____		Full duplex validation	Uplink + downlink at ops rate	[]
T+_____		Health assessment complete	All subsystems nominal	[]

Part E: Mission Operations Timeline (Gantt Chart)

Sketch the operations timeline from launch to end of life:

Phase:	LEOP			Commission				Early Ops				Nominal Operations				EOL	
Week:	1	2	3	4	5	6	7	8	9	...	26	...	52	...	104	...	156
Staffing:	24/7			16/7				8/5				8/5 or automated				8/5	

Key milestones:

L+___: First light

L+___: Commissioning complete

L+___: Orbit maintenance manoeuvre (if applicable)

L+___: End of nominal mission

L+___: Extended mission (if applicable)

L+___: Passivation and deorbit

Notes & Reflections

What is the most challenging aspect of your ground segment design? What would you do differently with more budget?

 Write your answer

Worksheet 5.2: Mission Operations Concepts

Name: _____ Date: ____ Team: _____

Mission Name: _____

Part A: Operational Modes

Define all operational modes for your spacecraft. Use the SpaceCDF ConOps Editor to enter these.

TABLE 109

Mode	Description	Power (W)	Data Rate	Entry Condition	Exit Condition
Safe					
Detumble					
Standby					
Science					
Downlink					
Eclipse					
Manoeuvre					

Verify: Does the power budget close in every mode?

TABLE 110

Mode	Power Consumption (W)	Power Available (W)	Margin (W)	Closes?
Safe				Y / N
Detumble				Y / N
Standby				Y / N
Science				Y / N
Downlink				Y / N
Eclipse (battery only)				Y / N

Part B: FDIR Rules

Define at least 5 FDIR rules for your spacecraft:

TABLE 111

#	Fault Description	Detection Method	Threshold	FDIR Level (0-4)	Autonomous Response	Recovery Procedure
1						
2						
3						
4						
5						
6						

Can Safe Mode sustain the spacecraft indefinitely (power + thermal)? Y / N

If not, what is the maximum Safe Mode duration? _____ hours

Can every autonomous FDIR action be overridden from ground? Y / N

If not, which cannot? _____

Part C: Nominal Procedure

Write one nominal procedure for your mission (science observation or data downlink):

Procedure ID: ____ **Title:** _____

Preconditions:

 Write your answer

TABLE 112

Step	Action	Expected Result	If Not Achieved
1			
2			
3			
4			

Step	Action	Expected Result	If Not Achieved
5			
6			
7			
8			

Post-conditions:

 Write your answer

Part D: Contingency Procedure

Write one contingency procedure (e.g., safe mode recovery, communication loss recovery):

Procedure ID: ____ Title: _____

Trigger condition:

 Write your answer

Severity level: Green / Yellow / Orange / Red

TABLE 113

Step	Action	Expected Result	If Not Achieved	Timeout
1				
2				
3				
4				
5				
6				

Escalation: If this procedure fails, escalate to: _____

Post-conditions:

✎ Write your answer

Part E: Operations Staffing

Estimate the staffing requirements for each mission phase:

TABLE 114

Phase	Duration	Shifts/Day	Staff/ Shift	Total FTE	Annual Cost (kEUR)
LEOP	_____ days	3 (24/7)			
Commissioning	_____ weeks	2 (16/7)			
Early Operations	_____ months	1 (8/5)			
Nominal Operations	_____ years	1 (8/5) or auto			
End of Life	_____ weeks	1 (8/5)			
Total					

Part F: Anomaly Scenario

Hypothetical scenario: Your satellite enters Safe Mode during a weekend. The next ground contact is Monday morning (40 hours away). Walk through your response:

1. What is the spacecraft doing in Safe Mode?

 Write your answer

1. Will it survive 40 hours? (Check power and thermal)

 Write your answer

1. What telemetry will you review first on Monday?

 Write your answer

1. What is your recovery plan?

 Write your answer

Notes & Reflections

How much autonomy should your spacecraft have? Where is the line between onboard decision-making and ground control?

 Write your answer

Worksheet 5.3: Mission Simulation Day

Name: _____ Date: ____ Team: _____

Mission Name: _____

Your Role: _____ (FD / SC / GSO / PO / FD-nav / Logger)

Simulation Event Log

Record ALL events, decisions, and actions in real-time during the simulation:

TABLE 115

#	Sim Time	Real Time	Event / Observation	Action Taken	Result	Logged By
1	T+0		Separation			
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						

#	Sim Time	Real Time	Event / Observation	Action Taken	Result	Logged By
20						

LEOP Checklist

Check off each LEOP milestone as it is achieved during the simulation:

TABLE 116

#	Milestone	Time Achieved	Status	Notes
1	Separation confirmed		[]	
2	30-min timer expired		[]	
3	Antenna deployed		[]	
4	Beacon acquired		[]	
5	First HK telemetry decoded		[]	
6	First uplink command ACK'd		[]	
7	Solar array deployed (if sep.)		[]	
8	ADCS detumble complete		[]	
9	ADCS calibration complete		[]	
10	Full duplex validated		[]	
11	All subsystems nominal		[]	

Anomaly Response Form 1

Complete this form for each injected anomaly during the simulation.

TABLE 117

Field	Entry
Anomaly ID	ANO-SIM-001
Sim Time	
Real Time	
Severity	Green / Yellow / Orange / Red
Affected Subsystem	

Observation (exact telemetry values and symptoms):

 Write your answer

Initial Assessment (what do you think happened?):

 Write your answer

Diagnosis (root cause after investigation):

 Write your answer

Action Taken (commands sent, procedures executed):

TABLE 118

Step	Time	Action	Expected Result	Actual Result
1				
2				
3				
4				
5				

Final Result (system state after response):

 Write your answer

Follow-up Required:

 Write your answer

Procedure used: ____ Did it work as written? Y / N / Partially

If not, what changes are needed? _____

Anomaly Response Form 2

TABLE 119

Field	Entry
Anomaly ID	ANO-SIM-002
Sim Time	
Real Time	
Severity	Green / Yellow / Orange / Red
Affected Subsystem	

Observation (exact telemetry values and symptoms):

 Write your answer

Initial Assessment (what do you think happened?):

 Write your answer

Diagnosis (root cause after investigation):

✎ Write your answer

Action Taken (commands sent, procedures executed):

TABLE 120

Step	Time	Action	Expected Result	Actual Result
1				
2				
3				
4				
5				

Final Result (system state after response):

✎ Write your answer

Follow-up Required:

✎ Write your answer

Procedure used: ____ Did it work as written? Y / N / Partially

If not, what changes are needed? _____

Anomaly Response Form 3

TABLE 121

Field	Entry
Anomaly ID	ANO-SIM-003
Sim Time	
Real Time	
Severity	Green / Yellow / Orange / Red
Affected Subsystem	

Observation (exact telemetry values and symptoms):

 Write your answer

Initial Assessment:

 Write your answer

Diagnosis:

 Write your answer

Action Taken:

TABLE 122

Step	Time	Action	Expected Result	Actual Result
1				
2				
3				
4				

Final Result:

 Write your answer

Procedure used: ____ Did it work as written? Y / N / Partially

Commissioning Status

After the commissioning phase of the simulation, record subsystem checkout status:

TABLE 123

Subsystem	Checkout Complete?	Performance vs Spec	Issues Found
EPS	[]	Nominal / Degraded / Failed	
OBC	[]	Nominal / Degraded / Failed	
AOCS	[]	Nominal / Degraded / Failed	
TTC	[]	Nominal / Degraded / Failed	
Thermal	[]	Nominal / Degraded / Failed	
Payload	[]	Nominal / Degraded / Failed	
Propulsion	[]	Nominal / Degraded / Failed / NA	

Nominal Operations Summary

After the nominal operations phase, record:

TABLE 124

Metric	Planned	Actual (Simulated)	Variance
Science observations completed			
Data downlinked (MB)			
Anomalies encountered			
Ground contacts made			
Safe mode entries			

Simulation Debrief

WHAT WENT WELL?

 Write your answer

WHAT COULD BE IMPROVED?

 Write your answer

DESIGN WEAKNESSES REVEALED BY SIMULATION:

 Write your answer

PROCEDURE CHANGES NEEDED:

 Write your answer

FDIR GAPS IDENTIFIED:

 Write your answer

Notes & Reflections

What was the most stressful moment during the simulation? What did it teach you about operations?

 Write your answer

Worksheet 5.4: Final Review & Presentations

Name: _____ Date: ____ Team: _____

Mission Name: _____

Part A: Final Design Summary

Record the final state of your design from the SpaceCDF Dashboard:

TABLE 125

Parameter	Value	Unit	Margin	Margin %	Status (G/A/R)
Dry mass		kg			
Wet mass (if propulsion)		kg			
SA power (EOL)		W			
Battery capacity		Wh			
Link margin (worst case)		dB			
Pointing accuracy		deg			
Data balance		MB/day			
Total cost (P50)		kEUR			
Total cost (P80)		kEUR			
Debris compliance score		/100			
Mission lifetime		years			

Do all budgets close? Y / N If not, which fail? _____

Number of unresolved conflicts: _____

Part B: Documentation Checklist

Tick each document generated from SpaceCDF Exports tab:

TABLE 126

Document	Generated?	Complete?	Notes
MRD (Mission Requirements Document)	☐	☐	
Technical Specification	☐	☐	
Verification Plan	☐	☐	
ConOps Document	☐	☐	
SEMP (Systems Engineering Mgmt Plan)	☐	☐	
IRD (Interface Requirements Document)	☐	☐	
Risk Management Plan	☐	☐	
Test Plan	☐	☐	
Bill of Materials	☐	☐	
ITU Filing Template	☐	☐	
RSSSA Filing	☐	☐	
Export Control Assessment	☐	☐	
End-of-Life Report	☐	☐	
COPUOS Registration	☐	☐	

Total documents generated: _____ / 14

Part C: Presentation Outline

Prepare your 12-minute final design review presentation:

TABLE 127

Section	Time	Key Points to Cover	Evidence / Data to Show
1. Mission Need	2 min		
2. Why Space?	2 min		
3. System Design	3 min		
4. Equipment & V&V	2 min		
5. Risk & Cost	2 min		
6. Operations & Lessons	1 min		

Presenter(s): _____

Backup slides prepared on: _____

Part D: Peer Review Evaluation

Complete this section while reviewing another team's presentation.

Team being reviewed: _____

Reviewers: _____

TABLE 128

#	Criterion	Score (0-2)	Comments / Questions
1	Mission need clearly justified		
2	Requirements complete and traceable		
3	All budgets close with margin		
4	Equipment selected with justified trades		
5	Interfaces defined, conflicts resolved		
6	V&V approach defined		
7	Risks identified with mitigations		
8	Cost estimate with WBS and P80		
9	ConOps and ground segment designed		
10	Sustainability compliance		
TOTAL		/ 20	

Presentation quality:

TABLE 129

Criterion	Score (1-5)	Comments
Clarity of communication		
Use of evidence (data, not assertions)		
Ability to answer questions		
Time management		

Board recommendation: GO / NO GO / GO WITH ACTIONS

Action items for the presenting team:

TABLE 130

#	Action	Responsible	Deadline
1			

#	Action	Responsible	Deadline
2			
3			

Strongest aspect of this team’s design:

 Write your answer

Biggest area for improvement:

 Write your answer

Part E: Lessons Learned

1. What was the most challenging design decision your team faced?

 Write your answer

1. What would you do differently if starting the course over?

 Write your answer

1. What does the design need next (Phase B activities)?

 Write your answer

1. What was the most valuable SpaceCDF feature?

 Write your answer

1. What feature was missing that you needed?

 Write your answer

1. What concept from this course will you apply in your future work?

 Write your answer

Part F: Self-Assessment Rubric

Rate your own learning across the three weeks of the course. Be honest – this is for your own reflection, not grading.

TABLE 131

Competency	Week 1 Start (1-5)	Now (1-5)	Evidence of Growth
Define a space mission starting from the problem, not the solution			
Write verifiable, traceable requirements (SMART format)			
Conduct a structured trade study with weighted criteria			
Size subsystems using parametric models and engineering budgets			
Select COTS equipment and verify interface compatibility			
Construct a verification matrix with IADT methods			
Assess risk using a 5x5 matrix and define mitigations			
Estimate mission cost using parametric and bottom-up methods			
Design a ground segment and calculate data budget			
Define operational modes, FDIR rules, and procedures			
Respond to anomalies using a systematic process			
Present a design to a review board with evidence			

Scale: 1 = No familiarity, 2 = Basic awareness, 3 = Can apply with guidance, 4 = Can apply independently, 5 = Can teach others

Overall self-assessment:

At the start of this course, I would describe my systems engineering ability as:

 Write your answer

Now, I would describe it as:

 Write your answer

One thing I am most proud of from this course:

 Write your answer

Notes & Reflections

Final thoughts on the course, the design process, and what comes next:

 Write your answer