



# SOP-201 — Vehicle Wash Procedure

Section 3: Installation Operations

SOP · Version 1.0

Organization: \_\_\_\_\_

Document ID: sop-201-vehicle-wash-procedure

Effective Date: \_\_\_\_\_

Approved By: \_\_\_\_\_

# SOP-201 — Vehicle Wash Procedure

---

Forge Standard Operating Procedures v1.0

Section 3: Installation Operations

---

## Purpose

---

Remove surface dirt safely before decontamination and film application.

## Scope

---

All vehicles receiving PPF, wrap, TPU, or coating. Performed in designated wash zone.

## Procedure

---

### Pre-rinse

1. Rinse entire vehicle top-down with pressure washer — max 1200 PSI, 12" standoff.
2. Focus wheel wells and lower panels where grit accumulates.
3. Never spray directly at panel gaps or damaged paint.

## Contact wash

1. Two-bucket method: clean soap solution + rinse bucket with grit guards.
2. Microfiber wash mitt only — no brushes on paint.
3. Work top-down; straight-line motion; rinse mitt between panels.

## Dry & handoff

1. Blow dry door jambs, mirrors, and emblems with filtered air.
2. Microfiber towel dry — no dragging across dry panels.
3. Move to decon bay immediately or cover vehicle if delay exceeds 30 minutes.

# Quality standards

---

- ☐ Zero towel scratches from wash process
- ☐ Vehicle enters decon within 2 hours of wash

# Safety notes

---



Wet floors — cones and caution signs required in wash bay.

# Related documents

---

| Document              | ID                      |
|-----------------------|-------------------------|
| Decontamination       | sop-202-decontamination |
| Contamination Control | sop-202-decontamination |

# Revision history

---

| Version | Date       | Author           | Changes         |
|---------|------------|------------------|-----------------|
| 1.0     | 2026-07-23 | Forge Operations | Initial release |

Confidential — Skill Forge training operations.