



SKILL FORGE
WHERE STUDENTS BECOME TEACHERS

PPF Surface Preparation SOP

Decontamination sequence before PPF install

SOP · Version 1.0

Organization: _____

Document ID: ppf-surface-prep-sop

Effective Date: _____

Approved By: _____

PPF Surface Preparation SOP

Decontamination sequence before pattern touch or bulk install

Purpose

Ensure paint is chemically clean and mechanically smooth before PPF adhesive contact.

Procedure

Step 1 — Wash

1. Foam pre-rinse, two-bucket hand wash, top to bottom
2. Dry with clean microfiber — no air-dry on paint

Step 2 — Decontaminate

1. Clay bar with lubricant on all install zones
2. Iron fallout remover — dwell per product, rinse thoroughly
3. Tar remover on lower panels if needed

Step 3 — Final wipe

1. IPA wipe (70% isopropyl) on every panel receiving film
2. One direction, clean microfiber per 2 panels
3. Final inspection under cross-light — no contamination visible

Step 4 — Lock environment

1. Close bay doors; minimize traffic until install complete
2. Do not apply tire dressing or quick detailer after IPA wipe

Checkpoint

Paint squeaks clean under nitrile glove test on random panels.

Related documents

Document	ID
PPF Master Install Manual — Ch 08	ppf-master-install
Pre-Install QC Checklist	pre-install-qc-checklist

Confidential — Skill Forge training operations.