



SOP-500 — Complete Vinyl Wrap Workflow

Section 6: Vinyl Wrap

SOP · Version 1.0

Organization: _____

Document ID: sop-500-complete-vinyl-wrap-workflow

Effective Date: _____

Approved By: _____

SOP-500 — Complete Vinyl Wrap Workflow

Forge Standard Operating Procedures v1.0

Section 6: Vinyl Wrap

Purpose

End-to-end procedure for cast vinyl color-change and commercial wrap installs.

Scope

Full and partial vinyl wraps. Follow Vinyl Wrap Master Install Manual for compound curves and inlays.

Procedure

Pre-install

1. Complete SOP-200 through SOP-204.
2. Remove or mask hardware per coverage map — photograph before removal.
3. Acclimate film roll to bay temperature minimum 2 hours.

Surface prep

1. Wash and decon per SOP-201 and SOP-202.
2. IPA wipe; ensure zero wax or sealant residue.
3. Degrease door jambs and fuel door if wrapped.

Application

1. Measure and cut with 2" bleed; label pieces by panel.
2. Apply dry or wet per film manufacturer — consistent method per job.
3. Post-heat all recessed areas and edges; use thermometer.
4. Knifeless tape or bladeless cutting at panel gaps where specified.

Reassembly & QC

1. Reinstall hardware with correct torque — no stripped clips.
2. Complete SOP-205 and SOP-206.
3. Customer aftercare: no wash 7 days; hand wash only first 30 days.

Quality standards

- ☐ No lifting at edges or mirrors at 30-day follow-up
- ☐ Color match across panels — no visible shade shift

Related documents

Document	ID
Vinyl Wrap Master Install Manual	vinyl-wrap-master-install
Vinyl Wrap Pricing Guide	wrap-pricing-guide

Revision history

Version	Date	Author	Changes
1.0	2026-07-23	Forge Operations	Initial release

Confidential — Skill Forge training operations.