




EBB SB2209 CAN V1.0 (RP2040)

BUILD GUIDE

VERSION 2025-05-08

Version	Date	Revisions
v1.0	2023.11	Original
v1.2	2024.02	• Corrected: Pinout diagram for the 4-wire PT100 DIP switch selection. • Added: Specifications for the optimal diameter and length of steel wire to securely fix the CAN bus cable. • Updated: All mentions of 'CanBoot' in the manual have been updated to 'Katapult'.
v1.3	2024.06	Revised BLTouch and MicroProbe connection methods.
v1.4	2025.05	Modified the menuconfig to Flash chip (GENERIC_03H with CLKDIV 4).



Thanks to **CHAOTICLAB** for providing guidance on Voron's official style build guide, and designing the printed part model for EBB SB2209 CAN V1.0 (RP2040).

- Highlighted in blue are included in this EBB SB2209 CAN V1.0 (RP2040).
- Highlighted in red are other accessories of the Voron StealthBurner, which are not included in this EBB SB2209 CAN V1.0 (RP2040) and will need to be purchased by yourself.

Table of Contents


Packing List

StealthBurner	1
EBB SB0000 CAN v1.0 Overview	1
Turbine Fan	3
Axial Fan	4
PWM Fan	5
LED	6
ClockWork2	7
EBB SB2209 CAN V1.0 (RP2040) Overview	7
Install EBB SB2209 CAN V1.0 (RP2040)	8
CAN BUS 120R Termination Resistor	10
Extruder Motor	11
Thermistor	12
PT100/1000	13
Heater Cartridge	14
X-Carriage	15
Proximity Switch	15
X Axis Limit Switch	16
Voron Tap	17
BLTouch & MicroProbe	18

StealthBurner Final Assembly	19
CW2 Cable Bridge	20
Fix CAN / USB-C Cable	22
StealthBurner to Mainboard Wiring	24
Klipper	25
Flashing Katapult	25
Compile Firmware	30
Firmware Update (via Katapult)	31
Firmware Update (via DFU)	33
CAN bus Configure	37
Klipper Configure	38


PACKING LIST

WWW.BIGTREE-TECH.COM




BIGTREETECH EBB SB2209 CAN V1.0 (RP2040)

1pc




BIGTREETECH EBB SB0000 CAN V1.0

1pc




CAN bus Cable

1pc




Crimp Terminal

2.0 mm pitch	30pcs
3.0 mm pitch	5pcs
2.54 mm pitch	20pcs




2.0 mm Pitch Connector Housing

2Way	1pc
3Way	2pcs
4Way	1pc
5Way	1pc




2.54mm Pitch Connector Housing

1Way	15pcs
------	-------




3.0 mm Pitch Connector Housing

2Way	1pc
------	-----




Jumper

15pcs



Insulated Wire Ferrule

2pcs




Heat Sink

1pc



M3 x 10 Button Head Cap Screw (BHCS)


4pcs



WIRE TERMINAL

EBB SB0000 CAN v1.0 use 2.54 pitch DuPont connector. Therefore, all fans and LED lights on StealthBurner Body should be 2.54 pitch DuPont connector.



Now you need to screw down the 5015 fan with the SB0000 PCB :)



TIPS

Install 5015 turbine fan, 4010 axial fan, and LED lamp before installing EBB SB0000 CAN v1.0.

You need to select Vin (24V) for all fans. Be sure to wire Gnd to Gnd and 24V to 24V! Otherwise you will experience magic smoke later.






FAN VOLTAGE


All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.

Note: The voltage for both the turbine fan and axial fan will be simultaneously set to 5/12/24V.


You need to select Vin (24V) for all fans. Be sure to wire Gnd to Gnd and 24V to 24V! Otherwise you will experience magic smoke later.



Fan Voltage: 24V



Fan Voltage: 12V




Fan Voltage: 5V

FAN VOLTAGE

All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.



Note: The voltage for both the turbine fan and axial fan will be simultaneously set to 5/12/24V.

Skip




PWM FAN


You can also use PWM fan on EBB SB0000 CAN v1.0. As shown in the figure, it contains a 4 pins PWM fan header (2.54 pitch) and 4 pins DuPont connector).



Fan Voltage: 24V



Fan Voltage: 12V





Fan Voltage: 5V

FAN VOLTAGE

All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.



WWW.BIGTREE-TECH.COM





TIPS


The Cable_Cover_EBB and Main_Body_EBB are modified from official VORON prints to be compatible, but have slight differences to facilitate easier wiring.





HEATSINK

Please attach the heatsink to the position shown in the diagram, which is on the back of the driver chip. It is crucial to avoid contacting the connector pins of the motor when installing the heatsink.


When the EBB SB2209 CAN V1.0 (RP2040) device uses CAN bus communication, if it is the final device in the CAN bus chain, you must plug a jumper at the 120R position.





TIPS


When EBB SB2209 CAN V1.0 (RP2040) is used on StealthBurner, the minimum wire length of the motor is 76mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 100mm or 110mm.



PH2.0-2PIN



TIPS

When EBB SB2209 CAN V1.0 (RP2040) is used on StealthBurner, the minimum wire length of the thermistor is 103mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 120mm or 130mm.



TIPS

EBB SB2209 CAN V1.0 (RP2040) is compatible with 2-wire and 4-wire PT100 or PT1000, but not 3-wire PT100 or PT1000. As shown in the figure, wire and adjust the dial switch according to the actual model. And the terminals are PH2.0.






Wire length shall be at least 130mm

MX3.0-2PIN


TIPS

When EBB SB2209 CAN V1.0 (RP2040) is used on StealthBurner, the minimum wire length of the heater cartridge is 130mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 150mm or 160mm.


Skip




24V CNC Fan



24V Proximity Switch



For NPN, short the two pins at "NPN" using a jumper.



TIPS

When EBB SB2209 CAN V1.0 (RP2040) is used on StealthBurner, the minimum wire length of the PL-08N is 100mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 130mm or 140mm.



FUNCTION SELECTION

Supports both NPN and PNP types. For NPN, short the two pins at "NPN" using a jumper; for PNP, remove the jumper.
Note: This interface can also be used for 24V CNC fans. By shorting the left two-pin connector with a jumper (FAN), it can be used for a 24V CNC fan. By shorting the right two-pin connector with a jumper (IND), it can be used for a 24V proximity switch.

Be sure to use the endstop labeled "To CAN_Endstop" which is the one with the short wires.

X LIMIT SWITCH

WWW.BIGTREE-TECH.COM




END-STOP SWITCHES FOR X

End-stops are wired in a "Normally Closed" configuration. On microswitches those are the 2 outer terminals indicated by C and NC.

TIPS


When EBB SB2209 CAN V1.0 (RP2040) is used on StealthBurner, the minimum wire length of the X Axis Limit Switch is 145mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 165mm or 175mm.




Skip



Method 1:


Method 2:



Skip, Stealthburner will be assembled later.









TIPS


The CW2 Cable Bridge differs slightly from the original CW version and is available for download on BIGTREETECH's GitHub in the EBB\EBB SB2240_2209 CAN\CAD or STL folders.

**TIPS**

If you are using the previous version of the CAN cable, as shown in the above image, please download the: Printed Part for CAN Cable.

TIPS


The Printed Part for CAN Cable and Printed Part for USB-C Cable are custom-printed parts, available for download on BIGTREETECH's GitHub in the EBB\EBB SB2240_2209 CAN\CAD or STL folders.



CABLE CLIP

The Cable Clip Printed Part is a custom-printed part, available for download on BIGTREETECH's GitHub in the EBB\EBB SB2240_2209 CAN\CAD or STL folders. Alternatively, zip ties can also be used to secure the cables.

You will need to Strip down the Isolation a bit so you have enough cable length to connect the cable to the PSU and to the Can port. Go back to the Tap Manual page 34 now, flashing the toolhead will be done later. Use the tight cable sleeve around the cable.



"Katapult" is the New Name for "CanBoot"

Note: Please note that Katapult is designed for the purpose of directly updating the MCU firmware via the CAN bus interface. If you prefer the DFU update method, you may skip this step.

“Flashing Katapult on a CB1/Raspberry Pi”

Refer to the instructions here to download the Katapult project

<https://github.com/Arksine/Katapult>

1.Run:

```
cd ~
```

to enter the home directory, then run:

```
git clone https://github.com/Arksine/Katapult
```

to download Katapult project.

run:

```
cd Katapult
```

to enter the Katapult directory.

2.Run:

```
make menuconfig
```


and configure according to the following figure

```
(Top)
Katapult Configuration v0.8.1-96-gbclecea
Micro-controller Architecture (Raspberry Pi RP2040/RP235x) ---->
Processor model (rp2040) ---->
Flash chip (GENERIC_03H with CLKDIV 4) ---->
Build Katapult deployment application (16KiB bootloader) ---->
Communication Interface (CAN bus) ---->
(4) CAN RX gpio number (NEW)
(5) CAN TX gpio number (NEW)
(1000000) CAN bus speed
( ) GPIO pins to set on bootloader entry
[*] Support bootloader entry on rapid double click of reset button
[ ] Enable bootloader entry on button (or gpio) state
[*] Enable Status LED
(gpio26) Status LED GPIO Pin
```


3.Run

make


to compile firmware, 'katapult.uf2' file will be generated in `home/biqu/Katapult/out` folder when **make** is finished, download it onto your computer using the SSH application.



4.1 Please use a Type-C cable to connect the EBB SB2209 CAN V1.0 (RP2040) to the Raspberry Pi/CB1, and ensure that the USB_5V jumper is connected, in order to supply power to the EBB SB2209 CAN V1.0 (RP2040) via Type-C.



4.2. Press and hold the Boot button, and then click the Reset button to enter the DFU mode.



4.3. Enter in the SSH terminal command line

```
lsusb
```

Query DFU device ID

```
pi@fluidpi: ~$ lsusb
Bus 001 Device 005: ID 2e8a:0003 Raspberry Pi RP2 Boot
Bus 001 Device 004: ID 1d50:6061 OpenMoko, Inc. Geschwister Schneider CAN adapter
Bus 001 Device 003: ID 0424:0c00 Microchip Technology, Inc. (formerly SMSC) SMC9512/9514 Fast Ethernet Adapter
Bus 001 Device 002: ID 0424:9514 Microchip Technology, Inc. (formerly SMSC) SMC9514 Hub
Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
pi@fluidpi: ~$
```

4.4. Please enter the following command to flash Katapult:

```
make flash FLASH_DEVICE=2e8a:0003
```

where "2e8a:0003" should be replaced with the actual device ID obtained in step 4.3.

4.5. After flashing is complete, remove the USB_5V jumper and the Type-C cable.

1.) After SSH is successfully connected to Raspberry Pi, run

```
cd ~/klipper/
make menuconfig
```

Compile the firmware with the following configuration (if the options below are not available, please update your Klipper source code to the newest version).

[*] Enable extra low-level configuration options

Micro-controller Architecture (Raspberry Pi RP2040/RP235x) --->

Processor model (rp2040) --->

If not using KATAPULT

Bootloader offset (No bootloader) --->

Flash chip (GENERIC_03H with CLKDIV 4) --->

If using KATAPULT

Bootloader offset (16KiB bootloader) --->

If using USB communication

Communication Interface (USB SERIAL) --->

If using CAN bus communication

Communication interface (CAN bus) --->


(4) CAN RX gpio number

(5) CAN TX gpio number

(1000000) CAN bus speed

2.) Press 'q' to exit, and "Yes" when asked to save the configuration.

3.) Run **make** to compile firmware, "klipper. bin" file will be generated in **home/pi/klipper/out** folder when **make** is finished, download it onto your computer using the SSH application.



1.To use the CAN bus, you need to connect the CAN bus cable and insert a jumper at the position of the 120R termination resistor.


2. Run:

```
cd ~/Katapult/scripts
```

then run:

```
python3 flash_can.py -i can0 -q
```

to query the canbus ID (connect the CAN cable and power it on in advance), as shown in the figure below, the UUID of the device has been found



```
biqu@BTT-CB1:~/Katapult/scripts$ python3 flash_can.py -i can0 -q
Resetting all bootloader node IDs...
Checking for katapult nodes
Detected UUID: be69315a613c, Application: Katapult
Query Complete
biqu@BTT-CB1:~/Katapult/scripts$
```

3. Run:

```
python3 flash_can.py -i can0 -f ~/klipper/out/klipper.bin -u be69315a613c
```

The be69315a613c is replaced with the actual UUID. Note: klipper.bin needs to be made in advance, and the application start offset of Katapult is 16KiB offset, so Klipper's menuconfig Bootloader offset should also be 16KiB bootloader, as shown in the following figure.

```
biqu@BTT-CB1:~/Katapult/scripts$ python3 flash_can.py -i can0 -f ~/klipper/out/klipper.bin -u be69315a613c
Sending bootloader jump command...
Resetting all bootloader node IDs...
Checking for katapult nodes...
Detected UUID: be69315a613c, Application: Katapult
Attempting to connect to bootloader
Katapult Connected
Protocol Version: 1.0.0
Block Size: 64 bytes
Application Start: 0x8002000
MCU type: stm32g0b1xx
Verifying canbus connection
Flashing '/home/biqu/klipper/out/klipper.bin'...

[#####]

Write complete: 13 pages
Verifying (block count = 414)...

[#####]

Verification Complete: SHA = C3B1F96A8FCE766587BF4A9119095D80465875A3
CAN Flash Success
biqu@BTT-CB1:~/Katapult/scripts$
```

4. Run:


```
python3 flash_can.py -i can0 -q
```

to query. At this time, the Application changes from Katapult to Klipper, indicating that Klipper has been running normally


```
biqu@BTT-CB1:~/Katapult/scripts$ python3 flash_can.py -i can0 -q
Resetting all bootloader node IDs...
Checking for katapult nodes...
Detected UUID: be69315a613c, Application: Klipper
Query Complete
biqu@BTT-CB1:~/Katapult/scripts$
```

Raspberry Pi or CB1 update via DFU.

1. Please use a Type-C cable to connect the EBB SB2209 CAN V1.0 (RP2040) to the Raspberry Pi/CB1, and ensure that the USB_5V jumper is connected, in order to supply power to the EBB SB2209 CAN V1.0 (RP2040) via Type-C.



2. Press and hold the Boot button, and then click the Reset button to enter the DFU mode.



3. Enter in the SSH terminal command line

```
lsusb
```

Query DFU device ID

```
pi@fluiddpi:~$ lsusb
Bus 001 Device 005: ID 2e8a:0003 Raspberry Pi RP2 Boot
Bus 001 Device 004: ID 1d50:6061 OpenMoko, Inc. Geschwister Schneider CAN adapter
Bus 001 Device 003: ID 0424:0c00 Microchip Technology, Inc. ( formerly SMSC ) SMC9512/9514 Fast Ethernet Adapter

Bus 001 Device 002: ID 0424:9514 Microchip Technology, Inc. ( formerly SMSC ) SMC9514 Hub
Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
pi@fluiddpi:~$
```

4. Run:

```
cd klipper
```

to enter to the klipper directory, then run the following command to write the firmware:

```
make flash FLASH_DEVICE=2e8a:0003
```

Note: Replace 2e8a:0003 with the actual device ID found in the previous step.

5. After the firmware is written, run

```
ls /dev/serial/by-id/
```

to query the serial ID of the device (this ID can only be found in the USB communication mode, and this step is ignored in CANBus mode).


6. If USB communication is used, after the first writing, it is not necessary to manually press the Boot and Reset buttons to enter the DFU mode when updating again. You can directly enter

```
make flash FLASH_DEVICE=/dev/serial/by-id/usb-Klipper_rp2040_4550357128922FC8-if00
```

to write the firmware (Note: replace /dev/serial/by id/xxx with the actual ID found in the previous step).

After flashing is complete, remove the USB_5V jumper and the Type-C cable.

Used with BIGTREETECH U2C module.



1. Enter the command

```
sudo nano /etc/network/interfaces.d/can0
```

in the SSH terminal and execute

```
allow-hotplug can0
iface can0 can static
    bitrate 1000000
up ifconfig $IFACE txqueuelen 1024
```

Set the CAN-BUS speed to 1M (it must be consistent with the speed set in the firmware (1000000) CAN bus speed), save (Ctrl+S) and exit (Ctrl+X) after modification, and enter

```
sudo reboot
```

to restart Raspberry Pi.

2. Each device on CAN bus will generate a `canbus_uuid` according to the UID of MCU, to find each microcontroller device ID, make sure the hardware is powered on and wired correctly, and then run:

```
~/klippy-env/bin/python ~/klipper/scripts/canbus_query.py can0
```


3. If an uninitialized CAN device is detected, the above command will report the device's `canbus_uuid`.

```
Found canbus_uuid=0e0d81e4210c
```


4. If Klipper has been running normally and connected to this device, then `canbus_uuid` will not be reported, which is normal.

1. Enter Raspberry Pi IP address into your browser, and find the reference config for the motherboard in the directory shown below, if there is no such config available, update your Klipper source code to the newest version or download it from GitHub:

<https://github.com/bigtree-tech/EBB>



2. Upload the configuration file of the motherboard to Configuration Files.



3. Add the configuration of this motherboard in the "printer.cfg" file:

```
[include sample-bigtreetech-ebb-sb-canbus-v1.0.cfg]
```

```
X      printer.cfg
11
12      [include sample-bigtreetech-ebb-canbus-v1.0.cfg]
13
```

4. Enter the correct ID (USB serial or canbus).

```
X      sample-bigtreetech-ebb-sb-canbus-v1.0.cfg
8      [mcu EBBCan]
9      serial : /dev/serial/by-id/usb-Klipper_firmware_12345-if00
10     #canbus_uuid: 0e0d81e4210c
```

5. Configure the module's specific functions according to

```
https://www.klipper3d.org/Overview.html
```

Website

www.bigtree-tech.com

GitHub

www.github.com/bigtreetech

Discord

www.discord.gg/5jdwbYYZuv