FOSE1025 — Scientific Computing

Week 7 Lecture 1: Cleaning Data

Diego Mollá

FOSE1025 2022H1

Abstract

In this lecture we will focus in the step of data cleaning, with particular emphasis on text data. We will look at various tools that both Excel and MATLAB provide to help cleaning raw data and process text: convert types, parse text, split text, filter data.

Update April 4, 2022

Contents

1	Cleaning Text Data in Excel	1
2	Cleaning Data in MATLAB	4

Reading

- LinkedIn Learning Excel 2016: Cleaning up Your Data https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data
- \bullet MATLAB Characters and Strings https://au.mathworks.com/help/matlab/characters-and-strings.html

1 Cleaning Text Data in Excel

Text as Unstructured Data

- Much of the information you find is input in text.
- People can understand text very easily ...
- ... but not machines!
- Text is often called a kind of unstructured data.
- Excel and MATLAB can help find structure from text.



Watch these LinkedIn Learning Videos for Excel



Macquarie University students have access to free videos from LinkedIn Learning. To access these, login using your student credentials. Watch these videos:

- Use Text Functions: https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/use-text-functions
- Use CONCAT and TEXTJOIN functions to combine data:

 https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/use-the-concat-and-textjoin-functions-to-combine-data
- Combine data via concatenation https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/combine-data-via-concatenation
- $\begin{tabular}{l} \bullet \ Split \ data \ into \ columns \\ https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/split-data-into-columns-with-the-text-to-columns-feature \\ \end{tabular}$
- Using Flash Fill

 https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/use-flash-fill-for-faster-combiningand-splitting

Some Useful Text Functions

CH-05.xlsx From https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/use-text-functions

Name	Description
LOWER PROPER UPPER	Converts all text to lowercase Capitalizes only letters than start the entry or follow a space or punctuation Converts all text to uppercase
REPLACE SUBSTITUTE REPT	Replaces characters within text, based on content, not on character position Replaces characters within text, based on character position, not on content Repeats text a given number of times
LEFT MID RIGHT	Returns the leftmost characters from a text value Returns a specific number of characters from a text string starting at the position you specify Returns the rightmost characters from a text value
FIND SEARCH EXACT	Finds one text value within another (case-sensitive) Finds one text value within another (not case-sensitive) Checks to see if two text values are identical
LEN TEXT VALUE	Returns the number of characters in a text string Formats a number and converts it to text Converts a text argument to a number
CLEAN TRIM	Removes all nonprintable characters from text Removes spaces from text
CONCATENATE CONCAT DOLLAR FIXED TEXTJOIN	Joins several text items into a cell (on older Excel versions) Joins several text items into a cell (on newer Excel versions) Converts a number to text, using the \$ (dollar) currency format Formats a number as text with a fixed number of decimals Joins several text items into a cell using a delimiter

These are only some of the functions that can work with text. At the lecture, we will see some of them at work using the file CH-05.xlsx.

Concatenating Text

Several ways to concatenate text:

• Using the & operator

```
=A1 & " " & B1
```

• CONCAT (in Excel versions from 2016, Mobile, Web)

```
=CONCAT("Stream population for ", A2, " ",
A3, " is ", A4, "/mile.")
=CONCAT(B2:C8)
```

- CONCATENATE (in older Excel versions)
- \bullet TEXTJOIN (in Excel versions from 2019, Web joins text using a text delimiter)

Parsing Text Using Text to Columns Feature

- Some columns have complex text that needs to be parsed.
- Excel can parse the text of a column and split it into several columns.
- On Excel Online, look at the "Data" tab

CH-05.xlsx; watch the video https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/split-data-into-columns-with-the-text-to-columns-feature



The Magic of Flash Fill

- Flash Fill is one of Excel's most powerful and least known features.
- Uses AI techniques to try to predict how you want to parse the text.
- Looks like magic, and sometimes might not work for your task.

CH-05.xlsx; watch the video https://www.linkedin.com/learning/excel-2016-cleaning-up-your-data/use-flash-fill-for-faster-combining-and-splitting



2 Cleaning Data in MATLAB

MATLAB's Column Types

https://au.mathworks.com/help/matlab/data-types.html

- All values of a MATLAB table column are of the same type.
- Common types in MATLAB are:

Numeric

- double This is the default numerical type. It is what is called double-precision floating point.
- There are other types that you can use to represent integers (with or without sign) and other numerical types.

Text

string — Starting in MATLAB's version R2016b, this is the preferred way to store text. It's called "string arrays".

- char — Available in all MATLAB versions but not recommended from MATLAB version R2016b.
 It's called "character arrays".

Dates and Time

- datetime MATLAB stores dates and times using the same format.
- We will look at MATLAB's dates and times in a subsequent lecture.

Categorical

- Use this type (instead of, say, string, if you know that the column has a finite set of possible values.)
- For example, C = categorical({'R','G','B','B','G','B'}) creates a categorical array with six elements that belong to the categories R, G, or B.

Examining the Type of a Table Column

 $File: mlb_players.csv$

- MATLAB's summary function gives a summary of a table.
- It reports various information, including the types of all of its columns.

Try This

- 1. Use (or generate) the live script that imports the file mlb_players.csv and stores the generated table in the variable mlb_players.csv.
- 2. Add this command to the live script (without ";" at the end):

```
summary(mlb_players)
```

The output should look like this:


```
Min 62
Median 69.5
Max 75
Weightlbs: 18x1 double
Values:
Min 98
Median 150
Max 176
```

In this output you can see the type of each column. For columns with categorical data, it will list the number of values in each category. And for columns with numerical data, it will show the minimum, median, and maximum value.


Text or string?

Depending on what part of MATLAB you use, it may say that a column type is "Text" or "string". Both are the same!

If using the text import tool you may see that the column type is "text".



If using summary you may see that the same column type is "string". >> \$ummary(mlb_players)



Setting the Type in a Table Column

File: mlb_players.csv

• A common problem with MATLAB (and Excel) is that the default settings when reading a CSV file might not be correct.

胴

- For example, by default, readtable may store text as a character array, not a string array.
- If we use MATLAB's import tool we can specify the data type (see lecture week 6).
 - Check how the generated script defines options to the readtable function.
- We can also change the data type after the table has been created.

```
mlb.Team = categorical(mlb.Team);
mlb.Name = string(mlb.Name);
```

In the example mlb.Team = categorical(mlb.Team);:

- mlb. Team indicates the column with name Team which is stored in the table with name mlb.
- categorical(mlb.Team) returns a column vector where the type of the elements is categorical.
- mlb.Team = ... means that the Team column of the table mlb is assigned the result on the right-hand side of the = (which, in our case, is the contents of the same column that has been converted to the categorical type).

Filtering Data in an Array



- MATLAB can identify what values meet a particular condition.
- For example, to find what elements in an array "ages" are larger than 10:

```
>> ages = [1 2 5 34 2 32];
>> ages > 10
ans =
1x6 logical array
0 0 0 1 0 1
```

- The result is a filter represented as a logical array: each element is either 0 ("false") or 1 ("true").
- We can now select all elements whose corresponding logical array indicates true.

```
>> ages(ages > 10)
ans =
34 32
```

Filtering Data in a Table

File trees.csv

• The same process can be used to select rows whose columns meet a particular condition.

```
>> trees.Girth_in_ > 15
ans =
    31x1 logical array
0 0 0 ... 1 1 1
>> wide_trees = trees(trees.Girth_in_ > 15, :)
```

- We can combine multiple filters by using Boolean operators.
- Can you tell what's the output of the following?

```
>> trees = readtable("trees.csv");
>> filtera = trees.Girth_in_ > 10;
>> filterb = trees.Girth_in_ < 15;
>> filterc = trees.Height_ft_ > 70;
>> result = trees(filtera & filterb | filterc, :)
```

Take-home Messages

Excel

- Fixing problems from manual data input.
- \bullet Importing text.
- Text to columns feature.
- Flash Fill.

MATLAB

- Changing data types.
- Text functions.
- Filtering data.

What's Next

- Friday 8 April: Communicator hurdle
- 2 weeks without classes, time to catch up!
- Week 8 lecture: Transforming Data