



Profiling oneAPI Code Using the VTune™ Server

Georg Zitzlsberger
IT4Innovations

Stephen Blair-Chappell
www.bayncore.com



Four Step Strategy



VTune Self-Checker

`<install-dir>/bin64/vtune-self-checker.sh`

Hotspots/Threading in the **user-mode** sampling

Hotspots hardware **event-based** sampling with/without stacks

HPC Performance Characterization

Microarchitecture Exploration analysis

Memory Access analysis with uncore events

Threading with hardware **event-based** sampling

Performance Snapshot

GPU Compute/Media Hotspots

Running the Self-Checker


```
#source the tools
source /opt/intel/oneapi/setvars.sh

#set profiling permissions
echo 0 | sudo tee /proc/sys/dev/i915/perf_stream_paranoid
echo 0 | sudo tee /proc/sys/kernel/kptr_restrict
echo 0 | sudo tee /proc/sys/kernel/yama/ptrace_scope
echo 0 | sudo tee /proc/sys/kernel/perf_event_paranoid

# call the self checker
vtune-self-checker.sh
```

VTune Profiler Server

- Light weight server.
- View from web browser
- Personal use
 - Already installed with HPC toolkit
 - Available on DevCloud
- Full-scale corporate deployment
 - Multi-User
 - Supports SAML SSO
 - Supports reverse proxy and transport security



<https://www.intel.com/content/www/us/en/develop/documentation/vtune-help/top/installation/install-web-server.html>

1-Client 1-Host setup

From laptop

Replace with
your compute
node name

```
ssh stephen@192.168.0.66  
source /opt/intel/oneapi/setvars.sh  
vtune-backend --web-port=55001 --enable-server-profiling  
# it returns a url to open in browser on laptop - do after next step
```

From laptop in a new command prompt :

```
ssh -L 127.0.0.1:55001:127.0.0.1:55001 stephen@192.168.0.66
```


DevCloud setup

- `ssh devcloud`
- `qsub -l`
- `ssh -L 127.0.0.1:55001:127.0.0.1:55001 devcloud`
- `ssh -L 127.0.0.1:55001:127.0.0.1:55001 s000-n000`
- `vtune-backend --web-port=55001 --enable-server-profiling`

Replace with
your compute
node name

Next Steps...

After running a performance snapshot, VTune recommends the next type of analysis to do.



Run and collect VTune™ data

```
vtune -collect gpu_hotspots -result-dir vtune_data a.out
```

Various types of profiling data can be collected like `hotspots`, `memory-consumption`, `memory-access`, `threading` ...

Use the command line help to find out more:

```
vtune --help -collect
```

Generate html report for collected VTune™ data:

```
vtune -report summary -result-dir vtune_data -format html -report-output  
$(pwd)/summary.html
```

Various types of report can be generated like `summary`, `top-down`, `callstacks` ...