ENG4014 Aerospace Design Project 4M
Interim Report
Group 8

School of Engineering

College of Science and Engineering

University of Glasgow

Anton Soderqvist, Fraser Morrison, Mark Sullivan, Matthew Murphy,
Rafał Trzeciak, Saad Saeed and Tomas Coelho

January 17, 2022

Contents

Chapter 1

Introduction

Introduction here

Chapter 2

Market Analysis and Concept Selection

Market Analysis and Concept Selection here

Chapter 3

Concept Summary and Aircraft Layout

Concept Summary and Aircraft Layout here

Chapter 4

Design Analysis and Feasibility

4.1 Safety

Safety here

4.2 Center of gravity (Fraser and Rafał)

Since the RJ100 is a commerial airctraft, when it's converted to a firefighter there will be lots of unnecessary weight, that has no use for a firefigher aircraft. For example passenger seats, Kitchen and cabin bins ect. This allows the plane to take more retardant, making it better at its job. But in removing all this unnecessary weight, the CG of the plane will change as well. The RJ100 has an acceptable safe range for the center of gravity in terms of the chord length which is INSERT VALUE to INSERT VALUE. The plane cannot fly safely if the value of the center of gravity along the x-axis of the plane is outwith this range. The center of gravity also has to within this range at every point from the tank being full to empty.

4.2.1 Method of Analysis

The process of calculating center of gravity of an object is relatively simple but can be time consuming by hand if there are a lot of different things that are being removed from the plane. Hand calculations would also make it harder to change individual values, as we need the ability to change the weight and/or the positions of objects in the airplane to help achieve the safe center of gravity position.

According to Baker & Haynes (2020) the formula for the x,y and z value of the center of gravity are shown in the equation 4.1:

$$\bar{x} = \frac{\sum \bar{x}_i m_i}{\sum m_i} \quad \bar{y} = \frac{\sum \bar{y}_i m_i}{\sum m_i} \quad \bar{z} = \frac{\sum \bar{z}_i m_i}{\sum m_i} \tag{4.1}$$

Since the weight of the aircraft and the cg position is already known with all the unnecessary weight that needs to be removed the aircraft can effectively be represented in the formula as a particle with a known mass and position. Then the new cg of the aircraft can be found using the formula 4.1, but the mass of all the objects that need to be removed are negative, since the old cg and mass of the plane already have these objects.

4.2.2 Matlab code

Code was written in Matlab to calculate the new cg position by implementing equation 4.1

```matlab
clc
clear
close all
format long g

Data = readtable("aircraft_items.xlsx"); %import data from excel file

starting_mass=25600; %starting mass in kg (operational empty weight 25600)(Operational zero fuel mass
    37875)
absoulute_cog_to_nose=14 + 1.719; %%distance from nose to the wing start + x_mgc

cg.x=-1*(absoulute_cog_to_nose+1.239056); % starting cg x position
cg.y=0; %starting cg y position
cg.z=0; %starting cg z position

%starting moment of inertia tensor values
I_convert=1.3558179619; %slug*ft^2 to kg/m

I.xx=533965*I_convert;
I.xy=0*I_convert;
I.xz=59261*I_convert;
I.yx=I.xy;
I.yy=607525*I_convert;
I.yz=0*I_convert;
I.zx=I.xz;
I.zy=I.yz;
I.zz=1019696*I_convert;

%calculating new cg
cg_sum.x=starting_mass*cg.x;
cg_sum.y=starting_mass*cg.y;
cg_sum.z=starting_mass*cg.z;

end_mass=starting_mass;

for i=1:1:height(Data)

    %extract mass,x,y and z values from file for object
    mass=Data{i,2};
    x=Data{i,3};
    y=Data{i,4};
    z=Data{i,5};

    %take away object mass
    end_mass=end_mass - Data{i,2};

    cg_sum.x=cg_sum.x - (mass*x);
    cg_sum.y=cg_sum.y - (mass*y);
    cg_sum.z=cg_sum.z - (mass*z);

end

%calculate new cg position
cg_new.x=cg_sum.x/end_mass;
cg_new.y=cg_sum.y/end_mass;
cg_new.z=cg_sum.z/end_mass;
```

```
56
57  %print new cg position
58  cg_new
59  %print new mass
60  end_mass
61
62  %calculate and print value of cg position in x axis as a fraction of the
63  %MAC
64  cg_from_mac = cg_new.x + absoulute_cog_to_nose;
65  fraction_of_mac = cg_from_mac / − 3.404
```

The data for the objects that are going to be removed from the airplane are in the excel file named "aircraftitems.xlsx" on line 8 the code and contain the mass and the x,y, and z position of the center of gravity of each other objects. The axis used for the positions is the standard aircraft axis with the origin at the nose of the aircraft. Because the code assumes each of the objects are being taken away from the plane, the tank can be added in to move the center of gravity by giving it a negative mass in the excel file.

4.2.3   Consequence of result of code on design decisions

4.3   Delivery release system / Tank Pressurisation

Tank pressure here

4.4   Structural Support

Structural Support here

Chapter 5

Draft Plans for the Preliminary Design Stage

Draft Plans for the Preliminary Design Stage here

Chapter 6

Conclusions

Conlusions here

Chapter 7

Project Plan

project plan here

References

Baker, D. W., & Haynes, W. (2020). Engineering statics: Open and interactive.