



DPUCANLOG

Records CAN bus messages in an ASCII file.

The same (CSV) file format as in DPUDataFile is used.

In contrast to DPUDataFile, it is easy to record all fields of a CAN message using DPUCANLOG (e.g. by setting the *Log* option in DPUCANDBC), because it is not necessary to connect each of the fields separately to the recording DPU.

1. Static parameters:

<i>LogFile</i>	File name of the log file. If a relative path is entered, the file is created in the SILAB data folder (e.g. D:\SILAB\Data).
<i>Overwrite</i>	Overwrite an existing log file (<i>true</i>) or create numbered recordings instead (<i>false</i>)?

2. Dependencies to other DPUs:

In addition to DPUCANLOG, the DPUCANDBC and DPUCANBUS must be running on the same computer. These DPUs provide the logged data.

3. Example:

```
DPUCANBUS ~localCAN {
    Computer = { LOCALHOST };
    Index = 11;

    CANMode = 0;
    CANType = 0; # standard
    Baud = 1; # 500 kBaud
};

DPUCANDBC CAN_549 {
    Computer = { LOCALHOST };
    Index = 12;

    CANMode = 0;
    DBCFile = "CAN\messages.dbc";
    ID = 549;
};
```



SILAB DRIVING SIMULATION

version Version 7.1 documentation

```
DPUCANLOG CANlog {  
    Computer = { LOCALHOST };  
    Index = 13;  
  
    LogFile = "CANLogData.asc";  
};
```