



DPULogSaver

Dies Saves SILAB log files permanently, if a serious delay occurred during the simulation.

1. Inputs:

In Additional input variable that is checked during the simulation (if desired)

2. Static parameters:

Path Path where the log files are stored. If an absolute path is not specified, the path will be located below the SILAB installation folder.
Default: (\SILAB\)\Log\
MaxIn Maximum tolerated value for the In variable. Default: 1
MaxTimeErrorMS Maximum tolerated simulation delay (ms). Default: 100

3. Outputs:

ErrorDetected Is set to true if an error has been detected during this simulation.

4. Functional principle:

Supervises the simulation: While the simulation is running, checks continuously for serious delays (i.e. the measurement time error exceeds the parameter *MaxTimeErrorMS*). Additionally, if the *In* variable exceeds the *MaxIn* value, this is also noted as an error.

If any error occurred during the simulation, SILAB's log files are copied to the location specified by the *Path* parameter, prefixed with the current time, as soon as the simulation has been stopped.

Note that this DPU should be used with a high Index value, so that it can accurately track the contents of all DPU variables.

5. Example:

This DPU works well using the following script:

In this case, the default values of all parameters are used, which usually work well.

```
DPULogSaver LogSaver
{
    Computer = {ALL};
    Index = 1000;
};
```