



DPUSCNXObjectsSGE

Inserts objects into the visualization SGE and positions them along the road network defined in the database SCNX.

Optionally, several alternative objects can be specified. Only one of them will be visible at any time.

1. Inputs:

Alternative

Show objects at this position within each object set.

Default: 0 (first object within each set)

2. Dynamic parameters:

PositionDelayMS

Delay (ms) when positioning an object on a road segment that has newly entered the visible area.

Default: 100

3. Static parameters:

Objects

Definition of the objects (see below)

ve

Design speed (km/h) for the objects. This parameter influences the size of traffic signs.

Default: 70

4. Definition of displayed objects:

The displayed objects are defined in the following format:

```
DPUSCNXObjectsSGE Obj {
    Objects = {
        # first object set
        (<Mod>.<LRN>, ("<object.model.name>", <S>, <D>, <rot>)),
        # second object (with alternative object)
        (<Mod>.<LRN>, ("<object.model.name>", <S>, <D>, <rot>),
        ("<alt.name>", <S>, <D>, <rot>)),
        ...
    };
};
```

The individual settings are detailed below:

<Mod>.<LRN>

Module and course instance names, along which the object is placed. They are separated by a dot.

Example: The module Module1, which has been instantiated in the map using Module1 m1; contains the road segment Course1, which



	has been instantiated in the module using Course1 c1;. To place an object along this course, enter m1.c1.
"<object.model.name>"	SGE resource name of the 3D model. The objects are searched within SILAB's model path \SILAB\lib\graphics\default\models or the project folder (such as \SILAB\Projects\MyProject); subfolders are separated by a dot. If a sign is selected (i.e. the object's name starts with "sign.") the object is generated automatically by SILAB when the simulation is loaded. More information on sign generation is available in the "Reference Database SCNX".
<S>	Position along the course (Track length in meters) where the object is placed.
<D>	Lateral distance [m] from the centerline of the road. Positive values are to the right.
<rot>	Object rotation relative to the road orientation (in degrees). Positive values signify a rotation to the right.

The first object within each set is shown, when Alternative = 0; the second, when Alternative = 1, and so forth.

5. Dependencies to other DPUs:

DPUSCNXObjectsSGE depends on functions of **DPUSCNX**, **DPUSCNXSGE** and **DPUSGEWorld**, which must also run on the computer(s) on which it is used.

The Index value of **DPUSCNXObjectsSGE** must be higher than the Index value of its dependencies.