



DPUSGEScreenServerNDI

Sends the dynamic contents of a window over the network. Implements the NDI protocol, which can be received using DPUSGETextureNDI.

1. Static parameters:

<i>Source</i>	DPU instance name window whose contents are sent. Instances of DPUSGEView, DPUMMI and DPUBirdsEye can be used. An empty string captures the contents of the desktop, i.e. any window that is located at the given coordinates. Note: When using an empty string, FourCC must be set to "RGBX". Default: <i>SGEView</i>
<i>Name</i>	Name of the NDI Stream. If you will receive the stream with any NDI-Tool or DPUSGETextureNDI, the name of the stream will be: <NameOfComuter> (<Name>). Default: <i>SGEView</i>
<i>X, Y</i>	Position of the top-left edge of the transmitted area within the selected window (or on the desktop).
<i>W, H</i>	Size of the transmitted area within the selected window (or on the desktop). Note: There is no default value; the parameters must be set.
<i>Subsample</i>	Proper divisor of the frame rate. The following equation is used: $\text{Transmission frame rate} = \text{Source window update rate} / \text{Subsample}$. Default: 1
<i>Refresh</i>	NDI refresh rate. Every <i>Refresh</i> 'th image is transmitted completely, even if the contents have not changed. This mechanism safeguards against packet loss. Default: 10, but in a LAN 100 can be used as well (which reduces the data rate).
<i>FourCC</i>	Four-character-code of the data format of the stream. Possible values are RGBA, BGRA, RGBX, BGRX and UYVY. Default: RGBA

2. Outputs:

<i>FrameNumber</i>	Frame number of the last sent image.
--------------------	--------------------------------------

3. Functional principle:

Using *DPUSGEScreenServerNDI*, the contents of a graphics window are captured. Using the NDI protocol, they are then sent using a UDP connection over the network.



4. Dependencies to other DPUs:

The DPU that provides the captured window must run on the computer on which *DPUSGEScreenServer* is executed. The *W* and *H* parameters must not be larger than the window size of the captured window.

5. Example:

This DPU works well using the following script:

```
DPUSGEScreenServerNDI ScreenServer
{
    Computer = {VIS};
    Index = 62;

    Source = SGEView;
    Name = "SGEView";

    W = 60;
    H = 480;
};
```