



DPUSGETextureScreen

Creates a dynamic video texture in the virtual world. The texture contains an image that is received over the network from a ScreenSend server, such as DPUSGEScreenServer.

1. Static parameters:

<i>View</i>	Name of the SGE view for which the dynamic texture is updated. Additionally, it will be visible in all views that share textures with the specified SGE view. Default: <i>SGEView</i>
<i>TextureName</i>	Name of the created video texture, which must start with a dollar sign (\$). Default: <i>\$Video</i>
<i>Server</i>	Computer name, alias name or IP address of the computer on which the ScreenSend server is running. Default: 127.0.0.1 (the local computer)
<i>Port</i>	UDP port of the ScreenSend server. Default: 5955
<i>Password</i>	Password for the ScreenSend server. If one is entered, the same password must be set in the server. Default: (<i>empty</i>)
<i>ConnectTimeoutMS</i>	Timeout in milliseconds for the connection to the ScreenSend server. Default: 3000

2. Outputs:

<i>ImageW, ImageH</i>	Image size (in pixels) of the received image.
<i>FPS</i>	Received image frame rate.
<i>FrameNumber</i>	Frame number of the last received image.

3. Functional principle:

Using *DPUSGETextureScreen*, a dynamic video texture is created in the virtual world. The texture contains a live image that is received uncompressed from a ScreenSend server over the network.

For example, when combined with *DPUSGEScreenServer*, the graphical view of one computer can be embedded into another's.

4. Example of a SGE object which references a video texture:

```
define SIG3DObject VideoObj
{
    AlphaTest = 0.2;
```



```
Blend = false;
// [...]
Texture = $MyVideo;
TextureFilter = NoCompression | ClampS | ClampT | MagLinear |
               MinLinear | Tex-ture;
// [...]
};
```

5. Dependencies to other DPUs:

Please make sure that the computer on which **DPUSGETextureScreen** runs also executes **DPUSGEWorld**, **DPUSGEObjectXXX** and **DPUSGEView**. The Index values of these DPUs must be set in the following order:

DPUSGEWorld.Index < DPUSGETextureScreen.Index < DPUSGEObjectXXX.Index < DPUSGEView.Index

6. Example:

This DPU works well using the following script:

```
DPUSGETextureScreen VidTexture
{
    Computer = {VIS};
    Index = 50;

    TextureName = "$MyVideo";
    Server = "VIS";
    # Alias name of the computer from which an image is received
    Port = 5955;      # UDP port
};
```