



DPUStopper

Automatically stops the simulation based on an input variable.

1. Inputs:

Stop

Whenever this input's value is 1, and the current simulation has been running for more than *MinTimeMS* milliseconds, it is stopped.

2. Static parameters:

MinTimeMS

Minimum time that the simulation must be running, before this DPU reacts to the input *Stop* (in milliseconds).

MaxTimeMS

Maximum allowed run time of the simulation. After this time (in milliseconds) has passed, the simulation is stopped, independent of the input value.

If this parameter is set to 0 (the default), the simulation can run indefinitely.

Notes:

If possible **DPUStopper** should be replaced by **DPURemoteControl**, which offers additional functionality and doesn't have to run on the operator computer.

3. Functional principle:

The DPUStopper must be run on the operator computer of a simulation. It communicates directly with the SILAB system and therefore has no output variables. A simulation that has been stopped by DPUStopper is in the same state that it had after the workspace was loaded and before the simulation was launched.

If desired, the simulation can be shut down completely using DPUStopper. To do so, the following statement has to be added to the *SILAB System* section:

```
SILAB System {  
    LaunchProcess = { LC_SWITCHOFF_ON_STOP, LC_CLOSE_ON_SWITCHOFF };  
};
```

Further information on the LaunchProcess statements can be found in the "Reference SILAB Configuration and Operation", chapter "System configuration".