



DPUTTSCient

Connects to a computer running DPUTTSServer and allows for electronic speech synthesis („text-to-speech“) using the operating system’s speech synthesis facilities.

1. Inputs:

Text

Text that should be processed next.

Speak

Changing this input from 0 to 1 triggers synthesis of *Text* and playback.

2. Static parameters:

ServerIP

IP address or alias name of the computer where DPUTTSServer is running.

default: *TTS*

Port

TCP port of that server that should be connected to.

default: 0 which means the port given in the SILAB network configuration (*sys.par*) is used.

3. Dependencies:

DPUTTSServer must be running at the computer named at *ServerIP*.

4. Functional principle:

DPUTTSServer opens a TCP port and waits for incoming connections.

As soon as a connection has been established, all data is read line by line, interpreted as UTF8 coded strings then synthesised using the operating system’s text to speech engine and played back on the default audio device.

DPUTTSCient can establish such TCP connections to **DPUTTSServer** and allows to send texts given to the DPU input which are then synthesised accordingly.

DPUTTSSCNX may be loaded additionally to *DPUTTSCient* or and allows to trigger playback via events of the SCN database. (See documentation for details.)

5. Example:

DPUTTSServer TTS

```
{  
    Computer = {TTS};  
    Index = 20;  
    TreeviewGroup = "Sound";
```



SILAB DRIVING SIMULATION

version Version 7.1 documentation

```
};  
DPUTTSCClient TTSCClient  
{  
    Computer = {TTS};  
    Index = 50;  
    TreeviewGroup = "Sound";  
};  
# support hedgehogs  
DPUTTSSCNX TTSSCNX  
{  
    Computer = {TTS};  
    Index = 51;  
    TreeviewGroup = "Sound";  
};
```