

# DGI ADAPTER SPECIFICATION TEST RESULTS

Performed on April 10, 2014

*Tester:*  
Michael Catanzaro

*Commit:*  
38f836d405b0c7c2305a1430a942c30a03ba7fbd

---

Test Prefix	Description	Expected Result	Result
BadXml1	Attempt to use an adapter of invalid type	Unregistered adapter type: golbat	PASS
BadXml2	Attempt to use an adapter that has no state tag	Failed to create adapter: No such node (state)	PASS
BadXml3	Attempt to use an adapter that has no command tag	Failed to create adapter: No such node (command)	PASS
BadXml4	Attempt to use an adapter with nonconsecutive state table indices	The state indices are not consecutive.	PASS
BadXml5	Attempt to use an adapter with nonconsecutive command table indices	The command indices are not consecutive.	FAIL <sup>1</sup>
BadXml6	Attempt to use an adapter with two devices of the same name and type in the state table	The device signal (SST1,gateway) is already registered as state information.	PASS
BadXml7	Attempt to use an adapter with two devices of the same name and type in the command table	The device signal (SST1,gateway) is already registered as command information.	PASS
BadXml8	Attempt to use an adapter with two devices of the same name and different type in the state table	Failed to create adapter: Multiple devices share the name: SST1	PASS

---

<sup>1</sup>The state indices are not consecutive.

Test Prefix	Description	Expected Result	Result
BadXml9	Attempt to use an adapter with two devices of the same name and different type in the command table	Failed to create adapter: Multiple devices share the name: SST1	PASS
BadXml10	Attempt to use an adapter with a device with no signals in the state table	Failed to create adapter: No such node (signal)	PASS
BadXml11	Attempt to use an adapter with a device with no signals in the state table	Failed to create adapter: No such node (signal)	PASS
BadXml12	Attempt to use an adapter with a device with an unrecognized signal	Failed to create adapter: The Sst device, SST1, does not recognize the signal: generation	PASS
BadXml13	Attempt to use an adapter with a device of unrecognized type	Unrecognized device type: Golbat	PASS
BadXml14	Attempt to use an adapter with two devices with the same index in the state table	Detected duplicate state index 1	PASS
BadXml15	Attempt to use an adapter with two devices with the same index in the command table	Detected duplicate command index 1	PASS
BadXml16	Attempt to use an adapter with an unclosed XML tag	unexpected end of data	PASS
BadXml17	Attempt to use an adapter with an incorrectly-specified host tag	resolve: Host not found (authoritative)	PASS
BadXml18	Attempt to use an adapter with an incorrectly-specified port tag	Failed to connect to localhost:40001 because: Connection refused	PASS
BadXml19	Attempt to use an adapter with one SST in the state table (but not in the command table)	Failed to create adapter: The device SST1 is missing at least one command.	PASS

Test Prefix	Description	Expected Result	Result
BadXml20	Attempt to use an adapter with one SST in the command table (but not in the state table)	Failed to create adapter: The device SST1 is missing at least one state.	PASS
BadXml21	Attempt to use an adapter with two state tables	XML contains multiple state tags	PASS
BadXml22	Attempt to use an adapter with two command tables	XML contains multiple command tags	PASS
BadXml23	Attempt to use an adapter that contains a device with two types	Invalid entry at state index = 1: too many subtags	FAIL <sup>2</sup>
BadXml24	Attempt to use two adapters with the same name	Multiple adapters share the name: HappyTestAdapter	PASS
BadXml25	Attempt to use two adapters with the same device name in each adapter	Duplicate device ID: SST1.	PASS
BadXml26	Attempt to use two adapters with the same host and port	Synchronous Read Timeout	PASS
SingleDgi1	Use an adapter with one SST	SST Gateway (01): 111.11	PASS
SingleDgi2	Use an adapter with one SST and one DESD	Net DESD (01): 1111.11, SST Gateway (01): 111.11	PASS
SingleDgi3	Use an adapter with one SST and another adapter with one DESD	Net DESD (01): 1111.11, SST Gateway (01): 111.11	PASS
SingleDgi4	Use an adapter with a device that correctly contains an empty state table	System runs correctly	PASS

---

<sup>2</sup>The DGI runs without any warnings.

Test Prefix	Description	Expected Result	Result
SingleDgi5	Use an adapter with a device that correctly contains an empty command table	System runs correctly	FAIL <sup>3</sup>
MultipleDgi1	Five DGI each have an SST. Ensure that normal is computed correctly.	Normal: 30.00	PASS
MultipleDgi2	Five DGI each have some number of SSTs. Ensure that normal is computed correctly.	Normal: 30.00	PASS
MultipleDgi3	Five DGI each have an SST but two have active FIDs. Ensure that normal is computed correctly among the non-isolated DGI.	Normal: 30.00	PASS

---

<sup>3</sup>No such device currently exists in the system, so this cannot be tested.