Microservices

Desarrollo de Aplicaciones Cliente-Servidor

Dr. Jorge E. Villaverde

Agenda

- What are micro-services?
- Why do we want them? Or maybe not..
- What are the key challenges?






What's a microservice?


A monolithic application puts all its functionality into a single process...




A microservices architecture puts each element of functionality into a separate service...



Independent Processes




DECOUPLED




Why do we want them? Or maybe not..

The right tool for the right job



RESILIENCE



SCALING


A monolithic application puts all its functionality into a single process...




A microservices architecture puts each element of functionality into a separate service...




... and scales by replicating the monolith on multiple



... and scales by distributing these services across servers, replicating as needed.




DEPLOYMENT



Conway's law


"organizations which design systems ... are constrained to designs which are copies of the communication structures of these organizations"

Conway's law




REPLACEABLE SERVICES

A microservices architecture puts each element of functionality into a separate service...




MORE INTEGRATION




Service Oriented Architecture

(Smart pipes, dumb endpoints)




Microservices Architecture

(Smart endpoints, dumb pipes)




Cloud Native Architecture

(Infrastructure focused smart platform, business logic focused smart services)



What are the key challenges?


- BOUNDED CONTEXT
 - Domain Driven Design
- CHANGING DATA
 - Refactoring Databases
- TESTING
 - CONSUMER DRIVEN CONTRACTS




CQRS and Event Sourcing

- Command Query Responsibility Segregation
 - You can use a different model to update information than the model you use to read information.
 - The mainstream approach people use for interacting with an information system is to treat it as a CRUD datastore.
 - We may want to look at the information in a different way to the record store, perhaps collapsing multiple records into one, or forming virtual records by combining information for different places.

CRUD Model



CQRS Model



CQRS Attributes

- As we move away from a single representation that we interact with via CRUD, we can easily move to a task-based UI.
- CQRS fits well with event-based programming models. It's common to see CQRS system split into separate services communicating with Event Collaboration. This allows these services to easily take advantage of Event Sourcing.
- Having separate models raises questions about how hard to keep those models consistent, which raises the likelihood of using eventual consistency.
- For many domains, much of the logic is needed when you're updating, so it may make sense to use EagerReadDerivation to simplify your query-side models.
- If the write model generates events for all updates, you can structure read models as EventPosters, allowing them to be MemoryImages and thus avoiding a lot of database interactions.
- CQRS is suited to complex domains, the kind that also benefit from Domain-Driven Design.

When to Use It?

- Should only be used on specific portions of a system (a BoundedContext in DDD lingo) and not the system as a whole.
- For handling high performance applications. CQRS allows you to separate the load from reads and writes allowing you to scale each independently.

Teorias de las Ciencias de la Computación

- Parnas' information hiding what pieces are
- Postel's Law how pieces compose
- Armstrong how software can respond to the physical world
- Conway's Law how software interacts with people
- Boehm's The Constructive Cost Model
- Constantine's Cohesion and Coupling
- Dijkstra's theory of cognitive limits ("Go to stmt considered harmful")
- Wirth's stepwise refinement
- Meyer's Design by Contract

Preguntas

