FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
Type	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR
Commit ID	1a664f5	3e71b5d	e61a754	3d7746c	b84ccd4	f731a65	bade23d	f30a732	f92f83b	dceb5f8
Commit Date	2017-03-08	2017-04-02	2017-04-04	2017-04-25	2017-05-16	2017-05-24	2017-06-02	2017-06-27	2017-07-01	2017-07-21

ANVL-ISIS-1.1

MUST

ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU

```
IS to IS Hello PDU
Level 1 LAN IS to IS hello PDU must have
1. Intra-domain Routing Protocol Discriminator = 0x83
2. PDU type = 15
3. Version/Protocol ID extension = 1
4. Version = 1
```

| Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass |
| FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass |

ANVL-ISIS-1.2

MUST

ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU

```
IS to IS Hello PDU
Bit 6-8 of PDU Type (5th octet), Reserved (7th octet), bit 3-8 of
Reserved/Circuit Type (9th octet) and 8th bit of Priority are
reserved which are always set to zero in Level 1 LAN IS to IS
hello PDU.
```

| Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass |
| FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass |

ANVL-ISIS-1.3

MUST

ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU

```
IS to IS Hello PDU
The valid ID Length field shall take any one of these following values:
1. An Integer between 1 and 8, inclusive, indicating an ID field of
the corresponding length
2. The Value zero, which indicates a six octet ID, field length
3. The Value 255, which means a null ID field (i.e., zero length)
```

| Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass |
| FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass |

ANVL-ISIS-1.4

MUST

ISO/IEC 10589:1992(E)s9.5 p49-50 Level 1 LAN IS to IS hello PDU

```
IS to IS Hello PDU
In a LAN Level 1 IIH the Circuit Type must be either 1 or 3
```

| Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass |
| FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass |

ANVL-ISIS-1.5

MUST

ISO/IEC 10589:1992(E)s9.5 p50 Level 1 LAN IS to IS hello PDU
RFC 1195 s5.3.1 p37-38 Level 1 LAN IS to IS hello PDU

```
IS to IS Hello PDU
The valid Codes that must be present in the VARIABLE LENGTH FIELD
of Level 1 LAN IS to IS hello PDU are:
Area Address
Protocols Supported
IP Interface Address
```

| Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass | Ubuntu 16.04: pass |
| FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: untested | FreeBSD 10.3: pass | FreeBSD 10.3: pass | FreeBSD 10.3: pass |

FRROUTING
RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-1.6 **MUST**	RFC 1195 s4.4 p32 Maintaining Router Adjacencies s5.2 p34 Overview of IP-specific Information for IS-IS									
	IS to IS Hello PDU The Protocol supported field must be present in all IS-IS Hello Packets send by IP-only routers									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.7 **MUST**	NEGATIVE : RFC 1195 s4.4 p32 Maintaining Router Adjacencies									
	IS to IS Hello PDU The Protocol Supported field must be present in all IS-IS Hello Packets send by IP-only routers									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.8 **MUST**	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU									
	IS to IS Hello PDU Level 2 LAN IS to IS hello PDU must have 1. Intra-domain Routing Protocol Discriminator = 0x83 2. PDU type = 16 3. Version/Protocol ID extension = 1 4. Version = 1									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.9 **MUST**	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU									
	IS to IS Hello PDU Bit 6-8 of PDU Type(5th octet), Reserved(7th octet), bit 3-8 of Reserved/Circuit Type(9th octet) and 8th bit of Priority are reserved which are always set to zero in Level 2 LAN IS to IS hello PDU.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.10 **MUST**	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU									
	IS to IS Hello PDU The valid ID Length field shall take any one of these following values: 1. An Integer between 1 and 8,inclusive,indicating an ID field of the corresponding length 2. The Value zero,which indicates a six octet ID, field length 3. The Value 255,which means a null ID field(ie. zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.11 **MUST**	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU									
	IS to IS Hello PDU In a LAN Level 2 IIH the Circuit Type must be either 2 or 3									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-1.12 **MUST**	ISO/IEC 10589:1992(E)s9.6 p51-52 Level 2 LAN IS to IS hello PDU RFC 1195 s5.3.2 p38-39 Level 2 LAN IS to IS hello PDU									
	IS to IS Hello PDU The valid Codes that must be present in the VARIABLE LENGTH FIELD of Level 2 LAN IS to IS hello PDU are : Area Address Protocols Supported IP Interface Address									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.13 **MUST**	RFC 1195 s4.4 p32 Maintaining Router Adjacencies s5.2 p34 Overview of IP-specific Information for IS-IS									
	IS to IS Hello PDU The Protocol supported field must be present in all IS-IS Hello Packets send by IP-only routers									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.14 **MUST**	NEGATIVE : RFC 1195 s4.4 p32 Maintaining Router Adjacencies									
	IS to IS Hello PDU The Protocol Supported field must be present in all IS-IS Hello Packets sent by IP-only routers									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.19 **MUST**	RFC 1195 s3.1 p15 Exchange of Routing information									
	IS to IS Hello PDU IP capable routers need to know what network layer protocols are supported by other routers in their area									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.20 **MUST**	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface									
	IS to IS Hello PDU Each interface corresponding to the SNPA over which is transmitted can have maximum of 63 IP addresses									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.21 **MUST**	RFC 1195 s3.1 p15 Exchange of Routing information									
	IS to IS Hello PDU IP capable routers need to know what network layer protocols are supported by other routers in their area									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-1.22 **MUST**	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface									
	IS to IS Hello PDU Each interface corresponding to the SNPA over which is transmitted can have maximum of 63 IP addresses									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.23 **MUST**	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface									
	IS to IS Hello PDU Each Interface corresponding to the SNPA over which a L1 LAN IIH PDU is transmitted can have a maximum of 63 IP Addresses									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-1.24 **MUST**	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface									
	IS to IS Hello PDU Each Interface corresponding to the SNPA over which a L2 LAN IIH PDU is transmitted can have a maximum of 63 IP Addresses									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.1 **MUST**	ISO/IEC 10589:1992(E) s9.8 p54 Level 1 LSPDU									
	Link State PDU Test that the level 1 LSP must have Intradomaim Routing Protocol Discriminator = 0x83, PDU Type = 18, Version/Protocol ID extension (2nd octet) = 1 and Version (6th octet) = 1 in the Header									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.2 **MUST**	ISO/IEC 10589:1992(E) s9.8 p54 Level 1 Link State PDU									
	Link State PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 1 Link State PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.3 **MUST**	ISO/IEC 10589:1992(E) s9.8 p54-55 Level 1 Link State PDU									
	Link State PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-2.4 **MUST**	ISO/IEC 10589:1992(E) s9.8 p54-55 Level 1 Link State PDU RFC 1195 s5.3.4, p40-43 Level 1 Link State PDU									
	Link State PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 1 link state PDU are: Area Addresses Intermediate system Neighbors Protocols Supported IP Interface Address IP internal Reachability Information									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-2.11 **MUST**	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 LSPDU									
	Link State PDU Test that the level 2 LSP must have Intradomaim Routing Protocol Discriminator =0x83, PDU Type=20,Version/Protocol ID extension(3rd octet) = 1 and Version (6th octet) = 1 in the Header									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.12 **MUST**	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 Link State PDU									
	Link State PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 2 Link State PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.13 **MUST**	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 Link State PDU									
	Link State PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.14 **MUST**	ISO/IEC 10589:1992(E) s9.9 p57-59 Level 2 Link State PDU RFC 1195 s5.3.5,p43-48 Level 2 Link State PDU									
	Link State PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 link state PDU are: Area Addresses Intermediate system Neighbors Protocols Supported IP Interface Address IP internal Reachability Information									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-2.17 **MUST**	RFC 1195 S3.1 P15 Exchange of routing information									

	`Link State PDU`
	`IS-IS requires that any codes in a received PDU that are not`
	`recognized are ignored and passed through unchanged`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-2.18 **MUST**	RFC 1195 S3.1 P15 Exchange of routing information									

	`Link State PDU`
	`IS-IS requires that any codes in a received PDU that are not`
	`recognized are ignored and passed through unchanged`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.1 **MUST**	ISO/IEC 10589:1992(E) s9.10 p60 Level 1 complete sequence numbers PDU									

	`Sequence Numbers PDU`
	`Level 1 complete sequence number PDU must have Intra-domain Routing`
	`protocol Discriminator = 0x83, PDU Type = 24, Version/Protocol ID`
	`extension (3rd octet) = 1 and Version (6th octet) = 1 in the header`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.2 **MUST**	ISO/IEC 10589:1992(E) s9.10 p60 Level 1 Complete sequence number PDU									

	`Sequence Numbers PDU`
	`Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are`
	`reserved which are always set to zero in Level 1 complete sequence`
	`numbers PDU`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.3 **MUST**	ISO/IEC 10589:1992(E) s9.10 p57 Level 1 complete sequence numbers PDU									

	`Sequence Numbers PDU`
	`The valid ID Length field in a Level 1 Complete Sequence Number PDU`
	`shall take any one of these following values:`
	`1. An integer between 1 and 8, inclusive, indicating an ID field of`
	`coresponding length`
	`2. The value zero, which indicates a six octet ID,field length`
	`3. The value 255, which means a null ID field (i.e., zero length)`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.4 **MUST**	ISO/IEC 10589:1992(E) s9.10 p60-61 Level 1 complete sequence numbers PDU RFC 1195 s5.3.6,p48-49 Level 1 complete sequence numbers PDU									

	`Sequence Numbers PDU`
	`The valid codes that must be present in the VARIABLE LENGTH FIELD of`
	`level 1 complete sequence numbers PDU are:`
	`1. LSP Entries`
	`2. Authentication Information`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-3.5 **MUST**	ISO/IEC 10589:1992(E) s9.10 p61-62 Level 2 complete sequence numbers PDU									
	Sequence Numbers PDU Level 2 complete sequence number PDU must have Intra-domain Routing protocol Discriminator = 0x83, PDU Type = 25, Version/Protocol ID extension (3rd octet) = 1 and Version (6th octet) = 1 in the header									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.6 **MUST**	ISO/IEC 10589:1992(E) s9.11 p62 Level 2 Complete sequence number PDU									
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are reserved which are always set to zero in Level 2 complete sequence numbers PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.7 **MUST**	ISO/IEC 10589:1992(E) s9.11 p61-62 Level 2 complete sequence numbers PDU									
	Sequence Numbers PDU The valid ID Length field in a Level 2 Complete Sequence Number PDU shall take any one of these following values: 1. An integer between 1 and 8, inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.8 **MUST**	ISO/IEC 10589:1992(E) s9.11 p62 Level 2 complete sequence numbers PDU RFC 1195 s5.3.7,p49 Level 2 complete sequence numbers PDU									
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 complete sequence numbers PDU are: 1. LSP Entries 2. Authentication Information									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-3.9 **MUST**	ISO/IEC 10589(E) s9.12 p62-63 Level 1 partial sequence numbers PDU									
	Sequence Numbers PDU Level 1 partial sequence number PDU must have Intra-domain Routing protocol Discriminator=0x83, PDU Type=26, Version/Protocol ID extension (3rd octet)=1 and Version (6th octet)=1 in the header									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-3.10 **MUST**	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU									
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 1 partial sequence numbers PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict
ANVL-ISIS-3.11 **MUST**	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU									
	Sequence Numbers PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 , inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID,field length 3. The value 255, which means a null ID field (i.e., zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict
ANVL-ISIS-3.12 **MUST**	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU RFC 1195 s5.3.8,p49 Level 1 partial sequence number PDU									
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 1 partial sequence numbers PDU are: 1. LSP Entries									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass
ANVL-ISIS-3.13 **MUST**	ISO/IEC 10589(E) s9.12 p64-65 Level 2 partial sequence numbers PDU									
	Sequence Numbers PDU Level 2 partial sequence number PDU must have Intra-domain Routing protocol Discriminator=0x83, PDU Type=27, Version/Protocol ID extension (3rd octet)=1 and Version (6th octet)=1 in the header									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: FAIL
ANVL-ISIS-3.14 **MUST**	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU									
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are reserved which are always set to zero in Level 2 partial sequence numbers PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-3.15 MUST	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU									
	Sequence Numbers PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive,indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID,field length 3. The value 255,which means anull ID field(ie zero length)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict
ANVL-ISIS-3.16 MUST	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU RFC 1195 s5.3.9,p49 Level 2 partial sequence number PDU									
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 partial sequence numbers PDU are: 1. LSP Entries									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass
ANVL-ISIS-4.1 MUST	ISO/IEC 10589:1992(E), s7.2.4, p14, Links									
	Level 1 Adjacency IS discover neighbours and forms adjacencies by exchanging ISIS Hello PDUs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.2 MUST	RFC 1195, s5.1, p33, Overview of ISIS PDUs									
	Level 1 Adjacency Hello packets are used to initialize and maintain adjacencies between neighbouring ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.3 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 Adjacency An L1 IS shall transmit only L1 LAN IIHs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.4 SHOULD	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 Adjacency An L1 IIH sent by L1 IS should contain the manualAreaAddresses and LAN Addresses of L1 IS adjacencies.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

FRROUTING

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-4.5 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 Adjacency An L1 IS shall transmit L1 LAN IIHs to the multi-destination address AllL1ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.6 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 Adjacency L1 ISs shall listen on the multi-destination address AllL1ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.7 **MUST**	NEGATIVE: ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 Adjacency L1 ISs shall reject any L1 LAN IIH that doesn"t have the destination as AllL1ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-4.8 **SHOULD**	ISO/IEC 10589:1992(E), s8.4.2.1, p44, IIH PDU acceptance tests									
	Level 1 Adjacency If the IDLength of the L1 IIH is not equal to the value of the IS routingDomainIDLength, it should be discarded.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.9 **SHOULD**	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 LAN IIH PDUs ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing									
	Level 1 Adjacency If the received L1 IIH"s areaAddresses do not match any of the manualAreaAddresses of the L1 IS, it should reject the adjacency.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.10 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 LAN IIH PDUs ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing									
	Level 1 Adjacency If the received L1 IIHs areaAddress field matches any of the values from the manualAreaAddresses of the L1 IS, it shall accept the adjacency.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-4.11 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing									
	Level 1 Adjacency If the received L1 IIHs maximumAreaAddresses value is equal to the ISs maximumAreaAddresses, accept the PDU.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.12 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs									
	Level 1 Adjacency If the L1 ISs maximumAreaAddresses is not 3, then it will discard all L1 LAN IIH with non matching maximumAreaAddresses value.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.13 **MUST**	ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU processing ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs									
	Level 1 Adjacency If the L1 IS only implements a value of three for maximumAreaAddresses, IS will accept an L1 IIH even if it has a non-matching maximumAreaAddresses value.									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-4.14 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies									
	Level 1 Adjacency When an L1 IS receives an L1 LAN IIH from another IS (R), then the next L1 IIH generated by the IS will include R.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.15 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies									
	Level 1 Adjacency When an L1 IS receives an L1 LAN IIH with its own entry, then it shall create an adjacency.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-4.16 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.2, p45, New Adjacencies									
	Level 1 Adjacency If a neighbour is not heard within the Holding Time, the L1 IS shall purge it from the database.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING
RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-5.1 **MUST**	ISO/IEC 10589:1992(E), s7.2.4, p14, Links									
	Level 2 Adjacency IS discover neighbours and forms adjacencies by exchanging ISIS Hello PDUs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.2 **MUST**	RFC 1195, s5.1, p33, Overview of ISIS PDUs									
	Level 2 Adjacency Hello packets are used to initialize and maintain adjacencies between neighbouring ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.3 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 2 Adjacency An L2 IS shall transmit only L2 LAN IIHs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.4 **SHOULD**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 2 Adjacency An L2 IIH sent by L2 IS should contain the manual Area Addresses and LAN Addresses of L2 IS adjacencies.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.5 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 2 Adjacency An L2 IS shall transmit L2 LAN IIHs to the multi-destination address AllL2ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.6 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 2 Adjacency L2 ISs shall listen on the multi-destination address AllL2ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.7 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 2 Adjacency L2 ISs shall reject any L2 LAN IIH that doesn"t have the destination as AllL2ISs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL

RFC Compliance Test Report
ISIS Results

FRROUTING

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-5.8 **SHOULD**	ISO/IEC 10589:1992(E), s8.4.2.1, p44, IIH PDU acceptance tests									
	Level 2 Adjacency If the IDLength of the L2 LAN IIH is not equal to the value of the ISs routingDomainIDLength, it should be discarded.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.9 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies									
	Level 2 Adjacency When an L2 IS receives an L2 LAN IIH from another IS (R), then the next L2 IIH generated by the IS will include R.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.10 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies									
	Level 2 Adjacency When an L2 IS receives an L2 LAN IIH with its own entry, then it shall create an adjacency.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-5.11 **MUST**	ISO/IEC 10589:1992(E), s8.4.2.5.2, p45, New Adjacencies									
	Level 2 Adjacency If a neighbour is not heard within the Holding Time, the L2 IS shall purge it from the database.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-6.1 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 and Level 2 Adjacency An L1/L2 IS shall create separate adjacencies on receipt of L1 and L2 LAN IIH.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass
ANVL-ISIS-6.2 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 and Level 2 Adjacency An L1/L2 IS shall transmit both L1 and L2 LAN IIHs.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-6.3 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 and Level 2 Adjacency An L1/L2 IS shall listen on the multi-destination address AllL1ISs and AllL2ISs for L1 and L2 LAN IIHs respectively.									
	Ubuntu 16.04: unpredict	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-6.4 **MUST**	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs									
	Level 1 and Level 2 Adjacency An L1/L2 IS shall reject any LAN IIH that doesn"t have the destination as AllL1ISs or AllL2ISs.									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-7.1 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-7.2 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-7.3 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH and the MAC address									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-7.4 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH and the MAC address									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-7.5 **MUST**	ISO/IEC 10589:1992(E) s8.4.5 p46 LAN designated IS									
	Level 1 Designated Routers and Pseudonodes An L1 IS becomes an L1 Designated IS, it shall transmit L1 pseudonode LSP									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-7.6 **MUST**	ISO/IEC 10589:1992(E) s8.4.5 p47 LAN designated ISs									
	Level 1 Designated Routers and Pseudonodes An L1 IS shall transmit L1 LAN IIHs with the LAN ID field set to the LAN ID of the designated L1 IS									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-8.1 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-8.2 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-8.3 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH and the MAC address									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-8.4 **MUST**	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes									
	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH and the MAC address									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-8.5 **MUST**	ISO/IEC 10589:1992(E) s8.4.5 p46 LAN designated IS									
	Level 2 Designated Routers and Pseudonodes An L2 IS becomes an L2 Designated IS,it shall transmit L2 pseudonode LSP									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

FRROUTING

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-8.6 **MUST**	ISO/IEC 10589:1992(E) s8.4.5 p47 LAN designated ISs									
	Level 2 Designated Routers and Pseudonodes An L2 IS shall transmit L2 LAN IIHs with the LAN ID field set to the LAN ID of the designated L2 IS									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-9.1 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p44 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH doesn"t contain the authentication information field, the L1 IS shall discard the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-9.2 **MUST**	ISO/IEC 10589:1992(E) s8.4.4 p46 Transmission of LAN IIH PDUs RFC 1195 s3.9 p25 Authentication									
	Level 1 LAN Circuit Authentication An L1 IS will include authentication information of type Password containing the circuitTransmitPassword as the authentication value in its L1 LAN IIH PDU if authentication is enabled on the circuit									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-9.3 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of type Password, and if this Password matches any of the circuitReceivePasswords, then the L1 IS accepts the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-9.4 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of type Password, and if this Password does not match any of the circuitReceivePasswords, then the L1 IS discards the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-9.5 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of a type that the IS doesn"t implement, then the IS discards the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-10.1 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH doesn"t contain the authentication information field, the L2 IS shall discard the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-10.2 **MUST**	ISO/IEC 10589:1992(E) s8.4.4 p46 Transmission of LAN IIH PDUs RFC 1195 s3.9 p25 Authentication									
	Level 2 LAN Circuit Authentication An L2 IS will include authentication information of type Password containing the circuitTransmitPassword as the authentication value in its L2 LAN IIH PDU if authentication is enabled on the circuit									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-10.3 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of type Password, and if this Password matches any of the circuitReceivePasswords, then the L2 IS accepts the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-10.4 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of type Password, and if this Password does not match any of the circuitReceivePasswords, then the L2 IS discards the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

FRROUTING

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org

OpenSourceRouting

a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-10.5 **MUST**	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication									
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of a type that the IS doesn"t implement, then the IS discards the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-11.1 **MUST**	ISO/IEC 10589:1992(E) s7.3.2 p19-p20 Generation of local link state information									
	Periodic LSP Generation The update process is responsible for generating Link State PDUs under the following circumtances. - Upon Timer Expiration (LSPGenerationTimer)									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-11.2 **MUST**	ISO/IEC 10589:1992(E) s7.3.5 p21 Periodic LSP Generation									
	Periodic LSP Generation The Intermediate System shall regenerate every LSP at intervals of atmost maximum LSPGeneration interval									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-11.3 **MUST**	ISO/IEC 10589:1992(E) s7.3.5 p21 Periodic LSP Generation									
	Periodic LSP Generation The Intermediate System shall regenerate every LSP at intervals of atmost maximum LSPGeneration interval									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-11.4 **SHOULD**	ISO/IEC 10589:1992(E) s7.3.16.1 p29 Sequence number									
	Periodic LSP Generation When the sequence number reaches the Sequence Modulus, the routing module should be disabled for a period of at least MaxAge + ZeroAgeLifetime									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-11.5 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.3-4 p29 Remaining LifeTime Field & LSP Expiration synchronization									
	Periodic LSP Generation If the Remaining LifeTime field of the received LSP is zero the system shall purge that LSP from its database and synchronizes by flooding an expired LSP									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-11.6 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.3-4 p29 Remaining LifeTime Field & LSP Expiration synchronization									

	`Periodic LSP Generation`
	`If the Remaining LifeTime field of the received LSP is zero`
	`the system shall purge that LSP from its database and synchronizes`
	`by flooding an expired LSP`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict
ANVL-ISIS-11.7 **MUST**	ISO/IEC 10589:1992(E) s7.3.2 p19-p20 Generation of local link state information									

	`Periodic LSP Generation`
	`The update process is responsible for generating Link State PDUs`
	`under the following circumtances.`
	`- Upon Timer Expiration (LSPGenerationTimer)`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-11.8 **SHOULD**	ISO/IEC 10589:1992(E) s7.3.16.1 p29 Sequence number									

	`Periodic LSP Generation`
	`When the sequence number reaches the Sequence Modulus, the routing`
	`module should be disabled for a period of at least MaxAge +`
	`ZeroAgeLifetime`									

	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-17.1 **MUST**	RFC 1195 S3.5 P23 Type of Service Routing									

	`Type of Service Routing`
	`If there is no path from source to destination made up of routers,`
	`which supports that particular type of service, then the packet will`
	`forwarded using default metric`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-17.2 **MUST**	ISO/IEC 10589:1992(E) S7.3.4 P21 Multiple LSPs									

	`Type of Service Routing`
	`If an LSP becomes empty because of all the adjacencies reported`
	`in that LSP no longer exists, an IS may purge that LSP instead`
	`of re-issuing it`									

	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-17.3 **MUST**	RFC 1195 s5.3.4 P42 Level 1 Link State PDU									

	`Type of Service Routing`
	`Bit 8 of DEFAULT METRIC is reserved and must be set to zero`
	`on transmission`									

	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-17.4 **MUST**	RFC 1195 s5.3.4 P42 Level 1 Link State PDU									
	Type of Service Routing Bit 7 of DEFAULT METRIC field (marked I/E) must be set to zero indicating internal metric									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-17.5 **MUST**	ISO/IEC 10589:1992(E) s7.2.8.1 p15 Computing routes through overloaded Intermediate systems									
	Type of Service Routing The Decision Process shall not utilise a link to an Intermediate system neighbour from an IS whose LSPs have the LSP Data-base Overload indication set.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-17.7 **MUST**	RFC 1195 S3.5 P23 Type of Service Routing									
	Type of Service Routing If there is no path from source to destination made up of routers, which supports that particular type of service, then the packet will forwarded using default metric									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-17.8 **MUST**	ISO/IEC 10589:1992(E) S7.3.4 P21 Multiple LSPs									
	Type of Service Routing If an LSP becomes empty because of all the adjacencies reported in that LSP no longer exists, an IS may purge that LSP instead of re-issuing it									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-17.9 **MUST**	RFC 1195 s5.3.5 P45 Level 2 Link State PDU									
	Type of Service Routing Bit 8 of DEFAULT METRIC is reserved and must be set to zero on transmission									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-17.10 **MUST**	RFC 1195 s5.3.4 P45 Level 2 Link State PDU									
	Type of Service Routing Bit 7 of DEFAULT METRIC field (marked I/E) must be set to zero indicating internal metric									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-17.11 **MUST**	ISO/IEC 10589:1992(E) s7.2.8.1 p15 Computing routes through overloaded Intermediate systems									
	Type of Service Routing The Decision Process shall not utilise a link to an Intermediate system neighbour from an IS whose LSPs have the LSP Data-base Overload indication set.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.1 **MUST**	ISO/IEC 10589:1992(E) S7.2.5 P14 Multiple LSPs for the same system									
	Propagation of LSPs The following information shall be taken only from LSP with LSP number zero and disregarded if the LSP number is non-zero 1. The setting of the LSP Database Overload bit 2. The value of the IS Type field 3. The Area Addresses option field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.2 **MUST**	ISO/IEC 10589:1992(E) S7.3 P19 Update process									
	Propagation of LSPs The update process is responsible for generating and propagating Link State information reliably throughout the routing domain									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.3 **MUST**	ISO/IEC 10589:1992(E) S7.3.2 P19-20 Generation of local link state " information									
	Propagation of LSPs The update process is responsible for generating Link State PDUs under the following circumstances: - When notified by the subnetwork dependent functions of an adjacency database change									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.4 **MUST**	ISO/IEC 10589:1992(E) S7.3.8 P22 Generation of level 1 pseudonode LSPs									
	Propagation of LSPs The Area Addresses option will not be present when an IS generates a level 1 Link State PDU on behalf of pseudonode									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.5 **MUST**	ISO/IEC 10589:1992(E) S7.3.15.1 P24-25 Action on receipt of Link state PDU									
	Propagation of LSPs If this is a level 1 LSP and the Maximum Area Address field is not equal to the value of the ISs Maximum Area Address then the PDU shall be discarded									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-18.6 **MUST**	ISO/IEC 10589:1992(E) s7.3.14.1 p23 Propagation of LSPs									
	Propagation of LSPs Duplicate PDUs are detected and dropped									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.7 **MUST**	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation ofLSPs									
	Propagation of LSPs Level 1 Link State PDUs shall be propagated on circuits, which have at least one Level 1 adjacency									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.8 **MUST**	ISO/IEC 10589:1992(E), s7.3.14.2, p24, Propagation of LSPs									
	Propagation of LSPs When propagating a L1 LSP on a broadcast subnetwork, the IS shall transmit to the multi-destination Address AllL1IS.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.9 **MUST**	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs									
	Propagation of LSPs When an Intermediate System receives a LSP older than the one stored in the database, the stored link state PDU needs to be sent on the link form which the older one was received									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-18.10 **MUST**	ISO/IEC 10589:1992(E) S7.3.16.3 P29 Remaining Lifetime Field									
	Propagation of LSPs When the source generates a link state PDU,it shall set the Remaining Lifetime to MaxAge. Before transmitting a link state PDU to a neighbour, a system shall decrement the Remaining Lifetime									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-18.12 **MUST**	RFC 1195 S3.1 P15 Exchange of routing information									
	Propagation of LSPs Level 1 routers need to know what IP address are reachable from each level 1 router in their area									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-18.13 **MUST**	RFC 1195 S3.7 P24 IP-Only Operation									
	Propagation of LSPs Some of the VARIABLE LENGTH fields from IS-IS link packet must be omitted for IP only routers - The End System Neighbours entries are omitted - The Prefix Neighbours entries are omitted									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.1 **MUST**	ISO/IEC 10589:1992(E) S7.2.5 P14 Multiple LSPs for the same system									
	Generation of Local Link State Information The following information shall be taken only from LSP with LSP number zero and disregarded if the LSP number is non-zero 1. The setting of the LSP Database Overload bit 2. The value of the IS Type field 3. The Area Addresses option field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.2 **MUST**	ISO/IEC 10589:1992(E) S7.3 P19 Update process									
	Generation of Local Link State Information The update process is responsible for generating and propagating Link State information reliably throughout the routing domain									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.3 **MUST**	ISO/IEC 10589:1992(E) S7.3.2 P19-20 Generation of local link state " information									
	Generation of Local Link State Information The update process is responsible for generating Link State PDUs under the following circumstances: - When notified by the subnetwork dependent functions of an adjacency database change									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.4 **MUST**	ISO/IEC 10589:1992(E) S7.3.8 P22 Generation of level 2 pseudonode LSPs									
	Generation of Local Link State Information The Area Addresses option will not be present when an IS generates a level 2 Link State PDU on behalf of pseudonode									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.5 **MUST**	ISO/IEC 10589:1992(E) S7.3.15 P24-25 Action on receipt of Link state PDU									
	Generation of Local Link State Information If this is a level 2 LSP and the Maximum Area Address field is not equal to the value of the ISs Maximum Area Address then the PDU shall be discarded									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-19.6 MUST	ISO/IEC 10589:1992(E) s7.3.14.1 p23 Propagation of LSPs									
	Generation of Local Link State Information Duplicate PDUs are detected and dropped									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.7 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation ofLSPs									
	Generation of Local Link State Information Level 2 Link State PDUs shall be propagated on circuits, which have at least one Level 2 adjacency									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.8 MUST	ISO/IEC 10589:1992(E), s7.3.14.2, p24, Propagation of LSPs									
	Generation of Local Link State Information When propagating a L2 LSP on a broadcast subnetwork, the IS shall transmit to the multi-destination Address AllL2IS.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.9 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs									
	Generation of Local Link State Information When an Intermediate System receives a LSP older than the one stored in the database, the stored link state PDU needs to be sent on the link form which the older one was received									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: FAIL
ANVL-ISIS-19.10 MUST	ISO/IEC 10589:1992(E) s7.3.15.1 p24 Action on receipt of a link state PDU									
	Generation of Local Link State Information If the ID Length of the PDU is not equal to the value of the ISs routingDomainISLength, the PDU shall be discarded									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.11 MUST	ISO/IEC 10589:1992(E) S7.3.16.3 P29 Remaining Lifetime Field									
	Generation of Local Link State Information When the source generates a link state PDU,it shall set the Remaining Lifetime to MaxAge. Before transmitting a link state PDU to a neighbour, a system shall decrement the Remaining Lifetime									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-19.13 **MUST**	colspan RFC 1195 S3.2 P17 Exchange of routing information Generation of Local Link State Information Level 2 routers need to know what IP address are reachable from each level 2 router in their area									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-19.14 **MUST**	RFC 1195 S3.7 P25 IP-Only Operation Generation of Local Link State Information Some of the VARIABLE LENGTH fields from IS-IS link packet must be omitted for IP only routers - The End System Neighbours entries are omitted - The Prefix Neighbours entries are omitted									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-20.1 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers Level 1 LSP Sequence Numbers When a system initializes, it shall start with sequence number with 1 for its own Link State PDUs:									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-20.2 **SHOULD**	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers Level 1 LSP Sequence Numbers The sequence number of any actually generated Link State PDU should not be zero									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-20.3 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers Level 1 LSP Sequence Numbers Update sequence number depending on the sequence number received from system in the domain									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-20.4 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.2 p29 LSP confusion Level 1 LSP Sequence Numbers If the sequence numbers match, but checksums do not and the LSP is not generated by the local system, then store the LSP with zero Remaining Lifetime, and flood the LSP									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-21.1 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers									
	Level 2 LSP Sequence Numbers When a system initializes, it shall start with sequence number with 1 for its own Link State PDUs									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-21.2 **SHOULD**	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers									
	Level 2 LSP Sequence Numbers The sequence number of any actually generated Link State PDU should not be zero:									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-21.3 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers									
	Level 2 LSP Sequence Numbers Update sequence number depending on the sequence number received from system in the domain									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-21.4 **MUST**	ISO/IEC 10589:1992(E) s7.3.16.2 p29 LSP confusion									
	Level 2 LSP Sequence Numbers If the sequence numbers match, but checksums do not and the LSP is not generated by the local system, then store the LSP with zero Remaining Lifetime, and flood the LSP									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict
ANVL-ISIS-24.1 **MUST**	ISO/IEC 10589:1992(E) s7.3.19.1 p31 Entering the waiting state									
	Waiting State When an LSP cannot be stored, the LSP shall be ignored and waiting State will be entered									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-24.2 **MUST**	ISO/IEC 10589:1992(E) s7.3.19.1 p31 Entering the waiting state									
	Waiting State When an LSP cannot be stored, the LSP shall be ignored and waiting State will be entered									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict
ANVL-ISIS-25.2 **SHOULD**	RFC3719 Section 2.1 Page 3 " MaxAge"									
	ISISUpdate - RFC 3719 MaxAge SHOULD exceed maximumLSPGenerationInterval by atleast 300 seconds Note: Verify the RemainingLifeTime of the Packet									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

FRROUTING

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-25.3 **MAY**	RFC3719 Section 2.2 Page 4 " ISISHoldingMultiplier"									
	ISISUpdate - RFC 3719 An implementation MAY allow ISISHoldingMultiplier to be configurable.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict
ANVL-ISIS-25.4 **MUST**	RFC3719 Section 3.1 Page 4 " ID Length"									
	ISISUpdate - RFC 3719 An implementation MUST use an ID Length of 6.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-25.5 **MUST**	RFC3719 Section 3.1 Page 4 " ID Length"									
	ISISUpdate - RFC 3719 If a router encounters a PDU with an ID Length different from 0 or 6, section 7.3.15.a.2 dictates that it MUST discard the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-25.6 **SHOULD**	RFC3719 Section 3.2 Page 5 "maximumAreaAddresses"									
	ISISUpdate - RFC 3719 An implementation SHOULD use the value 3.									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-25.7 **MUST**	RFC3719 Section 3.2 Page 5 " maximumAreaAddresses"									
	ISISUpdate - RFC 3719 If a router receives a PDU with maximumAreaAddresses that is not 0 or 3, it MUST discard the PDU, as described in section 7.3.15.a.3									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-25.8 **MUST**	RFC3719 Section 3.3 Page 5 " Protocol Version"									
	ISISUpdate - RFC 3719 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-25.9 **MUST**	RFC3719 Section 3.3 Page 5 " Protocol Version"									
	ISISUpdate - RFC 3719 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version/Protocol ID field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results
www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-25.23 **MUST**	RFC3719 Section 11 Page 11 "Doppelganger LSPs"									
	ISISUpdate - RFC 3719 A complete set of CSNPs is a set whose Start LSPID and End LSPID ranges cover the complete possible range of LSPIDs. (i.e., there is no possible LSPID value which does not appear within the range of one of the CSNPs in the set).									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-26.2 **SHOULD**	RFC3719 Section 2.1 Page 3 " MaxAge"									
	ISISUpdate - RFC 3719 Part 2 MaxAge SHOULD exceed maximumLSPGenerationInterval by atleast 300 seconds Note: Verify the RemainingLifeTime of the Packet									
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL
ANVL-ISIS-26.3 **MAY**	RFC3719 Section 2.2 Page 4 " ISISHoldingMultiplier"									
	ISISUpdate - RFC 3719 Part 2 An implementation MAY allow ISISHoldingMultiplier to be configurable.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass
ANVL-ISIS-26.4 **MUST**	RFC3719 Section 3.1 Page 4 " ID Length"									
	ISISUpdate - RFC 3719 Part 2 An implementation MUST use an ID Length of 6.									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-26.5 **MUST**	RFC3719 Section 3.1 Page 4 " ID Length"									
	ISISUpdate - RFC 3719 Part 2 If a router encounters a PDU with an ID Length different from 0 or 6, section 7.3.15.a.2 dictates that it MUST discard the PDU									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-26.8 **MUST**	RFC3719 Section 3.3 Page 5 " Protocol Version"									
	ISISUpdate - RFC 3719 Part 2 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass

RFC Compliance Test Report
ISIS Results

www.OpenSourceRouting.org
OpenSourceRouting
a project by the Network Device Education Foundation, Inc (www.NetDEF.org)

	Master 2017-03-07	Release 2.0	Master 2017-04-03	3.0-dev 2017-04-25	Master 2017-05-17	3.0-dev 2017-05-24	Master 2017-06-02	Master 2017-06-26	3.0-dev 2017-06-30	Master 2017-07-20
ANVL-ISIS-26.9	RFC3719 Section 3.3 Page 5 " Protocol Version"									
MUST	ISISUpdate - RFC 3719 Part 2 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version/Protocol ID field									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass
ANVL-ISIS-26.23	RFC3719 Section 11 Page 11 "Doppelganger LSPs"									
MUST	ISISUpdate - RFC 3719 Part 2 A complete set of CSNPs is a set whose Start LSPID and End LSPID ranges cover the complete possible range of LSPIDs. (i.e., there is no possible LSPID value which does not appear within the range of one of the CSNPs in the set).									
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass