

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
Type	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR	FRR
Commit ID	36a7e78	30283fd	5dff4ec	7a377a1	85f25d8	33e56da	056c0cd	23db048	ba0d195	b606b4e	c0038fc
Commit Date	2017-11-08	2017-11-08	2018-01-09	2018-03-12	2018-07-05	2019-05-09	2019-05-13	2019-06-18	2019-09-27	2019-10-15	2020-02-14
ANVL-ISIS-1.1	ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU										
MUST	IS to IS Hello PDU Level 1 LAN IS to IS hello PDU must have 1. Intra-domain Routing Protocol Discriminator = 0x83 2. PDU type = 15 3. Version/Protocol ID extension = 1 4. Version = 1										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.2	ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU										
MUST	IS to IS Hello PDU Bit 6-8 of PDU Type (5th octet), Reserved (7th octet), bit 3-8 of Reserved/Circuit Type (9th octet) and 8th bit of Priority are reserved which are always set to zero in Level 1 LAN IS to IS hello PDU.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-1.3 MUST	ISO/IEC 10589:1992(E)s9.5 p49 Level 1 LAN IS to IS hello PDU										
	IS to IS Hello PDU The valid ID Length field shall take any one of these following values: 1. An Integer between 1 and 8, inclusive, indicating an ID field of the corresponding length 2. The Value zero, which indicates a six octet ID, field length 3. The Value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.4 MUST	ISO/IEC 10589:1992(E)s9.5 p49-50 Level 1 LAN IS to IS hello PDU										
	IS to IS Hello PDU In a LAN Level 1 IIH the Circuit Type must be either 1 or 3										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.5 MUST	ISO/IEC 10589:1992(E)s9.5 p50 Level 1 LAN IS to IS hello PDU RFC 1195 s5.3.1 p37-38 Level 1 LAN IS to IS hello PDU										
	IS to IS Hello PDU The valid Codes that must be present in the VARIABLE LENGTH FIELD of Level 1 LAN IS to IS hello PDU are: Area Address Protocols Supported IP Interface Address										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-1.6	RFC 1195 s4.4 p32 Maintaining Router Adjacencies s5.2 p34 Overview of IP-specific Information for IS-IS										
MUST	IS to IS Hello PDU The Protocol supported field must be present in all IS-IS Hello Packets send by IP-only routers										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.7	NEGATIVE : RFC 1195 s4.4 p32 Maintaining Router Adjacencies										
MUST	IS to IS Hello PDU The Protocol Supported field must be present in all IS-IS Hello Packets send by IP-only routers										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.8	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU										
MUST	IS to IS Hello PDU Level 2 LAN IS to IS hello PDU must have 1. Intra-domain Routing Protocol Discriminator = 0x83 2. PDU type = 16 3. Version/Protocol ID extension = 1 4. Version = 1										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-1.9 MUST	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU										
	IS to IS Hello PDU Bit 6-8 of PDU Type(5th octet), Reserved(7th octet), bit 3-8 of Reserved/Circuit Type(9th octet) and 8th bit of Priority are reserved which are always set to zero in Level 2 LAN IS to IS hello PDU.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.10 MUST	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU										
	IS to IS Hello PDU The valid ID Length field shall take any one of these following values: 1. An Integer between 1 and 8, inclusive, indicating an ID field of the corresponding length 2. The Value zero, which indicates a six octet ID, field length 3. The Value 255, which means a null ID field (ie. zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.11 MUST	ISO/IEC 10589:1992(E)s9.6 p51 Level 2 LAN IS to IS hello PDU										
	IS to IS Hello PDU In a LAN Level 2 IIH the Circuit Type must be either 2 or 3										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-1.12 MUST	ISO/IEC 10589:1992(E)s9.6 p51-52 Level 2 LAN IS to IS hello PDU RFC 1195 s5.3.2 p38-39 Level 2 LAN IS to IS hello PDU										
	IS to IS Hello PDU The valid Codes that must be present in the VARIABLE LENGTH FIELD of Level 2 LAN IS to IS hello PDU are : Area Address Protocols Supported IP Interface Address										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.13 MUST	RFC 1195 s4.4 p32 Maintaining Router Adjacencies s5.2 p34 Overview of IP-specific Information for IS-IS										
	IS to IS Hello PDU The Protocol supported field must be present in all IS-IS Hello Packets send by IP-only routers										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.14 MUST	NEGATIVE : RFC 1195 s4.4 p32 Maintaining Router Adjacencies										
	IS to IS Hello PDU The Protocol Supported field must be present in all IS-IS Hello Packets sent by IP-only routers										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-1.19 MUST	RFC 1195 s3.1 p15 Exchange of Routing information										
	IS to IS Hello PDU IP capable routers need to know what network layer protocols are supported by other routers in their area										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.20 MUST	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface										
	IS to IS Hello PDU Each interface corresponding to the SNPA over which is transmitted can have maximum of 63 IP addresses										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-1.21 MUST	RFC 1195 s3.1 p15 Exchange of Routing information										
	IS to IS Hello PDU IP capable routers need to know what network layer protocols are supported by other routers in their area										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019- 09-26	Release 7.2	Release 7.3
ANVL- ISIS- 1.22 MUST	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface										
	IS to IS Hello PDU Each interface corresponding to the SNPA over which is transmitted can have maximum of 63 IP addresses										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 1.23 MUST	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface										
	IS to IS Hello PDU Each Interface corresponding to the SNPA over which a L1 LAN IIH PDU is transmitted can have a maximum of 63 IP Addresses										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 1.24 MUST	RFC 1195 s4.2 p31 Multiple IP Addresses per Interface										
	IS to IS Hello PDU Each Interface corresponding to the SNPA over which a L2 LAN IIH PDU is transmitted can have a maximum of 63 IP Addresses										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-2.1 MUST	ISO/IEC 10589:1992(E) s9.8 p54 Level 1 LSPDU										
	Link State PDU Test that the level 1 LSP must have Intradomain Routing Protocol Discriminator = 0x83, PDU Type = 18, Version/Protocol ID extension (2nd octet) = 1 and Version (6th octet) = 1 in the Header										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-2.2 MUST	ISO/IEC 10589:1992(E) s9.8 p54 Level 1 Link State PDU										
	Link State PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 1 Link State PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-2.3 MUST	ISO/IEC 10589:1992(E) s9.8 p54-55 Level 1 Link State PDU										
	Link State PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-2.4	ISO/IEC 10589:1992(E) s9.8 p54-55 Level 1 Link State PDU RFC 1195 s5.3.4, p40-43 Level 1 Link State PDU										
MUST	Link State PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 1 link state PDU are: Area Addresses Intermediate system Neighbors Protocols Supported IP Interface Address IP internal Reachability Information										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-2.11	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 LSPDU										
MUST	Link State PDU Test that the level 2 LSP must have Intradomain Routing Protocol Discriminator = 0x83, PDU Type=20, Version/Protocol ID extension(3rd octet) = 1 and Version (6th octet) = 1 in the Header										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-2.12	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 Link State PDU										
MUST	Link State PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 2 Link State PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-2.13 MUST	ISO/IEC 10589:1992(E) s9.9 p57 Level 2 Link State PDU										
	Link State PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive, indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-2.14 MUST	ISO/IEC 10589:1992(E) s9.9 p57-59 Level 2 Link State PDU RFC 1195 s5.3.5,p43-48 Level 2 Link State PDU										
	Link State PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 link state PDU are: Area Addresses Intermediate system Neighbors Protocols Supported IP Interface Address IP internal Reachability Information										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-2.17 MUST	RFC 1195 S3.1 P15 Exchange of routing information										
	Link State PDU IS-IS requires that any codes in a received PDU that are not recognized are ignored and passed through unchanged										
	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL-ISIS-2.18 MUST	RFC 1195 S3.1 P15 Exchange of routing information										
	Link State PDU IS-IS requires that any codes in a received PDU that are not recognized are ignored and passed through unchanged										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-3.1 MUST	ISO/IEC 10589:1992(E) s9.10 p60 Level 1 complete sequence numbers PDU										
	Sequence Numbers PDU Level 1 complete sequence number PDU must have Intra-domain Routing protocol Discriminator = 0x83, PDU Type = 24, Version/Protocol ID extension (3rd octet) = 1 and Version (6th octet) = 1 in the header										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-3.2 MUST	ISO/IEC 10589:1992(E) s9.10 p60 Level 1 Complete sequence number PDU										
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are reserved which are always set to zero in Level 1 complete sequence numbers PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-3.3 MUST	ISO/IEC 10589:1992(E) s9.10 p57 Level 1 complete sequence numbers PDU										
	Sequence Numbers PDU The valid ID Length field in a Level 1 Complete Sequence Number PDU shall take any one of these following values: 1. An integer between 1 and 8, inclusive, indicating an ID field of corresponding length 2. The value zero, which indicates a six octet ID,field length 3. The value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-3.4 MUST	ISO/IEC 10589:1992(E) s9.10 p60-61 Level 1 complete sequence numbers PDU RFC 1195 s5.3.6,p48-49 Level 1 complete sequence numbers PDU										
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 1 complete sequence numbers PDU are: 1. LSP Entries 2. Authentication Information										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-3.5 MUST	ISO/IEC 10589:1992(E) s9.10 p61-62 Level 2 complete sequence numbers PDU										
	Sequence Numbers PDU Level 2 complete sequence number PDU must have Intra-domain Routing protocol Discriminator = 0x83, PDU Type = 25, Version/Protocol ID extension (3rd octet) = 1 and Version (6th octet) = 1 in the header										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-3.6 MUST	ISO/IEC 10589:1992(E) s9.11 p62 Level 2 Complete sequence number PDU										
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are reserved which are always set to zero in Level 2 complete sequence numbers PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-3.7 MUST	ISO/IEC 10589:1992(E) s9.11 p61-62 Level 2 complete sequence numbers PDU										
	Sequence Numbers PDU The valid ID Length field in a Level 2 Complete Sequence Number PDU shall take any one of these following values: 1. An integer between 1 and 8, inclusive, indicating an ID field of corresponding length 2. The value zero, which indicates a six octet ID, field length 3. The value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-3.8 MUST	ISO/IEC 10589:1992(E) s9.11 p62 Level 2 complete sequence numbers PDU RFC 1195 s5.3.7.p49 Level 2 complete sequence numbers PDU										
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 complete sequence numbers PDU are: 1. LSP Entries 2. Authentication Information										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019- 09-26	Release 7.2	Release 7.3
ANVL- ISIS-3.9 MUST	ISO/IEC 10589(E) s9.12 p62-63 Level 1 partial sequence numbers PDU										
	Sequence Numbers PDU Level 1 partial sequence number PDU must have Intra-domain Routing protocol Discriminator=0x83, PDU Type=26, Version/Protocol ID extension (3rd octet)=1 and Version (6th octet)=1 in the header										
	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict
ANVL- ISIS-3.10 MUST	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU										
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved (7th octet) are reserved which are always set to zero in Level 1 partial sequence numbers PDU										
	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL- ISIS-3.11 MUST	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU										
	Sequence Numbers PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 , inclusive, indicating an ID field of corresponding length 2. The value zero, which indicates a six octet ID,field length 3. The value 255, which means a null ID field (i.e., zero length)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-3.12 MUST	ISO/IEC 10589:1992(E) s9.12 p63 Level 1 partial sequence number PDU RFC 1195 s5.3.8,p49 Level 1 partial sequence number PDU										
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 1 partial sequence numbers PDU are: 1. LSP Entries										
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL-ISIS-3.13 MUST	ISO/IEC 10589(E) s9.12 p64-65 Level 2 partial sequence numbers PDU										
	Sequence Numbers PDU Level 2 partial sequence number PDU must have Intra-domain Routing protocol Discriminator=0x83, PDU Type=27, Version/Protocol ID extension (3rd octet)=1 and Version (6th octet)=1 in the header										
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL-ISIS-3.14 MUST	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU										
	Sequence Numbers PDU Bit 6-8 of PDU Type (5th octet) and Reserved(7th octet) are reserved which are always set to zero in Level 2 partial sequence numbers PDU										
	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-3.15 MUST	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU										
	Sequence Numbers PDU The valid ID Length field shall take any one of these following values: 1. An integer between 1 and 8 ,inclusive,indicating an ID field of coresponding length 2. The value zero, which indicates a six octet ID,field length 3. The value 255,which means anull ID field(ie zero length)										
	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL-ISIS-3.16 MUST	ISO/IEC 10589:1992(E) s9.12 p64 Level 2 partial sequence number PDU RFC 1195 s5.3.9,p49 Level 2 partial sequence number PDU										
	Sequence Numbers PDU The valid codes that must be present in the VARIABLE LENGTH FIELD of level 2 partial sequence numbers PDU are: 1. LSP Entries										
	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict
ANVL-ISIS-4.1 MUST	ISO/IEC 10589:1992(E), s7.2.4, p14, Links										
	Level 1 Adjacency IS discover neighbours and forms adjacencies by exchanging ISIS Hello PDUs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-4.2 MUST	RFC 1195, s5.1, p33, Overview of ISIS PDUs										
	Level 1 Adjacency Hello packets are used to initialize and maintain adjacencies between neighbouring ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.3 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 Adjacency An L1 IS shall transmit only L1 LAN IIHs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.4 SHOULD	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 Adjacency An L1 IIH sent by L1 IS should contain the manualAreaAddresses and LAN Addresses of L1 IS adjacencies.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-4.5 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 Adjacency An L1 IS shall transmit L1 LAN IIHs to the multi-destination address AllL1ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.6 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 Adjacency L1 ISs shall listen on the multi-destination address AllL1ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.7 MUST	NEGATIVE: ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 Adjacency L1 ISs shall reject any L1 LAN IIH that doesn't have the destination as AllL1ISs.										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-4.8 SHOULD	ISO/IEC 10589:1992(E), s8.4.2.1, p44, IIH PDU acceptance tests										
	Level 1 Adjacency If the IDLength of the L1 IIH is not equal to the value of the IS routingDomainIDLength, it should be discarded.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.9 SHOULD	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 LAN IIH PDUs ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing										
	Level 1 Adjacency If the received L1 IIH's areaAddresses do not match any of the manualAreaAddresses of the L1 IS, it should reject the adjacency.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.10 MUST	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 LAN IIH PDUs ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing										
	Level 1 Adjacency If the received L1 IIHs areaAddress field matches any of the values from the manualAreaAddresses of the L1 IS, it shall accept the adjacency.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-4.11 MUST	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs										
	ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU Processing										
	Level 1 Adjacency If the received L1 IIHs maximumAreaAddresses value is equal to the ISs maximumAreaAddresses, accept the PDU.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
ANVL-ISIS-4.12 MUST	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs										
	Level 1 Adjacency If the L1 ISs maximumAreaAddresses is not 3, then it will discard all L1 LAN IIH with non matching maximumAreaAddresses value.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
ANVL-ISIS-4.13 MUST	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
	ISO/IEC 10589:1992(E), s8.2.4.2, p38, IIH PDU processing										
	ISO/IEC 10589:1992(E), s8.4.2.2, p45, Receipt of L1 IIH PDUs										
	Level 1 Adjacency If the L1 IS only implements a value of three for maximumAreaAddresses, IS will accept an L1 IIH even if it has a non-matching maximumAreaAddresses value.										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-4.14 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies										
	Level 1 Adjacency When an L1 IS receives an L1 LAN IIH from another IS (R), then the next L1 IIH generated by the IS will include R.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.15 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies										
	Level 1 Adjacency When an L1 IS receives an L1 LAN IIH with its own entry, then it shall create an adjacency.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-4.16 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.2, p45, New Adjacencies										
	Level 1 Adjacency If a neighbour is not heard within the Holding Time, the L1 IS shall purge it from the database.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-5.1 MUST	ISO/IEC 10589:1992(E), s7.2.4, p14, Links										
	Level 2 Adjacency IS discover neighbours and forms adjacencies by exchanging ISIS Hello PDUs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.2 MUST	RFC 1195, s5.1, p33, Overview of ISIS PDUs										
	Level 2 Adjacency Hello packets are used to initialize and maintain adjacencies between neighbouring ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.3 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 2 Adjacency An L2 IS shall transmit only L2 LAN IIHs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-5.4 SHOULD	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 2 Adjacency An L2 IIH sent by L2 IS should contain the manual Area Addresses and LAN Addresses of L2 IS adjacencies.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.5 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 2 Adjacency An L2 IS shall transmit L2 LAN IIHs to the multi-destination address AllL2ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.6 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 2 Adjacency L2 ISs shall listen on the multi-destination address AllL2ISs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-5.7 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 2 Adjacency L2 ISs shall reject any L2 LAN IIH that doesn't have the destination as AllL2ISs.										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-5.8 SHOULD	ISO/IEC 10589:1992(E), s8.4.2.1, p44, IIH PDU acceptance tests										
	Level 2 Adjacency If the IDLength of the L2 LAN IIH is not equal to the value of the ISs routingDomainIDLength, it should be discarded.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.9 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies										
	Level 2 Adjacency When an L2 IS receives an L2 LAN IIH from another IS (R), then the next L2 IIH generated by the IS will include R.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-5.10 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.1, p45, New Adjacencies										
	Level 2 Adjacency When an L2 IS receives an L2 LAN IIH with its own entry, then it shall create an adjacency.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-5.11 MUST	ISO/IEC 10589:1992(E), s8.4.2.5.2, p45, New Adjacencies										
	Level 2 Adjacency If a neighbour is not heard within the Holding Time, the L2 IS shall purge it from the database.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-6.1 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 and Level 2 Adjacency An L1/L2 IS shall create separate adjacencies on receipt of L1 and L2 LAN IIH.										
	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-6.2 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 and Level 2 Adjacency An L1/L2 IS shall transmit both L1 and L2 LAN IIHs.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-6.3 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 and Level 2 Adjacency An L1/L2 IS shall listen on the multi-destination address AllL1ISs and AllL2ISs for L1 and L2 LAN IIHs respectively.										
	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-6.4 MUST	ISO/IEC 10589:1992(E), s8.4.2, p44, Broadcast subnetwork IIH PDUs										
	Level 1 and Level 2 Adjacency An L1/L2 IS shall reject any LAN IIH that doesn't have the destination as AllL1ISs or AllL2ISs.										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-7.1	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-7.2	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-7.3	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH and the MAC address										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-7.4 MUST	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
	Level 1 Designated Routers and Pseudonodes Election process of level 1 designated IS is done by verifying priority field in the IIH and the MAC address										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-7.5 MUST	ISO/IEC 10589:1992(E) s8.4.5 p46 LAN designated IS										
	Level 1 Designated Routers and Pseudonodes An L1 IS becomes an L1 Designated IS, it shall transmit L1 pseudonode LSP										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-7.6 MUST	ISO/IEC 10589:1992(E) s8.4.5 p47 LAN designated ISS										
	Level 1 Designated Routers and Pseudonodes An L1 IS shall transmit L1 LAN IIHs with the LAN ID field set to the LAN ID of the designated L1 IS										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-8.1	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-8.2	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-8.3	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
MUST	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH and the MAC address										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-8.4 MUST	ISO/IEC 10589:1992(E) s7.2.3 p14 Broadcast subnetwork RFC 1195 s4.3 p31 Designated routers and Pseudonodes										
	Level 2 Designated Routers and Pseudonodes Election process of level 2 designated IS is done by verifying priority field in the IIH and the MAC address										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-8.5 MUST	ISO/IEC 10589:1992(E) s8.4.5 p46 LAN designated IS										
	Level 2 Designated Routers and Pseudonodes An L2 IS becomes an L2 Designated IS, it shall transmit L2 pseudonode LSP										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-8.6 MUST	ISO/IEC 10589:1992(E) s8.4.5 p47 LAN designated ISS										
	Level 2 Designated Routers and Pseudonodes An L2 IS shall transmit L2 LAN IIHs with the LAN ID field set to the LAN ID of the designated L2 IS										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-9.1 MUST	ISO/IEC 10589:1992(E) s8.4.2.1 p44 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH doesn't contain the authentication information field, the L1 IS shall discard the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-9.2 MUST	ISO/IEC 10589:1992(E) s8.4.4 p46 Transmission of LAN IIH PDUs RFC 1195 s3.9 p25 Authentication										
	Level 1 LAN Circuit Authentication An L1 IS will include authentication information of type Password containing the circuitTransmitPassword as the authentication value in its L1 LAN IIH PDU if authentication is enabled on the circuit										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-9.3 MUST	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of type Password, and if this Password matches any of the circuitReceivePasswords, then the L1 IS accepts the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-9.4	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
MUST	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of type Password, and if this Password does not match any of the circuitReceivePasswords, then the L1 IS discards the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-9.5	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
MUST	Level 1 LAN Circuit Authentication If authentication is enabled on a circuit and the received L1 LAN IIH contains authentication information of a type that the IS doesn't implement, then the IS discards the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-10.1	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
MUST	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH doesn't contain the authentication information field, the L2 IS shall discard the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-10.2 MUST	ISO/IEC 10589:1992(E) s8.4.4 p46 Transmission of LAN IIH PDUs RFC 1195 s3.9 p25 Authentication										
	Level 2 LAN Circuit Authentication An L2 IS will include authentication information of type Password containing the circuitTransmitPassword as the authentication value in its L2 LAN IIH PDU if authentication is enabled on the circuit										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-10.3 MUST	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of type Password, and if this Password matches any of the circuitReceivePasswords, then the L2 IS accepts the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-10.4 MUST	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of type Password, and if this Password does not match any of the circuitReceivePasswords, then the L2 IS discards the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-10.5 MUST	ISO/IEC 10589:1992(E) s8.4.2.1 p45 IIH PDU Acceptance Tests RFC 1195 s3.9 p25 Authentication										
	Level 2 LAN Circuit Authentication If authentication is enabled on a circuit and the received L2 LAN IIH contains authentication information of a type that the IS doesn't implement, then the IS discards the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-11.1 MUST	ISO/IEC 10589:1992(E) s7.3.2 p19-p20 Generation of local link state information										
	Periodic LSP Generation The update process is responsible for generating Link State PDUs under the following circumstances. - Upon Timer Expiration (LSPGenerationTimer)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-11.2 MUST	ISO/IEC 10589:1992(E) s7.3.5 p21 Periodic LSP Generation										
	Periodic LSP Generation The Intermediate System shall regenerate every LSP at intervals of atmost maximum LSPGeneration interval										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-11.3 MUST	ISO/IEC 10589:1992(E) s7.3.5 p21 Periodic LSP Generation										
	Periodic LSP Generation The Intermediate System shall regenerate every LSP at intervals of atmost maximum LSPGeneration interval										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-11.4 SHOULD	ISO/IEC 10589:1992(E) s7.3.16.1 p29 Sequence number										
	Periodic LSP Generation When the sequence number reaches the Sequence Modulus, the routing module should be disabled for a period of at least MaxAge + ZeroAgeLifetime										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-11.5 MUST	ISO/IEC 10589:1992(E) s7.3.16.3-4 p29 Remaining LifeTime Field & LSP Expiration synchronization										
	Periodic LSP Generation If the Remaining LifeTime field of the received LSP is zero the system shall purge that LSP from its database and synchronizes by flooding an expired LSP										
	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-11.6 MUST	ISO/IEC 10589:1992(E) s7.3.16.3-4 p29 Remaining LifeTime Field & LSP Expiration synchronization										
	Periodic LSP Generation If the Remaining LifeTime field of the received LSP is zero the system shall purge that LSP from its database and synchronizes by flooding an expired LSP										
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-11.7 MUST	ISO/IEC 10589:1992(E) s7.3.2 p19-p20 Generation of local link state information										
	Periodic LSP Generation The update process is responsible for generating Link State PDUs under the following circumstances. - Upon Timer Expiration (LSPGenerationTimer)										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-11.8 SHOULD	ISO/IEC 10589:1992(E) s7.3.16.1 p29 Sequence number										
	Periodic LSP Generation When the sequence number reaches the Sequence Modulus, the routing module should be disabled for a period of at least MaxAge + ZeroAgeLifetime										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-17.1 MUST	RFC 1195 S3.5 P23 Type of Service Routing										
	Type of Service Routing If there is no path from source to destination made up of routers, which supports that particular type of service, then the packet will be forwarded using default metric										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass
ANVL-ISIS-17.2 MUST	ISO/IEC 10589:1992(E) S7.3.4 P21 Multiple LSPs										
	Type of Service Routing If an LSP becomes empty because of all the adjacencies reported in that LSP no longer exists, an IS may purge that LSP instead of re-issuing it										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-17.3 MUST	RFC 1195 s5.3.4 P42 Level 1 Link State PDU										
	Type of Service Routing Bit 8 of DEFAULT METRIC is reserved and must be set to zero on transmission										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-17.4 MUST	RFC 1195 s5.3.4 P42 Level 1 Link State PDU										
	Type of Service Routing Bit 7 of DEFAULT METRIC field (marked I/E) must be set to zero indicating internal metric										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-17.5 MUST	ISO/IEC 10589:1992(E) s7.2.8.1 p15 Computing routes through overloaded Intermediate systems										
	Type of Service Routing The Decision Process shall not utilise a link to an Intermediate system neighbour from an IS whose LSPs have the LSP Data-base Overload indication set.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-17.7 MUST	RFC 1195 S3.5 P23 Type of Service Routing										
	Type of Service Routing If there is no path from source to destination made up of routers, which supports that particular type of service, then the packet will be forwarded using default metric										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-17.8 MUST	ISO/IEC 10589:1992(E) S7.3.4 P21 Multiple LSPs										
	Type of Service Routing If an LSP becomes empty because of all the adjacencies reported in that LSP no longer exists, an IS may purge that LSP instead of re-issuing it										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-17.9 MUST	RFC 1195 s5.3.5 P45 Level 2 Link State PDU										
	Type of Service Routing Bit 8 of DEFAULT METRIC is reserved and must be set to zero on transmission										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-17.10 MUST	RFC 1195 s5.3.4 P45 Level 2 Link State PDU										
	Type of Service Routing Bit 7 of DEFAULT METRIC field (marked I/E) must be set to zero indicating internal metric										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-17.11 MUST	ISO/IEC 10589:1992(E) s7.2.8.1 p15 Computing routes through overloaded Intermediate systems										
	Type of Service Routing The Decision Process shall not utilise a link to an Intermediate system neighbour from an IS whose LSPs have the LSP Data-base Overload indication set.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.1 MUST	ISO/IEC 10589:1992(E) S7.2.5 P14 Multiple LSPs for the same system										
	Propagation of LSPs The following information shall be taken only from LSP with LSP number zero and disregarded if the LSP number is non-zero 1. The setting of the LSP Database Overload bit 2. The value of the IS Type field 3. The Area Addresses option field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.2 MUST	ISO/IEC 10589:1992(E) S7.3 P19 Update process										
	Propagation of LSPs The update process is responsible for generating and propagating Link State information reliably throughout the routing domain										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-18.3 MUST	ISO/IEC 10589:1992(E) S7.3.2 P19-20 Generation of local link state " information										
	Propagation of LSPs The update process is responsible for generating Link State PDUs under the following circumstances: - When notified by the subnetwork dependent functions of an adjacency database change										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.4 MUST	ISO/IEC 10589:1992(E) S7.3.8 P22 Generation of level 1 pseudonode LSPs										
	Propagation of LSPs The Area Addresses option will not be present when an IS generates a level 1 Link State PDU on behalf of pseudonode										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.5 MUST	ISO/IEC 10589:1992(E) S7.3.15.1 P24-25 Action on receipt of Link state PDU										
	Propagation of LSPs If this is a level 1 LSP and the Maximum Area Address field is not equal to the value of the ISs Maximum Area Address then the PDU shall be discarded										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-18.6 MUST	ISO/IEC 10589:1992(E) s7.3.14.1 p23 Propagation of LSPs										
	Propagation of LSPs Duplicate PDUs are detected and dropped										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.7 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs										
	Propagation of LSPs Level 1 Link State PDUs shall be propagated on circuits, which have at least one Level 1 adjacency										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.8 MUST	ISO/IEC 10589:1992(E), s7.3.14.2, p24, Propagation of LSPs										
	Propagation of LSPs When propagating a L1 LSP on a broadcast subnetwork, the IS shall transmit to the multi-destination Address AllL1IS.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-18.9 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs										
	Propagation of LSPs When an Intermediate System receives a LSP older than the one stored in the database, the stored link state PDU needs to be sent on the link form which the older one was received										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict
ANVL-ISIS-18.10 MUST	ISO/IEC 10589:1992(E) S7.3.16.3 P29 Remaining Lifetime Field										
	Propagation of LSPs When the source generates a link state PDU, it shall set the Remaining Lifetime to MaxAge. Before transmitting a link state PDU to a neighbour, a system shall decrement the Remaining Lifetime										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-18.12 MUST	RFC 1195 S3.1 P15 Exchange of routing information										
	Propagation of LSPs Level 1 routers need to know what IP address are reachable from each level 1 router in their area										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019- 09-26	Release 7.2	Release 7.3
ANVL- ISIS- 18.13 MUST	RFC 1195 S3.7 P24 IP-Only Operation										
	Propagation of LSPs Some of the VARIABLE LENGTH fields from IS-IS link packet must be omitted for IP only routers - The End System Neighbours entries are omitted - The Prefix Neighbours entries are omitted										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 19.1 MUST	ISO/IEC 10589:1992(E) S7.2.5 P14 Multiple LSPs for the same system										
	Generation of Local Link State Information The following information shall be taken only from LSP with LSP number zero and disregarded if the LSP number is non-zero 1. The setting of the LSP Database Overload bit 2. The value of the IS Type field 3. The Area Addresses option field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 19.2 MUST	ISO/IEC 10589:1992(E) S7.3 P19 Update process										
	Generation of Local Link State Information The update process is responsible for generating and propagating Link State information reliably throughout the routing domain										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-19.3 MUST	ISO/IEC 10589:1992(E) S7.3.2 P19-20 Generation of local link state "information"										
	Generation of Local Link State Information The update process is responsible for generating Link State PDUs under the following circumstances: - When notified by the subnetwork dependent functions of an adjacency database change										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-19.4 MUST	ISO/IEC 10589:1992(E) S7.3.8 P22 Generation of level 2 pseudonode LSPs										
	Generation of Local Link State Information The Area Addresses option will not be present when an IS generates a level 2 Link State PDU on behalf of pseudonode										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-19.5 MUST	ISO/IEC 10589:1992(E) S7.3.15 P24-25 Action on receipt of Link state PDU										
	Generation of Local Link State Information If this is a level 2 LSP and the Maximum Area Address field is not equal to the value of the ISs Maximum Area Address then the PDU shall be discarded										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-19.6 MUST	ISO/IEC 10589:1992(E) s7.3.14.1 p23 Propagation of LSPs										
	Generation of Local Link State Information Duplicate PDUs are detected and dropped										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict
ANVL-ISIS-19.7 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs										
	Generation of Local Link State Information Level 2 Link State PDUs shall be propagated on circuits, which have at least one Level 2 adjacency										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-19.8 MUST	ISO/IEC 10589:1992(E), s7.3.14.2, p24, Propagation of LSPs										
	Generation of Local Link State Information When propagating a L2 LSP on a broadcast subnetwork, the IS shall transmit to the multi-destination Address AllL2IS.										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-19.9 MUST	ISO/IEC 10589:1992(E) s7.3.14.2 p24 Propagation of LSPs										
	Generation of Local Link State Information When an Intermediate System receives a LSP older than the one stored in the database, the stored link state PDU needs to be sent on the link form which the older one was received										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass
ANVL-ISIS-19.10 MUST	ISO/IEC 10589:1992(E) s7.3.15.1 p24 Action on receipt of a link state PDU										
	Generation of Local Link State Information If the ID Length of the PDU is not equal to the value of the ISS routingDomainISLength, the PDU shall be discarded										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-19.11 MUST	ISO/IEC 10589:1992(E) S7.3.16.3 P29 Remaining Lifetime Field										
	Generation of Local Link State Information When the source generates a link state PDU, it shall set the Remaining Lifetime to MaxAge. Before transmitting a link state PDU to a neighbour, a system shall decrement the Remaining Lifetime										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-19.13 MUST	RFC 1195 S3.2 P17 Exchange of routing information										
	Generation of Local Link State Information Level 2 routers need to know what IP address are reachable from each level 2 router in their area										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-19.14 MUST	RFC 1195 S3.7 P25 IP-Only Operation										
	Generation of Local Link State Information Some of the VARIABLE LENGTH fields from IS-IS link packet must be omitted for IP only routers - The End System Neighbours entries are omitted - The Prefix Neighbours entries are omitted										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-20.1 MUST	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers										
	Level 1 LSP Sequence Numbers When a system initializes, it shall start with sequence number with 1 for its own Link State PDUs:										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-20.2 SHOULD	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers										
	Level 1 LSP Sequence Numbers The sequence number of any actually generated Link State PDU should not be zero										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-20.3 MUST	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers										
	Level 1 LSP Sequence Numbers Update sequence number depending on the sequence number received from system in the domain										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-20.4 MUST	ISO/IEC 10589:1992(E) s7.3.16.2 p29 LSP confusion										
	Level 1 LSP Sequence Numbers If the sequence numbers match, but checksums do not and the LSP is not generated by the local system, then store the LSP with zero Remaining Lifetime, and flood the LSP										
	FreeBSD 10.3: unpredict	FreeBSD 10.3: unpredict	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-21.1 MUST	ISO/IEC 10589:1992(E) s7.3.16.1 p28 sequence numbers										
	Level 2 LSP Sequence Numbers When a system initializes, it shall start with sequence number with 1 for its own Link State PDUs										
	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL	FreeBS D 12.0: FAIL
ANVL-ISIS-21.2 SHOULD	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers										
	Level 2 LSP Sequence Numbers The sequence number of any actually generated Link State PDU should not be zero:										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-21.3 MUST	ISO/IEC 10589:1992(E) s7.3.16.1 p29 sequence numbers										
	Level 2 LSP Sequence Numbers Update sequence number depending on the sequence number received from system in the domain										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-21.4 MUST	ISO/IEC 10589:1992(E) s7.3.16.2 p29 LSP confusion										
	Level 2 LSP Sequence Numbers If the sequence numbers match, but checksums do not and the LSP is not generated by the local system, then store the LSP with zero Remaining Lifetime, and flood the LSP										
	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-24.1 MUST	ISO/IEC 10589:1992(E) s7.3.19.1 p31 Entering the waiting state										
	Waiting State When an LSP cannot be stored, the LSP shall be ignored and waiting State will be entered										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-24.2 MUST	ISO/IEC 10589:1992(E) s7.3.19.1 p31 Entering the waiting state										
	Waiting State When an LSP cannot be stored, the LSP shall be ignored and waiting State will be entered										
	FreeBS D 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBS D 10.3: FAIL	FreeBS D 10.3: FAIL	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict	FreeBSD 12.0: unpredict

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-25.2 SHOULD	RFC3719 Section 2.1 Page 3 "MaxAge"										
	ISISUpdate - RFC 3719 MaxAge SHOULD exceed maximumLSPGenerationInterval by atleast 300 seconds Note: Verify the RemainingLifeTime of the Packet										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: pass	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL
ANVL-ISIS-25.3 MAY	RFC3719 Section 2.2 Page 4 "ISISHoldingMultiplier"										
	ISISUpdate - RFC 3719 An implementation MAY allow ISISHoldingMultiplier to be configurable.										
	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: FAIL	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass
ANVL-ISIS-25.4 MUST	RFC3719 Section 3.1 Page 4 "ID Length"										
	ISISUpdate - RFC 3719 An implementation MUST use an ID Length of 6.										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-25.5 MUST	RFC3719 Section 3.1 Page 4 " ID Length"										
	ISISUpdate - RFC 3719 If a router encounters a PDU with an ID Length different from 0 or 6, section 7.3.15.a.2 dictates that it MUST discard the PDU										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass
ANVL-ISIS-25.6 SHOULD	RFC3719 Section 3.2 Page 5 "maximumAreaAddresses"										
	ISISUpdate - RFC 3719 An implementation SHOULD use the value 3.										
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL
ANVL-ISIS-25.7 MUST	RFC3719 Section 3.2 Page 5 " maximumAreaAddresses"										
	ISISUpdate - RFC 3719 If a router receives a PDU with maximumAreaAddresses that is not 0 or 3, it MUST discard the PDU, as described in section 7.3.15.a.3										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019- 09-26	Release 7.2	Release 7.3
ANVL- ISIS- 25.8 MUST	RFC3719 Section 3.3 Page 5 " Protocol Version"										
	ISISUpdate - RFC 3719 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 25.9 MUST	RFC3719 Section 3.3 Page 5 " Protocol Version"										
	ISISUpdate - RFC 3719 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version/Protocol ID field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL- ISIS- 25.23 MUST	RFC3719 Section 11 Page 11 "Doppelganger LSPs"										
	ISISUpdate - RFC 3719 A complete set of CSNPs is a set whose Start LSPID and End LSPID ranges cover the complete possible range of LSPIDs. (i.e., there is no possible LSPID value which does not appear within the range of one of the CSNPs in the set).										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-26.2 SHOULD	RFC3719 Section 2.1 Page 3 "MaxAge"										
	ISISUpdate - RFC 3719 Part 2 MaxAge SHOULD exceed maximumLSPGenerationInterval by atleast 300 seconds Note: Verify the RemainingLifeTime of the Packet										
	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: FAIL	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL	Ubuntu 16.04: FAIL
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL	FreeBSD 12.0: FAIL
ANVL-ISIS-26.3 MAY	RFC3719 Section 2.2 Page 4 "ISISHoldingMultiplier"										
	ISISUpdate - RFC 3719 Part 2 An implementation MAY allow ISISHoldingMultiplier to be configurable.										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: unpredict	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: unpredict	Ubuntu 16.04: unpredict	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: unpredict	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass
ANVL-ISIS-26.4 MUST	RFC3719 Section 3.1 Page 4 "ID Length"										
	ISISUpdate - RFC 3719 Part 2 An implementation MUST use an ID Length of 6.										
	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass	FreeBSD 12.0: pass



	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL-ISIS-26.5 MUST	RFC3719 Section 3.1 Page 4 " ID Length"										
	ISISUpdate - RFC 3719 Part 2 If a router encounters a PDU with an ID Length different from 0 or 6, section 7.3.15.a.2 dictates that it MUST discard the PDU										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-26.8 MUST	RFC3719 Section 3.3 Page 5 " Protocol Version"										
	ISISUpdate - RFC 3719 Part 2 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass
ANVL-ISIS-26.9 MUST	RFC3719 Section 3.3 Page 5 " Protocol Version"										
	ISISUpdate - RFC 3719 Part 2 If a router receives a PDU with a value other than 1 for either field, it MUST drop the packet. Note: Verify the Version/Protocol ID field										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass

	Release 2.0.2	Release 3.0.2	Release 3.0.3	Release 4.0	Release 5.0.1	Release 6.0.3	Release 7.0.1	Release 7.1	Dev 7.2 2019-09-26	Release 7.2	Release 7.3
ANVL- ISIS- 26.23 MUST	RFC3719 Section 11 Page 11 "Doppelganger LSPs"										
	ISISUpdate - RFC 3719 Part 2 A complete set of CSNPs is a set whose Start LSPID and End LSPID ranges cover the complete possible range of LSPIDs. (i.e., there is no possible LSPID value which does not appear within the range of one of the CSNPs in the set).										
	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBS D 10.3: pass	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested	FreeBSD 10.3: untested
	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass	Ubuntu 16.04: pass
	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBSD 12.0: untested	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass	FreeBS D 12.0: pass