

DELTA series

AC Output

1400 to 7200W

Capacity

882Wh to 25kWh





EcoFlow DELTA Pro

The EcoFlow DELTA Pro is the world's first portable home battery with an expandable ecosystem for home backup, smart energy management, lower energy bills, and more. It's the next leap in portable power technology.

GENERAL:

Capacity: 3600Wh (expandable up to 10.8kWh with 2 DELTA Pro Smart Extra Battery)

Weight: Approx. 99 lbs (45.0kg)

Dimensions: 25 × 11.2 × 16.4in (63.5 × 28.5 × 41.6 cm)

OUTPUTS:

AC Output (×5): 3600W (Surge 7200W), 100-120Vac (50Hz/60Hz)/High voltage region (×4): 3600W (Surge 7200W), 220-240Vac (50Hz/60Hz)

Max Device(s) Power Supported by X-Boost: 4500W

USB-A Output (×2): 12W Max per port, 5V DC, 2.4A
USB-A Fast Charge (×2): 18W Max per port, 5V DC, 2.4A/9V DC, 2A/12V DC, 1.5A

USB-C Output (×2): 100W Max per port, 5V/9V/12V/15V/20V DC, 5A

Car Power Output (×1): 126W Max, 12.6V DC, 10A
DC5521 Output (×2): 12.6V DC, 3A

Anderson Port: 12.6V, 30A

INPUTS:

AC Charge Input Voltage: 100-120Vac (50Hz/60Hz) (High voltage region 220-240Vac)

AC Charge Input Power: X-Stream Charge 1800W Max/High voltage region: X-Stream Charge 2900W Max

Solar Charge Input: 1600W Max, 11-150V, 15A

Car Charger Input: 12V/24V DC, Default 8A

BATTERY:

Cell Type: LFP

Life Cycle: 3500 Cycles to 80%+ capacity

3.6-25kWh

Power for any situation.

From tailgate power to extreme blackout that last for days on end, DELTA Pro delivers up to 25kWh of capacity. With that, you're covered for any situation. That's the industry gold standard.



3.6kWh

DELTA Pro



7.2kWh

**DELTA Pro + DELTA Pro
Smart Extra Battery**



10.8kWh

**DELTA Pro + DELTA Pro
Smart Extra Battery x 2**



12kWh

**DELTA Pro + DELTA Pro
Smart Extra Battery
+ Smart Generator**



25kWh

**DELTA Pro x 2 + DELTA Pro Smart
Extra Battery x 2 + Smart Home Panel
+ Smart Generator x 2**

3600-7200W

All the AC output you'll need.

A single DELTA Pro unit packs a 3600W AC output. Power devices at home, outdoors, or at work. That covers air compressors, electric grills, or other high-voltage devices.



7200W, 240V

Power pretty much anything with your home circuits.

If you're looking for more power during an outage, you can connect two DELTA Pro units to the Smart Home Panel. This method gives you up to 7200W through your home circuits and provides power for 240V devices.

7200W, 240V

Power heavy-duty devices with the Double Voltage Hub.

The Double Voltage Hub gives you another option to double your output to 7200W and power 240V devices. Connect two DELTA Pro units together with the Double Voltage Hub to power your electric heaters, well pumps, and other heavy-duty devices during any situation.

6500W MultiCharge

The world's fastest charging portable power station.

DELTA Pro is the world's fastest charging portable power station. Multiple charging delivers record-breaking speeds at 6500W. To reach 6500W, you can opt for one of these multiple charging methods.



6500W



Requires DELTA Pro to be connected to a DELTA Pro Smart Extra Battery.

DELTA SERIES COMPARISONS



DELTA mini



DELTA



DELTA Max



DELTA Pro









Capacity	882Wh	1260Wh	2016Wh	3600Wh
Battery Type	NCM Li-ion	NCM Li-ion	NCM Li-ion	LFP
Shelf Life	1 Year	1 Year	1 Year	1 Year
Life Cycles	800 cycles to 80%+ capacity	800 cycles to 80%+ capacity	800 cycles to 80%+ capacity	3500 cycles to 80%+ capacity
AC Output	1400W (Surge 2100W)	1800W (Surge 3300W)	2400W (Surge 5000W)	3600W (Surge 7200W)
AC Output Sockets	5/High Voltage Version 2	6/High Voltage Version 4	6/High Voltage Version 4	5/High Voltage Version 4
Total Ports	12/High Voltage Version 9	13/High Voltage Version 11	15/High Voltage Version 13	15/High Voltage Version 14
Wall Charging	900W Max	1200W Max	1800W Max	3000W Max /1800W Max
Wall Charging Time	1.6 Hours	1.6 Hours	1.8 Hours	1.8 Hours (at 3000W) 2.7 Hours (at 1800W)
Universal Solar Charging (MC4)	✓	✓	✓	✓
Solar Panel Charging	300W Max , 11-75V, 10A	400W Max , 10-65V, 10A	800W Max , 11-100V, 10A	1600W Max , 11-150V, 15A
Solar Panel Charging Time	3-6 Hours (400W×1)	4-8 Hours (400W×2)	3.2-6.3 Hours (400W×2)	4-8 Hours (400W×3)
APP	✓	✗	✓	✓
Weight	23.6lbs	30.9lbs	48lbs	99lbs

RUN TIMES

				
	DELTA mini	DELTA	DELTA Max	DELTA Pro
 Lightbulb 10W	30+ Hours	35+ Hours	60+ Hours	108+ Hours
 CPAP Mask 40W	13 Hours	20 Hours	28 Hours	50 Hours
 Television 110W	6 Hours	8 Hours	15 Hours	27 Hours
 Refrigerator 150W	5 Hours	6 Hours	11 Hours	20 Hours
 Coffee Maker 1000W	35-40 Cups	50-60 Cups	90-100 Cups	150-170 Cups
 Circular Saw 1400W (2300W)	0.5 Hours	0.8 Hours	1.3 Hours	2.3 Hours
 Hair Dryer 1600W (1900W)	0.5 Hours	0.7 Hours	1.2 Hours	2 Hours
 Grill 1650W	0.5 Hours	0.7 Hours	1.1 Hours	2 Hours

*The appliance run times and durations of use provided in the table above have been calculated with an AC Output. The data is for reference only. Please conduct tests to confirm actual run time of your appliances.

CHARGING TIMES

				
	DELTA mini	DELTA	DELTA Max	DELTA Pro
 AC Wall Outlet	1.6 Hours (900W)	1.6 Hours (1200W)	1.8 Hours (1800W)	2.7Hours (1800W)/ 1.8Hours (3000W)
 Gas Generator**	1.6 Hours (900W)	1.6 Hours (1200W)	1.8 Hours (1800W)	2.7 Hours (1800W)
 Car Charger	9.5 Hours	13.5 Hours	21 Hours	37.5 Hours
 Solar Panel	3-6 Hours (400W×1)	4-8 Hours (400W×1)	3.2-6.3 Hours (400W×2)	4-8 Hours (400W×3)

*The data above is for reference only.

**The rated output power of the gas generator should be higher than the power station max input power.

SOLAR CHARGING RECOMMENDATIONS

				
	DELTA mini	DELTA	DELTA Max	DELTA Pro
Max.Input	300W	400W	800W	1600W
Light Use When Portability matters	160W x 1 7.5-15 Hours	160W x 1 10.5-21 Hours	160W x 1 17-34 Hours	400W x 1 12-24 Hours
HEAVY USE When Quality time matters	400W x 1 3-6 Hours	400W x 1 4-8 Hours	400W x 2 3.2-6.3 Hours	400W x 3 4-8 Hours

*The data above is for reference only.

EcoFlow DELTA Pro Smart Extra Battery

Double or triple the capacity of DELTA Pro to 7.2kWh or 10.8kWh, longer runtime for your key appliances. DELTA Pro's Smart Extra Battery benefits from all the charging methods DELTA Pro has, that means you can charge anytime.



GENERAL:

Capacity: 3600Wh

Weight: Approx. 84 lbs (38kg)

Dimensions: 25 × 11.2 × 16.4in (63.5 × 28.5 × 41.6cm)

BATTERY:

Cell Type: LFP

Life Cycle: 3500 cycles to 80% capacity

ECOSYSTEM PRODUCTS



EcoFlow Smart Generator



Disasters can occur at any time of the year, sometimes lasting longer than we ever expected. When extended blackouts hit, the EcoFlow Smart Generator auto-starts when your DELTA Max or DELTA Pro hits a low level of charge, recharges the power station, and stops the engine all by itself once your the power station hits a full charge. This gives you a reliable emergency backup option that relies on minimum use of a generator.



DIMENSIONS:

Dry Weight: Approx. 62.8 lbs (28.5 kg)

Dimensions: 23.5 × 11.7 × 18.7 in (59.7 × 29.6 × 47.5 cm)

ENGINE:

Model: R80D-i

Engine type: Single cylinder, four-stroke, overhead valve

Cooling system: Forced air

Fuel Type: Unleaded gasoline

Fuel Tank Capacity: 1.05 gal. / 4 L

Engine oil capacity: 0.1 gal. / 0.38 L

GENERATOR:

Rated Power: 1800W rated (Surge 1900W)

DC Output: 42-58.8V, 32A, 1800W max

Generator Type: Inverter generator

RUNTIME:

3.5hrs with Full Load

DELTA Max 2.4 cycles

DELTA Max Smart Extra Battery 2.4 cycles

DELTA Pro 1.2 cycles

DELTA Pro Smart Extra Battery 1.2 cycles



ECOFLOW DELTA PRO SMART GENERATOR ADAPTOR (3.5M)

The Smart Generator Adapter plugs into the Extra Battery Port of DELTA Pro or DELTA Pro Extra Battery to give you more charging options.

Additional adapters are useful for charging DELTA Pro Extra Battery units.

Specs

Input/Output Voltage Range

42-58.8V

Dimension

72 x 60 x 68 mm

Weight

0.16kg

ECOFLOW SOLAR PANEL

EcoFlow Solar Panels are expertly designed to provide users with an efficient, reliable, and eco-friendly way to charge power stations and electrical devices. Made up of monocrystalline cells, our solar panels keep your adventure going, wherever you are.

GENERAL:

Rated Power: 400W(± 10 W)*

Open Circuit Voltage: 48V (Vmp 41V)

Short Circuit Current: 11A (Imp 9.8A)

Efficiency: 22.4%

Connector Type: MC4

Cell Type: Monocrystalline silicon

Weight:

Approx. 41.9 lbs (19.0kg)

Solar Panel 27.6 lbs (12.5kg)

Ratings: IP67

Unfolded Dimensions:

41.7 × 93.1 × 1.0in (105.8 × 236.5 × 2.4cm)

Folded Dimensions:

41.7 × 24.4 × 1.0in (105.8 × 62 × 2.4cm)

* Rated Power is tested under Standard Test Conditions: 1000W/m², AM1.5, 25°C



400W SOLAR PANEL

The EcoFlow 400W solar panel has a high conversion efficiency at 22.4% and gives you 400W power input in full, direct sunlight. Its foldable design makes it easy to transport and store. With the built-in layer of glass fiber and EVA, the panel cells are protected from damage.





Smart Solar Tracker

EcoFlow Solar trackers are unique solar racking and mounting devices that offer a higher efficiency than their standard model counterparts. The First Mobile Solar Tracker that can be placed and moved to anywhere at any time with only easy installation needed.



DIMENSIONS:

Holding Capacity: Approx. 55lbs (25Kg)

Support third part solar panel size:

43.3 × 94.5in (1.1 × 2.4m)

Support third part solar panel weight: 44lbs (20kg)

Pitch axis range: 0°-85°

Y-axis range: 0°-345°

Waterproof Level: IP44

GENERAL:

Dimensions: 98 × 59 × 59in (250 × 150 × 150cm)

Weight: Approx. 77lbs (35kg)



ECOFLOW XT60 SOLAR CABLE (3.5M)

Product Description

The Solar to XT60 Charging Cable lets you link the DELTA or RIVER series power stations to a solar panel. That includes EcoFlow or third-party panels.

Use Case

If you want to charge the DELTA or RIVER series power stations with solar panels, use the Solar to XT60 cable to connect the two. Perfect for use on campsites, beach trips, and family barbecues.

Inside the Box

1x Solar to XT60 Charging Cable

Specifications

Colour: Red and Black

Type: Solar to XT60 Charging Cable

Length: 3.5m



ECOFLOW MC4 SOLAR EXTENTION CABLE (3M)

Product Description

Gain an extra 3m in cable length for the to XT60 Solar Cable with the Solar Extension Cable by EcoFlow.

Use Case

With the extra cable length, you can keep your EcoFlow power station undercover or at a distance while it charges via solar.

Inside the Box

2x EcoFlow Solar Extension Cable

Specifications

Type: Solar Extension Cable

Length: 3m



ECOFLOW MC4 PARALLEL CONNECTION SOLAR CABLE (3M)

Product Description

A cable that connects solar panels in parallel to an EcoFlow DELTA or RIVER series power station.

Use Case

Increase the speed of charging by connecting multiple solar panels.

Used to link up to 4x solar panels to add power to a DELTA series unit.

Used to link up to 2x solar panels to add power to a RIVER series unit.

Inside the Box

Solar Parallel Connection Cable



ECOFLOW DELTA PRO SMART REMOTE

The first of its kind: The first remote control for a portable power station, designed for DELTA Pro. Ideal for storing your DELTA Pro in the garage, storage bay, or below deck. Connect over Bluetooth or an ethernet cable and get a second screen right where you need it.

Monitor your energy: The display shows how much energy you're using, the remaining battery time, and everything else DELTA Pro's screen shows. It's also a convenient place to turn on/off the AC outlets, DC outlets, or entire unit.

Two ways to connect: Move the screen around when connected with Bluetooth; set it and forget it with a wired connection that works over longer distances.

Control at a distance: Once set up, you can monitor & control your portable power station from afar. Ideal when your DELTA Pro is set up with solar panels, or at a charger.

Note: *This accessory is only compatible with the EcoFlow DELTA Pro.*

Specs

Internal Battery

Non-rechargeable AAA

USB-C Input

5V^{max}

Wired Connection

12V^{max} (standard ethernet cable)



ECOFLOW EV X-STREAM ADAPTER (FOR ECOFLOW PRO MOBILE POWER STATION)

The EV X-Stream Adapter allows you to charge your EcoFlow DELTA Pro at thousands of level 2 AC EV charging stations worldwide.

Fast Charging: Get super fast 3400W charging from EV charging stations at home, or on the road and charge your DELTA Pro to full in 1.7 hours.

Wide Compatibility: Type 2 connectors (Mennekes)

In the Box

1x EV X-Stream Adapter

Specs

Input/Output Voltage

100-240V~ 50Hz /60Hz

Maximum Input/Output Power

3400W Max

Connector Type

Type 2: Mennekes