

## 1 Default minted “C” lexer

```
1 def fn f(x) = x * sin(x * M_PI);
2 let vec3 position = vec3(0.0, 0.0, 0.0);
3 using namespace std; POKE 59458,62;
4 xyzzy is a generic keyword; removed stricken;
```

## 2 Custom lexer with new keywords

```
1 def fn f(x) = x * sin(x * M_PI);
2 let vec3 position = vec3(0.0, 0.0, 0.0);
3 using namespace std; POKE 59458,62;
4 xyzzy is a generic keyword; removed stricken;
```

## 3 Latex example

```
1 \documentclass{article}
2 \usepackage[cache=false]{minted}
3 \usepackage[strict]{changepage}
4
5 \begin{document}
6 \setminted{linenos=true, frame=single}
7
8 \section{Default minted ‘C’ lexer}
9 \inputminted{C}{example.c}
10
11 \section{Custom lexer with new keywords}
12 \inputminted{custom}{example.c}
13
14 \section{Latex example}
15 \inputminted[curlyquotes]{tex}{example.ltx}
16
17 \section{Makefile}
18 \setminted{linenos=false, frame=lines}
19 \inputminted{Makefile}{Makefile}
20
21 \clearpage\setminted{linenos=false, frame=none}
22 \changepage{4\baselineskip}{4cm}{-2cm}{-2cm}{-2cm}{-2cm}{}{}{}
23 \section{Custom keyword code}
24 \inputminted{python}{../pygments_custom/__init__.py}
25
26 \end{document}
```

## 4 Makefile

---

```
all: example.pdf

# The Pygments Custom language module uses Environment Variables to
# add keywords for syntax highlighting. All are optional.
# Note that this maps strings to subtypes of Token.Keyword.

export PYGMENTS_CUSTOM_TYPE      := [ "vec3", "Atom", "System" ]
export PYGMENTS_CUSTOM_CONSTANT := [ 'M_PI', 'Tau' ]
export PYGMENTS_CUSTOM_KEYWORD  := [ 'xyzy', 'plugh' ]
export PYGMENTS_CUSTOM_DECLARATION := [ 'def', 'fn' ]
export PYGMENTS_CUSTOM_NAMESPACE := [ 'using', 'hello_my_name_is' ]
export PYGMENTS_CUSTOM_PSEUDO    := [ 'let' ]
export PYGMENTS_CUSTOM_RESERVED  := [ 'POKE' ]
export PYGMENTS_CUSTOM_REMOVED   := [ 'removed' ]

# Pattern rule for building the pdf from latex and C source files.
# Note 1:  $\ell$  represents the latex filename.
# Note 2: The date embedded in the pdf is set to the last modification
#         time of the latex file according to the git commit log or
#         the file timestamp.
%.pdf: %.ltx %.c FORCE
    SOURCE_DATE_EPOCH=`(git log -1 --format=%at $< 2>/dev/null; \
                        date +%s -r $<) | head -1` \
    pdflatex -shell-escape $<

# Always re-create the pdf at each `make`.
FORCE:

.PHONY: clean
clean:
    rm -rf *.aux *.log *.out.pyg _minted-* *~
```

---

## 5 Custom keyword code

```
# pygments_custom
# This module uses environment variables to customize which
# keywords to highlight and which Pygments Lexer to inherit from.

from pygments.token import Name, Keyword
from pygments.lexers import *
from os import getenv
from sys import stderr
import json

# Previously we used "from pygments.lexers import CLexer as mysuper".
# Now, which lexer to inherit from is variable.
base = getenv( "PYGMENTS_CUSTOM_BASE_LEXER" )
if not base:
    base="CLexer"

try:
    mysuper = locals()[ base ]          # Do we have a class named that?
except KeyError:
    mysuper = CLexer
    print( f'\n*** CustomLexer Error: Unknown Lexer: "{base}". ',
           f'Defaulting to CLexer.', file=stderr )
    import pygments.lexers
    print( f'\n*** CustomLexer Error: Please set PYGMENTS_CUSTOM_BASE_LEXER '
           f'to one of {pygments.lexers.__all__}', file=stderr )

class CustomLexer(mysuper):
    """CustomLexer for pygments which extends an existing lexer with
    new keywords. The existing lexer defaults to CLexer but can be
    changed by the environment variable PYGMENTS_CUSTOM_BASE_LEXER.
    For example, one could inherit the C++ Lexer's keywords like so:

        export PYGMENTS_CUSTOM_BASE_LEXER="CppLexer"

    New keywords can be highlighted as Type, Constant, Namespace,
    Declaration, Pseudo, Removed, Reserved, or plain old Keyword. To
    add keywords, set the environment variables PYGMENTS_CUSTOM_TYPE,
    PYGMENTS_CUSTOM_CONSTANT, ..., PYGMENTS_CUSTOM_KEYWORD.

    Each variable is a Python list (square brackets surrounding a
    comma separated list of quoted strings). For example, this
    highlights new types (e.g., classes or typedefs):

        export PYGMENTS_CUSTOM_TYPE="[ 'vec3', 'Atom', 'System' ]"

    """
```

```

name = 'Custom'
aliases = ['custom']
kwtable = [ ('PYGMENTS_CUSTOM_TYPE',      Keyword.Type),
             ('PYGMENTS_CUSTOM_CONSTANT',  Keyword.Constant),
             ('PYGMENTS_CUSTOM_NAMESPACE',  Keyword.Namespace),
             ('PYGMENTS_CUSTOM_DECLARATION', Keyword.Declaration),
             ('PYGMENTS_CUSTOM_PSEUDO',     Keyword.Pseudo),
             ('PYGMENTS_CUSTOM_REMOVED',    Keyword.Removed),
             ('PYGMENTS_CUSTOM_RESERVED',   Keyword.Reserved),
             ('PYGMENTS_CUSTOM_KEYWORD',    Keyword),
             ]

EXTRA = {}

tr = str.maketrans( '"', "'" )          # transliterate python to JSON strings.
for v, k in kwtable:
    s = getenv( v )
    if s:
        s = s.translate(tr)
        try:
            EXTRA[k] = json.loads( s )
        except Exception as e:
            print( f'\n*** Could not parse: {s}',
                  '\n*** Error:', e, file=stderr)

def get_tokens_unprocessed( self, text, stack=('root',) ):
    for index, token, value in mysuper.get_tokens_unprocessed(self, text, stack):
        if token is Name:
            for key in self.EXTRA:
                if self.EXTRA[key] and value in self.EXTRA[key]:
                    token=key
                    break

            yield index, token, value

if __name__ == '__main__':
    print( "testing" )
    x = CustomLexer()
    for y in x.get_tokens_unprocessed( "M_PI", "hello_my_name is", "removed" ):
        print(y)
    for y in x.get_tokens_unprocessed( "vec3 x,y,z; System;", "reserved", Type):
        print(y)

```