# ACSR Lynx · 183.40 mm²

Aluminium Conductor Steel Reinforced · BS EN 50182 · BS EN 50182

| | |
|---|---|
| Product code | **ATC-ACS-B22** |
| Code name | **Lynx** |
| Designation | **183.40 mm²** |
| Aluminium area | **183.40 mm²** |
| Steel area | **42.80 mm²** |
| Total area | **226.2 mm²** |
| Stranding, aluminium | **30 x 2.79 mm** |
| Stranding, steel | **7 x 2.79 mm** |
| Overall diameter | **19.50 mm** |
| Approx. mass | **841.6 kg/km** |
| DC resistance at 20 °C | **0.1576 Ohm/km** |
| Rated tensile strength | **79.97 kN** |
| Current rating | **520 A** |



30 × 2.79 mm Al / 7 × 2.79 mm St · Ø 19.50 mm

Values are nominal unless stated; mass is approximate. Current rating per IEEE 738: 50 Hz, ambient 35 °C, conductor 80 °C, wind 0.6 m/s, solar 900 W/m², emissivity and absorptivity 0.5, sea level; for guidance only. Supplied on wooden or steel drums; grease to EN 50326 on request. Every drum ships with its routine test certificate. Other sizes, standards and product codes on request.