An Empirical Study of Training and Post-Training Strategies for VGG16–GeM Image Retrieval

Author 1 Author 2 Author 3

***Abstract*—We examine checkpoint selection and search-time processing in a VGG16–GeM image-retrieval pipeline trained with structure-from-motion supervision. The study combines historical augmentation and spatial-gate runs with a completed evaluation of the validation-selected B0 checkpoint on legacy Oxford5k and Paris6k. Five fixed search methods are tested on clean queries and six corruption families at three severity levels, producing 17,050 B0 per-query AP records. Average query expansion raises B0 corrupted dataset-macro mAP from 77.20 to 80.64 percent. An implementation audit also explains a severe archived diffusion failure: dense query seeds give 23.67 percent clean mAP on the R1 Oxford union graph, while fixed top-20 seeds recover 76.75 percent on that same graph. On B0, mutual/top-20 diffusion reaches 83.31 percent corrupted dataset-macro mAP, but its effect differs by dataset: clean Oxford falls from 81.06 to 78.35 percent, whereas Paris rises from 77.13 to 90.50 percent. The two historical fine-tuned runs show late-training validation deterioration and score below the selected B0 on both clean benchmarks. Archived geometry-verified expansion improves their rankings at a seconds-per-query cost. Together, the results identify checkpoint choice, feedback quality and diffusion initialization as practical determinants of retrieval performance. Published source, numerical outputs, input hashes and independent solver checks support reproducing the measurements.**

***Index Terms*—instance image retrieval, generalized-mean pooling, query expansion, geometric verification, robustness evaluation**

I. Introduction

Instance image retrieval ranks gallery images depicting the same particular object or landmark as a query. A global descriptor enables inexpensive similarity search, but its usefulness depends on both the learned representation and the processing applied after the initial ranking. Fine-tuning can adapt a classification backbone to retrieval, while query expansion, local verification, fusion, and graph propagation offer additional ways to alter rankings without updating encoder weights.

The VGG16–GeM pipeline provides an established setting for examining these choices. VGG networks supply convolutional representations [1], and generalized-mean pooling (GeM) supports compact descriptors learned from structure-from-motion (SfM) supervision [2]. Checkpoint selection and search processing both affect retrieval accuracy. Evaluating the training histories alongside search improvements on the selected baseline reveals how much each available pipeline improves its starting ranking.

We examine three available training histories: a baseline reproduction, denoted B0, an augmentation-only run (R1), and an augmentation-plus-spatial-gate run (R2). We separately conduct a fixed-encoder search study using the two new epoch-100 checkpoints, re-extracted with the same FP32 inference protocol. A third evaluation applies five fixed methods to validation-selected B0 on both clean and corrupted queries, so search conclusions also include the stronger baseline checkpoint.

Our study addresses three questions. *RQ1:* How do validation-selected and final checkpoints compare, and what evidence supports the training modifications? *RQ2:* Which post-training methods improve clean and corrupted-query retrieval for the same fixed encoder? *RQ3:* How much query-time computation is required for these gains?

The contributions are empirical: (1) an audit of training configuration, data splits, and checkpoint selection; (2) a four-family search study for two final encoders, extended by a five-method clean/robustness evaluation of validation-selected B0; and (3) a comparison of retrieval-only and direct end-to-end latency, including failure diagnosis and the cost of local verification.

II. Related Work

A. Learned Global Representations

Radenović *et al.* use SfM reconstructions to obtain matching and non-matching training examples without manual retrieval labels, and introduce trainable GeM pooling [2]. We adopt this descriptor-learning framework on a prepared subset, retaining a single global descriptor and disabling whitening and multi-scale inference.

Spatial attention is another way to alter feature aggregation. CBAM combines channel and spatial attention [3]. Our second run adapts its channel-mean and channel-max aggregation into a spatial gate with identity-preserving initialization and a scaled sigmoid.

Modern visual backbones broaden the representation choices. Vision Transformer (ViT) processes images as sequences of patches [4], while DINOv2 learns transferable visual features through large-scale self-supervision [5]. They broaden the backbone and pretraining choices for retrieval. We focus on checkpoint selection and search processing within the VGG16–GeM descriptor family.

B. Feedback, Geometry, and Ranking

Visual query expansion uses initially retrieved images to refine the query. Chum *et al.* combine feedback with spatial verification to limit false-positive expansion [6]. We evaluate descriptor-level averaging, similarity weighting, a cosine gate, and a geometry-filtered feedback pipeline. RootSIFT applies

a normalization and square-root transformation to local SIFT descriptors [7]; it supplies the local evidence in our re-ranking and verification stages. Homographies are estimated using RANSAC [8].

Reciprocal rank fusion (RRF) combines rank positions rather than requiring matching score scales [9]. Diffusion can exploit neighborhood structure; Iscen *et al.* study propagation over regional CNN representations [10]. We study propagation on a graph built from one global descriptor per gallery image, examining how query-seed support changes the ranking.

DELG unifies learned local and global features in one network, combining GeM-based global retrieval with attentive local representations [11]. SuperGlobal instead refines global representations for both retrieval and re-ranking [12]. These two directions motivate our comparison of local verification with global-only feedback. RootSIFT–RANSAC and residual QE provide reference pipelines for measuring feedback gains alongside feature storage and query cost.

C. Benchmark Protocols

Oxford and Paris originate from landmark-retrieval research [13], [14]. Revised annotations and evaluation protocols were subsequently introduced [15]. We use the available *legacy* ground truth with 55 queries per dataset. We extend these queries with deterministic corruptions to measure retrieval under controlled image degradation.

III. Methods

A. Encoder and Tuple Objective

For nonnegative convolutional activations $x_{c,u}$ at channel c and position $u \in \mathcal{U}$, GeM computes

$$g_c = \left(\frac{1}{|\mathcal{U}|} \sum_{u \in \mathcal{U}} x_{c,u}^p \right)^{1/p}, \qquad \mathbf{z} = \frac{\mathbf{g}}{\|\mathbf{g}\|_2}. \tag{1}$$

A shared learnable p starts at 3. VGG16 features, without the classifier and final pooling, produce a 512-dimensional normalized descriptor. The initial ranking uses cosine score $s_i = \mathbf{z}_q^\top \mathbf{z}_i$.

Each training tuple contains a query q, one metadata-defined positive p, and five negatives n_j. The implemented objective is

$$\mathcal{L} = \tfrac{1}{2} d(q,p)^2 + \tfrac{1}{2} \sum_{j=1}^{5} [m - d(q,n_j)]_+^2, \quad m = 0.7, \tag{2}$$

where $[a]_+ = \max(a, 0)$ and d is Euclidean descriptor distance. The implementation adds 10^{-6} to coordinate differences before computing the norm for numerical stabilization. Positive relations come from explicit metadata pairs; cluster membership alone does not assign a positive label. Hard-negative mining uses current clean descriptors, excludes the query cluster, and selects negatives from distinct clusters.

B. Training Modifications

R1 adds independent photometric and degradation transforms to the images used in the training forward pass. With probability 0.8, brightness and contrast factors are drawn from $[0.8, 1.2]$ and color from $[0.85, 1.15]$, in random order. Gaussian blur is applied with probability 0.15 and radius $[0.2, 1.0]$ pixels; JPEG encoding with probability 0.2 and integer quality 55–95; and erasing with probability 0.15, area 1–5%, and aspect ratio 0.5–2. Erasing fills zero after normalization, corresponding to the normalization mean in RGB. Clean mining and validation do not use these transforms.

R2 adds a spatial gate before GeM. For feature tensor X, the gate is

$$A(X) = 2\sigma(\mathrm{Conv}_{7\times 7}[\mathrm{mean}_c\, X; \max_c X]). \tag{3}$$

The two-input, one-output convolution has 99 parameters including bias. Zero-initialized weights and bias give $A(X) = 1$, so the initial gated tensor equals X. The output descriptor dimensionality remains unchanged.

C. Query Expansion and Feedback Selection

Let $\mathcal{F}$ be positive-cosine candidates from the first top-k ranking. We compute

$$\mathbf{q}' = \mathrm{norm}_2\left(\mathbf{q} + \lambda \frac{\sum_{i \in \mathcal{F}} w_i \mathbf{z}_i}{\sum_{i \in \mathcal{F}} w_i} \right), \quad w_i = \max(s_i, 0)^\alpha. \tag{4}$$

AQE uses $\alpha = 0$; weighted QE uses $\alpha = 3$. We fix $k = 10$ and $\lambda = 0.5$ for one feedback iteration. Gated QE additionally requires $s_i \geq 0.5$ and at least three accepted candidates, otherwise returning the original query. Setting $\lambda = 0$ also returns the baseline. The residual form in (4) is stated explicitly because conventions for mixing query and feedback differ.

D. Local and Geometric Evidence

We extract up to 2,000 RootSIFT keypoints per image. Matching uses a 0.75 nearest-neighbor ratio test and mutual nearest-neighbor consistency. Homography RANSAC uses a 3-pixel threshold, confidence 0.995, and at most 2,000 iterations. A valid result requires at least eight inliers and a finite, full-rank homography with condition number below 10^{12}.

For a top-50 candidate with M_i matches and I_i inliers, local re-ranking uses evidence $e_i = \min(M_i/50, 1)$. Geometric re-ranking instead uses

$$e_i = \frac{I_i}{\max(M_i, 1)} \min(I_i/20, 1) \tag{5}$$

when geometry is valid, and zero otherwise. The combined score is $(1 - \eta)(s_i + 1)/2 + \eta e_i$, with $\eta = 0.5$. Only the candidate prefix changes; the remaining ranking is retained. Invalid query features or no valid geometric candidate trigger a logged fallback where applicable.

Verified QE checks the first 50 global candidates, selects at most ten with valid geometry and positive cosine, and applies (4). Fewer than three valid feedback images returns the original query. Search is then repeated over the entire gallery, without a second re-ranking stage. Relevance and junk labels never select feedback.

E. Fusion and Diffusion

Score fusion averages the two encoders' cosine scores after image-ID alignment. RRF uses both full rankings:

$$S_{\mathrm{RRF}}(i) = \sum_{r=1}^{2} \frac{1}{60 + \mathrm{rank}_r(i)}. \tag{6}$$

We do not average raw embeddings across encoders.

Each encoder also defines a gallery graph with $k = 20$, no self-edges, and directed weights $\max(s_{ij}, 0)^3$. Union and mutual graphs use the elementwise maximum and minimum with the transposed affinity, respectively. Let $S = D^{-1/2} W D^{-1/2}$, using zero inverse degree for isolated nodes. Initial query scores y_i are positive-cosine cubes normalized to unit sum. We iterate

$$\mathbf{f}^{(t+1)} = (1 - \beta)\mathbf{y} + \beta S \mathbf{f}^{(t)}, \quad \beta = 0.9, \tag{7}$$

starting at $\mathbf{f}^{(0)} = \mathbf{y}$, stopping at relative L2 change below 10^{-6} or 100 iterations. Non-finite results or absent initial mass fall back to cosine. Labels are not used in graph construction or propagation.

The archived grid above uses a dense positive-similarity seed. A subsequent implementation audit evaluates a fixed sparse alternative: retain only the first 20 query neighbors in $\mathbf{y}$, with graph construction, exponent and β unchanged. For this diagnostic, both dense and sparse variants use tolerance 10^{-12} and at most 1,000 iterations, and an independent linear solver checks the result. The sparse seed follows the support convention in the reference implementation [10]; it is evaluated separately from the archived main grid.

IV. Experimental Setup

A. Training Data and Validation

The prepared SfM subset contains 15,953 training images from 100 clusters and 34,337 explicit query–positive pairs. Validation contains 739 images from 20 clusters and 181 pairs. Image identifiers and clusters are disjoint between these partitions. We have not established semantic landmark disjointness between SfM and the retrieval benchmarks.

Each epoch samples 2,000 training tuples. The requested mining pool of 20,000 is clipped to the 15,953 available training images. Thus, an epoch does not enumerate all positive pairs. Five tuple losses are summed before each Adam update, giving 400 updates per epoch. Although each update contains 35 image positions, duplicate images are possible. The microbatch limit of eight applies only to same-shape forward groups; it does not change the optimizer's five-tuple batch. Tuple fusion is one in the new runs.

Validation uses no augmentation or gradient updates. With batch size five and the final incomplete batch dropped, 180 of the 181 validation tuples are processed. For the two new runs, validation pair sampling is seeded consistently, but mined negatives still depend on the current encoder. The selection criterion is validation contrastive loss, not benchmark mAP. Pair metadata alone does not provide exhaustive relevance labels for a retrieval development set.

TABLE I
Training configuration. LR denotes base learning rate before scheduling. B0 is a historical reproduction.

Setting	B0	R1 / R2
Optimizer	Adam	Adam
Backbone LR	10^{-6}	10^{-6}
GeM LR	10^{-5}	10^{-5}
Gate LR	—	— / 10^{-4}
Backbone weight decay	10^{-6}	10^{-6}
GeM / gate weight decay	0 / —	0 / 0
Training seed	42	42
Image long-edge cap	1024	1024
Tuples / update	5	5
Negatives / tuple	5	5
Completed epochs	14	100 / 100
Backbone train precision	FP32	BF16 autocast

B. Optimization and Checkpoint Identity

Table I summarizes the settings. Adam [16] uses a pre-epoch schedule $\mathrm{LR}(e) = \mathrm{LR}_0 \exp(-0.01e)$, beginning at $e = 1$. The new runs retain FP32 for GeM, descriptor normalization, loss, weights, and Adam state. They use four workers, extraction window eight, prefetch factor two, and no image cache. Training uses Colab; the new runs were configured for an A100 40-GB GPU. Runtime differences prevent an algorithm-only speed comparison with B0.

We distinguish three evidence tracks. The *historical checkpoint comparison* uses saved clean evaluations: B0 best at epoch 12 and last available at 14, R1 best at 27, and R2 best at 28. The archived new-run best evaluations use BF16 backbone inference. The *post-training comparison* uses both latest epoch-100 checkpoints, re-extracted in FP32 with TF32 disabled. The completed B0 study applies five fixed search methods to its validation-selected epoch-12 checkpoint, using the same query-corruption schedule and FP32 inference with TF32 disabled. B0 historical evaluations are also FP32; archived clean checkpoint scores remain separate from the new inference results.

The R1 epoch-27 weight file is absent from the supplied archive, although its saved evaluation and history remain available. Its clean scores are reported as historical evidence, not as a newly repeated inference. Both final checkpoints and the B0 best checkpoint are available. Archive, source-checkpoint, exported-weight, and metadata hashes identify the inputs; exported final weights were checked against the source model before extraction.

C. Retrieval Protocol and Corruptions

Oxford5k contains 5,063 gallery images and Paris6k 6,392, each with 55 query regions. We retain the legacy bounding boxes, relevant-image labels, junk handling, and trapezoidal AP evaluator. Image-source queries may also occur in the gallery. AP is averaged over queries to form mAP. We additionally retain P@10 and relevant Recall@20/50/100 after junk removal. These are legacy scores, not revisited-protocol results [15].

TABLE II
QUERY CORRUPTIONS AT SEVERITIES 1/2/3. L IS THE RESIZED QUERY LONG EDGE; THE GALLERY STAYS CLEAN.

Family	Severity parameters
Darkening	RGB factors 0.8 / 0.6 / 0.4
Contrast	Factors about channel mean: 0.8 / 0.6 / 0.4
Blur	Gaussian σ/L: 0.001 / 0.002 / 0.004
Noise	Gaussian RGB std.: 0.02 / 0.05 / 0.08
JPEG	Quality 80 / 50 / 25; subsampling 2
Occlusion	Area fractions 0.05 / 0.10 / 0.20; query RGB-mean fill

TABLE III
HISTORICAL CLEAN MAP (%). BEST MEANS MINIMUM VALIDATION LOSS. R1/R2 BEST USE ARCHIVED BF16-BACKBONE EVALUATIONS; FINAL ROWS ARE THE NEW FP32 COSINE BASELINES.

Checkpoint	Epoch	Oxford	Paris
B0 best	12	81.06	77.12
B0 last available	14	80.77	76.08
R1 best	27	79.53	71.93
R2 best	28	80.49	72.76
R1 final	100	74.00	64.29
R2 final	100	71.37	62.72

Inference uses one scale and no whitening. RGB images preserve aspect ratio under a long-edge cap of 1024. Query crops retain the upstream relative-resize rule: their cap is scaled by the ratio of crop to original long edge, rather than enlarging every crop to 1024. Values in $[0, 1]$ are normalized by mean $(0.485, 0.456, 0.406)$ and standard deviation $(0.229, 0.224, 0.225)$.

Corruptions in Table II are applied after crop/resize and before normalization. Blur uses a minimum sigma of 0.1 pixels. Noise and occlusion each have three fixed realizations per severity; other families have one. This produces 30 corrupted views plus clean per query: 3,410 query instances per encoder, or 6,820 forwards in the original two-encoder study. The completed B0 study uses those same 3,410 query instances, and all pixel checksums match the saved R1 inputs. Corruption seed 20261030 is independent of training seed 42. Pixel checksums enforce consistency between global and local features. Noise is absent from the training augmentation; the remaining families overlap in part but differ in generation or strength.

For $C = 18$ family–severity conditions and their realization counts R_c, we report

$$\mathrm{mAP}_{\mathrm{corr}} = \frac{1}{C} \sum_{c=1}^{C} \frac{1}{R_c} \sum_{r=1}^{R_c} \mathrm{mAP}_{c,r}. \tag{8}$$

Dataset-macro results average Oxford and Paris equally. Worst-condition mAP is the minimum of the 18 realization-averaged condition scores. Drop is clean minus corrupted mAP in percentage points. Repeated views of the same query are not independent training replications.

D. Frozen Parameters, Sensitivity, and Cost

Main parameters are fixed across datasets and corruption conditions. Clean-only, one-axis sensitivity varies QE $k \in \{5, 10, 20\}$, $\alpha \in \{1, 3, 5\}$, $\lambda \in \{0.25, 0.5, 1\}$, gate $\tau \in \{0.4, 0.5, 0.6\}$; re-ranking $K \in \{20, 50, 100\}$ and $\eta \in \{0.25, 0.5, 0.75\}$; RRF $c \in \{10, 60, 100\}$; and diffusion $k \in \{10, 20, 40\}$ and $\beta \in \{0.5, 0.9, 0.99\}$. Main settings supply the reference, with 100 additional model–method–configuration–dataset rows. Sensitivity results are reported separately; the main configuration remains fixed throughout evaluation.

The original FP32 extraction used a Kaggle Tesla T4, PyTorch 2.11.0+cu128, NumPy 2.1.3 and Pillow 13.0.0. The completed B0 run used a Tesla T4 with PyTorch 2.11.0+cu130, the same NumPy/Pillow versions and OpenCV 4.14.0. It finished its measured work in 1,594.45 seconds, reusing verified Oxford gallery and clean-query descriptors; this is not a from-scratch extraction time or an online latency benchmark. Local processing used OpenCV 4.14.0; CPU jobs used SciPy 1.16.3. CPU allocation can differ between Kaggle jobs, so timings describe the measured deployment rather than a hardware-normalized algorithm benchmark.

Retrieval-only latency assumes cached descriptors. Direct end-to-end latency includes decoding, query crop/resize, corruption when applicable, encoding, search, and query local extraction/matching for local methods. Gallery descriptors, gallery local features, and graphs are offline assets. Timing uses batch one, warm-up, and GPU synchronization. For each model/dataset/method, 28 samples cover clean and severity-three queries from all six families, with two queries per condition and two repeats. Across 40 groups, this gives 1,120 direct samples. We report medians and retain p95 in the released tables; independently measured medians are not additive component costs.

V. RESULTS AND DISCUSSION

A. RQ1: Checkpoint Selection and Training Changes

B0 best remains strongest on both clean benchmarks (Table III), reaching 81.06% on Oxford and 77.12% on Paris. The best available historical evaluations for R1 reach 79.53% and 71.93%; R2 reaches 80.49% and 72.76%. The gate run is higher at these selected checkpoints, but this ordering reverses at epoch 100. The gate advantage therefore depends on checkpoint selection, and both new runs remain below the selected B0 checkpoint.

The histories show late-training deterioration (Fig. 1). R1 has minimum validation loss 0.100764 at epoch 27, rising to 0.123108 at epoch 100; R2 rises from 0.100519 at epoch 28 to 0.119673. Meanwhile, training loss falls to approximately 0.0288 and 0.0280. Combined with lower final retrieval scores, this is consistent with overfitting. The training and validation trajectories separate as learning continues.

All best checkpoints use minimum validation loss: B0 epoch 12, R1 epoch 27 and R2 epoch 28. Benchmark mAP does not select epochs; the historical evaluations retain these original choices.




Fig. 1. Training and validation contrastive loss for the two new runs. Dotted lines mark validation-selected epochs 27 and 28. Validation negatives depend on the current encoder; curves show the implemented monitoring objective.

TABLE IV
COMPLETE B0 EPOCH-12 EVALUATION, MAP (%). C: CLEAN; R: MEAN OVER 18 CORRUPTED CONDITIONS. THE CHECKPOINT IS SELECTED BY VALIDATION LOSS; SEARCH SETTINGS ARE FIXED.

Method	Oxford		Paris	
	C	R	C	R
Cosine	81.06	78.77	77.13	75.63
AQE	83.77	82.22	80.19	79.07
α-QE	83.76	82.25	80.17	79.05
Gated QE	83.76	82.25	80.17	79.05
Sparse diffusion	78.35	77.46	90.50	89.16

B. RQ2: Search Improvements for Fixed Encoders

Table IV applies all five fixed methods to the validation-selected B0 checkpoint on both benchmarks. AQE increases clean mAP from 81.06% to 83.77% on Oxford and from 77.13% to 80.19% on Paris. Its corrupted dataset-macro mAP rises from 77.20% to 80.64%. Weighted and cosine-gated QE give similar scores.

Sparse diffusion is encoder- and dataset-dependent: Oxford clean mAP falls to 78.35%, whereas Paris rises to 90.50%. Its corresponding corrupted scores are 77.46% and 89.16%, yielding 83.31% dataset-macro mAP. Correcting query seeding therefore resolves the earlier collapse without guaranteeing an improvement for every encoder and dataset.

The completed B0 grid contains 310 method/view groups and 17,050 per-query AP records; all 3,410 query pixel checksums match the R1 inputs.

a) Expansion provides low-cost gains: AQE and weighted QE improve both clean and corrupted mAP for both final encoders (Table V). For R1, weighted QE increases Oxford clean from 74.00% to 76.45% and Paris clean from 64.29% to 65.89%. Equal-dataset corrupted mAP rises from 66.82% to 69.34%, a 2.52-percentage-point gain. AQE and weighted QE give similar improvements.

The cosine gate opens for every measured query view and accepts ten feedback images, causing gated QE to equal weighted QE. Identical scores identify an inactive selection constraint.

b) Geometry is most useful as a feedback filter: For R1, local-match re-ranking reaches 78.53% Oxford clean, exceeding the geometric-score re-ranker at 76.68%. Geometric verification is therefore not uniformly stronger when used only to reorder a short prefix. In contrast, verified QE reaches 78.94% and 66.97% clean on Oxford and Paris, and 76.28% and 65.82% under corruption. Its corrupted dataset-macro mAP is 71.05%, or 4.23 points above cosine. Within the archived grid, R2 verified QE gives the highest scores in all four columns: 76.85%, 74.25%, 65.10%, and 64.31%.

Verified feedback is not always available. Across clean and corrupted views, its gate opens for 88.39% of R1 Oxford cases and 92.96% of Paris cases. The mean feedback counts, including closed gates, are 6.87 and 8.56. Fallbacks are retained rather than removing difficult queries from evaluation. The logged feedback counts expose how often geometric filtering can operate.

c) Fusion does not beat the stronger encoder: Neither score fusion nor RRF exceeds R1 cosine on either clean dataset or their corrupted means (Table VI). Score fusion obtains 73.55% Oxford clean and 64.04% Paris clean, compared with 74.00% and 64.29% for R1. The additional encoder and combination step provide no accuracy gain for this pair.

d) Dense query seeds explain the archived diffusion collapse: Mutual diffusion reduces R1 Oxford clean from 74.00% to 48.95%, and union diffusion to 23.67%. Paris also deteriorates. This is not primarily explained by numerical failure: aggregate diagnostics report full convergence for both R1 graphs, zero fallback, and mean iteration counts approximately 63–93. R2 Oxford mutual diffusion reaches convergence in 99.77% of views, with the remaining views retained at the iteration cap.

An implementation audit changes this interpretation. Holding the cached graph, descriptors and β fixed, top-20 query seeds raise R1 Oxford clean mAP to 76.75% on the union graph and 77.46% on the mutual graph, compared with 74.00% cosine. Paris mutual diffusion reaches 77.26%, compared with 64.29% cosine. Dense-seed replay reproduces the original collapse. Fixed-point solutions agree with independent

TABLE V

ARCHIVED POST-TRAINING RESULTS, MAP (%). C DENOTES CLEAN AND R THE MEAN OVER 18 CORRUPTED-QUERY CONDITIONS. BOTH ENCODERS ARE FIXED AT EPOCH 100 AND USE FP32 EXTRACTION. EACH METHOD USES ITS ENCODER'S OWN COSINE BASELINE; DIFFUSION HERE USES THE ORIGINAL DENSE SEEDS.

	R1: augmentation				R2: augmentation + gate			
	Oxford5k		Paris6k		Oxford5k		Paris6k	
Method	C	R	C	R	C	R	C	R
Cosine	74.00	70.80	64.29	62.84	71.37	68.15	62.72	61.59
AQE	76.41	73.81	65.90	64.84	73.64	70.86	64.06	63.36
α-QE	76.45	73.86	65.89	64.83	73.63	70.90	64.06	63.36
Gated QE	76.45	73.86	65.89	64.83	73.63	70.90	64.06	63.36
Local re-rank	78.53	75.08	65.42	64.01	76.55	73.35	63.92	62.83
Geometric re-rank	76.68	73.46	64.83	63.40	74.98	71.84	63.33	62.19
Verified QE	78.94	76.28	66.97	65.82	76.85	74.25	65.10	64.31
Mutual diffusion	48.95	47.32	53.11	52.26	51.15	49.63	52.55	52.01
Union diffusion	23.67	22.10	45.61	45.15	25.79	24.13	46.15	46.05

TABLE VI

TWO-ENCODER FUSION, MAP (%). BOTH USE R1+R2 EPOCH 100; COLUMN ORDER MATCHES TABLE V.

	Oxford		Paris	
Method	C	R	C	R
Score fusion	73.55	70.40	64.04	62.77
RRF	73.43	70.25	64.11	62.80

TABLE VII

REVISED MUTUAL DIFFUSION WITH FIXED TOP-20 SEEDS, MAP (%). C: CLEAN; R: MEAN OVER 18 CORRUPTED CONDITIONS. THE SAME CACHED EPOCH-100 DESCRIPTORS AND GRAPHS ARE REUSED.

	Oxford		Paris	
Encoder	C	R	C	R
R1	77.46	76.21	77.26	76.34
R2	73.80	72.45	77.79	77.06

conjugate-gradient solutions within 1.5×10^{-11} relative error on three fixed queries per case; hand-checkable graphs also agree with direct linear solves. The replay isolates query-seed support as the source of the large ranking change. The archived table retains its original dense-seed measurements for traceability.

Replaying this single fixed mutual/top-20 configuration on all 31 archived views produces 6,820 new per-query AP records (Table VII). For R1, corrupted dataset-macro mAP is 76.27%, compared with 66.82% cosine and 71.05% verified QE in the archived study. This extends the seed-support diagnosis to the prescribed corruptions without additional encoder inference. It adds no new end-to-end latency measurement.

C. Corruption Severity

Figure 2 shows that severe blur is B0's worst cosine condition on both datasets: mAP is 63.03% on Oxford and 66.42% on Paris. AQE raises these scores to 71.92% and 72.58%, while sparse diffusion gives 73.64% and 81.37%. Diffusion can therefore improve a severely corrupted condition even when it lowers clean Oxford mAP. Absolute accuracy, clean-to-corrupted drop and the starting encoder provide complementary information.

With the same corruption definition, B0 cosine corrupted dataset-macro mAP is 77.20%, compared with 66.82% for R1 and 64.87% for R2 at epoch 100. After sparse diffusion, these scores are 83.31%, 76.27% and 74.76%, respectively. The stronger selected B0 remains an important reference for judging search improvements; the historical training budgets and checkpoint rules are discussed in Limitations.

The suite partially overlaps training augmentation but is not identical. In particular, Gaussian noise is not included in the saved augmentation policy. Occlusion includes cases where identifying content is removed; this stress test covers the prescribed transformations.

The supplement preserves all 100 clean sensitivity evaluations and their 5,500 per-query AP values for traceability. The main experiments use the fixed settings described in Section IV; sensitivity maxima do not select the reported configuration.

D. RQ3: Quality–Latency Trade-offs

QE adds approximately 3–5 ms to retrieval-only processing for R1. Direct weighted-QE medians are 75.55 ms on Oxford and 87.34 ms on Paris. Verified QE has medians 8.48 s and 5.82 s; local matching and geometric processing dominate this scale of cost. These methods occupy substantially different deployment regimes (Fig. 3).

The direct cosine medians for R1 are 85.52 and 109.53 ms, larger than the corresponding weighted-QE medians despite QE's additional operation. Independent timing samples show execution variability; retrieval-only timings expose the added expansion work more directly.

Offline computation also matters. The shared local-feature cache reports approximately 2.56 GB of stored data. Its recorded builds take 2,464 s for Oxford and 3,049 s for Paris, covering gallery and query-view features. Query local features are nevertheless recomputed in the direct timer so cached queries do not hide online costs. Both fusion encoders must also be executed: direct score-fusion medians are 147.17 ms




Fig. 2. Validation-selected B0 under increasing query corruption. Solid curves: Oxford; dashed: Paris. Blue: cosine; orange: AQE; green: mutual/top-20 diffusion. Each non-clean point averages the prescribed realizations. The gallery is always clean.

Oxford and 160.30 ms Paris. Its extra encoding cost does not yield an accuracy improvement here.

E. Reproducibility

The main grid has 20 ranking configurations per dataset: nine per encoder and two fusion rules. Across 110 queries and 31 views this yields 68,200 main AP records, with no missing cells in the saved coverage audit. Together with sensitivity, the archived records total 73,700. The sparse-seed replay adds 6,820 AP records and the completed B0 study adds 17,050, giving 97,570 per-query AP records across the post-training grids. Historical checkpoint evaluations are indexed separately. All 310 saved B0 rankings were checked as full gallery permutations and independently rescored into the 17,050 AP records. Descriptors, rankings, image IDs, pixel checksums, checkpoint hashes, graph diagnostics, and job completion states identify the evaluated artifacts. Smoke checks cover export/reload consistency, finite descriptors, perfect/junk evaluator cases, QE identity and closed-gate behavior, single-ranker fusion, prefix-preserving re-ranking, and graph numerical behavior.

Source and numerical releases are available in the project repository[1] and the public B0 and archived R1/R2 output releases. The repository's artifact index provides download instructions and checksum inventories.

[1]https://github.com/FUAVX/IIR-Robust-Retrieval

VI. Limitations

Only one training seed is available. Corrupted views of the same query and related landmark queries are not independent training replications. The training comparison is historical, with different budgets, precision and runtime; it is not a controlled augmentation or attention ablation. R1's validation-selected weights are absent from the supplied archive. These constraints limit attribution of differences to augmentation or attention. The study evaluates established components within VGG16–GeM; ViT, DINOv2, DELG and SuperGlobal are related work, not experimental baselines. Evaluation uses legacy Oxford/Paris annotations, whose scores are not interchangeable with revisited Easy/Medium/Hard results. Comparison with modern systems requires ROxford/RParis Medium/Hard under a shared protocol. The sparse-seed audit is a post-review implementation diagnosis on the existing benchmarks, rather than an independent validation set. Search sensitivity is descriptive: no test-set maximum replaces the frozen main settings. A separately labeled retrieval development set is still needed for parameter selection. The corruption suite reuses benchmark queries and does not provide independent query-level replication. The completed B0 study covers five fixed search methods on both clean and corrupted queries; local and geometry-verified re-ranking have not been rerun on B0. Direct latency samples are small, and no new direct B0 latency measurement is available. Revised sparse diffusion has no new end-to-end timing measurement.




Fig. 3. Archived R1 corrupted mAP versus direct end-to-end median query latency (logarithmic axis). Quality uses the complete corruption suite; latency uses the predefined 28-sample subset. Diffusion points retain the original dense seeds. Revised sparse diffusion has no new direct timing and is omitted. Offline gallery preparation is excluded.

VII. Conclusion

This study separates historical training observations from search-time improvements in VGG16–GeM retrieval. The validation-selected B0 remains a strong baseline, while the two new training runs exhibit late validation deterioration. On the completed B0 corruption study, AQE raises dataset-macro mAP from 77.20% to 80.64%. Sparse diffusion reaches 83.31%, with a strong Paris gain but a clean Oxford loss. The same method therefore benefits some encoder/dataset combinations more than others.

An independent implementation audit identifies dense query seeding as the cause of the severe archived diffusion collapse. Sparse query seeds recover useful rankings, with gains that depend on the encoder and dataset. Archived local/geometric experiments also show that feedback quality and query cost matter: verified expansion improves the weaker epoch-100 encoders but costs seconds per query. Validation-based checkpoint selection, faithful implementation and separate quality/latency accounting are necessary for useful comparisons. The released source, numerical records and solver checks make these findings traceable.

References

[1] K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," in *International Conference on Learning Representations*, 2015. [Online]. Available: https://arxiv.org/abs/1409.1556

[2] F. Radenović, G. Tolias, and O. Chum, "Fine-tuning CNN image retrieval with no human annotation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 41, no. 7, pp. 1655–1668, 2019.

[3] S. Woo, J. Park, J.-Y. Lee, and I. S. Kweon, "CBAM: Convolutional block attention module," in *European Conference on Computer Vision*, 2018. [Online]. Available: https://arxiv.org/abs/1807.06521

[4] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby, "An image is worth 16x16 words: Transformers for image recognition at scale," in *International Conference on Learning Representations*, 2021. [Online]. Available: https://arxiv.org/abs/2010.11929

[5] M. Oquab, T. Darcet, T. Moutakanni *et al.*, "DINOv2: Learning robust visual features without supervision," *arXiv preprint arXiv:2304.07193*, 2023. [Online]. Available: https://arxiv.org/abs/2304.07193

[6] O. Chum, J. Philbin, J. Sivic, M. Isard, and A. Zisserman, "Total recall: Automatic query expansion with a generative feature model for object retrieval," in *IEEE International Conference on Computer Vision*, 2007, pp. 1–8. [Online]. Available: https://www.robots.ox.ac.uk/~vgg/publications/2007/Chum07b/chum07b.pdf

[7] R. Arandjelović and A. Zisserman, "Three things everyone should know to improve object retrieval," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2012, pp. 2911–2918.

[8] M. A. Fischler and R. C. Bolles, "Random sample consensus: A paradigm for model fitting with applications to image analysis and automated cartography," *Communications of the ACM*, vol. 24, no. 6, pp. 381–395, 1981. [Online]. Available: https://www.sri.com/wp-content/uploads/2021/12/ransac-publication.pdf

[9] G. V. Cormack, C. L. A. Clarke, and S. Büttcher, "Reciprocal rank fusion outperforms condorcet and individual rank learning methods," in *International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2009, pp. 758–759.

[10] A. Iscen, G. Tolias, Y. Avrithis, T. Furon, and O. Chum, "Efficient diffusion on region manifolds: Recovering small objects with compact CNN representations," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2017. [Online]. Available: https://arxiv.org/abs/1611.05113

[11] B. Cao, A. Araujo, and J. Sim, "Unifying deep local and global features for image search," in *European Conference on Computer Vision*, 2020. [Online]. Available: https://arxiv.org/abs/2001.05027

[12] S. Shao, K. Chen, A. Karpur, Q. Cui, A. Araujo, and B. Cao, "Global features are all you need for image retrieval and reranking," in *IEEE/CVF International Conference on Computer Vision*, 2023. [Online]. Available: https://arxiv.org/abs/2308.06954

[13] J. Philbin, O. Chum, M. Isard, J. Sivic, and A. Zisserman, "Object retrieval with large vocabularies and fast spatial matching," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2007, pp. 1–8. [Online]. Available: https://www.robots.ox.ac.uk/~vgg/publications/2007/Philbin07/philbin07.pdf

[14] ——, "Lost in quantization: Improving particular object retrieval in large scale image databases," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2008, pp. 1–8. [Online]. Available: https://www.robots.ox.ac.uk/~vgg/publications/2008/Philbin08/philbin08.pdf

[15] F. Radenović, A. Iscen, G. Tolias, Y. Avrithis, and O. Chum, "Revisiting Oxford and Paris: Large-scale image retrieval benchmarking," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2018. [Online]. Available: https://arxiv.org/abs/1803.11285

[16] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *International Conference on Learning Representations*, 2015. [Online]. Available: https://arxiv.org/abs/1412.6980