



SMART INDIA HACKATHON 2026



Adaptive Path Planning and Collision Avoidance for Autonomous Vehicles on Unstructured Indian Roads

- **Problem Statement ID** – SIH26037
- **Problem Statement Title** –
Adaptive Path Planning and Collision Avoidance for Autonomous
Vehicles on Unstructured Indian Roads
- **Theme** – Smart Vehicles
- **PS Category** – Software
- **Team ID** – 162509
- **Team Name (Registered on portal)** – CraterFinders





PROPOSED SOLUTION



Problem at Hand


No Lanes to Follow: Village and peri-urban roads are unmarked, so lane-keeping ADAS and AV stacks lose their reference path.

Mixed, Rule-Free Traffic: Autos, cyclists, pedestrians, cattle and pushcarts share one carriageway with no lane discipline.

Unpredictable Intent: A rickshaw may brake, drift or cut in. A single predicted path hides that uncertainty from the planner.

High Human Cost: India recorded 1,68,491 road deaths in 2022 (MoRTH). Autonomy built for Western roads does not transfer.

Our Solution



Closed-loop simulation: in NUDGE mode the ego plans a smooth path past a parked pushcart on an unmarked village road.

Why We Stand Out

- **Lane-free by design:** plans inside a drivable corridor and passes on either side, as Indian drivers do.
- **Working prototype today:** all 5 required scenarios run end-to-end and complete collision-free, scored against ground truth.
- **Zero-licence core:** toolbox-free MATLAB/Octave code that ports directly to Simulink & Stateflow.

Key Features



Corridor Planning

Frenet lattice over free space, not painted lanes.



Multi-Sensor Fusion

Camera + radar + LiDAR into EKF tracks that survive occlusion.



Intent Prediction

Four class-weighted hypotheses per road user.



Behaviour FSM

Cruise, Nudge, Yield, Creep and Stop set the planner's limits.



Safety First

Risk-dominated cost, 0.45 m margin and emergency braking.



Real-Time

10 Hz replanning; 51–66 ms mean cycle.




TECHNICAL APPROACH



SMART INDIA
HACKATHON
2026

Closed-Loop Autonomy Pipeline




Technologies Used

- MATLAB R2025 / GNU Octave**
Toolbox-free algorithm core
- Simulink + Stateflow**
Closed-loop model, behaviour chart
- RoadRunner + ASAM OpenDRIVE**
Indian road scenes (.xodr)
- YOLO on IDD**
Indian road-user detection demo
- Python · Matplotlib · FFmpeg**
Replays and metrics figures

Implementation Roadmap

- 1 Core loop + village-road scenario ✓
- 2 All 5 scenarios + submission video ✓
- 3 Simulink closed-loop model
- 4 Metrics & technical report, dashboard
- 5 Stateflow, RoadRunner scenes, YOLO-IDD



All 5 scenarios complete collision-free. Shown: the 188 m village road, ego path coloured by behaviour.



FEASIBILITY AND VIABILITY



Technical Feasibility

- **All 5 scenarios run:** sensing → fusion → prediction → planning → control closes end-to-end.
- **Tested:** 8/8 tests pass, including the full closed-loop regression run (EKF, Frenet, Hungarian, collision, bicycle model).
- **15× faster planner** (919 → 61 ms/cycle) from batched candidate checks.
- **One scenario spec** feeds Octave, Simulink and drivingScenario, so nothing is authored twice.

Measured Results · All 5 Scenarios

Scenario	Time	Coll.	Min clear	Replan p95
Village road	48.1 s	0	0.46 m	92 ms
Crossroads	43.5 s	0	3.33 m	107 ms
Highway merge	38.0 s	0	3.89 m	86 ms
Market street	97.1 s	0	0.13 m	98 ms
Cattle crossing	84.2 s	0	1.47 m	98 ms

5 of 5 completed · 0 collisions · clearance scored on ground truth

Resource Feasibility

Tier 0 · GNU Octave – free, unlimited: algorithms, all 5 scenarios, metrics

Tier 1 · MATLAB Online Basic – free: Simulink closed-loop model

Tier 2 · 30-day trial – used last, only for Stateflow, RoadRunner & YOLO-IDD

Hardware: a standard laptop; no GPU needed.

Potential Challenges & Risks → Strategies for Overcoming Them

#	Challenge / Risk	Strategy to Overcome
1	Replan latency crosses the 100 ms budget on busy cycles (p95 86–107 ms by scenario)	Batching already cut cost 15×; next, adaptive lattice size and MATLAB Coder C code
2	Hybrid A* fallback is written and verified, but enabling it made results worse	Kept off: it raised p95 to 250–400 ms and cost a completion; re-enable once search cost and margins are reconciled
3	Dense market clears by only 0.13 m at its tightest	Most margin-sensitive scenario; tune the safety margin and re-validate all five runs
4	COCO-trained YOLO mislabels auto-rickshaws and pushcarts	Class-agnostic tracking fallback; fine-tune on the IDD dataset when a GPU is available
5	RoadRunner is available only in the one-time 30-day trial	Hand-author OpenDRIVE scenes first, so trial days go to assembly, not development



IMPACT AND BENEFITS



1.68 lakh

road deaths in India in 2022 (MoRTH): the problem we target

5

Indian road scenarios — village, crossroads, merge, market, cattle — all completing

0

collisions across all 5 scenarios, scored against ground truth

₹0

licence cost to develop and verify the algorithm core

Who Benefits



Automotive OEMs & Tier-1s

ADAS/AV behaviour tuned for Indian traffic



Logistics & Last-Mile

Autonomous delivery pods, campus shuttles



Rural Mobility

Agri-vehicles and buses on unmarked roads



Students & Researchers

Open, toolbox-free baseline and scenarios



Road-Safety & Test Agencies

Repeatable Indian-road test scenarios

Benefits of the Solution



Social

- Class-aware caution around pedestrians, cyclists & cattle, the most vulnerable road users
- Legible yield/creep behaviour that other road users can anticipate



Environmental

- Jerk-limited, smooth speed profiles avoid harsh braking and wasted energy
- A natural fit for electric autonomous vehicles and low-emission mobility



Economic

- Free-tier development cuts R&D and licence cost
- Reusable scenario library lowers validation cost; indigenous tech for Atmanirbhar Bharat



Technological

- Benchmark scenarios and metrics for unstructured roads
- Stateflow chart keeps every decision explainable to judges and regulators



RESEARCH AND REFERENCES



SMART INDIA
HACKATHON
2026

Research Insights That Shaped the Design

Lanes are the wrong prior

IDD shows Indian scenes break lane-centric assumptions, so we plan in a free-space corridor [3].

Keep uncertainty visible

Multi-hypothesis prediction feeds a risk field instead of collapsing to one guess.

Frenet lattices give comfort

Jerk-optimal quintic/quartic trajectories are smooth by construction [1].

Score safety on ground truth

Clearance measured from our own tracks would be circular, so we use true positions.

References

- [1] M. Werling, J. Ziegler, S. Kammel, S. Thrun, "Optimal trajectory generation for dynamic street scenarios in a Frenét frame," IEEE ICRA, 2010.
- [2] D. Dolgov, S. Thrun, M. Montemerlo, J. Diebel, "Path planning for autonomous vehicles in unknown semi-structured environments," IJRR, vol. 29, no. 5, 2010.
- [3] G. Varma, A. Subramanian, A. Namboodiri, M. Chandraker, C. V. Jawahar, "IDD: A dataset for exploring problems of autonomous navigation in unconstrained environments," IEEE WACV, 2019.
- [4] R. C. Coulter, "Implementation of the pure pursuit path tracking algorithm," CMU-RI-TR-92-01, Carnegie Mellon University, 1992.
- [5] H. W. Kuhn, "The Hungarian method for the assignment problem," Naval Research Logistics Quarterly, vol. 2, 1955.
- [6] S. Thrun, W. Burgard, D. Fox, Probabilistic Robotics, MIT Press, 2005.
- [7] Ministry of Road Transport & Highways, "Road Accidents in India 2022," Government of India, 2023.
- [8] ASAM e.V., "ASAM OpenDRIVE" road-network standard; MathWorks RoadRunner & Automated Driving Toolbox documentation.

Prototype Evidence



Project Links

- [1\) Source Code Repository](#)
- [2\) Demo Video: All 5 Scenarios](#)
- [3\) Metrics & Run Data \(JSON\)](#)