

HiSim Simulation Report

Developers:

Dr. Noah Pflugradt

Dr. Sebastian Dickler

Kevin Knosala

Katharina Rieck

Johanna Ganglbauer

David Neuroth

Tjarko Tjaden

Vitor Hugo Bellotto Zago

Maximilian Hillen

Frank Burkrad

Marwa Alfouly

Franz Oldopp

Markus Blasberg

Forschungszentrum Jülich Institute of Energy and Climate Research Techno - Economic Systems Analysis (IEK - 3) Wilhelm - Johnen - Straße 52428 Jülich Germany

Mon Sep 16 22:08:58 2024

Table of contents

Operational Costs and Emissions for simulated period	4
2. Investment Cost and CO2-Emissions of devices for simulated period	6
3 KPIs	8

1. Operational Costs and Emissions for simulated period

BUI2_Building 0 BUI2_UTSPConnector 0		0	0
BUI2_UTSPConnector 0			
		0	0.0
BUI2_PVSystem 2.3	.34	0	0
BUI2_HeatDistributionController 0		0	0
BUI2_HeatPumpController 0		0	0
BUI2_AdvancedHeatPumpHPLib 5.4	.61	0	159.3
BUI2_DHWBoiler 2.8	.5	0	0
BUI2_DHWHeatpumpController 0		0	0
BUI2_DHWHeatPump 4.:	.35	0	27.0
BUI2_SimpleHotWaterStorage 0.4	.0	0	0
BUI2_HeatDistributionSystem 1.	.53	0	0
BUI2_Battery 3.	.16	0	0.0
BUI2_L2EMSElectricityController 0		0	0
BUI2_Total 19	9.5	0.0	186.3
BUI2_Total_without_heatpump 9.4	.53	0.0	0.0
BUI2_Total_only_heatpump 9.4	.97	0.0	186.3
BUI1_Building 0		0	0
BUI1_UTSPConnector 0		0	0.0
BUI1_PVSystem 2.3	.34	0	0
BUI1_HeatDistributionController 0		0	0
BUI1_HeatPumpController 0		0	0
BUI1_AdvancedHeatPumpHPLib 5.4	.61	0	159.3
BUI1_DHWBoiler 2.	.5	0	0
BUI1_DHWHeatpumpController 0		0	0
BUI1_DHWHeatPump 4.:	.35	0	27.0
BUI1_SimpleHotWaterStorage 0.4	.0	0	0
BUI1_HeatDistributionSystem 1.4	.53	0	0
BUI1_Battery 3.	.16	0	0.0
BUI1_L2EMSElectricityController 0		0	0
BUI1_Total 19	9.5	0.0	186.3
BUI1_Total_without_heatpump 9.8	.53	0.0	0.0
BUI1_Total_only_heatpump 9.9	.97	0.0	186.3
District_Weather 0		0	0
District_PV_Park 2.5	.29	0	0

District_Total	2.29	0.0	0.0
District_Total_without_heatpump	2.29	0.0	0.0
District_Total_only_heatpump	0.0	0.0	0.0
Total	41.29	0.0	372.6
Total_without_heatpump	21.35	0.0	0.0
Total_only_heatpump	19.93	0.0	372.6

Comments:
Operational Costs are the sum of fuel costs and maintenance costs for the devices, calculated for the simulated period.
Emissions are fuel emissions emitted during simulad period.
Consumption for Diesel_Car in I, for EV in kWh.

2. Investment Cost and CO2-Emissions of devices for simulated period

Component	Investment in EUR	Device CO2-footprint in kg	Lifetime in years
BUI2_Building	0	0	1
BUI2_UTSPConnector	0	0	1
BUI2_PVSystem	9.36	3.89	25
BUI2_HeatDistributionController	0	0	1
BUI2_HeatPumpController	0	0	1
BUI2_AdvancedHeatPumpHPLib	22.45	2.46	10
BUI2_DHWBoiler	6.26	0.0	20
BUI2_DHWHeatpumpController	0	0	1
BUI2_DHWHeatPump	17.42	1.91	10
BUI2_SimpleHotWaterStorage	2.64	0.02	100
BUI2_HeatDistributionSystem	3.07	0.0	50
BUI2_ElectricityMeter	0	0	1
BUI2_Battery	0.0	0.0	10
BUI2_L2EMSElectricityController	0	0	1
BUI2_Total_per_simulated_period_without_heatpump	21.33	3.91	
BUI2_Total_per_simulated_period_only_heatpump	39.87	4.37	
BUI2_Total_per_simulated_period	61.2	8.28	
BUI2_Total_without_heatpump	48736.45	7181.67	
BUI2_Total_only_heatpump	20787.53	2277.41	
BUI2_Total	69523.97	9459.08	
BUI1_Building	0	0	1
BUI1_UTSPConnector	0	0	1
BUI1_PVSystem	9.36	3.89	25
BUI1_HeatDistributionController	0	0	1
BUI1_HeatPumpController	0	0	1
BUI1_AdvancedHeatPumpHPLib	22.45	2.46	10
BUI1_DHWBoiler	6.26	0.0	20
BUI1_DHWHeatpumpController	0	0	1
BUI1_DHWHeatPump	17.42	1.91	10
BUI1_SimpleHotWaterStorage	2.64	0.02	100
BUI1_HeatDistributionSystem	3.07	0.0	50
BUI1_ElectricityMeter	0	0	1
BUI1_Battery	0.0	0.0	10
BUI1_L2EMSElectricityController	0	0	1

BUI1_Total_per_simulated_period_without_heatpump	21.33	3.91	
BUI1_Total_per_simulated_period_only_heatpump	39.87	4.37	
BUI1_Total_per_simulated_period	61.2	8.28	
BUI1_Total_without_heatpump	48736.45	7181.67	
BUI1_Total_only_heatpump	20787.53	2277.41	
BUI1_Total	69523.97	9459.08	
District_Weather	0	0	1
District_PV_Park	9.14	3.8	25
District_ElectricityMeter	0	0	1
District_Total_per_simulated_period_without_heatpump	9.14	3.8	
District_Total_per_simulated_period_only_heatpump	0.0	0.0	
District_Total_per_simulated_period	9.14	3.8	
District_Total_without_heatpump	11916.15	4957.65	
District_Total_only_heatpump	0.0	0.0	
District_Total	11916.15	4957.65	
Total_per_simulated_period	131.53	20.36	
Total_per_simulated_period_without_heatpump	51.8	11.63	
Total_per_simulated_period_only_heatpump	79.73	8.74	
Total	150964.09	23875.81	
Total_without_heatpump	109389.04	19320.99	
Total_only_heatpump	41575.05	4554.82	

Values for Battery are calculated with lifetime in cycles instead of lifetime in years

3. KPIs

Object	KPI	Value	Unit
BUI2	Building		
BUI2	Building heating load:	7732.56	W
BUI2	Conditioned floor area:	121.2	m2
BUI2	Rooftop area:	168.9	m2
BUI2	Specific heating load:	63.8	W/m2
BUI2	Specific heating demand according to TABULA:	128.1	kWh/m2a
BUI2	Temperature deviation of building indoor air temperature being below set tempera ture 20.0 Celsius:	3.24	°C*h
BUI2	Temperature deviation of building indoor air temperature being above set temperature 25.0 Celsius:	0.0	°C*h
BUI2	Minimum building indoor air temperature reached:	18.61	°C
BUI2	Maximum building indoor air temperature reached:	23.59	°C
BUI2	Solar energy gains:	4.7	kWh
BUI2	Internal energy gains:	114.69	kWh
BUI2	Energy transfer from transmission:	648.19	kWh
BUI2	Energy transfer from ventilation:	195.61	kWh
BUI2	Heat demand calculated based on TABULA:	732.76	kWh
BUI2	Residents		
BUI2	Residents' total electricity consumption:	112.49	kWh
BUI2	Heat Pump For Space Heating		
BUI2	Number of SH heat pump cycles:	65	-
BUI2	Seasonal performance factor of SH heat pump:	3.55	-
BUI2	Seasonal energy efficiency ratio of SH heat pump:	None	-
BUI2	Heating output energy of SH heat pump:	564.68	kWh
BUI2	Cooling output energy of SH heat pump:	0.0	kWh
BUI2	Electrical input energy for heating of SH heat pump:	159.28	kWh
BUI2	Electrical input energy for cooling of SH heat pump:	0.0	kWh
BUI2	Total electrical input energy of SH heat pump:	159.28	kWh

BUI2 BUI2	Heating hours of SH heat pump: Cooling hours of SH heat pump:	2157.6 0.0	h h
DOIZ	Cooling Hours of Stritteat pump.	0.0	"
BUI2	Heat Pump For Domestic Hot Water		
BUI2	DHW heat pump total electricity consumption:	26.98	kWh
BUI2	Heating output energy of DHW heat pump:	102.95	kWh
BUI2	Heat Distribution System		
BUI2	Thermal output energy of heat distribution system:	512.59	kWh
BUI2	Mean flow temperature of heat distribution system:	33.09	°C
BUI2	Mean return temperature of heat distribution system:	30.32	°C
BUI2	Mean temperature difference of heat distribution system:	2.76	°C
BUI2	Max flow temperature of heat distribution system:	43.86	°C
BUI2	Max return temperature of heat distribution system:	41.07	°C
BUI2	Max temperature difference of heat distribution system:	5.8	°C
BUI2	Min flow temperature of heat distribution system:	20.96	°C
BUI2	Min return temperature of heat distribution system:	20.96	°C
BUI2	Min temperature difference of heat distribution system:	0.0	°C
BUI2	Electricity Meter		
	Total an army frame avid.	054.04	LAMI
BUI2	Total energy from grid:	254.31	kWh
BUI2	Total energy to grid:	11.87	kWh
BUI2	Opex costs of electricity consumption from grid:	75.53	Euro
BUI2	CO2 footprint of electricity consumption from grid:	104.27	kg
BUI2	Energy Management System		
BUI2	Residents' electricity consumption from grid:	22.83	kWh
BUI2	Domestic hot water heat pump electricity from grid:	139.27	kWh
BUI2	Space heating heat pump electricity from grid:	254.31	kWh
DUILO			

BUI2

General

BUI2	Total electricity consumption:	298.8	kWh
BUI2	Total electricity production:	56.3	kWh
BUI2	PV production:	56.3	kWh
BUI2	Windturbine production:	0.0	kWh
BUI2	Ratio between total production and total consumption:	18.84	%
BUI2	Ratio between PV production and total consumption:	18.84	%
BUI2	Ratio between Windturbine production and total consumption:	0.0	%
BUI2	Ratio between Building production and total consumption:	0.0	%
BUI2	Grid injection of electricity:	11.87	kWh
BUI2	Self-consumption of electricity:	44.45	kWh
BUI2	Self-consumption rate of electricity:	78.95	%
BUI2	Autarky rate of electricity:	14.88	%
BUI2	Relative electricity demand from grid:	85.11	%
BUI2	Self-consumption rate according to solar htw berlin:	78.92	%
BUI2	Autarky rate according to solar htw berlin:	14.89	%
DUILO	Datta.		
BUI2	Battery		
DLIIO	Pottony charging anarayy	0.0	IAM/b
BUI2	Battery charging energy:	0.0	kWh
BUI2	Battery discharging energy:	0.0	kWh
BUI2	Battery consumption:	0.0	kWh
BUI2	Costs		
BUI2	Costs of grid electricity for simulated period:	75.53	EUR
BUI2	Costs of grid gas for simulated period:	0	EUR
BUI2	Costs of grid heat for simulated period:	0	EUR
BUI2	Investment costs for equipment per simulated period:	61.2	EUR
BUI2	Maintenance costs for simulated period:	19.5	EUR
BUI2	Total costs for simulated period:	156.23	EUR
BUI2	Investment costs for equipment without heatpump per simulated period:	21.33	EUR
BUI2	Maintenance costs without heatpump for simulated period:	9.53	EUR
BUI2	Total costs without heatpump for simulated period:	106.39	EUR
BUI2	Investment costs for equipment only heatpump per simulated period:	39.87	EUR
BUI2	Maintenance costs only heatpump for simulated period:	9.97	EUR
BUI2	Total costs only heatpump for simulated period:	49.84	EUR

2	Emissions		
-	CO2 footprint of grid electricity for simulated period:	104.27	kg
	CO2 footprint of grid gas for simulated period:	0	kg
	CO2 footprint of grid heat consumption for simulated period:	0	kg
	CO2 footprint for equipment per simulated period:	8.28	kg
	Total CO2 emissions for simulated period:	112.55	kg
	CO2 footprint for equipment without heatpump per simulated period:	3.91	kg
	Total CO2 emissions without heatpump for simulated period:	108.18	kg
	CO2 footprint for equipment only heatpump per simulated period:	4.37	kg
	Total CO2 emissions only heatpump for simulated period:	4.37	kg
	Building		
	Building heating load:	7732.56	W
	Conditioned floor area:	121.2	m2
ı	Rooftop area:	168.9	m2
	Specific heating load:	63.8	W/m2
;	Specific heating demand according to TABULA:	128.1	kWh/m2a
	Temperature deviation of building indoor air temperature being below set tempera ture 20.0 Celsius:	3.24	°C*h
	Temperature deviation of building indoor air temperature being above set tempera ture 25.0 Celsius:	0.0	°C*h
	Minimum building indoor air temperature reached:	18.61	°C
	Maximum building indoor air temperature reached:	23.59	°C
	Solar energy gains:	4.7	kWh
	Internal energy gains:	114.69	kWh
	Energy transfer from transmission:	648.19	kWh
	Energy transfer from ventilation:	195.61	kWh
	Heat demand calculated based on TABULA:	732.76	kWh
	Residents		
	Residents' total electricity consumption:	112.49	kWh

BUI1	Heat Pump For Space Heating		
BUI1	Number of SH heat pump cycles:	65	-
BUI1	Seasonal performance factor of SH heat pump:	3.55	-
BUI1	Seasonal energy efficiency ratio of SH heat pump:	None	-
BUI1	Heating output energy of SH heat pump:	564.68	kWh
BUI1	Cooling output energy of SH heat pump:	0.0	kWh
BUI1	Electrical input energy for heating of SH heat pump:	159.28	kWh
BUI1	Electrical input energy for cooling of SH heat pump:	0.0	kWh
BUI1	Total electrical input energy of SH heat pump:	159.28	kWh
BUI1	Heating hours of SH heat pump:	2157.6	h
BUI1	Cooling hours of SH heat pump:	0.0	h
BUI1	Heat Pump For Domestic Hot Water		
BUI1	DHW heat pump total electricity consumption:	26.98	kWh
BUI1	Heating output energy of DHW heat pump:	102.95	kWh
BUI1	Heat Distribution System		
		512 50	k\N/b
 BUI1	Thermal output energy of heat distribution system:	512.59 33.00	kWh °C
BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system:	33.09	°C
BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system:	33.09 30.32	°C
BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system:	33.09 30.32 2.76	°C °C
BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system:	33.09 30.32 2.76 43.86	°C °C
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system:	33.09 30.32 2.76 43.86 41.07	°C °C °C °C
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system:	33.09 30.32 2.76 43.86 41.07 5.8	°C °C °C °C °C
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system:	33.09 30.32 2.76 43.86 41.07 5.8 20.96	°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°°
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system:	33.09 30.32 2.76 43.86 41.07 5.8	°C °C °C °C °C
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system: Min return temperature of heat distribution system:	33.09 30.32 2.76 43.86 41.07 5.8 20.96	, , , , , , , , , ,
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system: Min return temperature of heat distribution system:	33.09 30.32 2.76 43.86 41.07 5.8 20.96	, , , , , , , , , ,
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system: Min return temperature of heat distribution system: Min return temperature of heat distribution system: Min temperature difference of heat distribution system: Electricity Meter	33.09 30.32 2.76 43.86 41.07 5.8 20.96 20.96 0.0	, , , , , , , , , , , , , , , , , , ,
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system: Min return temperature of heat distribution system: Min return temperature of heat distribution system: Min temperature difference of heat distribution system: Electricity Meter Total energy from grid:	33.09 30.32 2.76 43.86 41.07 5.8 20.96 20.96 0.0	°C °C °C °C °C °C °C
BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1 BUI1	Thermal output energy of heat distribution system: Mean flow temperature of heat distribution system: Mean return temperature of heat distribution system: Mean temperature difference of heat distribution system: Max flow temperature of heat distribution system: Max return temperature of heat distribution system: Max temperature difference of heat distribution system: Min flow temperature of heat distribution system: Min return temperature of heat distribution system: Min return temperature of heat distribution system: Min temperature difference of heat distribution system: Electricity Meter	33.09 30.32 2.76 43.86 41.07 5.8 20.96 20.96 0.0	, , , , , , , , , , , , , , , , , , ,

BUI1	CO2 footprint of electricity consumption from grid:	104.27	kg
BUI1	Energy Management System		
 BUI1	Residents' electricity consumption from grid:	22.83	kWh
BUI1	Domestic hot water heat pump electricity from grid:	139.27	kWh
BUI1	Space heating heat pump electricity from grid:	254.31	kWh
BUI1	General		
 BUI1	Total electricity consumption:	298.8	kWh
BUI1	Total electricity production:	56.3	kWh
BUI1	PV production:	56.3	kWh
BUI1	Windturbine production:	0.0	kWh
BUI1	Ratio between total production and total consumption:	18.84	%
BUI1	Ratio between PV production and total consumption:	18.84	%
BUI1	Ratio between Windturbine production and total consumption:	0.0	%
BUI1	Ratio between Building production and total consumption:	0.0	%
BUI1	Grid injection of electricity:	11.87	kWh
BUI1	Self-consumption of electricity:	44.45	kWh
BUI1	Self-consumption rate of electricity:	78.95	%
BUI1	Autarky rate of electricity:	14.88	%
BUI1	Relative electricity demand from grid:	85.11	%
BUI1	Self-consumption rate according to solar htw berlin:	78.92	%
BUI1	Autarky rate according to solar htw berlin:	14.89	%
BUI1	Battery		
BUI1	Battery charging energy:	0.0	kWh
BUI1	Battery discharging energy:	0.0	kWh
BUI1	Battery consumption:	0.0	kWh
BUI1	Costs		
BUI1	Costs of grid electricity for simulated period:	75.53	EUR
BUI1	Costs of grid gas for simulated period:	0	EUR

DUIA		0	ELID
BUI1	Costs of grid heat for simulated period:	0	EUR
BUI1	Investment costs for equipment per simulated period:	61.2	EUR
BUI1	Maintenance costs for simulated period:	19.5	EUR
BUI1	Total costs for simulated period:	156.23	EUR
BUI1	Investment costs for equipment without heatpump per simulated period:	21.33	EUR
BUI1	Maintenance costs without heatpump for simulated period:	9.53	EUR
BUI1	Total costs without heatpump for simulated period:	106.39	EUR
BUI1	Investment costs for equipment only heatpump per simulated period:	39.87	EUR
BUI1	Maintenance costs only heatpump for simulated period:	9.97	EUR
BUI1	Total costs only heatpump for simulated period:	49.84	EUR
BUI1	Emissions		
BUI1	CO2 footprint of grid electricity for simulated period:	104.27	kg
BUI1	CO2 footprint of grid gas for simulated period:	0	kg
BUI1	CO2 footprint of grid heat consumption for simulated period:	0	kg
BUI1	CO2 footprint for equipment per simulated period:	8.28	kg
BUI1	Total CO2 emissions for simulated period:	112.55	kg
BUI1	CO2 footprint for equipment without heatpump per simulated period:	3.91	kg
BUI1	Total CO2 emissions without heatpump for simulated period:	108.18	kg
BUI1	CO2 footprint for equipment only heatpump per simulated period:	4.37	kg
BUI1	Total CO2 emissions only heatpump for simulated period:	4.37	kg
District	Electricity Meter		
District	Total energy from grid:	508.62	kWh
District	Total energy to grid:	23.73	kWh
District	Opex costs of electricity consumption from grid:	151.05	Euro
District	CO2 footprint of electricity consumption from grid:	208.53	kg
District	Electricity Grid		
District	Total electricity consumption:	508.6	kWh
District	Total electricity production:	23.7	kWh
District	PV production:	0.0	kWh
District	Windturbine production:	0.0	kWh

District	Building production:	23.7	kWh
District	Total building electricity consumption:	508.6	kWh
District	Ratio between total production and total consumption:	4.66	%
District	Ratio between PV production and total consumption:	0.0	%
District	Ratio between Windturbine production and total consumption:	0.0	%
District	Ratio between Building production and total consumption:	4.66	%
District	Grid injection of electricity:	23.73	kWh
District	Self-consumption of electricity:	0.0	kWh
District	Self-consumption rate of electricity:	0.0	%
District	Autarky rate of electricity:	0.0	%
District	Relative electricity demand from grid:	100.0	%
District	Self-consumption rate according to solar htw berlin:	-0.13	%
District	Autarky rate according to solar htw berlin:	0.0	%
District	Battery		
District	Battery charging energy:	0.0	kWh
District	Battery discharging energy:	0.0	kWh
District	Battery consumption:	0.0	kWh
District	Costs Of District Grid		
District	Costs of grid electricity for simulated period:	151.05	EUR
District	Costs of grid gas for simulated period:	0	EUR
District	Costs of grid heat for simulated period:	0	EUR
District	Investment costs for equipment per simulated period:	9.14	EUR
District	Maintenance costs for simulated period:	2.29	EUR
District	Total costs for simulated period:	162.48	EUR
District	Investment costs for equipment without heatpump per simulated period:	9.14	EUR
District	Maintenance costs without heatpump for simulated period:	2.29	EUR
District	Total costs without heatpump for simulated period:	162.48	EUR
District	Investment costs for equipment only heatpump per simulated period:	0.0	EUR
District	Maintenance costs only heatpump for simulated period:	0.0	EUR
District	Total costs only heatpump for simulated period:	0.0	EUR

District Emissions Of District Grid

			
District	CO2 footprint of grid electricity for simulated period:	208.53	kg
District	CO2 footprint of grid gas for simulated period:	0	kg
District	CO2 footprint of grid heat consumption for simulated period:	0	kg
District	CO2 footprint for equipment per simulated period:	3.8	kg
District	Total CO2 emissions for simulated period:	212.33	kg
District	CO2 footprint for equipment without heatpump per simulated period:	3.8	kg
District	Total CO2 emissions without heatpump for simulated period:	212.33	kg
District	CO2 footprint for equipment only heatpump per simulated period:	0.0	kg
District	Total CO2 emissions only heatpump for simulated period:	0.0	kg
District	General		
District	Electricity consumption of all single buildings:	597.6	kWh
District	Electricity production of all single buildings:	112.6	kWh
District	Self-consumption of all single buildings:	88.9	kWh
District	Electricity production of district without buildings:	0.0	kWh
District	Electricity consumption of district without buildings:	0.0	kWh
District	Self-consumption of district without buildings:	0.0	kWh
District	Overall electricity production in district:	112.6	kWh
District	Overall electricity consumption in district:	597.6	kWh
District	Overall self-consumption in district:	88.9	kWh
District	Overall ratio between total production and total consumption in district:	18.84	%
District	Overall relative electricity demand from grid in district:	85.11	%
District	Overall autarky rate of electricity in district:	14.88	%
District	Overall self-consumption rate according to solar htw berlin in district:	78.92	%
District	Overall autarky rate according to solar htw berlin in district:	14.89	%
District	Costs		
District	Total investment costs for equipment for all single buildings per simulated peri od:	122.4	EUR
District	Total investment costs without heatpump for all single buildings per simulated p eriod:	42.66	EUR
District	Total investment costs only heatpump for all single buildings per simulated peri od:	79.74	EUR

District Total maintenance costs for all single buildings per simulated period:

EUR

39.0

District	Total maintenance costs without heatpump for all single buildings per simulated period:	19.06	EUR
District	Total maintenance costs only heatpump for all single buildings per simulated per iod:	19.94	EUR
District	Total investment costs for equipment for district without buildings per simulate d period:	9.14	EUR
District	Total investment costs without heatpump for district per simulated period:	9.14	EUR
District	Total investment costs only heatpump for district per simulated period:	0.0	EUR
District	Total maintenance costs for district without buildings per simulated period:	2.29	EUR
District	Total maintenance costs without heatpump for district per simulated period:	2.29	EUR
District	Total maintenance costs only heatpump for district per simulated period:	0.0	EUR
District	Overall investment for equipment costs in district per simulated period:	131.54	EUR
District	Overall investment costs without heatpump in district per simulated period:	51.8	EUR
District	Overall investment costs only heatpump in district per simulated period:	79.74	EUR
District	Overall maintenance costs in district per simulated period:	41.29	EUR
District	Overall maintenance costs without heatpump in district per simulated period:	21.35	EUR
District	Overall maintenance costs only heatpump in district per simulated period:	19.94	EUR
District	Emissions		
District	Emissions		
		16 56	ka
District District	CO2 footprint for equipment for all single buildings per simulated period:	16.56	kg
		16.56 7.82	kg kg
District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simula		
District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simula ted period: CO2 footprint for equipment only heatpump for all single buildings per simulated	7.82 8.74	kg
District District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simulated period: CO2 footprint for equipment only heatpump for all single buildings per simulated period: CO2 footprint for equipment for district without buildings per simulated period:	7.82	kg
District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simula ted period: CO2 footprint for equipment only heatpump for all single buildings per simulated period:	7.82 8.74	kg kg
District District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simulated period: CO2 footprint for equipment only heatpump for all single buildings per simulated period: CO2 footprint for equipment for district without buildings per simulated period:	7.82 8.74 3.8	kg kg kg
District District District District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simulated period: CO2 footprint for equipment only heatpump for all single buildings per simulated period: CO2 footprint for equipment for district without buildings per simulated period: CO2 footprint for equipment without heatpump for district per simulated period:	7.82 8.74 3.8 3.8	kg kg kg kg
District District District District District District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simulated period: CO2 footprint for equipment only heatpump for all single buildings per simulated period: CO2 footprint for equipment for district without buildings per simulated period: CO2 footprint for equipment without heatpump for district per simulated period: CO2 footprint for equipment only heatpump for district per simulated period:	7.82 8.74 3.8 3.8 0.0	kg kg kg kg kg
District District District District District District District District	CO2 footprint for equipment for all single buildings per simulated period: CO2 footprint for equipment without heatpump for all single buildings per simula ted period: CO2 footprint for equipment only heatpump for all single buildings per simulated period: CO2 footprint for equipment for district without buildings per simulated period: CO2 footprint for equipment without heatpump for district per simulated period: CO2 footprint for equipment only heatpump for district per simulated period: CO2 footprint for equipment in district per simulated period: Overall CO2 footprint for equipment without heatpump in district per simulated p	7.82 8.74 3.8 3.8 0.0 20.36	kg kg kg kg kg

Here a comment on calculation of numbers will follow