

Page 1 of 4

### This information was generated by the HP KEYMARK database on 22 Jun 2022

#### <u>Login</u>

Summary of	AEROTOP M 048	Reg. No.	ICIM-PDC-000097-00	
Certificate Holder				
Name	ELCO GmbH	ELCO GmbH		
Address	Hohenzollernstrasse 31	Zip	72379	
City	Hechingen	Country	Germany	
Certification Body	ICIM S.p.A.	ICIM S.p.A.		
Subtype title	AEROTOP M 048	AEROTOP M 048		
Heat Pump Type	Outdoor Air/Water	Outdoor Air/Water		
Refrigerant	R32	R32		
Mass of Refrigerant	14 kg	14 kg		
Certification Date	30.03.2021	30.03.2021		
Testing basis	HP KEYMARK certification sch	HP KEYMARK certification scheme rules rev. no. 7		



# **Model: AEROTOP M 048**

Configure model			
Model name	AEROTOP M 048		
Application	Heating (low temp)		
Units	Outdoor		
Climate Zone	n/a		
Reversibility	Yes		
Cooling mode application (optional)	n/a		

General Data		
Power supply	3x400V 50Hz	

# Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	48.60 kW	4.80 kW	
El input	12.12 kW	1.90 kW	
СОР	4.01	2.53	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	

## **Average Climate**



 $$\operatorname{\textit{Page}}\ 3$$  of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

EN 12102-1		
	Low temperature	Medium temperature
Sound power level outdoor	84 dB(A)	64 dB(A)

EN 14825			
	Low temperature	Medium temperature	
$\eta_{s}$	154 %	129 %	
Prated	31.00 kW	7.00 kW	
SCOP	3.91	3.30	
Tbiv	-10 °C	-7 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	27.80 kW	5.90 kW	
COP Tj = -7°C	2.72	2.00	
Cdh Tj = -7 °C	0.90		
Pdh Tj = +2°C	16.90 kW	3.70 kW	
COP Tj = +2°C	3.85	3.18	
Cdh Tj = +2 °C	0.90		
Pdh Tj = +7°C	10.90 kW	2.50 kW	
COP Tj = +7°C	4.90	4.52	
Cdh Tj = +7 °C	0.90		
Pdh Tj = 12°C	14.20 kW	1.10 kW	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



Page 4 of 4 This information was generated by the HP KEYMARK database on 22 Jun 2022

COP Tj = 12°C	6.02	5.09
Cdh Tj = +12 °C	0.90	
Pdh Tj = Tbiv	31.40 kW	5.90 kW
COP Tj = Tbiv	2.42	2.00
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	31.40 kW	6.60 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.42	1.80
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.90	0.90
WTOL	54 °C	49 °C
Poff	30 W	16 W
РТО	404 W	16 W
PSB	30 W	16 W
PCK	o w	34 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	16591 kWh	4202 kWh