

This information was generated by the HP KEYMARK database on 18 Mar 2022

[Login](#)

Summary of	ecoGEO B3/C3 1-6 PRO	Reg. No.	011-1W0430
Certificate Holder			
Name	Ecoforest Geotermia S.L.		
Address	Rúa das Pontes, 25	Zip	36350
City	Nigrán (Pontevedra)	Country	Spain
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	ecoGEO B3/C3 1-6 PRO		
Heat Pump Type	Brine/Water		
Refrigerant	R290		
Mass of Refrigerant	0.15 kg		
Certification Date	17.11.2020		
Testing basis	HP KEYMARK certification scheme rules rev. 7		

Model: ecoGEO B3/C3 1-6 PRO

Configure model	
Model name	ecoGEO B3/C3 1-6 PRO
Application	Heating + DHW + low temp
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6.12 kW	4.39 kW
El input	1.61 kW	1.53 kW
COP	4.30	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	178 %	136 %
Prated	6.00 kW	5.50 kW
SCOP	4.64	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.35 kW	4.45 kW
COP Tj = -7°C	3.87	2.89
Cdh Tj = -7 °C	0.99	0.99
Pdh Tj = +2°C	3.28 kW	2.73 kW
COP Tj = +2°C	4.68	3.60
Cdh Tj = +2 °C	0.98	0.98
Pdh Tj = +7°C	2.10 kW	2.01 kW
COP Tj = +7°C	5.26	4.14
Cdh Tj = +7 °C	0.97	0.98
Pdh Tj = 12°C	1.24 kW	1.16 kW

This information was generated by the HP KEYMARK database on 18 Mar 2022

COP Tj = 12°C	5.44	4.48
Cdh Tj = +12 °C	0.95	0.96
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.18 kW	0.00 kW
Annual energy consumption Qhe	2669 kWh	3152 kWh

Warmer Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature

This information was generated by the HP KEYMARK database on 18 Mar 2022

η_s	178 %	134 %
Prated	6.00 kW	5.50 kW
SCOP	4.65	3.56
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	5.82 kW	5.50 kW
COP Tj = +2°C	3.72	2.79
Cdh Tj = +2 °C	0.99	0.99
Pdh Tj = +7°C	3.86 kW	3.55 kW
COP Tj = +7°C	4.43	3.27
Cdh Tj = +7 °C	0.99	0.99
Pdh Tj = 12°C	1.71 kW	3.44 kW
COP Tj = 12°C	5.37	4.24
Cdh Tj = +12 °C	0.96	0.99
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
WTOL	70 °C	70 °C
Poff	11 W	11 W

This information was generated by the HP KEYMARK database on 18 Mar 2022

PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.18 kW	0.00 kW
Annual energy consumption Q _{he}	1728 kWh	2066 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	186 %	141 %
Prated	6.00 kW	5.50 kW
SCOP	4.85	3.73
T _{biv}	-22 °C	-22 °C
TOL	-22 °C	-22 °C
P _{dh} T _j = -7°C	3.64 kW	3.35 kW
COP T _j = -7°C	4.59	3.42

This information was generated by the HP KEYMARK database on 18 Mar 2022

Cdh Tj = -7 °C	0.99	0.99
Pdh Tj = +2°C	2.24 kW	2.06 kW
COP Tj = +2°C	5.27	4.04
Cdh Tj = +2 °C	0.97	0.98
Pdh Tj = +7°C	1.44 kW	1.41 kW
COP Tj = +7°C	5.40	4.40
Cdh Tj = +7 °C	0.96	0.96
Pdh Tj = 12°C	0.88 kW	1.19 kW
COP Tj = 12°C	4.91	4.77
Cdh Tj = +12 °C	0.94	0.95
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.18 kW	0.00 kW

This information was generated by the HP KEYMARK database on 18 Mar 2022

Annual energy consumption Q_{he}	3059 kWh	3631 kWh
------------------------------------	----------	----------

Domestic Hot Water (DHW)

Average Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Warmer Climate

This information was generated by the HP KEYMARK database on 18 Mar 2022

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Colder Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l