

Page 1 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	Samsung EHS TDM Plus R410A 9 kW 3Phase (wall-mounted hydro unit)	Reg. No.	011- 1W0377
Certificate Holder			
Name	Samsung Electronics Air Conditioner Europe B.V.		
Address	Evert van de Beekstraat 310	Zip	1118 CX
City	Schiphol	Country	Netherlands
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Name of testing laboratory	KIWA, Netherlands		
Subtype title	Samsung EHS TDM Plus R410A 9 kW 3Phase (wall-mounted h	ydro unit)
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410a		
Mass Of Refrigerant	2.4 kg		
Certification Date	29.07.2020		
Testing basis	European KEYMARK Scheme for Heat Pumps Rev. 7		



This information was generated by the HP KEYMARK database on 17 Dec 2020

Model: AE090MXTPGH/EU & AE090MNYDGH/EU

General Data		
Power supply	3x400V 50Hz	

Heating

EN 14511-2			
	Low temperature	Medium temperature	
Heat output	9.00 kW	7.66 kW	
El input	2.12 kW	2.82 kW	
СОР	4.25	2.69	
Indoor water flow rate	1.56 m³/h	0.86 m³/h	

EN 14511-4		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	

Average Climate



 $$\operatorname{\textit{Page}}\xspace$ 3 of 4 This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	48 dB(A)	48 dB(A)
Sound power level outdoor	69 dB(A)	69 dB(A)

EN 14825			
	Low temperature	Medium temperature	
η_{s}	175 %	111 %	
Prated	6.00 kW	5.00 kW	
SCOP	4.44	2.86	
Tbiv	-10 °C	-10 °C	
TOL	-10 °C	-10 °C	
Pdh Tj = -7°C	5.00 kW	4.60 kW	
COP Tj = -7°C	2.63	1.91	
Cdh	0.90	0.90	
Pdh Tj = +2°C	3.00 kW	2.80 kW	
COP Tj = +2°C	4.47	2.78	
Cdh	0.90	0.90	
Pdh Tj = +7°C	3.20 kW	2.60 kW	
COP Tj = +7°C	5.96	3.59	
Cdh	0.90	0.90	

EHPA Secretariat | Rue dArlon 63-67 | Phone: +32 2 400 10 17 | Email: secretariat@heatpumpkeymark.com | www.heatpumpkeymark.com



 $$\operatorname{\textit{Page}}4 of 4$ This information was generated by the HP KEYMARK database on 17 Dec 2020$

Pdh Tj = 12°C	3.00 kW	2.50 kW
COP Tj = 12°C	8.27	4.72
Cdh	0.90	0.90
Pdh Tj = Tbiv	5.60 kW	5.20 kW
COP Tj = Tbiv	2.31	1.68
Pdh Tj = TOL	5.60 kW	5.20 kW
COP Tj = TOL	2.31	1.68
WTOL	55 °C	55 °C
Poff	22 W	22 W
РТО	22 W	22 W
PSB	22 W	22 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	2644 kWh	3871 kWh